

Date:

Name 1:

Name 2:

Assume you have a relation $R(\underline{a}, b, c)$. Suppose the blocks can hold either 10 tuples (heap) or 100 search keys (b+tree index). Nodes of the index are 70% full. The relation contains 1 million records. The values of a are expected to be ≥ 0 and $< 10^6$.

Consider the following two queries:

a) $\sigma_{a=5} R$

1 matching record

b) $\sigma_{a \geq 10,000 \text{ and } a < 20,000} R \Rightarrow 10,000 \text{ matching rec.}$

Every value of a between 1 and 10^6

70% full

$\frac{1}{10^6} = 10^{-6} \text{ selec.}$
 $\frac{10^4}{10^6} = 10^{-2} \text{ selec.}$

1. Determine for each query:

- the number of expected matching records

2. Determine, for each of the structures below:


- Expected number of leaf blocks of each index
- The expected height of each index
- The average number of disk I/Os needed to answer each query

Assume that nothing is in memory initially, and that the search key is the primary key of the table.

- The B+tree is dense and the heap is unsorted
- The B+tree is a sparse.

Redo assuming that a is not a primary key, values of a vary from ≥ 0 and $\leq 10^5$

a) B + tree dense



$$\text{Block index} = \frac{10^6}{70} = \frac{1}{7} \cdot 10^5 \text{ blocks.}$$


$$h = \left\lceil \log_{70} 10^6 \right\rceil$$

$$= \left\lceil \frac{\log_{10} (10^6)}{\log_{10} 70} \right\rceil$$

$$h = 4$$

$$\text{For } \sigma_{a=5} R \Rightarrow h+1 = 5$$


For $\sigma_{a>10k \text{ and } a < 20k}$



$$\text{blocks} = \left\lceil \frac{10^4}{70} \right\rceil = 143$$

$$\text{Cost} = 3 + 143 + 10,000 = 10,146$$

b) Tree is sparse.




$$h = \left\lceil \log_{70} 10^5 \right\rceil$$

$$= \left\lceil \frac{\log_{10}(10^5)}{\log_{10} 70} \right\rceil$$

$$= \lceil 2.7 \rceil = 3$$

$$\sigma_{a=5} R \Rightarrow h+1 = 4.$$

$$\sigma_{\substack{a \geq 10k \text{ and} \\ a < 20k}} R.$$



$$\text{blocks in heap} = \frac{10^4 \text{ tuples}}{10 \text{ tuples/block}} = 1,000 \text{ blocks.}$$

$$\text{Cost} = 1003 \text{ blocks.}$$

$\sigma_{a=s} R$ a not primary key.

Indexes will be the same

matching tuples 10 (each value is repeated 10 times).

$$\text{Cost} = h + 10 = 14$$


(10 index records found in one block of index)

Sparse index 10 tuples can be found in one block of heap
(most likely 2 if they don't start in the beginning of block)

$$\begin{aligned} \text{Cost} &= h + 1 \text{ or } h + 2 \\ &= 4 \text{ or } 5. \end{aligned}$$

$\sigma_{a \geq 10k \text{ and } a < 20k} R \Rightarrow 10^5 \text{ tuples would match.}$

Dense:



$$\# \text{block index} = \frac{10^5 \text{ tuples}}{70}$$

$$\begin{aligned} \text{Cost} &= h - 1 + \frac{10^5}{70} + 10^5 \\ &= 3 + \frac{10^5}{70} + 10^5 \end{aligned}$$

Sparse index

$h + \# \text{ blocks in heap.}$

$$\text{Cost} = h + \frac{10^5}{10} = 3. + 10^4 = 10,003 \text{ blocks.}$$