Name 1: Date:

## Assume:

- Relation R(a,b) contains 10,000 tuples, and has 10 tuples per block
- Relation S(a,c) contains 2,000 tuples and has 10 tuples per block
- Both relations are stored as simple heap files
- Neither relation has any indexes built on them

## Part A:

Compute SELECT \* FROM R NATURAL JOIN S;

Assume that the join is computed using a block oriented, simple nested loop. What is the minimum number of memory buffer blocks required to do this join in exactly one pass?

## Part B:

How many memory blocks do we need to calculate  $\Pi_a R \cap \Pi_b S$  in one pass?

## Part C:

How many block reads do we need to compute the following query in one pass. Assume a naive evaluation plan (execute the intersection first, then the join)

SELECT a FROM
R JOIN
(SELECT b FROM R
INTERSECT
SELECT c FROM S);

Part A.

To do the join in one pass he need to have enough memory for the smallest table + 1 bbck.

$$B(2) = 10^{5}/10 = 10^{4}$$
 blocks

 $B(5) = \frac{2 \cdot 10^{3}}{10} = 2 \cdot 10^{2}$  blocks.

 $B(5) < B(R)$  Pead Sead Sead | block of R.

 $B(5) < B(R)$  Pead Sead | block of Remarks.

> We need B(S) + 1 block memory.

Cost = 
$$B(S) + \left[\frac{B(R) \cdot B(S)}{B(S)}\right]$$
  
=  $B(S) + B(R)$  memon for the join  
One pass!!


Part B.

To do this join we:

antherly — The Te-entherly

Seg. segn.

to do it in one parr ne need enough memony to either place TIBP in memory or TICS in memory. We don't know anything else about either eithibute.



Total Memory  $\geq \min(B(T_cS), B(T_bR)) + 2$ +  $B(T_cS \cap T_bR) + 1$ .