

Supplementary Material for: Federated O-RAN Slice SLA Prediction: A Cross-Architecture Empirical Benchmark on Colosseum/ColO-RAN

Hsiu-Chi Tsai, *Student Member, IEEE*

Cross-architecture federated-learning benchmark on Colosseum/ColO-RAN: per-section appendix material moved out of the main paper for length compliance with IEEE journal main-body conventions. Each section heading carries the originating main-paper section in parentheses.

APPENDIX A

MECHANISM ANALYSIS DETAILS (EXTENDS § 7.1)

A. Applicability boundary (extends § 7.1.3)

The empirical finding (natural-by-BS dominance and inverted α_{dir} monotonicity) is dataset-structural, not algorithm-mechanistic. We therefore expect it to replicate whenever a FL deployment satisfies (a) clients are partitioned along an axis on which the dataset has measurable distributional heterogeneity (here: `bs_id`), (b) the alternative partition strategy redistributes rows along an orthogonal axis that *does not* correspond to dataset structure (here: `slice_id`, which is statistically uniform across `bs_ids` in this corpus). Conversely, datasets where the natural client partition has uniform marginals on every axis would be expected to behave classically (lower $\alpha_{\text{dir}} \Rightarrow$ harder). We conjecture similar inversion will appear in other near-RT RIC forecasting workloads (uplink throughput-prediction, latency-budget breach prediction) where per-gNB telemetry distributions differ measurably; quantitative verification on additional corpora is open future work.

B. Hardware drift caveat for the § 7.1.1 ablation (extends § 7.1.4)

The § 7.1.1 `random_split` ablation cells were run on 4× Tesla V100-SXM2-32GB (sm_70, driver 535.161, CUDA 12.1) while the Phase 5 baseline (natural-by-BS and Dirichlet partitions) was run on RTX 4080 (sm_89). The two GPU generations have different bf16 implementations (V100 emulates bf16 via fp16 tensor cores with possible fp32 fallback; Lovelace has native bf16 tensor cores), and `cudnn_deterministic=True` pins kernel choice within a hardware target but does not impose bit-equivalence across hardware. We bound the resulting AUC drift by comparing V100 `random_split` AUC to 4080 Dirichlet $\alpha_{\text{dir}} = 5.00$ AUC (both are partition strategies that destroy bs grouping, so

they should yield equivalent AUC under hardware-independent training): the residual delta is at most 0.0072 (LSTM), 0.0043 (Mamba), 0.0021 (Spiking-SSM), all within the corresponding seed σ . Hardware drift is therefore bounded above by ~ 0.007 AUC, more than an order of magnitude smaller than the ~ 0.18 mechanism signal (ratio $\approx 25\times$). Strict elimination of hardware confound would require re-running Phase 5’s IID column on V100 (≈ 10 GPU-hours on the 4× cluster); we did not undertake this because the bounded-drift argument is sufficient to interpret § 7.1.1’s ablation conclusion.

APPENDIX B

REPRODUCIBILITY INFRASTRUCTURE DETAIL (EXTENDS § 5)

A. Test infrastructure (extends § 5.2)

The release ships **277 passing tests** across four suites that protect numerical and pipeline-level invariants:

- `tests/test_v7_*.py` — 202 unit + integration tests for `fl_v7` trainer (model-build, partition correctness, scaler determinism, FedDyn canonical-vs-Option-II contract).
- `tests/test_aggregate_v7_results.py` — 22 tests for the aggregator (paired-bootstrap, BLAKE2b decorrelation, JSON round-trip, schema-mismatch detection, 1260-cell scaling).
- `tests/test_paper_draft_invariants.py` — 37 paper-text invariants (forbidden hallucinated facts; required corrected facts; license consistency; hardware specs).
- `tests/test_paper_claims_sources.py` — 16 paper-vs-data claims tests that re-read `artifacts/step1_factfinding.json`, `step2_mechanism_search.json`, and `aggregated_phase5.json` and assert paper-reported numbers match the underlying measurements within rounding tolerance.

The latter two suites (53 tests total) form a paper-correctness developer pre-commit gate: every `PAPER_DRAFT.md` edit is verified by re-running them, preventing quick-claim regressions.

B. Statistical pipeline (extends §5.3)

`scripts/aggregate_v7_results.py` consumes the `per-cell_summary.json` files and produces `aggregated_phase5.json` (90 group means + 270 paired-bootstrap distributions: 180 algorithm-pairs + 90 architecture-pairs) plus a paper-grade Markdown table. Each pairwise comparison’s bootstrap RNG seed is derived from a BLAKE2b hash of the pair identifier added to a base seed (2026 for algorithm-pairs, 2027 for arch-pairs), guaranteeing independent bootstrap streams across all 270 distributions and supporting joint coverage claims (§4.5).

C. Croissant dataset metadata (extends §5.4)

The Colosseum/CoLO-RAN public release is upstream-licensed; our preprocessed `coloran_raw_unified.parquet` (≈ 18 M rows) and the partition specifications are documented in a Croissant 1.0 metadata file shipped with the release archive. The metadata block describes the (`bs_id`, `slice_id`, `sched`, `tr`) keying, the 17 continuous features (§3.1), the OOD train/val/test split (§3.3), and the `add_classification_target` derivation rule (§3.2).

D. Reproducible execution environment (extends §5.5)

The release archive bundles:

- `Dockerfile.repro` — pinned to the exact CUDA / PyTorch / `nvidia-ml-py` versions used in Phase 5 (CUDA 12.8, PyTorch 2.10, `nvidia-ml-py` 12.x);
- `requirements.lock` — SHA256-pinned Python dependencies (74 packages);
- `repro.sh` — one-line entry point that loads the `parquet`, runs a 1-cell smoke (LSTM, FedAvg, IID, `seed=42`, 5 rounds $\times$ 20 max-steps, ~ 30 s on RTX 4080), and verifies bit-equivalent test AUC against a stored reference value within 10^{-6} .

E. Demo notebook (extends §5.6)

A Jupyter notebook (`notebooks/colosseum_oran_federated_slicing_demo.ipynb`) walks through (a) loading aggregator JSON, (b) reproducing Figures 1–3, (c) running a downscaled smoke version of the §7.1.1 `random_split` ablation on a single GPU (the full ablation runs on the $4\times$ V100 setup documented in App. A–B), and (d) regenerating §6 paired-bootstrap CI_{95} from raw cells. The notebook is the recommended onboarding entry point for downstream researchers extending the benchmark.

on CoLO-RAN (LSTM, Mamba, Spiking-SSM) whose pre-registered hardware budget, precision policy, and gradient-step count are inherited by Phase 5 (the federated extension reported in this paper). “ADR-001 D-N” denotes the N -th preregistered design decision in the project’s Architecture Decision Record. Both artefacts are documented in the release archive for downstream reproduction.

A. L9 full discussion: `pos_weight_split=train` choice (extends §8 L9)

We compute the BCE positive-class weight from the train partition’s positive rate (per ADR-001 D-12), in line with standard practice that prevents test-set positive-rate from leaking into the loss. Two alternative computations (val-derived `pos_weight`; held-out-fold `pos_weight`) would also be valid and might shift absolute AUC numbers slightly, but per §7.1 our V100 `random_split` ablation confirms the inverted- α_{dir} mechanism direction is robust to the partition-axis shuffle, and the BCE loss reweighting is identical (globally pooled) across all clients regardless of which split the rate is computed from — so the *direction* of all our findings is invariant to this choice.

B. L10 full discussion: `bf16` mixed-precision training versus `fp32` (extends §8 L10)

All Phase 5 cells use `bf16` mixed precision per the Stage 1 inheritance contract for memory and throughput on RTX 4080. The numerical-precision gap between `bf16` and `fp32` is bounded for our model architectures by the lack of overflow-prone operations (no exponential losses, no large-fan-in matmul without LayerNorm); we do not report a `fp32` verification cell and treat `bf16` vs `fp32` cross-check as a reproducibility-supplementary item for the camera-ready archive. Readers reproducing on hardware without native `bf16` (Pascal `sm_60` and earlier) should expect $O(0.001)$ AUC drift.

C. L11 full discussion: `per-client` compute budget split (extends §8 L11)

Our (round, max_steps) configuration matches Stage 1’s audit-corrected 25 000 total-gradient-steps budget. An alternative split (e.g., 50 rounds $\times$ 100 max-steps, 200 rounds $\times$ 25 max-steps) would shift the round-vs-step ratio and potentially affect server-side aggregation count by 2–4 $\times$; we did not sweep this dimension, treating round count as a fixed reproducibility anchor. Whether the FedAdam-saturates-headroom finding (§6.3) survives at $4\times$ more rounds with proportionally fewer steps per round is open.

D. L12 full discussion: SLA-threshold sensitivity (extends §8 L12)

The 10% BLER threshold is the canonical CoLO-RAN SLA gate [1]; the empirical positive rate at this threshold on the train partition is 30.9% (§7.1 setup-level facts). A threshold sweep over 5% / 15% / 20% would test whether the inverted- α_{dir} monotonicity strengthens at sparser-positive regimes (where any structural specialisation has higher loss-leverage) and weakens at higher thresholds; we did not run

APPENDIX C

EXTENDED LIMITATIONS AND THREATS TO VALIDITY (EXTENDS §8)

Each subsection below holds the full prose of an §8 limitation whose main-paper bullet was condensed to a 1–2 sentence headline. The §1 contribution(s) each item threatens are stated in the main-paper §8 bullet headers.

A note on internal references in C.1–C.6: “Stage 1” refers to the predecessor centralized 3-architecture benchmark

this sweep but predict (a) inversion strengthens as threshold tightens and (b) inversion weakens or disappears as threshold approaches the symmetric 50% regime. This is the highest-leverage open ablation for the camera-ready revision after § 7.1.1.

E. L13 full discussion: bootstrap CI percentile vs BCa (extends § 8 L13)

§ 4.5 explains the choice: at our $n = 10$ paired seeds with approximately symmetric per-seed delta distributions, the bias-correction term in the BCa interval is bounded above by $O(1/\sqrt{n}) \approx 0.32$ standard errors; this magnitude is smaller than our seed σ on every reported finding except § 6.4’s Mamba×SCAFFOLD interaction, where σ inflation by $23\times$ makes the CI choice less consequential than the Wilcoxon p -value. Readers who prefer BCa should treat our CI_{95} as a slightly tighter version of the BCa interval; the qualitative conclusions are unchanged.

F. L14 full discussion: FedAdam hyperparameter sensitivity (extends § 8 L14)

$\beta_1 = 0.9$, $\beta_2 = 0.99$, $\eta_{\text{server}} = 0.01$ follow the FedAdam paper’s preregistered values [2]; $\beta_2 = 0.99$ differs from canonical Adam’s 0.999. We did not run a $(\beta_1, \beta_2, \eta_{\text{server}})$ sensitivity sweep — the FedAdam-vs-FedAvg deltas reported in § 6.3 are anchored to paper-canonical hyperparameter choices rather than to a per-task hyperparameter optimum. Whether the FedAdam-saturates-headroom finding survives at alternative β_2 (e.g., 0.999) is open; we expect modest sensitivity (≤ 0.005 AUC drift) given Adam’s relative robustness to β_2 variation in offline ML literature, but this is anticipated, not measured.

APPENDIX D

FUTURE WORK DIRECTIONS (EXTENDS § 9.1)

Several open questions remain. **First**, § 7.1.5 disambiguates the inverted- α_{dir} mechanism (the strong reading of § 7.1.1 (i) — bs grouping alone suffices — is refuted; (ii) per-client structural coherence is the additional necessary ingredient), but two design constraints (`sub_per_bs=2` halving per-client data, 5/14 sampling fraction vs Phase 5’s 5/7) prevent a clean decomposition of the 1–4 pp residual gap to natural-by-BS; an isolation re-run keeping `sub_per_bs=2` while bumping `clients-per-round` to 10 (matches Phase 5’s 5/7 sampling fraction at the doubled client count) would isolate the slice-mixing effect from per-round participation, following the non-IID-impact assessment methodology of Jimenez-Gutierrez et al. [3] and the proximity-partition framing of ProFed [4]. **Second**, our 10% BLER threshold should be perturbed to {5, 15, 20}% to confirm operational robustness, in line with recent rare-event metric-stability work [5]. **Third**, scaling beyond $N = 7$ base stations to the larger- N 6G slicing and edge-FL regimes studied by Chiarani et al. [6] and Sezgin et al. [7] would test whether inverted- α_{dir} is a small- N artefact. **Fourth**, the FedAdam headroom-saturation finding may be soft: variance-aware sharpness methods such as FedSCAM [8] and synthetic-data-guided FedSynSAM [9]

introduce per-client perturbation modulation that could extract additional accuracy. **Fifth**, integrating differential privacy via over-the-air channel noise [10] and exploring neuromorphic edge deployment — both sparse-RNN acceleration on Loihi-class accelerators [11] and spiking-NN low-power edge sensing [12] — would close the loop toward production-deployable privacy-preserving energy-efficient O-RAN slice prediction.

REFERENCES

- [1] M. Polese, L. Bonati, S. D’Oro, S. Basagni, and T. Melodia, “CoO-RAN: Developing machine learning-based xApps for Open RAN closed-loop control on programmable experimental platforms,” *IEEE Transactions on Mobile Computing*, 2022.
- [2] S. J. Reddi, Z. Charles, M. Zaheer, Z. Garrett, K. Rush, J. Konečný, S. Kumar, and H. B. McMahan, “Adaptive federated optimization (FedAdam),” in *ICLR*, 2021.
- [3] D. M. Jimenez-Gutierrez, M. Hassanzadeh, A. Anagnostopoulos, I. Chatzigiannakis, and A. Vitaletti, “A thorough assessment of the non-IID data impact in federated learning,” 2025, arXiv:2503.17070.
- [4] D. Domini, G. Aguzzi, and M. Viroli, “ProFed: a benchmark for proximity-based non-IID federated learning,” 2025, arXiv:2503.20618.
- [5] E. Minus, R. Y. Coley, S. M. Shortreed, and B. D. Williamson, “Rare-event metric stability under threshold perturbation,” 2025, arXiv:2504.16185.
- [6] M. Chiarani, S. Roy, C. Verikoukis, and F. Granelli, “XAI-driven client selection for FL in scalable 6G network slicing,” 2025, arXiv:2503.12435.
- [7] Y. E. Sezgin, M. Özdem, and T. Bilen, “Federated edge learning for predictive maintenance in 6G small cell networks,” 2025, arXiv:2509.11421.
- [8] “FedSCAM: Sharpness-aware clustering for federated learning,” 2026, arXiv:2601.00853 (Jan 2026).
- [9] Y. Gu, R. Jin, Z. Zhang, and H. Dai, “Gradient compression may hurt generalization: A remedy by synthetic data guided sharpness aware minimization,” 2026, arXiv:2602.11584; introduces the FedSynSAM method.
- [10] H. Liang, H. Wen, K. Wu, and H. Xing, “Differential privacy as a perk: Federated learning over multiple-access fading channels with a multi-antenna base station,” 2026, arXiv:2510.23463.
- [11] A. Pierro, S. Abreu, J. Timcheck, P. Stratmann, A. Wild, and S. B. Shrestha, “Accelerating linear recurrent neural networks for the edge with unstructured sparsity,” in *ICML*, 2025, arXiv:2502.01330.
- [12] G. O. Y. L.-F. Lundstrom-Imanov and T. Yilmaz, “EdgeSpike: Spiking neural networks for low-power autonomous sensing in edge IoT architectures,” 2026, arXiv:2604.27004.