# Writing a Python Script

# Our First Program

# Our First Program

**Convert a temperature given in degrees Fahrenheit to Celsius**

# Our First Program

**Convert a temperature given in degrees Fahrenheit to Celsius**

$$t_C = (t_F - 32) \times \frac{5}{9}$$

# Our First Program

**Convert a temperature given in degrees Fahrenheit to Celsius**

$$t_C = (t_F - 32) \times \frac{5}{9}$$

$t_C$: degrees Celsius

# Our First Program

**Convert a temperature given in degrees Fahrenheit to Celsius**

$$t_C = (t_F - 32) \times \frac{5}{9}$$

$t_C$: degrees Celsius

$t_F$: degrees Farenheit

# Our First Program

**Convert a temperature given in degrees Fahrenheit to Celsius**

$$t_C = (t_F - 32) \times \frac{5}{9}$$

$t_C$: degrees Celsius

$t_F$: degrees Farenheit

```
>>> tF = 50
```

# Our First Program

**Convert a temperature given in degrees Fahrenheit to Celsius**

$$t_C = (t_F - 32) \times \frac{5}{9}$$

$t_C$: degrees Celsius

$t_F$: degrees Farenheit

```
>>> tF = 50
```

```
>>> tC = ?
```

# Converting to Kelvins

# Converting to Kelvins

$$t_K = t_C - 273.15$$

# Converting to Kelvins

$$t_K = t_C - 273.15$$

$t_K$: temperature in Kelvins

# Basic Program Structure

# Basic Program Structure



# Basic Program Structure



```
x = (input / 56.7) ** 2.5
y = x + 57.0 % 6
z = (x + y) / 2.0
z = z + 4 * x ** 2
```

# Basic Program Structure



```
x = (input / 56.7) ** 2.5
y = x + 57.0 % 6
z = (x + y) / 2.0
z = z + 4 * x ** 2
```

# Developer's Cycle

# Developer's Cycle



# Developer's Cycle



# Developer's Cycle



# Developer's Cycle