

ParMOO: A Python library for parallel multiobjective simulation optimization

Tyler Chang^a and Stefan Wild^{a,b}

^aMathematics and Computer Science Division,
Argonne National Laboratory

^bApplied Mathematics and Computational Research Division,
Lawrence Berkeley National Laboratory

SIAM CSE 23

Outlines

Introduction to MOSO + my experience

3 challenges + solutions

ParMOO software design + release

Example Problems


Conclusions + some closing thoughts

Multiobjective Optimization Problems


$$\min_{x \in \mathcal{X}} F(x)$$

Multiojective Optimization Problems

$$\min_{x \in \mathcal{X}} F(x)$$




$$F : \mathcal{X} \rightarrow \mathcal{Y}$$




Multiobjective Optimization Problems

$$\min_{x \in \mathcal{X}} F(x)$$



$$F : \mathcal{X} \rightarrow \mathcal{Y}$$

expensive
blackbox process




Multiobjective Response Surface Methodology

or Model-Based Optimization or Active Learning


Multiobjective Response Surface Methodology

or Model-Based Optimization or Active Learning





Multiobjective Response Surface Methodology

or Model-Based Optimization or Active Learning






Multiobjective Response Surface Methodology

or Model-Based Optimization or Active Learning




Multiobjective Response Surface Methodology

or Model-Based Optimization or Active Learning







Simulation 1 output




Simulation 2 output

Multiobjective Response Surface Methodology

or Model-Based Optimization or Active Learning




Simulation 1 output



Simulation 2 output

Example: HPC Performance Tuning




VT VarSys Project – 40 runs of HPL



ANL – LCRC Computing Resources: Bebop

Example: HPC Performance Tuning




VT VarSys Project – 40 runs of HPL



ANL – LCRC Computing Resources: Bebop

```
HPL.dat
HPLpack benchmark input file
Innovative Computing Laboratory, University of Tennessee
HPL.out
output file name (if any)
0
device set (0=cpu, 1=gpu, 2=hybrid)
4
# of problems sizes (N)
20 30 34 35
N
4
# of Hb
4
2 3 4
N
0
PMAP process mapping (0=Row-major, 1=Column-major)
3
# of process grids (P x Q)
2 3 4
P
2 4 1
Q
16.0
threshold
0 3 2
PFACTS (0=left, 1=Cross, 2=right)
# of recursive stopping criterion
2 4
NRANKS (0=1)
# of panels in recursion
12
NRANKS
# of recursive panel fact.
0 3 2
PFACTS (0=left, 1=Cross, 2=right)
# of broadcast
0
RCASTS (0=left, 1=Cross, 2=right, 3=2P, 4=2Q, 5=4P)
# of localized KSPs
1
DEPTHs (0=0)
# of
64
mapping threshold
0
L1 is (0=transposed, 1=non-transposed) form
0
L1 is (0=transposed, 1=non-transposed) form
1
Equilibrate (0=No, 1=yes)
0
memory alignment in double (> 0)
```

VTMOP solver



[1] Chang, Larson, and Watson. Multiobjective optimization of the variability of the high-performance LINPACK solver. In Proc. WSC 2020.

Challenge 1: mixed vars + problem types

Example: Particle Accelerator Design

Example: Parallel Runs

Challenge 2: parallel evals + computing environments

Design goals:

1. Highly customizable framework for multiobjective RSM
2. Exploit structure and domain knowledge simulation-based optimization problems
3. Flexible problem types (mixed-variables, constraints, etc.)

ParMOO Design Criteria


Design goals:

1. Highly customizable framework for multiobjective RSM
2. Exploit structure and domain knowledge simulation-based optimization problems
3. Flexible problem types (mixed-variables, constraints, etc.)


Design constraints:

1. Easy to deploy (parallelism, checkpointing, logging, flexibility)
2. Easy to maintain and extend
3. Easy to use (clean interfaces)

ParMOO uses an object-oriented framework:




ParMOO uses an object-oriented framework:




- ▶ Search/DOE
- ▶ Surrogate model
- ▶ Acquisition function
- ▶ Single-obj solver

Simulation Structure




Design space

Objective Functions



Objective space

Simulation Structure




Design space

Simulations



\mathcal{S}

Objectives



Objective space

Simulation Structure

Simulation Structure

$$f_i(x) = h_i(x, S(x)) \quad i = 1, \dots, o$$

Simulation Structure

$$f_i(x) = h_i(x, S(x)) \quad i = 1, \dots, o$$

Sum-of-squares structure:

$$h_i(x, S(x)) = \sum_{j \in N_i} (S_j(x))^2$$

where each N_1, \dots, N_o is an index set.

Increases order of approximation \Rightarrow
increases order of convergence

Simulation Structure

$$f_i(x) = h_i(x, S(x)) \quad i = 1, \dots, o$$

Sum-of-squares structure:

$$h_i(x, S(x)) = \sum_{j \in N_i} (S_j(x))^2$$

where each N_1, \dots, N_o is an index set.

Increases order of approximation \Rightarrow
increases order of convergence

Heterogeneous MOOPs:

$$h_1(x, S(x)) = S_1(x)$$

$$h_2(x, S(x)) = \|x\|^2$$

Use expensive surrogate models for h_1 (i.e., S_1) but not for h_2

Flexible Problem Types

Flexible Problem Types

- ▶ Mixed variable-types

Flexible Problem Types

- ▶ Mixed variable-types **Ex: categorical variables**

Flexible Problem Types



- ▶ Mixed variable-types **Ex: categorical variables**
 - ▶ Focus on *embedding* into continuous space

Flexible Problem Types

- ▶ Mixed variable-types **Ex: categorical variables**
 - ▶ Focus on *embedding* into continuous space
- ▶ (Nonlinear) constraints

Flexible Problem Types

- ▶ Mixed variable-types **Ex: categorical variables**
 - ▶ Focus on *embedding* into continuous space
- ▶ (Nonlinear) constraints
 - ▶ Focus on *augmented Lagrangian* penalties (relax to augmented unconstrained problem)



Design constraints

Design constraints

Easy to use:

- ▶ OOP gives a clean interface for adding attributes to a MOOP instance
- ▶ Total modularity (free to mix-and-match)

Design constraints

Easy to use:

- ▶ OOP gives a clean interface for adding attributes to a MOOP instance
- ▶ Total modularity (free to mix-and-match)

Easy to deploy:

- ▶ Simulation/experiment evaluations are only called in the `MOOP.solve()` method
- ▶ Extend MOOP class and overwrite `solve()` to deploy in different workflows
- ▶ **Ex:** Deploy parallel solvers on HPC systems using `libEnsemble`

Design constraints

Easy to use:

- ▶ OOP gives a clean interface for adding attributes to a MOOP instance
- ▶ Total modularity (free to mix-and-match)

Easy to deploy:

- ▶ Simulation/experiment evaluations are only called in the `MOOP.solve()` method
- ▶ Extend MOOP class and overwrite `solve()` to deploy in different workflows
- ▶ **Ex:** Deploy parallel solvers on HPC systems using `libEnsemble`

Easy to maintain and extend:

- ▶ OOP + total modularity makes adding new features easy
- ▶ Agile development with continuous integration
- ▶ Well-documented interface, contributing, and release process

ParMOO Release



Written in Python (available on pip and GitHub)



<https://parmoo.readthedocs.io/en/latest/quickstart.html>



Combine with `libEnsemble` to use parallel solvers

Chang and Wild. ParMOO: A Python library for parallel multiobjective simulation optimization. *JOSS* 8(82):4468 (2023).

Example 1: Fayans EDF Model Calibration

Find params $x \in [0, 1]^{13}$ to fit the Fayans model to data d_i :

$$M(\xi_i; x) \approx d_i \quad i = 1, \dots, 198$$

ParMOO simulation:

$$S_i(x) = M(\xi_i; x) - d_i, \quad i = 1, \dots, 198;$$


Min SOS across 3 observable classes

$$F_t = \sum_{i=1}^{m_t} (S_{t,i}(x))^2$$

Bollapragada et al. Journal of Physics G: Nuclear and Particle Physics 48(2), 2020.

Fayans Solution with ParMOO

- ▶ Approximated Fayans model using inv dist weighting on existing dataset
- ▶ Implemented parallel solver in ParMOO using libEnsemble
- ▶ Just **14-25 lines of Python code**
- ▶ Ran for **10K** sim evals
- ▶ Compared against same solver w/o exploiting SOS structure



Example 2: Material Manufacturing with ParMOO

Choose optimal settings for material manufacturing in a continuous flow reactor (CFR)

We know how to make a desired material, need to produce at scale:

1. **Maximize the product** (battery electrolyte: TFML)
2. Can increase temperature to **reduce reaction time**
3. Too much heat activates a side reaction; need to **minimize unwanted byproduct**

Challenges:

- ▶ Mixed variable types
- ▶ Heterogeneous objectives
- ▶ Must send experiments to run on CFR

CFR Optimization with ParMOO


Extend MOOP class to send/receive experiment data using MDML library (Apache Kafka)

Used categorical variable embeddings

Modeled Product/Byproduct as simulations and reaction time using algebraic equation of input



Pareto Front



Next Release

Coming in v. 0.2

- ▶ Interactive post-run visualization tools
- ▶ Support for customized embeddings and passing raw (unscaled) inputs
- ▶ MDML (Apache Kafka) interface for distributing simulation evaluations
- ▶ (Maybe) advanced techniques for design-of-experiments

Resources

E-mail: `tchang@anl.gov`

E-mail: `parmoo@mcs.anl.gov`

JOSS 8(82):4468 (2023)

GitHub: `github.com/parmoo/parmoo`

Docs: `parmoo.readthedocs.io`

PyPI: `pip install parmoo`

This material is based upon work supported by the U.S. Department of Energy, Office of Science, Office of Advanced Scientific Computing Research, SciDAC program under contract number DE-AC02-06CH11357.