

# Data sampling for surrogate modeling and optimization

Tyler Chang  
(and others)

Argonne National Laboratory

ICIAM 2023, Tokyo, Japan  
Aug 23, 2023

# Outlines


Inference problems, the curse of dimensionality, and measure collapse

Modeling for high-dimensional optimization

Applications


# The fundamental machine learning problem

# The fundamental machine learning problem




- Want to predict unknown  $f(x)$  for observation  $x$

# The fundamental machine learning problem




- ▶ Want to predict unknown  $f(x)$  for observation  $x$
- ▶ **ML**: Learn approximation  $\hat{f} \sim f$  based on *training data*  $\mathcal{X}$
- ▶ **NA**: fit an interpolant (piecewise-linear) to  $f$  on  $\mathcal{X}$

# The fundamental machine learning problem




- ▶ Want to predict unknown  $f(x)$  for observation  $x$
- ▶ **ML**: Learn approximation  $\hat{f} \sim f$  based on *training data*  $\mathcal{X}$
- ▶ **NA**: fit an interpolant (piecewise-linear) to  $f$  on  $\mathcal{X}$
- ▶ Both cases: more data  $\Rightarrow$  better  $\hat{f}$

# The fundamental machine learning problem



- ▶ Want to predict unknown  $f(x)$  for observation  $x$
- ▶ **ML**: Learn approximation  $\hat{f} \sim f$  based on *training data*  $\mathcal{X}$
- ▶ **NA**: fit an interpolant (piecewise-linear) to  $f$  on  $\mathcal{X}$
- ▶ Both cases: more data  $\Rightarrow$  better  $\hat{f}$
- ▶ Real data not perfectly balanced  $\Rightarrow \hat{f} \rightarrow f$  non-uniformly

# The fundamental machine learning problem



- ▶ Want to predict unknown  $f(x)$  for observation  $x$
- ▶ **ML**: Learn approximation  $\hat{f} \sim f$  based on *training data*  $\mathcal{X}$
- ▶ **NA**: fit an interpolant (piecewise-linear) to  $f$  on  $\mathcal{X}$
- ▶ Both cases: more data  $\Rightarrow$  better  $\hat{f}$
- ▶ Real data not perfectly balanced  $\Rightarrow \hat{f} \rightarrow f$  non-uniformly
- ▶ If we have enough data, it doesn't matter




# Some basic numerical analysis results

When  $\hat{f}$  is a piecewise linear spline:

For  $h$  “small enough” – let  $q$  be the query point

$$|f(q) - \hat{f}(q)| \sim \mathcal{O}(h^2)$$




- ▶  $h$  is a “mesh fineness” parameter  $\sim$  distance between points in  $\mathcal{X}$
- ▶ For irregular  $\mathcal{X}$ ,  $h$  could be the distance from  $q$  to the nearest neighbor in  $\mathcal{X}$
- ▶ Constants proportional to the Lip constant of  $\nabla f$

# Some basic numerical analysis results

When  $\hat{f}$  is a piecewise linear spline:

For  $h$  “small enough” – let  $q$  be the query point

$$|f(q) - \hat{f}(q)| \sim \mathcal{O}(h^2)$$




- ▶  $h$  is a “mesh fineness” parameter  $\sim$  distance between points in  $\mathcal{X}$
- ▶ For irregular  $\mathcal{X}$ ,  $h$  could be the distance from  $q$  to the nearest neighbor in  $\mathcal{X}$
- ▶ Constants proportional to the Lip constant of  $\nabla f$

## Some basic deep learning


- ▶ Train a fully-connected multi-layer perceptron (MLP) using  $\mathcal{X}$
- ▶ The most popular activation function is ReLU (piecewise linear)
- ▶ In modern ML, train as close to zero error as possible (interpolate)

# Some basic deep learning


- ▶ Train a fully-connected multi-layer perceptron (MLP) using  $\mathcal{X}$
- ▶ The most popular activation function is ReLU (piecewise linear)
- ▶ In modern ML, train as close to zero error as possible (interpolate)



# The curse of dimensionality




10 training points in 1D




10 training points in 2D

# The curse of dimensionality no data



Need data in all quadrants?

# The curse of dimensionality no data



Need data in all quadrants?

- ▶ Inference in 2D :  $2^2 = 4$
- ▶ Inference in 10D :  $2^{10} \approx 1000$
- ▶ Inference in 100D :  $2^{100} \approx 10^{30}$  (orders of magnitude bigger than exascale)
- ▶ Many ML problems : inference in 1000+ dimensions

## Measure collapse

Can we still make good predictions where we **do** have data?



## Measure collapse

Can we still make good predictions where we **do** have data?

**No, because we have no data anywhere**

We measure where we *might* have enough data to make a prediction using the “convex hull” of the training data  $CH(\mathcal{X})$

# Measure collapse

Can we still make good predictions where we **do** have data?

**No, because we have no data anywhere**

We measure where we *might* have enough data to make a prediction using the “convex hull” of the training data  $CH(\mathcal{X})$

If  $\mathcal{X}$  are sampled from *any* distribution,  $\mu(CH(\mathcal{X})) \rightarrow 0$  *exponentially* as  $d$  grows

This is called a *concentration of measure*

Gorban and Tyukin, Stochastic separation theorems. *Neural Networks* 94, pp. 255-259 (2017).

## Example

Suppose that we uniformly sample  $x = (x_1, x_2, \dots, x_d)$  from  $[0, 1]^d$



$$\|x - \frac{1}{2}\|_2^2 = \sum_{i=1}^d (x_i - \frac{1}{2})^2.$$

$$\mathbb{E} \left[ \left( x_i - \frac{1}{2} \right)^2 \right] = \int_0^1 \left( u - \frac{1}{2} \right)^2 du = \frac{1}{12}$$

with finite variance  $v$

By CLT for all  $x \in \mathcal{X}$ :  $\mathbb{E}[\|x - \frac{1}{2}\|_2^2] = \frac{d}{12}$  with variance  $\frac{v}{d} \rightarrow 0$  as  $d \rightarrow \infty$ .

# Collapse of some common distributions





Garg, Chang, and Raghavan, Stochastic optimization of Fourier coefficients to generate space-filling designs. *To appear in Winter Sim 2023.*

**“There’s more to machine learning than function approximation”**

## Representation learning solution


“There’s more to machine learning than function approximation”

- ▶  $f$  is often highly *structured* – MLPs with nothing else are from the 60s





$28 \times 28$  pixels  $\neq$  784 dimensions...

# Modern deep learning pipeline




# Multiobjective Black-Box Optimization





# General Workflow and Data Acquisition





# Global optimization

In global optimization literature...


- ▶ Balance exploration vs. exploitation
- ▶ Drive *global model error* to zero
- ▶ Need exponentially many samples to guarantee global convergence

Guarantees convergence for problems with thousands of local minima




# Local optimization

- ▶ Only exploit – maybe multi-start or large initial search
- ▶ Fit a model that is *locally accurate*
  - ▶ Sample requirement grows only *linearly with dimension*
- ▶ Modification is as simple as putting a *trust-region* around interesting points




# Local optimization

- ▶ Only exploit – maybe multi-start or large initial search
- ▶ Fit a model that is *locally accurate*
  - ▶ Sample requirement grows only *linearly with dimension*
- ▶ Modification is as simple as putting a *trust-region* around interesting points




# Local optimization

- ▶ Only exploit – maybe multi-start or large initial search
- ▶ Fit a model that is *locally accurate*
  - ▶ Sample requirement grows only *linearly with dimension*
- ▶ Modification is as simple as putting a *trust-region* around interesting points



# Local optimization

- ▶ Only exploit – maybe multi-start or large initial search
- ▶ Fit a model that is *locally accurate*
  - ▶ Sample requirement grows only *linearly with dimension*
- ▶ Modification is as simple as putting a *trust-region* around interesting points





Written in Python

Version 0.3.0 is now available on available on pip,  
conda-forge, and GitHub


<https://github.com/parmoo/parmoo>

<https://parmoo.readthedocs.io>



# Chemical Design on a Limited Budget


- ▶ 6-dimensional latent space embedding of a mixed-variable problem
- ▶ 3-objectives electrolyte manufacturing
  - ▶ high yield, minimal byproduct, low reaction times
- ▶ Running real-world experiments with very limited budget






# Fayans Model Calibration (Inverse Problem)

- ▶ 13-variable, 3-objective problem
- ▶ Higher dimensional, requires trust-region methods



# Particle Accelerator Beam Design

- ▶ 22-variable, 2-objective problem
- ▶ 3 physics constraints, nearly impossible to satisfy
- ▶ Matched well-known reference gun geometry with just **1300** true simulation evaluations



Chen, Chang, et al. An Integrated Multi-Physics Optimization Framework for Particle Accelerator Design. *Under review.*

## Some Conclusions

- ▶ Doing anything global (modeling, optimization, etc.) in high-dimensions is very hard (maybe impossible)
- ▶ Easier to identify low-dimensional structures and model these *locally*
  - ▶ In my experience, giving up global accuracy is the only thing that scales to big problems
- ▶ Some problems (optimization) don't necessarily require global accuracy
  - ▶ Don't demand it if you don't need it!
- ▶ Optimization rarely truly requires global accuracy

## Some Conclusions

- ▶ Doing anything global (modeling, optimization, etc.) in high-dimensions is very hard (maybe impossible)
- ▶ Easier to identify low-dimensional structures and model these *locally*
  - ▶ In my experience, giving up global accuracy is the only thing that scales to big problems
- ▶ Some problems (optimization) don't necessarily require global accuracy
  - ▶ Don't demand it if you don't need it!
- ▶ Optimization rarely truly requires global accuracy
- ▶ *But there are other problems that do require global accuracy...*

## References

*Garg, Chang, and Raghavan. Stochastic optimization of Fourier coefficients to generate space-filling designs. To appear in Winter Sim 2023.*

*Chang and Wild. ParMOO: A Python library for parallel multiobjective simulation optimization. JOSS 8(82):4468 (2023).*

*Chang and Wild. Designing a framework for solving multiobjective simulation optimization problems. Under Review, ArXiv preprint 2304.06881 (2023).*

*Chang et al. A framework for fully autonomous design of materials via multiobjective optimization and active learning: challenges and next steps. In ICLR 2023, Workshop on ML4Materials.*

*Chen, Chang, et al. An Integrated Multi-Physics Optimization Framework for Particle Accelerator Design. Under review.*

## Resources

GitHub: `github.com/parmoo/parmoo`

Pip: `pip install parmoo`

Conda: `conda install --channel=conda-forge parmoo`

Test problems: `github.com/parmoo/parmoo-solver-farm`

`tchang@anl.gov`

This material is based upon work supported by the U.S. Department of Energy, Office of Science, Office of Advanced Scientific Computing Research, SciDAC program under contract number DE-AC02-06CH11357.