A simple neural classifier

Antoine Bosselut







Section Outline

- Setting up an NLP problem
- Embeddings how do we represent sequences of discrete words?
- Model how do we compose our embeddings into higher-level representations?
- **Prediction** how do we map our model's representation of the task to a prediction?

• Example: Convert a sentence describing a movie review to a sentiment



• Example: Convert a sentence describing a movie review to a sentiment



I really enjoyed the movie we watched on Saturday!

Question

What words should we model as vectors?

Choosing a vocabulary

- Language contains many words (e.g., ~600,000 in English)
 - What about other tokens: Capitalisation? Accents ? Typos!? Words in other languages!? In other scripts!? Emojis !? Unicode !?
 - Millions of potential unique tokens! Most rarely appear in our training data (Zipfian distribution)
 - Model has limited capacity

Choosing a vocabulary

- Language contains many words (e.g., ~600,000 in English)
 - What about other tokens: Capitalisation? Accents? Typos!? Words in other languages!? In other scripts!? Emojis!? Unicode!?
 - Millions of potential unique tokens! Most rarely appear in our training data (Zipfian distribution)
 - Model has limited capacity
- How should we select which tokens we want our model to process?
 - Week 11 tokenisation!
 - For now, initialize a vocabulary V of tokens that we can represent as a vector
 - Any token not in this vocabulary V is mapped to a special <UNK> token (e.g., unknown).

Question

How should we model a word as a vector?

One upon a time: sparse word representations

- Define a vocabulary V
- Each word in the vocabulary is represented by a sparse vector
- Dimensionality of sparse vector is size of vocabulary (e.g., thousands, possibly millions)

$$x_i \in \{0,1\}^V$$

Word Vector Composition

 To represent sequences, beyond single words, define a composition function over sparse vectors

```
I really enjoyed the movie! —— [1...1101...01] Simple Counts
```

```
I really enjoyed the movie! ——> [0.01 ... 0.1 0.1 0 0.001 ... 0 0.5]
```

Weighted by
Corpus Statistics
(e.g., TF-IDF)

Many others...

Problem

With sparse vectors, similarity is a function of common words!


How do you learn learn similarity between words?

```
enjoyed → [0...001...00]

loved → [0...1...0000]
```

sim(enjoyed, loved) = 0

Embeddings Goal



How do we train semantics-encoding embeddings of words?

Dense Word Vectors

- Represent each word as a high-dimensional*, real-valued vector
 - $*Low-dimensional compared to V-dimension sparse representations, but still usually <math>O(10^2 10^3)$

```
| → [0.113 -0.782 1.893 0.984 6.349 ...]
| really → [0.906 0.661 -0.214 -0.894 -0.880 ...]
| enjoyed → [-0.842 0.647 -0.882 0.045 0.029 ...]
| the → [0.100 0.765 -0.333 -0.538 -0.150 ...]
| movie → [0.104 -0.054 -0.268 -0.877 0.005 ...]
| : → [0.439 -0.577 -0.727 0.261 0.699 ...]
```

word vectors

word embeddings


neural embeddings

dense embeddings

others...


Similarity of vectors represents similarity of meaning for particular words

ullet For each sequence S, we have a corresponding sequence of embeddings X



S = I really enjoyed the movie we watched on Saturday!

ullet For each sequence S, we have a corresponding sequence of embeddings X




 $S_1 = 1$ really enjoyed the movie we watched on Saturday!

• Embeddings $x_t \in X$ are indexed from shared embedding dictionary $\mathbb E$ for all items in vocabulary V

$$S_{2}=$$
 We **really** loved a film **we** saw last Sunday !

Bolded words would index the same embedding in **E**


ullet For each sequence S, we have a corresponding sequence of embeddings X



Question

What should we use as a model?


• Our model modifies and / or composes these word embeddings to formulate a representation that allows it to predict the correct label



S= I really enjoyed the movie we watched on Saturday!

- Our model modifies and / or composes these word embeddings to formulate a representation that allows it to predict the correct label
 - Recurrent neural networks (RNNs) and variants (LSTM, GRU) Week 2
 - Self-attention & Transformer Week 3
 - State-space Models (not covered in this course)
 - Multiple of the above ?


- Our model modifies and / or composes these word embeddings to formulate a representation that allows it to predict the correct label
 - Recurrent neural networks (RNNs) and variants (LSTM, GRU) Week 2
 - Self-attention & Transformer Week 3
 - State-space Models (not covered in this course)
 - Multiple of the above ?
 - Or perhaps something super simple: Sum-pool, Avg-pool, Max-pool?




Question

How do we convert the output of our model to a prediction?

Predicting the label



Predicting the label



S = I really enjoyed the movie we watched on Saturday!

Learn using backpropagation:

compute gradients of loss with respect to initial embeddings *X*

Learn embeddings that allow you to do the task successfully!


$$X = \{x_0, x_1, \dots, x_T\}$$

Question

How could we use our model for tasks beyond classification?

Sequence Labeling


• Example: Identify which words correspond to sentimental words



S=1 really enjoyed the movie we watched on Saturday!

Sequence Labeling


• Example: Identify which words correspond to sentimental words




S= I really enjoyed the movie we watched on Saturday!

Sequence Labeling

• Example: Identify which words correspond to sentimental words




• Example: Generate the next sentence in the review.




S= I really enjoyed the movie we watched on Saturday!


• Example: Generate the next sentence in the review. Word-by-word!



Example: Generate the next sentence in the review. Word-by-word!



• Example: Generate the next sentence in the review. Word-by-word!




Comprehension Questions

 What are the learnable parameters in our system?

Embeddings E

Logistic Regression matrix W_o




I enjoyed the movie I watched on Saturday

Comprehension Questions

- What are the learnable parameters in our system?
- How many unique embeddings are in X for this example sentence S?

7




S= I enjoyed the movie I watched on Saturday

Comprehension Questions

- What are the learnable parameters in our system?
- How many unique embeddings are in X for this example sentence S
- How many unique
 embeddings are in E ?

Vocabulary size V



 $S=\,$ I enjoyed the movie I watched on Saturday

Recap

- Words and other tokens become vectors; no longer discrete symbols!
- Define a vocabulary of words (or token types) V that our system can assign to a vector
- Define a model that composes these vectors (or embeddings) of words into some sequence representation
- A classifier can map this representation to a set of labels to make a prediction
- The prediction depends on the natural language task we are trying to accomplish
- By learning to make these predictions, we learn better embeddings for the words in the sequences

Tomorrow

What could be a better way to learn word embeddings?

Self-supervised learning of word embeddings

References

Shen, D., Wang, G., Wang, W., Min, M., Su, Q., Zhang, Y., Li, C., Henao, R., & Carin, L. (2018). Baseline Needs More Love: On Simple Word-Embedding-Based Models and Associated Pooling Mechanisms. *Annual Meeting of the Association for Computational Linguistics*.