PCM Series

Ultraminiature Surface Mount Slide Switches





Specifications

Contact Rating	0.3A @ 6 VDC.
Electrical Life	10,000 cycles
Contact Resistance	70 m Ω max.
Insulation Resistance	100 M Ω min. @ 500V.
Dielectric Strength	500 VAC min.
Operating Temperature	-40°C to 85°C
Solderability	255C max. solder temperature
Packaging	Tape & reel.

Description

Makers of computer peripherals, network products, telecommunication products and test & measurement equipment choose the PCM series ultraminiature surface mount slide switches when they need a long-lasting, low-profile switch. PCM switches are available in SPDT or SP3T models.

Features & Benefits

- Ultraminiature surface mount
- SPDT & SP3T models
- Low profile
- RoHS compliant

Applications

- Computer peripherals & network products
- Telecommunication products
- Test & measurement equipment


Materials

Case	PPA			
Cover	Stainless steel.			
Slider	Nylon 4/6			
Contacts	Copper alloy, silver or gold plated.			
Terminals				

Notes: All models RoHS compliant and compatible with all options. Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

Ordering Number

Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and place it in the appropriate box.





PCM Series

Ultraminiature Surface Mount Slide Switches




PCM12SMTR SPDT


Circuit Diagram


Part Number	POS.1	POS.2
PCM12SMTR SPDT	On	On
Conn. Terminals	1-2	2-3
Schematic, SPDT	2 3	


PC Mounting




Dimensions inchers (mm)







Tape & Reel





Quanity per reel 3500

PCM Series

Ultraminiature Surface Mount Slide Switches





PCM13SMTR SP3T


Circuit Diagram


Part Number	POS.1	POS.2	POS.3			
PCM13SMTR	On	On	On			
Conn. Terminals	1-3	2-3	3-4			
Schematic, SP3T 3 4						

PC Mounting










Tape & Reel



Note: For part number PCM13SMTR

Quanity per reel 3500

Feed Direction

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at http://www.littelfuse.com/disclaimer-electronics.

