

ACCESSORIES

DBRY-6

Models

- DBRY100: Bulk 100 connectors (100 tubes loose in box, plus inner box with 100 wire nuts)
- DBRY2X25: 25 x 2-packs (2 tubes and 2 wire nuts in a plastic bag, x 25 units)

Features

- UL Listed for 600 Volts direct burial
- Improved red-and-yellow wire nut, eliminating the need for two different sizes
- A snap-lock feature that secures the wire nut in the bottom of the light blue waterproof tube
- 3 wire exit cutouts in the strain relief cap, to ease wire routing
- Meets Directive 2006/95/EC and IEC standards EN61984:2009, EN60998-1:2004, and EN60998-2-4:2005



Waterproof Wire Connectors

DBRY100, DBRY2X25

HCV

Models

- HC-50F-50F: ½" Female inlet x ½" Female outlet
- HC-50F-50M: ½" Female inlet x ½" Male outlet
- HC-75F-75M: ¾" Female inlet x ¾" Male outlet

Features

- Adjustment access through top of valve
- Adjusts to compensate for elevational changes up to 32': Maximum flexibility
- Variety of inlet and outlet options: Reduces need for additional fittings
- Meets schedule 80 specifications: Durable under high pressure

Pressure loss charts for HCV products on page 180



HCV Check Valve

Overall height: 3"

HUNTER SPIRAL BARB ELBOWS

Models

- HSBE-050: ½" male NPT x spiral barb elbow
- HSBE-075: ¾" male NPT x spiral barb elbow
- HSBE TOOL: Insert tool

Features

- For use with FLEX_{SG} Tubing
- Acetal material for sharp barbs
- Operating pressure up to 80 PSI
- Compatible with FLEX_{SG} and other brands



Spiral Barb Elbows

HSBE-TOOL, HSBE-050, HSBE-075

FLEX_{SG} TUBING

Model

- FLEX_{SG}: 100' roll
- FLEX_{SG}-18: 18" pre-cut lengths

Features

- Engineered to resist kinking
- Inside diameter: 0.49"
- Operating pressure: up to 80 PSI
- Linear low-density polyethylene material
- Meets ASTM D2104, D2239, D2737



FLEX_{SG} Tubing

100' and 18" pre-cut lengths