

BLUEPRINT DOCUMENT V1.0

DIKO.CO TECHNICAL BLUEPRINT

FULL REVERSE-ENGINEERING — ANIMATIONS · LAYOUT · INTERACTIONS · MOTION SYSTEM

This document is a comprehensive technical specification for recreating diko.co — a full-service brand agency website built on Webflow with heavy custom CSS and JavaScript. Every section, animation, interaction, and visual effect is dissected and documented with implementable code.

WEBFLOW CMS

GSAP / VANILLA JS

CSS KEYFRAMES

MP4 / VIMEO VIDEO

SVG ILLUSTRATIONS

CUSTOM CURSOR

INFINITE MARQUEE

00 DESIGN SYSTEM

DIKO.co operates on a tight, aggressive visual language. The aesthetic is *anti-corporate brutalism* — dark, raw, typographically dominant, with humor embedded as a design material. Every motion choice reinforces personality over polish.

DESIGN PRINCIPLES

ANTI-VANILLA

Every design choice deliberately avoids the expected. No soft gradients, no friendly rounded corners, no predictable layouts.

MOTION AS VOICE

Animations don't just decorate — they carry attitude. Overshooting springs, unexpected pauses, asymmetric timing.

TEXT IS TEXTURE

Headlines are compositional elements, not just labels. Huge type fills space the way images normally would.

INTERACTIVE HUMOR

Copy changes on click, elements behave unexpectedly. The site rewards exploration and punishes passive reading.

VIDEO-FIRST

Autoplay MP4s with no controls dominate case study sections. Video is wallpaper, not content.

RAW SVG ILLUSTRATION

Custom hand-drawn SVG icons (bomb, hotdog, faces, dumpster) give it a zine / streetwear energy.

01 TYPOGRAPHY

The typeface selection is the backbone of DIKO's personality. Headlines are extremely large, condensed grotesque — tight leading,

all caps, designed to fill horizontal space completely.

ROLE	TYPEFACE	WEIGHT	CHARACTERISTICS
Primary Display	ABC Favorit Extended or similar condensed grotesque (Webflow custom font)	700–900	All caps, very tight leading (0.85–0.95), 8–15vw size at hero
Statement / Quote	Same display font	700	Mixed case allowed, sometimes italic for one word mid-phrase
Marquee Text	Same display font	700	Large, continuous loop, with asterisk (*) separators
Navigation	Condensed grotesque	700	Uppercase, duplicated text in one link, small tracking
Body / Captions	Clean sans-serif (likely GT America or similar)	400	Minimal usage — site is almost entirely display type

TYPE SCALE (RESPONSIVE)

```
/* — DIKO Type Scale — */
:root {
  --type-hero: clamp(60px, 12vw, 180px); /* Hero headline */
  --type-xlarge: clamp(48px, 8vw, 120px); /* Statement sections */
  --type-large: clamp(36px, 5.5vw, 80px); /* Sub-sections */
  --type-marquee: clamp(40px, 7vw, 100px); /* Marquee strip */
  --type-nav: 14px; /* Navigation */
  --line-display: 0.88; /* Leading for display type */
  --tracking-display: -0.02em; /* Slight negative tracking */
}

/* Italic accent — single word within a headline */
.headline-italic-word {
  font-style: italic;
  color: inherit; /* No color change, just style */
}
```

FONT LOADING (WEBFLOW CUSTOM FONTS)

```
/* Self-hosted via Webflow CDN — use @font-face for recreation */
@font-face {
  font-family: 'DikoDisplay';
  src: url('/fonts/display-bold.woff2') format('woff2');
  font-weight: 700;
  font-display: block; /* Prevents FOUT; preloader ensures fonts load */
}
```

02 COLOR PALETTE

 BLACK #050505	 OFF-WHITE #F5F0EB	 ORANGE #F04E0F	 YELLOW #F9D020	 RED #D9261C
--	--	---	---	--

The palette is binary at its core — near-black background + off-white text. The three accent colors (orange, yellow, red) appear

The palette is binary at its core — **near-black background + on-white text**. The three accent colors (orange, yellow, red) appear exclusively in SVG illustrations and preloader elements. They never appear as text colors in the main content.

```
:root {
  /* Core */
  --color-bg:      #050505;
  --color-text:    #F5F0EB;

  /* Accents — illustrations only */
  --color-orange:  #F04E0F;
  --color-yellow:  #F9D020;
  --color-red:     #D9261C;

  /* Structural */
  --color-divider: rgba(245, 240, 235, 0.12);
  --color-overlay: rgba(5, 5, 5, 0.55);
}
```

03 ASSETS & MEDIA INVENTORY

SVG ILLUSTRATIONS (PRELOADER / ICONS)

FILE	USAGE	DESCRIPTION
bomb.webp	Preloader	Main bomb character — animated floating/rotating. Appears 6× in preloader grid with staggered delays.
orange_65k.svg	Preloader	Orange smoke/explosion cloud SVG. Accompanies each bomb.
yellow_14k.svg	Preloader	Yellow spark/smoke SVG. Layered above orange cloud.
red_36k.svg	Preloader	Red explosion element. Third layer in preloader stack.
hotdog.svg	Icon conveyor	Hotdog illustration for scrolling icon strip.
third.svg	Icon conveyor	Abstract icon for scrolling strip.
dumpster.svg	Icon conveyor	Dumpster illustration — scrolling strip.
face.svg	Icon conveyor	Face/head icon for scrolling strip.
oil.svg	Icon conveyor	Oil can/drum icon for scrolling strip.
smile.svg	Icon conveyor	Smile/emoji icon for scrolling strip.
good-1.svg — good-4.svg	Statement section	Four SVG expression icons. Reveal on scroll, one at a time.
only-1.svg — only-4.svg	Services section	Four service/capability icons alongside services list.
car_wheel_spin.webp	Transition section	Spinning car wheel — animated with CSS <code>rotate</code> keyframe.
dollar-dollar-bill.webp	Dollar section	Dollar bill — 5 instances, animated with CSS <code>rotateY</code> 3D spin.

tiapa.svg	Hero area	Decorative SVG near hero text.
fly-cursor-img.png	Custom cursor	Fly image replacing the default cursor globally.
face-a.webp , face-b.webp	Love/Hate toggle	Two face states for the interactive love/hate toggle section.
obama-head.webp	Testimonials strip	Obama face image × 8 instances. Each paired with a rotating quote string.
hup.webp , hmid.webp , hdown.webp	Burger/joy section	Three states of a hamburger SVG — bounce animation sequence.
fc.webp	Click section	Background image for the interactive "click here" section.
diko-computer.webp	Services section	Illustrated retro computer mascot.
diko-logo-big-light.svg	Hero + Footer	Large DIKO wordmark in white. Used hero background + footer.
logo-main.svg	Navigation	Primary nav logo (light version).
logo-cute.svg	Navigation	Alt nav logo — shown on hover or specific scroll state.

VIDEO ASSETS

FILE	SECTION	BEHAVIOR
GGLE_Hero_Slow.mp4	Hero panel "Full—"	Autoplays, looped, muted. Fills panel behind text.
rumpl-hero.mp4	Hero panel "Service"	Same treatment as above.
2741871977.mp4	Below hero marquee	Full-bleed background video, parallax on scroll.
no-one-transcode.mp4	"No one else" section	Full-bleed background video, low opacity overlay.
2836006219.mp4	NOT BAD transition	Video plays on scroll entry.
Exported_1200×674.mp4	"Only people in advertising"	Background video, lower opacity.
Videoleap-6s.mp4	"IMITATION IS THE GREATEST"	Full-screen background video.
final_6239cac.mp4	"AN AD FROM A MILE AWAY"	Full-screen background video.
moshed-12f_1.mp4	"Safe thinking" section	Glitched/moshed video treatment.
Vimeo: Rumpl case	Case study card	Vimeo progressive redirect, plays on hover/click.
Vimeo: Google Pizza	Case study card	Same treatment.
Vimeo: iMeet	Case study card	Same treatment.
Vimeo: New Amsterdam	Case study card	Same treatment.

The preloader is a **6-cell grid of bomb characters**, each with three layered SVG explosion elements. The bombs float and rotate independently, then the entire preloader *wipes off-screen* once the page is ready.

STRUCTURE

```
<!-- Preloader HTML -->
<div class="preloader">
  <div class="preloader__grid">

    <!-- Cell - repeated 6 times -->
    <div class="preloader__cell">
      
      
      
      
    </div>

  </div>
</div>
```

CSS - PRELOADER LAYOUT & ANIMATION

```
.preloader {
  position: fixed;
  inset: 0;
  z-index: 9999;
  background: #050505;
  display: flex;
  align-items: center;
  justify-content: center;
  /* Exit: slide up when done */
  transition: transform 0.9s cubic-bezier(0.76, 0, 0.24, 1) 0.2s,
    opacity 0.4s ease 0.9s;
}

.preloader.is-hidden {
  transform: translateY(-100%);
  opacity: 0;
  pointer-events: none;
}

.preloader__grid {
  display: grid;
  grid-template-columns: repeat(3, 1fr);
  grid-template-rows: repeat(2, 1fr);
  gap: 20px;
  width: 80vw;
  max-width: 900px;
}

.preloader__cell {
  position: relative;
  display: flex;
  align-items: center;
  justify-content: center;
  aspect-ratio: 1 / 1;
}
```

```

}

/* — Bomb float animation — */
.bomb {
  width: clamp(60px, 8vw, 120px);
  position: relative;
  z-index: 2;
  animation: bombFloat 2.4s ease-in-out infinite;
}

/* Each cell gets a different delay */
.preloader__cell:nth-child(1) .bomb { animation-delay: 0s; }
.preloader__cell:nth-child(2) .bomb { animation-delay: 0.2s; }
.preloader__cell:nth-child(3) .bomb { animation-delay: 0.4s; }
.preloader__cell:nth-child(4) .bomb { animation-delay: 0.6s; }
.preloader__cell:nth-child(5) .bomb { animation-delay: 0.3s; }
.preloader__cell:nth-child(6) .bomb { animation-delay: 0.5s; }

@keyframes bombFloat {
  0%, 100% { transform: translateY(0) rotate(-4deg); }
  50%      { transform: translateY(-14px) rotate(4deg); }
}

/* — Smoke / Explosion SVGs — */
.smoke {
  position: absolute;
  pointer-events: none;
}

.smoke--orange {
  width: 140%; bottom: -10%; left: -20%;
  animation: smokePulse 2.8s ease-in-out infinite;
}

.smoke--yellow {
  width: 80%; top: 5%; right: -10%;
  animation: smokePulse 2.2s ease-in-out infinite 0.4s;
}

.smoke--red {
  width: 60%; top: -5%; left: 5%;
  animation: smokePulse 3.1s ease-in-out infinite 0.2s;
}

@keyframes smokePulse {
  0%, 100% { transform: scale(1) rotate(0deg); opacity: 0.85; }
  50%      { transform: scale(1.08) rotate(5deg); opacity: 1; }
}

```

JS — PRELOADER DISMISSAL

```

// Dismiss preloader after fonts + window load
document.fonts.ready.then(() => {
  window.addEventListener('load', () => {
    const preloader = document.querySelector('.preloader');
    setTimeout(() => {
      preloader.classList.add('is-hidden');
      setTimeout(() => preloader.remove(), 1400);
    }, 800); // Minimum display time
  });
});

```

05 HERO — SPLIT-PANEL OPEN

ENTRY ANIMATION — PANELS SLIDE OPEN FROM CENTER

The hero is a **4-panel split-screen** that reveals on page load. Each panel contains a word from "Full- / Service / Brand / Agency" with a looping MP4 video behind each. The panels start center-collapsed and expand outward, revealing the video + text.

PANEL STRUCTURE

```
<section class="hero">
  <div class="hero__panels">

    <div class="hero__panel hero__panel--1">
      <video src="GGLE_Hero_Slow.mp4" autoplay loop muted playsinline></video>
      <span class="hero__word">Full-</span>
    </div>

    <div class="hero__panel hero__panel--2">
      <video src="rumpl-hero.mp4" autoplay loop muted playsinline></video>
      <span class="hero__word">Service</span>
    </div>

    <div class="hero__panel hero__panel--3">
      <span class="hero__word">Brand</span>
    </div>

    <div class="hero__panel hero__panel--4">
      <span class="hero__word">Agency</span>
    </div>

  </div>

  <div class="hero__logo">
    
  </div>

</section>
```

CSS — HERO LAYOUT & REVEAL

```
.hero {
  height: 100vh;
  position: relative;
  overflow: hidden;
}

.hero__panels {
  display: flex;
  height: 100%;
}

.hero__panel {
  position: relative;
  overflow: hidden;
  flex: 1;
}
```

```

display: flex;
align-items: flex-end;
padding: 32px;
/* Initial state: panels collapsed to 0 width */
clip-path: inset(0 50%);
transition: clip-path 1.2s cubic-bezier(0.76, 0, 0.24, 1);
}

/* Stagger the open by 80ms per panel */
.hero__panel--1 { transition-delay: 0ms; }
.hero__panel--2 { transition-delay: 80ms; }
.hero__panel--3 { transition-delay: 160ms; }
.hero__panel--4 { transition-delay: 240ms; }

.hero.is-loaded .hero__panel {
  clip-path: inset(0 0%); /* Fully revealed */
}

/* Video fills the panel */
.hero__panel video {
  position: absolute;
  inset: 0;
  width: 100%; height: 100%;
  object-fit: cover;
}

.hero__word {
  font-size: clamp(48px, 6vw, 96px);
  font-weight: 900;
  text-transform: uppercase;
  color: white;
  position: relative; z-index: 2;
  mix-blend-mode: difference; /* White on any video */
}

/* Large DIKO logo – positioned center, behind panels */
.hero__logo {
  position: absolute;
  inset: 0;
  display: flex;
  align-items: center;
  justify-content: center;
  z-index: 5;
  pointer-events: none;
  opacity: 0;
  transition: opacity 0.6s ease 1.5s; /* Fades in after panels open */
}
.hero.is-loaded .hero__logo { opacity: 1; }
.hero__logo img { width: 60%; max-width: 480px; }

```

JS – HERO TRIGGER

```

// Trigger hero open after preloader exits
const hero = document.querySelector('.hero');
setTimeout(() => {
  hero.classList.add('is-loaded');
}, 1200); // After preloader slide-out begins

```


06 MARQUEE / TICKER STRIP

INFINITE HORIZONTAL SCROLL – TWO ROWS, OPPOSING DIRECTIONS

Below the hero sits a classic **infinite scrolling marquee** in two rows. Row 1 scrolls left, Row 2 scrolls right. The text is "Full-service brand agency *" — the asterisk acts as a separator between repeats.

HTML STRUCTURE

```
<div class="marquee-wrap">

  <!-- Row 1: scrolls left -->
  <div class="marquee marquee--left">
    <div class="marquee__track">
      <span>Full-service brand agency *</span>
      <span>Full-service brand agency *</span>
      <!-- Duplicated enough times to fill 200% width -->
    </div>
  </div>

  <!-- Row 2: scrolls right -->
  <div class="marquee marquee--right">
    <div class="marquee__track">
      <span>Full-service brand agency *</span>
      <span>Full-service brand agency *</span>
    </div>
  </div>

</div>
```

CSS – MARQUEE ANIMATION

```
.marquee-wrap {
  overflow: hidden;
  padding: 16px 0;
  border-top: 1px solid rgba(245,240,235,0.12);
  border-bottom: 1px solid rgba(245,240,235,0.12);
}

.marquee {
  overflow: hidden;

  white-space: nowrap;
  padding: 6px 0;
}

.marquee__track {
  display: inline-flex;
  gap: 0.5em;
  /* Track width = 2x total text width for seamless loop */
}

.marquee--left .marquee__track {
  animation: scrollLeft 22s linear infinite;
}

.marquee--right .marquee__track {
```

```

    animation: scrollRight 22s linear infinite;
  }

.marquee__track span {
  font-size: clamp(40px, 7vw, 100px);
  font-weight: 900;
  text-transform: uppercase;
  padding-right: 1em;
  color: var(--color-text);
}

@keyframes scrollLeft {
  0% { transform: translateX(0); }
  100% { transform: translateX(-50%); }
}
@keyframes scrollRight {
  0% { transform: translateX(-50%); }
  100% { transform: translateX(0); }
}

/* Pause on hover – optional */
.marquee:hover .marquee__track { animation-play-state: paused; }

```

JS – DYNAMIC MARQUEE CLONING

```

// Ensure marquee fills viewport regardless of font size

function initMarquee(track) {
  const item      = track.querySelector('span');
  const itemWidth = item.offsetWidth;
  const needed    = Math.ceil((window.innerWidth * 3) / itemWidth);
  for (let i = 0; i < needed; i++) {
    track.appendChild(item.cloneNode(true));
  }
}

document.querySelectorAll('.marquee__track').forEach(initMarquee);

```

07 ICON CONVEYOR BELT — "NOT BAD / IS NOT GOOD"

MULTI-ROW AUTO-SCROLLING ICON + TEXT STRIPS

One of the most distinctive sections: **4–5 horizontal strips** of alternating SVG icons and text labels, each row moving at a slightly different speed. Odd rows go left, even rows go right. Text alternates between "NOT BAD" and "is not good" paired with rotating icons (hotdog, face, dumpster, oil, smile).

HTML

```

<section class="icon-belt">

  <div class="icon-belt__row icon-belt__row--left" style="--speed: 18s">
    <div class="icon-belt__track">
      <!-- Repeated items -->
      <div class="icon-belt__item">
        

```

```

        <span>NOT BAD</span>
    </div>
    <div class="icon-belt__item">
        
        <span>is not good</span>
    </div>
    <!-- ...more items, then duplicated for loop -->
</div>
</div>

<div class="icon-belt__row icon-belt__row--right" style="--speed: 24s">
    <!-- Different icon set, opposite direction -->
</div>

</section>

```

CSS

```

.icon-belt { overflow: hidden; padding: 0; }

.icon-belt__row {
    display: flex;
    overflow: hidden;
    padding: 8px 0;
    border-bottom: 1px solid rgba(245,240,235,0.08);
}

.icon-belt__track {
    display: inline-flex;
    align-items: center;
    gap: 24px;
    white-space: nowrap;
}

.icon-belt__row--left .icon-belt__track {
    animation: scrollLeft var(--speed) linear infinite;
}

.icon-belt__row--right .icon-belt__track {
    animation: scrollRight var(--speed) linear infinite;
}

.icon-belt__item {
    display: flex;
    align-items: center;
    gap: 16px;
    padding: 0 20px;
}

.icon-belt__item img {
    height: clamp(40px, 5vw, 80px);
    width: auto;
}

.icon-belt__item span {
    font-size: clamp(28px, 4vw, 64px);
    font-weight: 900;
    text-transform: uppercase;
    letter-spacing: -0.02em;
}

```

08 INTERACTIVE CLICK BUTTON — RANDOM TEXT CYCLING

STATEFUL RANDOM TEXT ON EACH CLICK

A large clickable button occupies a full section. Each click cycles through a **pre-written array of absurdist copy**. The text never repeats consecutively. This section also has an `fc.webp` background image visible behind the text.

THE FULL TEXT ARRAY

```
const CLICK_TEXTS = [
  "You have the wrong number",
  "You will click this again",
  "Astronomers will need more space",
  "You will get tired of this",
  "Can't believe you clicked",
  "Dirty Harry's day will finally be made",
  "Someone else will figure it out",
  "Inchworms will grow a foot",
  "A scientist will be cloned",
  "Your budget will get cut",
  "You'll forget to eat",
  "The algorithm will get it wrong",
  "A record will happily skip",
  "The End?",
  "You'll have second thoughts",
  "What she/he/they said",
  "The buck won't stop here",
  "A cat will think it's a dog",
  "A turd will be polished",
  "Stop. Just stop",
  "666 666 666 666",
  "Sorry - writers on strike",
  "You missed the Easter egg",
  "Someone else will figure it out."
];
```

HTML + CSS

```
<section class="click-section">
  <div class="click-section__bg"></div>
  <div class="click-section__content">
    <button class="click-btn" id="clickBtn">
      <span class="click-btn__text">CRACK OPEN</span>
    </button>
  </div>
</section>
```

```
.click-section {
  min-height: 80vh;
  display: flex;
  align-items: center;
  justify-content: center;
  position: relative;
```

```

        overflow: hidden;
    }
    .click-section__bg {
        position: absolute; inset: 0;
        opacity: 0.15;
    }
    .click-section__bg img {
        width: 100%; height: 100%; object-fit: cover;
    }

    .click-btn {
        background: none; border: none;
        cursor: pointer;
        font-size: clamp(48px, 9vw, 140px);
        font-weight: 900;
        text-transform: uppercase;
        color: var(--color-text);
        line-height: 0.9;
        text-align: center;
        padding: 40px;
        position: relative; z-index: 2;
        max-width: 90vw;
    }

    .click-btn:hover { opacity: 0.8; }

    /* Text swap animation */
    .click-btn__text {
        display: block;
        transition: opacity 0.15s ease, transform 0.15s ease;
    }
    .click-btn__text.is-exiting {
        opacity: 0;
        transform: translateY(-12px);
    }
    .click-btn__text.is-entering {
        opacity: 0;
        transform: translateY(12px);
    }

```

JS - CLICK HANDLER

```

let clickIndex = -1;
const btn = document.getElementById('clickBtn');
const textEl = btn.querySelector('.click-btn__text');

btn.addEventListener('click', () => {
    // Pick next, skip current
    let next;

    do { next = Math.floor(Math.random() * CLICK_TEXTS.length); }
    while (next === clickIndex);
    clickIndex = next;

    // Exit animation
    textEl.classList.add('is-exiting');

    setTimeout(() => {
        textEl.textContent = CLICK_TEXTS[clickIndex];
        textEl.classList.remove('is-exiting');
        textEl.classList.add('is-entering');
    }, 100);
});

```

```

    // Force reflow
    textEl.offsetHeight;
    textEl.classList.remove('is-entering');
  }, 150);
});

```

09 DOLLAR BILL SPIN — 3D ROTATION

CSS 3D ROTATEY — 5 STAGGERED DOLLAR BILLS

Five dollar bill images arranged horizontally, each spinning on the Y-axis in a continuous loop with staggered offsets, creating a ripple effect. Headline: "YOU DON'T KNOW WHERE THAT DOLLAR HAS BEEN".

```

/* — Container — */
.dollar-section {
  display: flex;
  flex-direction: column;
  align-items: center;
  gap: 40px;
  padding: 80px 40px;
}

.dollar-bills {
  display: flex;
  gap: clamp(8px, 2vw, 32px);

  perspective: 600px; /* Required for 3D context */
}

.dollar-bill {
  width: clamp(80px, 12vw, 200px);
  animation: billSpin 1.8s linear infinite;
  transform-style: preserve-3d;
}

/* Stagger each bill by 0.36s (= duration / count) */
.dollar-bill:nth-child(1) { animation-delay: 0s; }
.dollar-bill:nth-child(2) { animation-delay: -0.36s; }
.dollar-bill:nth-child(3) { animation-delay: -0.72s; }
.dollar-bill:nth-child(4) { animation-delay: -1.08s; }
.dollar-bill:nth-child(5) { animation-delay: -1.44s; }

@keyframes billSpin {
  0% { transform: rotateY(0deg); }
  100% { transform: rotateY(360deg); }
}

```

10 LOVE / HATE TOGGLE

TWO-STATE TOGGLE WITH FACE SWAP

A section with a large "I love it / I hate it" toggle. Two face images (face-a.webp = happy, face-b.webp = grimacing). Clicking toggles

between states with a brief scale + opacity transition on the face image.

```
<!-- HTML -->
<section class="love-hate">
  <div class="love-hate__face">
    
    
  </div>
  <div class="love-hate__toggle">
    <button class="toggle-btn is-active" data-state="love">I love it</button>

    <button class="toggle-btn" data-state="hate">I hate it</button>
  </div>
  <p>If everyone loves what you're doing, you're doing something wrong.</p>
</section>
```

```
.love-hate__face {
  position: relative;
  width: clamp(120px, 18vw, 280px);
}

.face {
  width: 100%;
  transition: opacity 0.3s ease, transform 0.3s cubic-bezier(0.34, 1.56, 0.64, 1);
  position: absolute; top: 0; left: 0;
  opacity: 0; transform: scale(0.9);
}

.face.is-active { opacity: 1; transform: scale(1); position: relative; }

.toggle-btn {
  font-size: clamp(32px, 5vw, 72px);
  font-weight: 900;
  background: none; border: none;
  cursor: pointer;
  color: rgba(245,240,235,0.3);
  text-transform: uppercase;
  transition: color 0.25s ease, opacity 0.25s ease;
}

.toggle-btn.is-active { color: var(--color-text); }
```

```
// JS toggle handler
const btns = document.querySelectorAll('.toggle-btn');
const faces = document.querySelectorAll('.face');

btns.forEach(btn => {
  btn.addEventListener('click', () => {
    const state = btn.dataset.state;
    btns.forEach(b => b.classList.toggle('is-active', b === btn));
    faces.forEach(f => f.classList.toggle('is-active', f.classList.contains(`face--${state}`)));
  });
});
```

11 "EVERYTHING IS A WORK IN PROGRESS" — STAGGERED TEXT REVEAL

Each word of the phrase "Everything is a work in progress" is wrapped in a `span` and reveals from below on scroll entry, staggered by index. The asterisk at the end pulses independently.

```
<!-- HTML: Each word wrapped in a reveal span -->
<div class="progress-text">
  <span class="word-reveal">Everything</span>
  <span class="word-reveal">is</span>
  <span class="word-reveal">a</span>
  <span class="word-reveal">work</span>
  <span class="word-reveal">in</span>
  <span class="word-reveal">progress</span>
</div>
```

```
.progress-text {
  font-size: clamp(48px, 9vw, 140px);
  font-weight: 900;
  text-transform: uppercase;
  line-height: 0.88;
  display: flex;
  flex-wrap: wrap;
  gap: 0.2em;
}

.word-reveal {
  display: inline-block;
  overflow: hidden;
  vertical-align: bottom;
}

.word-reveal__inner {
  display: block;
  transform: translateY(110%);
  transition: transform 0.7s cubic-bezier(0.16, 1, 0.3, 1);
}

.word-reveal.is-visible .word-reveal__inner {
  transform: translateY(0);
}

/* Stagger delays set via JS */
```

```
// Wrap inner content + set stagger delays
document.querySelectorAll('.word-reveal').forEach((word, i) => {
  const inner = document.createElement('span');
  inner.classList.add('word-reveal__inner');
  inner.innerHTML = word.innerHTML;
  word.innerHTML = '';
  word.appendChild(inner);
  inner.style.transitionDelay = `${i * 0.09}s`;
});

const revealObs = new IntersectionObserver(entries => {
  entries.forEach(e => {
    if (e.isIntersecting) {
      e.target.classList.add('is-visible');
    }
  });
});
```



```

        revealObs.unobserve(e.target);
    }
    });
}, { threshold: 0.2 });

document.querySelectorAll('.word-reveal').forEach(el => revealObs.observe(el));

```

12 SCROLL-TRIGGERED ANIMATIONS

SCROLL VELOCITY – MARQUEE SPEED

The marquee strips *accelerate on fast scroll* and return to normal speed when scrolling stops — a popular technique that makes the page feel alive.

```

let scrollVelocity = 0;
let lastScrollY   = 0;
let ticking       = false;

window.addEventListener('scroll', () => {
  if (!ticking) {
    requestAnimationFrame(() => {
      scrollVelocity = Math.abs(window.scrollY - lastScrollY);
      lastScrollY   = window.scrollY;
      ticking       = false;

      // Map velocity to animation duration: faster scroll = shorter duration
      const factor   = Math.max(0.3, 1 - scrollVelocity * 0.02);
      const duration = 22 * factor + 's';
      document.querySelectorAll('.marquee__track').forEach(t => {
        t.style.animationDuration = duration;
      });
    });
    ticking = true;
  }
});

```

PARALLAX VIDEO BACKGROUNDS

Full-bleed video sections move at ~60% scroll speed relative to the page, creating a parallax depth effect.

```

document.querySelectorAll('.parallax-video').forEach(section => {
  const video = section.querySelector('video');
  const obs = new IntersectionObserver([entry] => {
    if (entry.isIntersecting) {
      window.addEventListener('scroll', onScroll);
    } else {
      window.removeEventListener('scroll', onScroll);
    }
  }, { threshold: 0 });
  obs.observe(section);

  function onScroll() {
    const rect = section.getBoundingClientRect();
    const pct  = rect.top / window.innerHeight;
    video.style.transform = `translateY(${pct * 30%})`; // 30% = depth amount
  }
});

```

```
    }  
  });  
});
```

13 CUSTOM CURSOR — FLY IMAGE

DELAYED FOLLOW — LERP SMOOTHING

The native cursor is hidden globally. A fly PNG image element follows the mouse with a **lerp (linear interpolation) lag**, giving it a floaty, organic feel. The fly also rotates slightly in the direction of movement.

```
/* CSS */  
* { cursor: none !important; }  
  
.cursor-fly {  
  position: fixed;  
  pointer-events: none;  
  z-index: 99999;  
  width: 32px; height: 32px;  
  transform: translate(-50%, -50%);  
  will-change: transform;  
}
```

```
// JS — smooth cursor follow with lerp  
const fly = document.querySelector('.cursor-fly');  
let mouseX = 0, mouseY = 0;  
let flyX = 0, flyY = 0;  
let prevX = 0, prevY = 0;  
  
const LERP_FACTOR = 0.12; // Lower = more lag (0.05-0.2 range)  
  
document.addEventListener('mousemove', e => {  
  mouseX = e.clientX;  
  mouseY = e.clientY;  
});  
  
function lerp(a, b, t) { return a + (b - a) * t; }  
  
function animateCursor() {  
  const dx = mouseX - flyX;  
  const dy = mouseY - flyY;  
  
  flyX = lerp(flyX, mouseX, LERP_FACTOR);  
  flyY = lerp(flyY, mouseY, LERP_FACTOR);  
  
  // Rotate in direction of velocity  
  const angle = Math.atan2(flyY - prevY, flyX - prevX) * (180 / Math.PI);  
  prevX = flyX; prevY = flyY;  
  
  fly.style.transform = `translate(calc(${flyX}px - 50%), calc(${flyY}px - 50%)) rotate(${angle}deg)`;  
  requestAnimationFrame(animateCursor);  
}  
animateCursor();
```

14 NAVIGATION — DUPLICATED TEXT HOVER EFFECT

CSS 3D FLIP ON NAV LINKS

Each nav link shows its text twice (e.g. "WORK WORK", "FAQ U FAQ U"). On hover, the text performs a **vertical 3D flip** — the first copy flips away, the second copy flips in. This is a clip-path + translateY technique.

```
<nav class="nav">
  <a class="nav-link" href="/work">

    <span class="nav-link__text" aria-hidden="true">WORK</span>
    <span class="nav-link__text">WORK</span>
  </a>
  <a class="nav-link" href="/about">
    <span class="nav-link__text" aria-hidden="true">FAQ U</span>
    <span class="nav-link__text">FAQ U</span>
  </a>
</nav>
```

```
.nav-link {
  position: relative;
  display: inline-flex;
  flex-direction: column;
  overflow: hidden;
  height: 1.2em; /* Clip to one line height */
  text-decoration: none;
  font-weight: 700;
  font-size: 14px;
  text-transform: uppercase;
  letter-spacing: 0.05em;
  color: var(--color-text);
}

.nav-link__text {
  display: block;
  transition: transform 0.35s cubic-bezier(0.16, 1, 0.3, 1);
}

/* On hover: slide both texts up by 100% */
.nav-link:hover .nav-link__text {
  transform: translateY(-100%);
}
```

LOGO SWAP (MAIN → CUTE ON SCROLL)

```
const logoMain = document.querySelector('.logo-main');
const logoCute = document.querySelector('.logo-cute');

window.addEventListener('scroll', () => {
  const scrolled = window.scrollY > 100;
  logoMain.style.opacity = scrolled ? '0' : '1';
  logoCute.style.opacity = scrolled ? '1' : '0';
});
```

15 CASE STUDY CARDS

FULL-BLEED VIDEO WITH HOVER REVEAL CTA

Case study sections occupy nearly full-viewport height. A Vimeo video plays in the background (or a static poster frame). On hover, a darkening overlay + "case study →" link fades in.

TIMING & EASING REFERENCE

INTERACTION	DURATION	EASING	PROPERTY
Case study hover overlay	300ms	ease	opacity
CTA link reveal	400ms	cubic-bezier(0.16,1,0.3,1)	translateY + opacity
Video scale on hover	600ms	ease	scale(1.04)

```
.case-study {
  position: relative;
  height: 90vh;
  overflow: hidden;
}

.case-study video {
  position: absolute; inset: 0;
  width: 100%; height: 100%;
  object-fit: cover;
  transition: transform 600ms ease;
}

.case-study:hover video {
  transform: scale(1.04);
}

.case-study__overlay {
  position: absolute; inset: 0;
  background: rgba(0,0,0,0.5);
  opacity: 0;
  transition: opacity 300ms ease;
  display: flex;
  align-items: flex-end;
  padding: 48px;
}

.case-study:hover .case-study__overlay { opacity: 1; }

.case-study__cta {
  font-size: clamp(20px, 3vw, 42px);
  font-weight: 900;
  text-transform: uppercase;
  color: white;
  text-decoration: none;
  transform: translateY(20px);
  opacity: 0;
  transition: transform 400ms cubic-bezier(0.16,1,0.3,1) 100ms,
```

```

        opacity 300ms ease 100ms;
    }
    .case-study:hover .case-study__cta {
        transform: translateY(0);
        opacity: 1;
    }

```

16 COMPLETE PAGE SECTION MAP

1 - PRELOADER

6-bomb floating grid. Full-screen #050505 overlay. Slides up on load complete (~2.5s). Triggers hero open after exit.

2 - HERO SPLIT-PANEL

4 panels: "Full- / Service / Brand / Agency". clip-path reveal. Video behind panels 1 & 2. Large DIKO wordmark fades in center. Subtitle "Made in Austin, Texas, America" bottom center.

3 - MARQUEE STRIP (1ST)

Two rows "Full-service brand agency *", opposing directions. Sits between hero and first case study. Speed increases with scroll velocity.

4 - RUMPL CASE STUDY

Full-bleed Vimeo video. Link to /work/rumpl. "Some people are allergic to vanilla *" statement text above.

5 - ICON CONVEYOR "NOT BAD / IS NOT GOOD"

4-5 rows of SVG icons + alternating text. Each row different speed & direction. Background video (2836006219.mp4) plays beneath.

6 - "NO ONE ELSE CAN SHARE THE NAME YOU MAKE FOR YOURSELF"

Full-bleed video (no-one-transcode.mp4). Large statement text with parallax. fc.webp image layer.

7 - INTERACTIVE CLICK BUTTON

"CRACK OPEN / Circle" — large clickable headline. Random text cycling from 24-item array on each click.

8 - GOOGLE PIZZA CASE STUDY

Vimeo video. Link to /work/google-pizza. "ONLY PEOPLE IN ADVERTISING Like advertising" statement above.

9 - OBAMA TESTIMONIALS STRIP

Obama head × 8 instances in horizontal scrolling strip. Each paired with a different quote. Scrolls automatically.

10 - LOVE / HATE TOGGLE

Two-state toggle. face-a.webp (happy) / face-b.webp (grimace). Quote: "If everyone loves what you're doing, you're doing something wrong."

11 - DOLLAR BILL SPIN

5 × dollar-dollar-bill.webp spinning on Y-axis with staggered timing. Headline "YOU DON'T KNOW WHERE THAT DOLLAR HAS BEEN."

12 - IMEET CASE STUDY

Vimeo video. "IMITATION IS THE GREATEST FORM OF THEFT" large text above.

13 - "PEOPLE CAN SMELL AN AD FROM A MILE AWAY"

Video (final_6239cac.mp4) background. Large statement text split across 3 lines. Link to /work/one-blade.

14 - "SAFE THINKING IS A DANGEROUS PLACE"

Glitched video (moshed-12f.mp4). Four SVG expression faces (good-1 to good-4) reveal on scroll. Link to /work/new-amsterdam-vodka.

15 - SPINNING CAR WHEEL

car_wheel_spin.webp spinning via CSS rotate animation. "Don't put all your happiness in one basket" text.

16 - HAMBURGER BOUNCE

hup/hmid/hdown.webp sequence animating like a bouncing hamburger. CSS animation cycling between 3 states.

17 - SERVICES / COMPUTER SECTION

diko-computer.webp alongside 4 service icons (only-1 to only-4). Scroll-reveal stagger.

18 - "EVERYTHING IS A WORK IN PROGRESS"

Word-by-word reveal on scroll. Each word in overflow:hidden container. translateY from 110% → 0 with 90ms stagger.

19 - FOOTER / SUBSCRIBE MARQUEE

"Subscribe to Unsubscribable *" marquee (link to unsubscribable.co). Large DIKO logo. "Made in Austin, TX" + info@diko.co. Nav repeated in footer.

17 JAVASCRIPT ARCHITECTURE

The site is built on **Webflow** with custom JS injected via the project's custom code panel. No bundler or framework — pure vanilla JS modules loaded in order. Likely uses GSAP for complex scroll triggers (especially the hero panel reveal).

PROBABLE DEPENDENCIES

LIBRARY	VERSION	USAGE
GSAP (GreenSock)	~3.x	Hero panel clip-path animation, scroll-triggered reveals, smooth scrubbing
GSAP ScrollTrigger	plugin	Parallax, pinned sections, scroll-linked progress
Webflow.js	built-in	CMS, interactions 2.0 base layer
Lenis (or similar)	optional	Smooth scroll for momentum feel
Vanilla JS	ES6+	Cursor, marquee, click randomizer, toggle, billboard

INITIALIZATION ORDER

```
// Page initialization sequence
document.addEventListener('DOMContentLoaded', () => {

  initCursor();           // Custom fly cursor
  initPreloader();        // Bomb grid + dismissal
  initMarquees();         // All ticker strips
  initIconBelt();         // NOT BAD icon conveyors
  initClickBtn();         // Random text cycling
  initLoveHate();         // Toggle section
  initWordReveal();       // IntersectionObserver reveals
  initNavSwap();          // Logo + nav scroll state
  initScrollVelocity();   // Marquee speed on scroll

  // GSAP-dependent (load after GSAP cdn)
  initHeroReveal();       // clip-path panel open
  initParallax();         // Video parallax
  initScrollReveal();     // All scroll-triggered elements
});
```

18 HAMBURGER 3-STATE BOUNCE ANIMATION

Three images (hup.webp, hmid.webp, hdown.webp) simulate a bouncing hamburger — like a sprite sheet, but done with opacity switching. Each image is absolutely positioned on top of each other; CSS animation cycles through their visibility.

```
.burger-wrap {
  position: relative;
  width: clamp(80px, 10vw, 160px);
  aspect-ratio: 1 / 1.2;
}

.burger-frame {
  position: absolute; inset: 0;
  width: 100%;

  opacity: 0;
}

.burger-frame--up { animation: burgerUp 0.6s steps(1) infinite; }
.burger-frame--mid { animation: burgerMid 0.6s steps(1) infinite; }
.burger-frame--down { animation: burgerDown 0.6s steps(1) infinite; }

@keyframes burgerUp {
  0%, 33% { opacity: 1; }
  34%, 100% { opacity: 0; }
}
@keyframes burgerMid {
  0%, 33% { opacity: 0; }
  34%, 66% { opacity: 1; }
  67%, 100% { opacity: 0; }
}
@keyframes burgerDown {
  0%, 66% { opacity: 0; }
  67%, 100% { opacity: 1; }
}
```

19 FOOTER — SUBSCRIBE MARQUEE + CLOSING

The footer has two marquee strips: "Subscribe to Unsubscribable *" and "Click Here *", moving in opposite directions. Below sits the large DIKO wordmark, contact info, and navigation repeated from the header.

```
<footer class="footer">

  <!-- Subscribe marquee (same pattern as hero marquee) -->
  <a href="https://www.unsubscribable.co/">
    <div class="marquee marquee--left">
      <div class="marquee__track">
        <span>Subscribe to Unsubscribable *</span>
      </div>
    </div>
    <div class="marquee marquee--right">
      <div class="marquee__track">
        <span>Click Here *</span>
      </div>
    </div>
  </a>
</footer>
```

```

    </div>
</a>

<div class="footer__body">
  <div class="footer__address">
    <p>Made IN Austin, TX</p>
    <a href="mailto:info@diko.co">info@diko.co</a>
  </div>
  
</div>

</footer>

```

20 FULL KEYFRAME REFERENCE

```

/* =====
ALL KEYFRAMES USED ACROSS DIKO.CO
===== */

/* Preloader */
@keyframes bombFloat { 0%,100%{transform:translateY(0) rotate(-4deg)} 50%{transform:translateY(-14px) rotate(4deg)} }
@keyframes smokePulse { 0%,100%{transform:scale(1) rotate(0deg);opacity:.85} 50%{transform:scale(1.08) rotate(5deg);opac

/* Marquee / Ticker */
@keyframes scrollLeft { 0%{transform:translateX(0)} 100%{transform:translateX(-50%)} }
@keyframes scrollRight { 0%{transform:translateX(-50%)} 100%{transform:translateX(0)} }

/* Dollar bill 3D spin */
@keyframes billSpin { 0%{transform:rotateY(0deg)} 100%{transform:rotateY(360deg)} }

/* Car wheel */
@keyframes wheelSpin { 0%{transform:rotate(0deg)} 100%{transform:rotate(360deg)} }

/* Burger 3-frame */
@keyframes burgerUp { 0%,33%{opacity:1} 34%,100%{opacity:0} }
@keyframes burgerMid { 0%,33%{opacity:0} 34%,66%{opacity:1} 67%,100%{opacity:0} }
@keyframes burgerDown { 0%,66%{opacity:0} 67%,100%{opacity:1} }

/* Asterisk pulse (marquee separator) */
@keyframes asteriskPulse { 0%,100%{transform:rotate(0deg)} 50%{transform:rotate(180deg)} }

/* Fade-in from below (generic scroll reveal) */
@keyframes fadeUp {
  from { opacity:0; transform:translateY(32px) }
  to { opacity:1; transform:translateY(0) }
}

```

GLOBAL EASING VARIABLES

```

:root {
  --ease-out-expo: cubic-bezier(0.16, 1, 0.3, 1);
  --ease-in-out: cubic-bezier(0.76, 0, 0.24, 1);
  --ease-spring: cubic-bezier(0.34, 1.56, 0.64, 1); /* overshoot */
  --ease-linear: linear;
}

```



```
--duration-fast: 200ms;
--duration-mid: 400ms;
--duration-slow: 900ms;
--duration-panel: 1200ms; /* Hero panels */
}
```

21 ACCESSIBILITY & PERFORMANCE NOTES

△ PREFERENCES-REDUCED-MOTION

All animations must respect the `prefers-reduced-motion: reduce` media query. Marquees pause, reveals snap immediately, cursor defaults to native pointer.

```
@media (prefers-reduced-motion: reduce) {
  .marquee__track { animation: none !important; }
  .cursor-fly { display: none !important; }
  * { cursor: auto !important; }
  .word-reveal__inner { transform: none !important; transition: none !important; }
  .preloader { transition: none !important; }
  .hero__panel { transition: none !important; }
  .dollar-bill { animation: none !important; }
  .bomb { animation: none !important; }
}
```

⚡ PERFORMANCE

All videos use `autoplay muted playsinline`. Only load Vimeo embeds on hover/intersection, not on page load. Use `will-change: transform` sparingly — only on cursor, marquee tracks, and animated panels.

📱 MOBILE

On mobile: custom cursor is removed, hero panels collapse to stacked layout, video backgrounds are replaced with poster images (autoplay blocked on iOS without muted + playsinline). Icon conveyor belt touch-scrolls natively.

22 NAVIGATION — FULL ANATOMY

FIXED HEADER · LOGO SWAP · “*WOW* COOL” BRANDING ELEMENT

The navigation bar is **fixed to the top** at all times with a transparent background that never gains a backdrop — the dark page content behind it serves as the “background.” It contains four distinct zones: a branding cluster on the left, links on the right, and a decorative copy element that reads “*WOW* COOL” alongside the two logo variants.

FULL HEADER HTML

```
<header class="site-nav">

  <!-- Left: Logo cluster -->

  <a href="/" class="nav-logo">
```

```

    
    
  </a>

  <!-- Center: Decorative copy — *WOW* COOL — -->
  <div class="nav-wow" aria-hidden="true">
    <span class="nav-wow__line">*WOW*</span>
    <span class="nav-wow__line">COOL</span>
  </div>

  <!-- Right: Navigation links -->
  <nav class="nav-links">
    <a href="/work" class="nav-link">
      <span class="nav-link__text">WORK</span>
      <span class="nav-link__text">WORK</span>
    </a>
    <a href="/about" class="nav-link">
      <span class="nav-link__text">FAQ U</span>
      <span class="nav-link__text">FAQ U</span>
    </a>
  </nav>

</header>

```

NAVIGATION CSS — COMPLETE

```

.site-nav {
  position: fixed;
  top: 0; left: 0; right: 0;
  z-index: 1000;
  display: flex;
  align-items: center;
  justify-content: space-between;
  padding: 20px 28px;
  /* Transparent — never gains background color */
  mix-blend-mode: normal;
  pointer-events: none; /* Let scroll pass through */
}
.site-nav a, .site-nav nav { pointer-events: all; }

/* — Logo — */
.nav-logo {
  position: relative;
  width: 64px;
  height: 32px;
  display: block;
}
.logo {
  position: absolute; inset: 0;
  width: 100%; height: 100%;
  object-fit: contain;
  transition: opacity 0.35s ease, transform 0.35s var(--ease-out-expo);
}
.logo--main { opacity: 1; transform: translateY(0); }
.logo--cute { opacity: 0; transform: translateY(8px); }

/* Swap on scroll > 80px */
.site-nav.is-scrolled .logo--main { opacity: 0; transform: translateY(-8px); }
.site-nav.is-scrolled .logo--cute { opacity: 1; transform: translateY(0); }

/* — *WOW* COOL — */

```

```

.nav-wow {
  display: flex;
  flex-direction: column;
  align-items: center;
  line-height: 1;
  font-size: 9px;
  font-weight: 700;
  text-transform: uppercase;
  letter-spacing: 0.15em;
  color: rgba(245,240,235,0.4);
  user-select: none;
}
.nav-wow__line:first-child {
  font-style: italic;
  color: rgba(245,240,235,0.6);
}

/* — Nav Links — */
.nav-links {
  display: flex;

  gap: 24px;
  align-items: center;
}

.nav-link {
  position: relative;
  display: inline-flex;
  flex-direction: column;
  overflow: hidden;
  height: 1.1em;
  text-decoration: none;
  font-size: 13px;
  font-weight: 700;
  text-transform: uppercase;
  letter-spacing: 0.06em;
  color: var(--color-text);
  gap: 0;
}

.nav-link__text {
  display: block;
  transition: transform 0.4s cubic-bezier(0.16, 1, 0.3, 1);
  line-height: 1.1;
}

.nav-link:hover .nav-link__text {
  transform: translateY(-100%); /* Both shift up – 2nd copy enters from bottom */
}

```

JS – NAV SCROLL STATE

```

const nav = document.querySelector('.site-nav');
let lastY = 0;

window.addEventListener('scroll', () => {
  const y = window.scrollY;
  nav.classList.toggle('is-scrolled', y > 80);
  /* Hide nav on fast scroll down, show on scroll up */
  nav.classList.toggle('is-hidden', y > lastY + 4 && y > 200);
  nav.classList.toggle('is-hidden', false); /* DIKO keeps it always visible */
});

```

```
    lastY = y;
  });
```

23 OBAMA TESTIMONIALS STRIP

HORIZONTAL AUTO-SCROLL · FACE + RANDOM QUOTE PAIRS

Eight instances of an Obama head image are arranged in a horizontal scrolling strip. Each is paired with a short quote. The strip is a separate marquee that auto-scrolls left infinitely. The quotes rotate independently from the image positions, creating an absurdist "testimonial" feel. The background video `Exported_1200×674.mp4` plays behind this at low opacity.

HTML

```
<section class="testimonial-section">

  <video class="testimonial-section__bg-video"
    src="Exported_1200×674.mp4"
    autoplay loop muted playsinline></video>

  <!-- Statement above strip -->
  <div class="testimonial-section__label">
    <span>ONLY PEOPLE IN ADVERTISING</span>
    <span>Like advertising</span>
  </div>

  <div class="quote-strip">
    <div class="quote-strip__track">

      <!-- Repeat this block 8 times, duplicate for seamless loop -->
      <div class="quote-card">
        
        <p class="quote-card__text">Love it</p>
      </div>
      <div class="quote-card">
        
        <p class="quote-card__text">I hate it</p>
      </div>
      <div class="quote-card">
        
        <p class="quote-card__text">You are amazing</p>
      </div>
      <!-- ...5 more cards... then duplicate entire set -->

    </div>
  </div>

</section>
```

FULL QUOTE ARRAY

```
const OBAMA_QUOTES = [
  "Love it",
  "You are amazing",
  "...",
```

```
"We got 5 pages of feedback",  
"Smells like an effie",  
"Слава Україні",  
"Truly A Masterpiece",  
"You suck",  
"Love is all we need right now"  
];
```

CSS - QUOTE STRIP

```
.testimonial-section {  
  position: relative;  
  overflow: hidden;  
  padding: 80px 0;  
}  
  
.testimonial-section__bg-video {  
  position: absolute; inset: 0;  
  width: 100%; height: 100%;  
  object-fit: cover;  
  
  opacity: 0.18;  
  z-index: 0;  
}  
  
.testimonial-section__label {  
  position: relative; z-index: 2;  
  padding: 0 40px 40px;  
  display: flex;  
  gap: 0.5em;  
  flex-wrap: wrap;  
  align-items: baseline;  
}  
  
.testimonial-section__label span:first-child {  
  font-size: clamp(24px, 4vw, 64px);  
  font-weight: 900;  
  text-transform: uppercase;  
  line-height: 0.9;  
}  
  
.testimonial-section__label span:last-child {  
  font-size: clamp(20px, 3vw, 48px);  
  font-style: italic;  
  font-weight: 700;  
}  
  
/* Strip */  
.quote-strip { overflow: hidden; position: relative; z-index: 2; }  
  
.quote-strip__track {  
  display: inline-flex;  
  gap: 40px;  
  padding: 20px 0;  
  animation: scrollLeft 28s linear infinite;  
}  
  
.quote-card {  
  display: flex;  
  align-items: center;  
  gap: 16px;  
  flex-shrink: 0;  
  background: rgba(255,255,255,0.04);  
  border: 1px solid rgba(255,255,255,0.08);
```

```
padding: 16px 24px;

border-radius: 2px;
}

.quote-card__face {
width: clamp(40px, 5vw, 72px);
height: auto;
border-radius: 50%;
filter: grayscale(30%);
}

.quote-card__text {
font-size: clamp(14px, 2vw, 24px);
font-weight: 700;
white-space: nowrap;
}
```

24 FULL-BLEED VIDEO SECTION PATTERN

REUSABLE PATTERN USED ACROSS ALL STATEMENT SECTIONS

The majority of DIKO's content sections share a single composable pattern: a **full-viewport-height container** with an autoplay MP4 covering the entire background, a dark overlay at controlled opacity, and large text content centered or bottom-aligned over it. This is the single most frequently used layout primitive on the site.

THE UNIVERSAL VIDEO SECTION TEMPLATE

```
<!-- Reusable video section -->
<section class="video-section" data-overlay="0.45">

  <!-- Background video -->
  <div class="video-section__media">
    <video
      class="video-section__video"
      src="[VIDEO].mp4"
      autoplay loop muted playsinline
      poster="[POSTER].webp"
    ></video>
  <!-- Overlay -->
  <div class="video-section__overlay"></div>
</div>

  <!-- Content -->
  <div class="video-section__content">
    <h2 class="video-section__headline">
      NO ONE ELSE CAN SHARE THE NAME<br>
      YOU MAKE FOR YOURSELF
    </h2>
  </div>

</section>
```

```

.video-section {
  position: relative;
  min-height: 100vh;
  display: flex;
  align-items: center;
  justify-content: center;
  overflow: hidden;
}

.video-section__media {
  position: absolute; inset: 0;
}

.video-section__video {
  width: 100%; height: 100%;
  object-fit: cover;
  /* Parallax via JS transform – see scroll section */
  will-change: transform;
}

.video-section__overlay {
  position: absolute; inset: 0;
  /* Opacity driven by data-overlay attribute via JS */

  background: #050505;
  opacity: 0.45; /* default; varies per section */
}

.video-section__content {
  position: relative;
  z-index: 2;
  padding: 60px 40px;
  max-width: 1400px;
  width: 100%;
  margin: 0 auto;
}

.video-section__headline {
  font-size: clamp(36px, 7vw, 120px);
  font-weight: 900;
  text-transform: uppercase;
  line-height: 0.88;
  color: #F5F0EB;
  letter-spacing: -0.02em;
}

/* Overlay opacity driven from data attribute */
.video-section[data-overlay="0.3"] .video-section__overlay { opacity: 0.3; }
.video-section[data-overlay="0.45"] .video-section__overlay { opacity: 0.45; }
.video-section[data-overlay="0.6"] .video-section__overlay { opacity: 0.6; }
.video-section[data-overlay="0.7"] .video-section__overlay { opacity: 0.7; }

```

OVERLAY OPACITY BY SECTION

SECTION	OVERLAY	RATIONALE
Hero panels (video behind text)	0.0	No overlay — text uses mix-blend-mode
"Some people are allergic to vanilla"	0.35	Video is recognizable brand content
"No one else can share the name"	0.50	Moderate — video mood, not distraction

"IMITATION IS THE GREATEST FORM OF THEFT"	0.65	Text legibility is priority
"PEOPLE CAN SMELL AN AD FROM A MILE AWAY"	0.60	Glitched/moshed video — heavier overlay
"Safe thinking is a dangerous place"	0.55	Four SVG icons also over video
Obama testimonial strip BG	0.82	Very dark — strip is the focus

25 CAR WHEEL SPIN + TRANSITION SECTIONS

CONTINUOUS ROTATE · SECTION SEPARATOR DEVICE

The `car_wheel_spin.webp` image is used as a visual separator between content sections. It rotates continuously. The wheel is centered in a full-width band and is intentionally oversized relative to the section height — it bleeds off the edges of the container.

```
.wheel-section {
  display: flex;
  align-items: center;
  justify-content: center;
  padding: 60px 0;
  overflow: hidden; /* Clip the bleed */
  position: relative;
}

.wheel-section__headline {
  position: absolute;
  font-size: clamp(16px, 2.5vw, 36px);
  font-weight: 700;
  text-transform: uppercase;
  letter-spacing: 0.04em;
  z-index: 2;
  text-align: center;
}

.car-wheel {
  width: clamp(300px, 50vw, 700px);
  height: auto;
  animation: wheelSpin 4s linear infinite;
  transform-origin: center center;
  position: relative; z-index: 1;
  opacity: 0.15; /* Subtle — content text sits on top */
}

@keyframes wheelSpin {
  from { transform: rotate(0deg); }
  to { transform: rotate(360deg); }
}
```

TIP

The spin speed changes with scroll velocity — faster scrolling spins the wheel faster. Tie it to the same `scrollVelocity` variable used for the marquees: `wheelEl.style.animationDuration = Math.max(0.8, 4 - scrollVelocity * 0.1) + 's' .`

SCROLL-LINKED ANIMATIONS · PIN · SCRUB

DIKO uses GSAP ScrollTrigger for the more complex scroll-linked animations that CSS IntersectionObserver can't handle — particularly the hero panel reveal and any scrubbed parallax. Below are the exact patterns to replicate each.

HERO PANEL CLIP-PATH VIA GSAP

```
// Load GSAP from CDN:
// <script src="https://cdnjs.cloudflare.com/ajax/libs/gsap/3.12.5/gsap.min.js"></script>
// <script src="https://cdnjs.cloudflare.com/ajax/libs/gsap/3.12.5/ScrollTrigger.min.js"></script>

gsap.registerPlugin(ScrollTrigger);

// Hero panels — fire ONCE on load, not on scroll
function initHeroReveal() {
  const panels = gsap.utils.toArray('.hero__panel');

  gsap.fromTo(panels,
    { clipPath: 'inset(0 50%)' },
    {
      clipPath: 'inset(0 0%)',
      duration: 1.2,
      ease: 'power4.inOut',
      stagger: 0.08,
      delay: 1.2 // After preloader begins exiting
    }
  );

  // Hero logo fades in after panels open
  gsap.fromTo('.hero__logo',
    { opacity: 0, scale: 0.96 },
    { opacity: 1, scale: 1, duration: 0.7, ease: 'power2.out', delay: 2.1 }
  );
}
```

SCROLL-SCRUBBED PARALLAX

```
function initParallax() {
  gsap.utils.toArray('.video-section__video').forEach(video => {
    gsap.fromTo(video,
      { yPercent: -12 },
      {
        yPercent: 12,
        ease: 'none',
        scrollTrigger: {
          trigger: video.closest('.video-section'),
          start: 'top bottom',
          end: 'bottom top',
          scrub: 1.5 /* Lag in seconds — smoother */
        }
      }
    );
  });
}
```

STAGGERED SVG ICON REVEAL

```
// The 4 "good-1 to good-4" expression icons reveal on scroll

gsap.fromTo('.good-icon',
  { y: 40, opacity: 0, rotation: -12 },
  {
    y: 0, opacity: 1, rotation: 0,
    duration: 0.7,
    ease: 'back.out(1.4)', /* Spring overshoot */
    stagger: 0.12,
    scrollTrigger: {
      trigger: '.safe-thinking-section',
      start: 'top 65%',
      toggleActions: 'play none none reverse'
    }
  }
);

// The 4 "only-1 to only-4" service icons
gsap.fromTo('.only-icon',
  { x: -30, opacity: 0 },
  {
    x: 0, opacity: 1,
    duration: 0.6,
    ease: 'power3.out',
    stagger: 0.1,
    scrollTrigger: {
      trigger: '.services-section',
      start: 'top 60%'
    }
  }
);
```

PINNED TEXT SPLIT - "IMITATION IS THE GREATEST / FORM OF THEFT"

```
// The two halves of the phrase separate as you scroll through the section
gsap.timeline({
  scrollTrigger: {
    trigger: '.imitation-section',
    start: 'top top',
    end: '+=120%',
    pin: true,
    scrub: 1
  }
})
.fromTo('.imitation-line--1', { xPercent: 0 }, { xPercent: -8 })
.fromTo('.imitation-line--2', { xPercent: 0 }, { xPercent: 8 }, '<');
```

27 RESPONSIVE BREAKPOINTS

BREAKPOINT	WIDTH	KEY CHANGES
Mobile	≤ 479px	Hero stacks vertically (4 panels → 1 column), custom cursor removed, marquee font-size halved, icon belt icons ~40px, nav links hidden → hamburger menu, dollar bills reduce to 3
Tablet	480px – 991px	Hero panels 2x2 grid, marquee speed slightly slower, icon belt 3 rows visible, nav links show, case studies 70vh
Desktop	≥ 992px	Full layout as described throughout this document
Wide	≥ 1440px	Max-width containers active. Font sizes hit clamp ceiling. Marquee slightly faster for wider viewport fill.

MOBILE HERO ADAPTATION

```

@media (max-width: 767px) {

  .hero__panels {
    flex-direction: column;
    height: auto;
    min-height: 100dvh;
  }

  .hero__panel {

    flex: 1 0 25vh;
    padding: 16px 20px;
  }

  /* Remove parallax on mobile – performance */
  .video-section__video {
    transform: none !important;
    will-change: auto;
  }

  /* Cursor – remove entirely */
  .cursor-fly { display: none !important; }
  * { cursor: auto !important; }

  /* Marquee – slow down slightly */
  .marquee--left .marquee__track { animation-duration: 30s; }
  .marquee--right .marquee__track { animation-duration: 30s; }

  /* Dollar bills – 3 not 5 */
  .dollar-bill:nth-child(n+4) { display: none; }

  /* Icon belt – reduce icon size */
  .icon-belt__item img { height: 36px; }
  .icon-belt__item span { font-size: 24px; }
}

```

28 SMOOTH SCROLL — LENIS SETUP

MOMENTUM SCROLL · GSAP INTEGRATION

DIKO uses a smooth scroll library to give the page its characteristic **buttery, momentum-based feel**. The most likely candidate is

Lenis (by Studio Freight), which is the modern standard and integrates cleanly with GSAP ScrollTrigger.

```
<!-- CDN -->
<script src="https://cdn.jsdelivr.net/npm/@studio-freight/lenis@1.0.42/dist/lenis.min.js"></script>

// Initialize Lenis smooth scroll
const lenis = new Lenis({
  duration: 1.2,
  easing: t => Math.min(1, 1.001 - Math.pow(2, -10 * t)),
  direction: 'vertical',
  gestureDirection: 'vertical',
  smooth: true,
  smoothTouch: false, /* Disable on touch - can feel wrong */ touchMultiplier: 2
});

// Connect Lenis to GSAP ticker (required)
gsap.ticker.add((time) => {
  lenis.raf(time * 1000);
});
gsap.ticker.lagSmoothing(0);

// Connect Lenis scroll to ScrollTrigger
lenis.on('scroll', ScrollTrigger.update);

// Expose globally if needed
window.lenis = lenis;
```

CRITICAL

When using Lenis + ScrollTrigger together, always set `ScrollTrigger.scrollerProxy` or use the `lenis.on('scroll', ScrollTrigger.update)` pattern shown above. Without this, scroll-triggered animations will lag behind the smooth scroll position.

29 SECTION DIVIDERS & VISUAL RHYTHM

DIKO uses **four types of section boundaries**. Understanding which to use where is key to reproducing the site's pacing.

TYPE	CSS	WHERE USED
Hard Cut	Adjacent sections, no gap, no border	Between most video sections — visual slam cut
Thin Rule	<code>border-top: 1px solid rgba(245,240,235,0.12)</code>	Marquee strips, around conveyor belt section
Padding Gap	<code>padding: 80px 40px</code> on content sections	Statement text sections (dollar bills, love/hate)
Full Bleed Video Transition	Previous section ends, video section starts at 100vh	Hero → marquee → Rumpl case study

PAGE RHYTHM MAP

```
/*
  Vertical rhythm pattern (top to bottom):

  [PRELOADER - fixed overlay]
```

[HERO – 100vh, full bleed panels]

[MARQUEE STRIP – ~160px high, thin rules above/below]

[RUMPL CASE – 90vh video]

[ICON CONVEYOR – auto height, ~5 rows × 80px]

[NO ONE ELSE – 100vh video + statement]

[CLICK SECTION – 80vh]

[GOOGLE PIZZA CASE – 90vh video]

[OBAMA STRIP – ~320px, padded]

[LOVE/HATE – 60vh, padded]

[DOLLAR BILLS – 60vh, centered]

[IMEET CASE – 90vh video]

[IMITATION/THEFT – 100vh video + text]

[PEOPLE CAN SMELL – 100vh video + text → ONE BLADE link]

[SAFE THINKING – 100vh video + 4 SVG icons]

[CAR WHEEL + "DON'T PUT ALL YOUR HAPPINESS" – ~50vh]

[BURGER BOUNCE – ~40vh]

[SERVICES/COMPUTER – ~80vh]

[EVERYTHING IS A WORK IN PROGRESS – ~60vh]

[SUBSCRIBE MARQUEE – ~120px]

[FOOTER – logo + address + nav]

*/

30 COMPLETE STARTER TEMPLATE

DROP-IN SCAFFOLD – WIRES TOGETHER ALL SYSTEMS

This is the minimal scaffold that bootstraps all systems documented above. Drop in your own content, videos, and SVGs. The JavaScript initializes every module in correct dependency order.

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>DIKO – Full-service Brand Agency</title>
```

```
<!-- Fonts -->
<link rel="preconnect" href="https://fonts.googleapis.com">
<link href="[YOUR-FONT-CDN]" rel="stylesheet">

<!-- GSAP -->
<script src="https://cdnjs.cloudflare.com/ajax/libs/gsap/3.12.5/gsap.min.js"></script>
<script src="https://cdnjs.cloudflare.com/ajax/libs/gsap/3.12.5/ScrollTrigger.min.js"></script>

<!-- Lenis -->
<script src="https://cdn.jsdelivr.net/npm/@studio-freight/lenis@1.0.42/dist/lenis.min.js"></script>

<style>
/* — GLOBAL RESET — */
*, ::before, ::after { box-sizing: border-box; margin: 0; padding: 0; }
html { scroll-behavior: auto; } /* Lenis handles this */

:root {
  --color-bg: #050505;
  --color-text: #F5F0EB;
  --color-orange: #F04E0F;
  --color-yellow: #F0D020;
  --color-red: #D0261C;
  --ease-expo: cubic-bezier(0.16, 1, 0.3, 1);
  --ease-inout: cubic-bezier(0.76, 0, 0.24, 1);
  --ease-spring: cubic-bezier(0.34, 1.56, 0.64, 1);
}

body {
  background: var(--color-bg);
  color: var(--color-text);
  font-family: 'YourDisplayFont', sans-serif;
  overflow-x: hidden;
}

/* — CURSOR — */
* { cursor: none !important; }
.cursor-fly {
  position: fixed; pointer-events: none; z-index: 99999;
  width: 32px; height: 32px;
  transform: translate(-50%, -50%);
  will-change: transform;
}

/* — PRELOADER — */
.preloader {
  position: fixed; inset: 0; z-index: 9999;
  background: var(--color-bg);
  display: flex; align-items: center; justify-content: center;
  transition: transform 0.9s var(--ease-inout) 0.2s, opacity 0.4s ease 0.9s;
}

.preloader.is-hidden { transform: translateY(-100%); opacity: 0; pointer-events: none; }

.preloader__grid {
  display: grid; grid-template-columns: repeat(3, 1fr); grid-template-rows: repeat(2, 1fr);
  gap: 20px; width: 80vw; max-width: 900px;
}

.preloader__cell {
  position: relative; display: flex; align-items: center;
  justify-content: center; aspect-ratio: 1;
}

.bomb { width: clamp(60px, 8vw, 120px); position: relative; z-index: 2;
  animation: bombFloat 2.4s ease-in-out infinite; }
```

```

.preloader__cell:nth-child(1) .bomb { animation-delay: 0s; }
.preloader__cell:nth-child(2) .bomb { animation-delay: .2s; }
.preloader__cell:nth-child(3) .bomb { animation-delay: .4s; }
.preloader__cell:nth-child(4) .bomb { animation-delay: .6s; }
.preloader__cell:nth-child(5) .bomb { animation-delay: .3s; }
.preloader__cell:nth-child(6) .bomb { animation-delay: .5s; }

.smoke { position: absolute; pointer-events: none; }
.smoke--orange { width:140%; bottom:-10%; left:-20%; animation: smokePulse 2.8s ease-in-out infinite; }
.smoke--yellow { width:80%; top:5%; right:-10%; animation: smokePulse 2.2s ease-in-out infinite .4s; }
.smoke--red { width:60%; top:-5%; left:5%; animation: smokePulse 3.1s ease-in-out infinite .2s; }

/* — HERO — */
.hero { height: 100vh; position: relative; overflow: hidden; }
.hero__panels { display: flex; height: 100%; }
.hero__panel {
  position: relative; overflow: hidden; flex: 1;
  display: flex; align-items: flex-end; padding: 32px;
  clip-path: inset(0 50%);
}
.hero__panel video {
  position: absolute; inset: 0;
  width: 100%; height: 100%; object-fit: cover;
}
.hero__word {
  font-size: clamp(48px, 6vw, 96px); font-weight: 900;
  text-transform: uppercase; color: white;
  position: relative; z-index: 2; mix-blend-mode: difference;
}
.hero__subtitle {

  position: absolute; bottom: 24px; left: 50%;
  transform: translateX(-50%);
  font-size: 11px; font-weight: 700; text-transform: uppercase;
  letter-spacing: 0.2em; white-space: nowrap; z-index: 10;
  opacity: 0; transition: opacity 0.5s ease 2.2s;
}
.hero.is-loaded .hero__subtitle { opacity: 0.5; }

/* — MARQUEE — */
.marquee-wrap { overflow: hidden;
  border-top: 1px solid rgba(245,240,235,.12);
  border-bottom: 1px solid rgba(245,240,235,.12); }
.marquee { overflow: hidden; white-space: nowrap; padding: 8px 0; }
.marquee__track { display: inline-flex; gap: .5em; }
.marquee--left .marquee__track { animation: scrollLeft 22s linear infinite; }
.marquee--right .marquee__track { animation: scrollRight 22s linear infinite; }
.marquee__track span {
  font-size: clamp(40px, 7vw, 100px); font-weight: 900;
  text-transform: uppercase; padding-right: 1em;
}

/* — VIDEO SECTION — */
.video-section { position: relative; min-height: 100vh;
  display: flex; align-items: center; overflow: hidden; }
.video-section__media { position: absolute; inset: 0; }
.video-section__video { width:100%; height:100%; object-fit:cover; will-change: transform; }
.video-section__overlay { position: absolute; inset: 0; background: #050505; opacity: .5; }
.video-section__content { position: relative; z-index:2; padding: 60px 40px; width:100%; }
.video-section__headline {
  font-size: clamp(36px, 7vw, 120px); font-weight: 900;
  text-transform: uppercase; line-height: 0.88; letter-spacing: -.02em;
}

```

```

/* — ICON BELT — */
.icon-belt { overflow: hidden; }
.icon-belt__row { display: flex; overflow: hidden; padding: 10px 0;
  border-bottom: 1px solid rgba(245,240,235,.08); }
.icon-belt__track { display: inline-flex; align-items: center; gap: 24px; white-space: nowrap; }
.icon-belt__row--left .icon-belt__track { animation: scrollLeft var(--speed, 20s) linear infinite; }
.icon-belt__row--right .icon-belt__track { animation: scrollRight var(--speed, 20s) linear infinite; }
.icon-belt__item { display: flex; align-items: center; gap: 16px; padding: 0 20px; }
.icon-belt__item img { height: clamp(40px, 5vw, 80px); width: auto; }

.icon-belt__item span { font-size: clamp(28px, 4vw, 64px); font-weight: 900; text-transform: uppercase; }

/* — DOLLAR BILLS — */
.dollar-bills { display: flex; gap: clamp(8px, 2vw, 32px); perspective: 600px; }
.dollar-bill {
  width: clamp(80px, 12vw, 200px);
  animation: billSpin 1.8s linear infinite;
  transform-style: preserve-3d;
}
.dollar-bill:nth-child(2) { animation-delay: -.36s; }
.dollar-bill:nth-child(3) { animation-delay: -.72s; }
.dollar-bill:nth-child(4) { animation-delay: -1.08s; }
.dollar-bill:nth-child(5) { animation-delay: -1.44s; }

/* — WORD REVEAL — */
.word-reveal { display: inline-block; overflow: hidden; vertical-align: bottom; }
.word-reveal__inner { display: block; transform: translateY(110%);
  transition: transform 0.7s var(--ease-expo); }
.word-reveal.is-visible .word-reveal__inner { transform: translateY(0); }

/* — NAV — */
.site-nav {
  position: fixed; top: 0; left: 0; right: 0; z-index: 1000;
  display: flex; align-items: center; justify-content: space-between;
  padding: 20px 28px; pointer-events: none;
}
.site-nav > * { pointer-events: all; }
.nav-logo { position: relative; width: 64px; height: 32px; display: block; }
.logo { position: absolute; inset: 0; width: 100%; height: 100%;
  object-fit: contain; transition: opacity .35s ease, transform .35s var(--ease-expo); }
.logo--main { opacity: 1; transform: translateY(0); }
.logo--cute { opacity: 0; transform: translateY(8px); }
.site-nav.is-scrolled .logo--main { opacity: 0; transform: translateY(-8px); }
.site-nav.is-scrolled .logo--cute { opacity: 1; transform: translateY(0); }
.nav-links { display: flex; gap: 24px; }
.nav-link {
  position: relative; display: inline-flex; flex-direction: column;
  overflow: hidden; height: 1.1em; text-decoration: none;
  font-size: 13px; font-weight: 700; text-transform: uppercase;
  letter-spacing: .06em; color: var(--color-text);
}
.nav-link__text { display: block; line-height: 1.1;
  transition: transform 0.4s var(--ease-expo); }
.nav-link:hover .nav-link__text { transform: translateY(-100%); }

/* — KEYFRAMES — */
@keyframes bombFloat { 0%, 100% { transform: translateY(0) rotate(-4deg); } 50% { transform: translateY(-14px) rotate(4deg); } }
@keyframes smokePulse { 0%, 100% { transform: scale(1) rotate(0deg); opacity: .85; } 50% { transform: scale(1.08) rotate(5deg); opacity: .85; } }
@keyframes scrollLeft { 0% { transform: translateX(0); } 100% { transform: translateX(-50%); } }
@keyframes scrollRight { 0% { transform: translateX(-50%); } 100% { transform: translateX(0); } }
@keyframes billSpin { 0% { transform: rotateY(0deg); } 100% { transform: rotateY(360deg); } }
@keyframes wheelSpin { from { transform: rotate(0deg); } to { transform: rotate(360deg); } }

```



```

/* — REDUCED MOTION — */
@media (prefers-reduced-motion: reduce) {
  .marquee__track, .dollar-bill, .bomb, .car-wheel { animation: none !important; }
  .cursor-fly { display: none !important; }
  * { cursor: auto !important; }
  .word-reveal__inner { transform: none !important; transition: none !important; }
  .hero__panel { transition: none !important; clip-path: inset(0 0%) !important; }
}
</style>
</head>
<body>

<!-- CUSTOM CURSOR -->


<!-- PRELOADER -->
<div class="preloader">
  <div class="preloader__grid">
    <!-- 6 cells -->
  </div>
</div>

<!-- NAV -->
<header class="site-nav">
  <a href="/" class="nav-logo">
    
    
  </a>
  <div class="nav-wow"><span>*WOW*</span><span>COOL</span></div>
  <nav class="nav-links">
    <a href="/work" class="nav-link"><span class="nav-link__text">WORK</span><span class="nav-link__text">WORK</span></a>

    <a href="/about" class="nav-link"><span class="nav-link__text">FAQ U</span><span class="nav-link__text">FAQ U</span></a>
  </nav>
</header>

<!-- HERO -->
<section class="hero">
  <div class="hero__panels">
    <div class="hero__panel"><video src="hero-1.mp4" autoplay loop muted playsinline></video><span class="hero__word">Full</span>
    <div class="hero__panel"><video src="hero-2.mp4" autoplay loop muted playsinline></video><span class="hero__word">Service</span>
    <div class="hero__panel"><span class="hero__word">Brand</span></div>
    <div class="hero__panel"><span class="hero__word">Agency</span></div>
  </div>
  <div class="hero__logo"></div>
  <p class="hero__subtitle">Full-service brand agency MADE in austin, TEXAS, AMERICA</p>
</section>

<!-- ...all other sections here... -->

<script>
gsap.registerPlugin(ScrollTrigger);

// — Lenis smooth scroll —
const lenis = new Lenis({ duration: 1.2 });
gsap.ticker.add(t => lenis.raf(t * 1000));
gsap.ticker.lagSmoothing(0);
lenis.on('scroll', ScrollTrigger.update);

// — Cursor —
const fly = document.querySelector('.cursor-fly');
let mx=0,my=0,fx=0,fy=0;
document.addEventListener('mousemove', e => { mx=e.clientX; my=e.clientY; });

```

```

(function tick() {
  fx += (mx-fx)*0.12; fy += (my-fy)*0.12;
  fly.style.transform = `translate(calc(${fx}px - 50%), calc(${fy}px - 50%))`;
  requestAnimationFrame(tick);
})();

// — Preloader —
document.fonts.ready.then(() => {
  window.addEventListener('load', () => {
    setTimeout(() => {
      document.querySelector('.preloader').classList.add('is-hidden');

      setTimeout(() => {
        document.querySelector('.preloader').remove();
        gsap.fromTo('.hero__panel',
          { clipPath: 'inset(0 50%)' },
          { clipPath: 'inset(0 0%)', duration: 1.2, ease: 'power4.inOut', stagger: 0.08 }
        );
      }, 1100);
    }, 800);
  });
});

// — Parallax —
gsap.utils.toArray('.video-section__video').forEach(v => {
  gsap.fromTo(v, { yPercent: -12 }, {
    yPercent: 12, ease: 'none',
    scrollTrigger: { trigger: v.closest('.video-section'), start: 'top bottom', end: 'bottom top', scrub: 1.5 }
  });
});

// — Word reveals —
document.querySelectorAll('.word-reveal').forEach((w, i) => {
  const inner = document.createElement('span');
  inner.className = 'word-reveal__inner';
  inner.style.transitionDelay = i * 0.09 + 's';
  inner.innerHTML = w.innerHTML;
  w.innerHTML = '';
  w.appendChild(inner);
});

const revObs = new IntersectionObserver(es => {
  es.forEach(e => { if(e.isIntersecting) { e.target.classList.add('is-visible'); revObs.unobserve(e.target); } });
}, { threshold: 0.2 });
document.querySelectorAll('.word-reveal').forEach(el => revObs.observe(el));

// — Marquee clone —
document.querySelectorAll('.marquee__track').forEach(track => {
  const item = track.querySelector('span');
  const n = Math.ceil(window.innerWidth * 3 / item.offsetWidth);
  for(let i=0; i// — Nav scroll state —
window.addEventListener('scroll', () => {
  document.querySelector('.site-nav').classList.toggle('is-scrolled', window.scrollY > 80);
});

// — Click button random text —
const CLICK_TEXTS = ["You have the wrong number", "You will click this again",
  "Astronomers will need more space", "Can't believe you clicked",
  "Someone else will figure it out", "Your budget will get cut",
  "A turd will be polished", "Stop. Just stop", "The End?"];

let ci = -1;
const clickBtn = document.getElementById('clickBtn');
if (clickBtn) {
  const txt = clickBtn.querySelector('.click-btn__text');

```

```

clickBtn.addEventListener('click', () => {
  let n; do { n=Math.floor(Math.random()*CLICK_TEXTS.length); } while(n===ci);
  ci=n; txt.style.opacity='0'; txt.style.transform='translateY(-10px)';
  setTimeout(() => {
    txt.textContent=CLICK_TEXTS[ci];
    txt.style.transition='none';txt.style.opacity='0';txt.style.transform='translateY(10px)';
    requestAnimationFrame(() => { txt.style.transition=''; txt.style.opacity='1';txt.style.transform='translateY(0)';
  }, 150);
});
}

// — Love/Hate toggle —
document.querySelectorAll('.toggle-btn').forEach(b => {
  b.addEventListener('click', () => {
    const s = b.dataset.state;
    document.querySelectorAll('.toggle-btn').forEach(x => x.classList.toggle('is-active', x===b));
    document.querySelectorAll('.face').forEach(f => f.classList.toggle('is-active', f.classList.contains('face--'+s)));
  });
});
</script>
</body>
</html>

```

31 WEBFLOW-SPECIFIC IMPLEMENTATION NOTES

DIKO.co is built on **Webflow**. If recreating within Webflow rather than raw HTML, these are the critical mappings and constraints to know.

FEATURE	WEBFLOW APPROACH	CUSTOM CODE NOTES
Preloader	Custom code in <code><head></code> via Project Settings → Custom Code	Must use <code>display:none</code> on <code><body></code> until preloader resolves to prevent FOUC
Hero clip-path panels	Webflow Interactions 2.0 OR custom GSAP	Webflow's built-in interactions can drive clip-path but GSAP stagger is cleaner
Marquee	Not natively supported — pure custom JS + CSS	Inject via <code></body></code> custom code embed
Custom cursor	Custom code embed — add to Project Settings body	Hide Webflow's cursor with <code>* { cursor: none !important }</code> in Custom CSS
Lenis smooth scroll	Custom code embed	Disable Webflow's default smooth scroll if enabled (Site Settings → Accessibility)
Video backgrounds	Webflow Background Video component OR HTML embed	Use HTML embed for full control; Webflow's component adds extra wrapper divs that can interfere with parallax
CMS case studies	Webflow CMS Collection	Fields: title, slug, video URL (Vimeo), poster image, link
SVG illustrations	Inline via embed or as <code></code> assets	SVGs should be inlined for animation control; use Webflow's Asset Manager for static SVGs
Font loading	Webflow Fonts panel (Custom Fonts upload)	Upload WOFF2 files; Webflow serves them from its CDN automatically

GSAP ScrollTrigger	CDN in <code><head></code> custom code	Register plugin after DOM ready — use <code>DOMContentLoaded</code> wrapper
-----------------------	--	--

WEBFLOW INTERACTIONS 2.0 VS GSAP

Webflow's built-in Interactions 2.0 can handle many of the scroll animations (fade-ins, staggered reveals, the word reveal). Use it for simple enter/exit animations. Use custom GSAP for anything requiring **scrubbing, pinning, or clip-path** transitions — Webflow Interactions doesn't support these well.

32 RECREATION CHECKLIST

STEP-BY-STEP BUILD ORDER

PHASE 1 — FOUNDATION

Set up CSS variables (colors, easing, type scale). Load custom display font via @font-face or Webflow Fonts. Set global reset including `cursor: none`. Add `body { background: #050505; color: #F5F0EB; overflow-x: hidden; }`. Init Lenis + GSAP.

PHASE 2 — PRELOADER

Build the 6-cell bomb grid. Implement CSS animations (bombFloat, smokePulse). Write preloader dismissal JS. Test that it blocks page visibility until fonts load, then slides up cleanly.

PHASE 3 — NAVIGATION

Fixed header, transparent. Two logo variants with scroll-state swap. Nav link duplicated text flip hover effect. *WOW* COOL decorative element. Custom fly cursor.

PHASE 4 — HERO

4-panel flexbox layout. Autoplay muted videos in panels 1 & 2. clip-path: inset(0 50%) start state. GSAP tween to inset(0 0%) on load. Large DIKO wordmark fade-in. Subtitle reveal.

PHASE 5 — MARQUEE SYSTEM

Build reusable marquee component. JS clone function for viewport fill. Scroll velocity connection. Both rows (left + right). Apply to hero marquee AND footer marquee.

PHASE 6 — VIDEO SECTIONS

Implement the universal video section template. Set up GSAP ScrollTrigger parallax on all videos. Match overlay opacities per section. Add statement headlines.

PHASE 7 — INTERACTIVE SECTIONS

Click button random text array + animation. Love/hate toggle with face swap. Dollar bill 3D spin. Obama testimonial auto-scroll strip. Icon conveyor belt multi-row.

PHASE 8 — SCROLL REVEALS

Word-by-word IntersectionObserver on "Everything is a work in progress." GSAP stagger reveals on SVG icon groups (good-1 to good-4, only-1 to only-4). Generic fadeUp on case study labels.

PHASE 9 — CASE STUDIES

Full-bleed video cards. Hover overlay + CTA link reveal. Vimeo embed (lazy-load on intersection). Poster images for no-JS fallback.

PHASE 10 — POLISH

Mobile breakpoints. prefers-reduced-motion. Performance audit (lazy video, will-change, passive event listeners). Cross-browser test clip-path in Safari. Add meta og:image, og:title.

DIKO.CO BLUEPRINT

32 SECTIONS · COMPLETE TECHNICAL SPECIFICATION

ANALYZED MAY 2026
MADE IN AUSTIN, TEXAS
INFO@DIKO.CO

THIS DOCUMENT REVERSE-ENGINEERS DIKO.CO FOR EDUCATIONAL AND IMPLEMENTATION PURPOSES. ALL ORIGINAL DESIGN, COPY, AND CREATIVE DIRECTION BELONG TO DIKO. SOME PEOPLE ARE ALLERGIC TO VANILLA.