

# Performance

martes, 15 de marzo de 2022 06:56 a. m.

Ideally :

$$t_p^{\text{ideal}} = \left[ \frac{t_s}{n_p} \right] \rightarrow \text{sequential time}$$

$$\rightarrow \text{number of processors}$$

When working in parallel. From this, we can calculate Overcharged Time:


$$t_{sc} = [t_p - t_p^{\text{ideal}}]$$

↓  
usually bigger than  $t_p^{\text{ideal}}$

→ this time can tell:

• In Shared Memory

→ Means we have problems in communication. There are many synchronization techniques that involve Blockers to Critical Sections. Example



→ Blocking serializes our program, which also involves dependency

• In Distributed Memory


→ Each processor has its memory, and thus only with Messaging the Overcharge Time increases.

→ The more Data we need to message through the network, the more Overcharge Time we will have

$$\uparrow \text{Data} = \uparrow t_{sc}$$

→ Amdahl's Law

Is a specific case of the General Form



Let's now calculate acceleration

$$S = \frac{t_s}{t_p} = \frac{t_s}{\frac{t_s + T_{s \rightarrow p}}{n_p}} = \frac{n_p t_s}{t_s + T_{s \rightarrow p}}$$

with  $T_s = a t_s$  and  $T_{s \rightarrow p} = (1-a) t_s$ , we now have

$$S = \frac{a t_s + (1-a) t_s}{a t_s + \frac{(1-a) t_s}{n_p}} \left\{ \begin{array}{l} \text{we have } \frac{t_s (\text{num})}{t_s (\text{denom})} \text{ thus we can} \\ \text{cancel out } t_s \text{ term.} \end{array} \right.$$

$$= \frac{a + (1-a)}{a + \frac{(1-a)}{n_p}}$$

$$S = \frac{1}{a + \frac{(1-a)}{n_p}}$$


Amdahl's Law: a relationship of how time changes from 1 to  $n_p$  processors

If we say  $n_p \rightarrow \infty$ , then

$$\lim_{n_p \rightarrow \infty} S = \lim_{n_p \rightarrow \infty} \frac{1}{a + \frac{(1-a)}{n_p}} = \frac{1}{a} \quad \text{the acceleration limit we can achieve}$$

$\frac{(1-a)}{\infty} \approx 0$

If we plot Amdahl's Law



Let's say  $a = 0.1$  (10%),


$$S_{MAX} = \frac{1}{a} = \frac{1}{0.1} = 10 \quad \left\{ \begin{array}{l} \text{maximum scalability we can} \\ \text{achieve in a problem where} \\ 10\% \text{ of total time not parallel:} \\ \text{no matter how many processors we put,} \\ \text{acceleration (s) will be } S = 10 \end{array} \right.$$

Let's say  $a = 0.01$  (1%)

$$S_{MAX} = \frac{1}{a} = \frac{1}{0.01} = 100$$

The problem itself has almost no dependencies ( $a$  small), thus 100 of  $S$ .

However, Amdahl's Law does not take on account  $n$  (problem's size), and since  $n$  is fixed in the law, scalability (Weak) is not considered. So if we want to scale  $n$  naturally, we need to scale it  $\beta (T_{s \rightarrow p})$ :



Thus,

$$a t_s \rightarrow \alpha a t_s \quad \left\{ \begin{array}{l} \text{represents that the problem increases} \end{array} \right.$$

$(1-\alpha)t_s \rightarrow \beta(1-\alpha)t_s$  with the amount of processors

Let's calculate scalability (acceleration),

$$S = \frac{t_s}{t_p} = \frac{T_s + T_{s \rightarrow p}}{T_s + \left[ \frac{T_{s \rightarrow p}}{n_p} \right]} \quad \text{with } T_s = \alpha t_s \text{ and } T_{s \rightarrow p} = \beta(1-\alpha)t_s$$

$$= \frac{\alpha t_s + \beta(1-\alpha)t_s}{\alpha t_s + \left[ \frac{\beta(1-\alpha)t_s}{n_p} \right]}$$

Once again  $t_s$  is a common factor on both numerator and denominator, and therefore we can cancel it out,

$$= \frac{\alpha + \beta(1-\alpha)}{\alpha + \left[ \frac{\beta(1-\alpha)}{n_p} \right]}$$

If we divide numerator and denominator by  $1/\alpha$ ,

$$= \frac{\frac{\alpha}{\alpha} + \frac{\beta(1-\alpha)}{\alpha}}{\frac{\alpha}{\alpha} + \left[ \frac{\beta(1-\alpha)}{\alpha n_p} \right]}$$

And we can again cancel out  $\alpha$ ,

$$= \frac{1 + \left[ \frac{\beta}{\alpha} \right] (1-\alpha)}{1 + \left[ \frac{\beta}{\alpha} \right] \frac{(1-\alpha)}{n_p}}, \quad \text{with } \gamma = \left[ \frac{\beta}{\alpha} \right], \text{ we have}$$

$$\boxed{S = \frac{1 + \gamma(1-\alpha)}{1 + \gamma \left[ \frac{(1-\alpha)}{n_p} \right]}} \quad \text{General Law}$$

→ If we have  $\gamma = 1$  ( $\beta = \alpha$ ), we get Amdahl's Law:


$$S = \frac{1 + (1-\alpha)}{1 + \left[ \frac{1-\alpha}{n_p} \right]} = \boxed{\frac{1}{1 + \left[ \frac{1-\alpha}{n_p} \right]}} \quad \text{Amdahl's Law}$$

→ We want to scale the problem as always, that is, multiplying  $n \times n_p$ . Here, that would mean  $\gamma = n_p$ ,


$$S = \frac{1 + n_p(1-\alpha)}{1 + n_p \left[ \frac{1-\alpha}{n_p} \right]} = \frac{1 + n_p(1-\alpha)}{1 + (1-\alpha)} = 1 + n_p(1-\alpha)$$

$$\boxed{S = (1-\alpha)n_p + 1} \quad \text{Gustafson's Law}$$

And we also can derive from General's Law, the Gustafson's Law. It has a linear form:



And these Scalability plots resemble what we have been doing:



Confirming that  
indeed strong  
and weak scalab  
have a log an  
linear form



these two plots  
are just the compu-  
tation time, if you  
have communication,  
just add it at the  
end.