


Week 4

Saturday, February 19, 2022 10:40 AM



World

Graph: nodes connected by lines/arrows.

↓
Circles

The world contains a set of States
↓
describes the configuration of the world.


→ states will be the nodes in the graph: S_1, S_2, \dots, S_n
↳ the n states are visualized through the graph

→ Set of states: $S = \{S_1, \dots, S_n\}$ ie: the H^0 state in the game
↓
Capitalized S
each state: S_1, S_n .

→ if we can pass with an ACTION from a state to another, we connect the nodes with a line

→ To define the lines, we thus need to define the ACTIONS
 $A = \{a_1, \dots, a_m\}$ → not the same as n (states)

→ We transit from a state to another through an action (a).



Write an arrow for each action you need to transition from a node to another

The set of states (S) and set of actions (A) are not enough to describe World, we need:

Transition Model: from which node to which node and with what action

1. Deterministic: defined by a two variable function

$$S_f = f_{MT}(s, a)$$

↳ final state ↳ current state ↳ action to do

This function can be seen in a matrix


$$S \xrightarrow{a} \begin{bmatrix} S_f \end{bmatrix} \quad S_i a_j = S_f \quad \text{↳ the state to which we transition}$$

Example: we have a world:




Thus $S = \{S_1, S_2, S_3\}$ → the domain of s is S
 $A = \{a_1, a_2\}$ → the domain of a is A

$S_f = f_{MT}(s, a)$
↳ Transition Model Function
↳ another variable whose domain is S also
 $S_f \in S$




since there's no $S_3 \xleftarrow{a} S_2$



2. Non-deterministic: it is modeled through a probability distribution that is conditioned.



$$S_f \sim P_{MT}(S_f | s, a)$$

you need a probab. distribution per pair of actions possible x




Let's see one of the six prob distrib func:

$$P_{MT}(S_f | s_1, a_1)$$




$$P_{MT}(S_f | s_1, a_2)$$

We can skip plotting drawing a 3D box:




We can draw this 3D box like:



transition to S_f with a_1 ,
thus we stay in current state s
with probability = 1.


→ there's a probability of transition since in
a NON-DETERMINISTIC world there is a randomness
assumed



After defining S, A, f_{MT} , we need to define a prize and punish.

normally $\left\{ \begin{array}{l} (+) \text{ prizes} \\ (-) \text{ punishes} \end{array} \right\}$ the program aims to accomplish
the highest price possible

→ Price: 3 variable function f_R (can also be deterministic/non deterministic)



We can draw a 4D Plot by grouping 3D boxes


We now have defined The world, but how to define the AGENT?

→ we define how the agent performs the action.

ACTIONS:

1. Deterministic $a = f_{\pi}(s)$

π = Policy, since given a state s it tells which action a to do.
one variable defined as a vector




NON DET: helps model uncertainty

2. NonDeterministic:

$a \sim P_{\pi}(a|s)$
given (or conditioned by) s state

Transition model: $P_{MT}(S_f | s, a)$
 $\begin{bmatrix} S_1 \\ \vdots \\ S_n \end{bmatrix} \begin{bmatrix} a_1 & \dots & a_m \\ P_{11} & \dots & P_{1m} \\ \vdots & \vdots & \vdots \\ P_{n1} & \dots & P_{nm} \end{bmatrix} = 1$
given S_1 , we have m probabilities since we have m possible actions
each row sums 1




Deterministic action

Transition model tables:

	a_1	a_2
S_1	S_1	S_2
S_2	S_2	S_3
S_3	S_3	S_3

$a = f_{\pi}(s) = \begin{bmatrix} S_1 \\ S_2 \\ S_3 \end{bmatrix} \begin{bmatrix} a_1 \\ a_2 \\ a_1 \end{bmatrix}$

deterministic (its results are predictable)
we defined arbitrarily what actions are done given a state
we stay in S_3 if we perform a_1 after seeing the tables



Same $P_{MT}(S_f | s, a)$

$a \sim P_{\pi}(a|s) = \begin{bmatrix} S_1 \\ S_2 \\ S_3 \end{bmatrix} \begin{bmatrix} a_1 & a_2 \\ 0.6 & 0.4 \\ 0.5 & 0.5 \\ 1 & 0 \end{bmatrix}$
These are the probabilities that define the stochastic action a
 $P_{\pi}(a|S_1) = 1$
 $P_{\pi}(a|S_3) = 1$
These are...

World

to

$$P_{\pi}(a|s) = 1$$

action a

These are
the probabilities
of the agent
(inside the world)

→ How does the agent acts inside the world?

↳ Suppose we first position agent in S_1 ,

thus the probability of the agent taking
action a_1 is 60% and a_2 is 40% (decided by a random generator)

you can
go either
to state
 S_2 or S_3

directly
goes
to S_3

probability
of taking
action a_1
↑
prob given a_1
of arriving
to S_2

→ The probability of arriving to S_2 from S_1 is $= (0.6)(0.7) = \boxed{0.42}$