Scan Report

November 7, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone "Coordinated Universal Time", which is abbreviated "UTC". The task was "Metasploitable2 Scan". The scan started at Fri Nov 6 23:43:27 2026 UTC and ended at Sat Nov 7 00:23:07 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1 Result Overview **2**
1.1 Host Authentications . . . 2

2 Results per Host **2**
2.1 192.168.153.133 . . . 2
2.1.1 Critical 80/tcp . . . 3
2.1.2 Critical general/tcp . . . 3
2.1.3 Critical 3632/tcp . . . 4
2.1.4 Critical 5900/tcp . . . 5
2.1.5 Critical 513/tcp . . . 6
2.1.6 Critical 8787/tcp . . . 6
2.1.7 Critical 512/tcp . . . 7
2.1.8 Critical 1524/tcp . . . 7
2.1.9 Critical 8009/tcp . . . 8
2.1.10 Critical 5432/tcp . . . 12
2.1.11 Critical 3306/tcp . . . 13
2.1.12 High 2121/tcp . . . 14
2.1.13 High 514/tcp . . . 15
2.1.14 High 80/tcp . . . 15
2.1.15 High 513/tcp . . . 18
2.1.16 High 1099/tcp . . . 19
2.1.17 High 21/tcp . . . 20
2.1.18 High 6697/tcp . . . 21
2.1.19 High 5432/tcp . . . 22
2.1.20 Medium 2121/tcp . . . 24
2.1.21 Medium 80/tcp . . . 24
2.1.22 Medium 22/tcp . . . 33
2.1.23 Medium 23/tcp . . . 36
2.1.24 Medium 5900/tcp . . . 37
2.1.25 Medium 445/tcp . . . 37

2.1.26 Medium 25/tcp 38
2.1.27 Medium 21/tcp 50
2.1.28 Medium 5432/tcp 52
2.1.29 Low general/tcp 63
2.1.30 Low 22/tcp 64
2.1.31 Low 25/tcp 65
2.1.32 Low general/icmp 69
2.1.33 Low 5432/tcp 69

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
192.168.153.133	11	11	40	6	0	0
Total: 1	11	11	40	6	0	0

Vendor security updates are not trusted.
Overrides are off. Even when a result has an override, this report uses the actual threat of the result.
Information on overrides is included in the report.
Notes are included in the report.
This report might not show details of all issues that were found.
Issues with the threat level "Log" are not shown.
Issues with the threat level "Debug" are not shown.
Issues with the threat level "False Positive" are not shown.
Only results with a minimum QoD of 70 are shown.

This report contains all 68 results selected by the filtering described above. Before filtering there were 633 results.

1.1 Host Authentications

Host	Protocol	Result	Port/User
192.168.153.133	SMB	Success	Protocol SMB, Port 445, User

2 Results per Host

2.1 192.168.153.133

Host scan start Fri Nov 6 23:45:39 2026 UTC
Host scan end Sat Nov 7 00:22:59 2026 UTC

Service (Port)	Threat Level
80/tcp	Critical
general/tcp	Critical
3632/tcp	Critical
5900/tcp	Critical
513/tcp	Critical
8787/tcp	Critical
512/tcp	Critical
1524/tcp	Critical
8009/tcp	Critical
5432/tcp	Critical
3306/tcp	Critical
2121/tcp	High
514/tcp	High
80/tcp	High
513/tcp	High
1099/tcp	High
21/tcp	High
6697/tcp	High
5432/tcp	High
2121/tcp	Medium
80/tcp	Medium
22/tcp	Medium
23/tcp	Medium
5900/tcp	Medium
445/tcp	Medium
25/tcp	Medium

. . . (continues) . . .

... (continued) ...

Service (Port)	Threat Level
21/tcp	Medium
5432/tcp	Medium
general/tcp	Low
22/tcp	Low
25/tcp	Low
general/icmp	Low
5432/tcp	Low

2.1.1 Critical 80/tcp

Critical (CVSS: 10.0)

NVT: TWiki < 4.2.4 Multiple XSS / Command Execution Vulnerabilities

Summary
TWiki is prone to multiple cross-site scripting (XSS) and command execution vulnerabilities.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`Installed version: 01.Feb.2003`
`Fixed version: 4.2.4`

Impact
Successful exploitation could allow execution of arbitrary script code or commands. This could let attackers steal cookie-based authentication credentials or compromise the affected application.

Solution:
Solution type: VendorFix
Update to version 4.2.4 or later.

Affected Software/OS
TWiki versions prior to 4.2.4.

Vulnerability Insight
The flaws are due to:
- %URLPARAM}}% variable is not properly sanitized which lets attackers conduct cross-site scripting attack.
- %SEARCH}}% variable is not properly sanitised before being used in an eval() call which lets the attackers execute perl code through eval injection attack.

Vulnerability Detection Method
Details: `TWiki < 4.2.4 Multiple XSS / Command Execution Vulnerabilities`
OID:1.3.6.1.4.1.25623.1.0.800320
Version used: `2025-12-11T05:46:19Z`

References
`cve: CVE-2008-5304`
`cve: CVE-2008-5305`
`url: http://twiki.org/cgi-bin/view/Codev.SecurityAlert-CVE-2008-5304`
`url: http://www.securityfocus.com/bid/32668`
`url: http://www.securityfocus.com/bid/32669`
`url: http://twiki.org/cgi-bin/view/Codev/SecurityAlert-CVE-2008-5305`

[return to 192.168.153.133]

2.1.2 Critical general/tcp

Critical (CVSS: 10.0)

NVT: Operating System (OS) End of Life (EOL) Detection

Product detection result
cpe:/o:canonical:ubuntu_linux:8.04
Detected by OS Detection Consolidation and Reporting (OID: 1.3.6.1.4.1.25623.1.0
↪.105937)

Summary
The Operating System (OS) on the remote host has reached the end of life (EOL) and should not be used anymore.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The "Ubuntu" Operating System on the remote host has reached the end of life.
CPE: cpe:/o:canonical:ubuntu_linux:8.04
Installed version,
build or SP: 8.04
EOL date: 2013-05-09
EOL info: https://documentation.ubuntu.com/project/release-team/list-of
↪-releases/

Impact
An EOL version of an OS is not receiving any security updates from the vendor. Unfixed security vulnerabilities might be leveraged by an attacker to compromise the security of this host.

Solution:
Solution type: Mitigation
Update the OS on the remote host to a version which is still supported and receiving security updates by the vendor.
Note / Important: Please create an override for this result if the target host is a:
- Windows system with Extended Security Updates (ESU)
- System with additional 3rd-party / non-vendor security updates like e.g. from 'TuxCare', 'Freexian Extended LTS' or similar

Vulnerability Detection Method
Checks if an EOL version of an OS is present on the target host.
Details: Operating System (OS) End of Life (EOL) Detection
OID:1.3.6.1.4.1.25623.1.0.103674
Version used: 2025-05-21T05:40:19Z

Product Detection Result
Product: cpe:/o:canonical:ubuntu_linux:8.04
Method: OS Detection Consolidation and Reporting
OID: 1.3.6.1.4.1.25623.1.0.105937

[return to 192.168.153.133]

2.1.3 Critical 3632/tcp

Critical (CVSS: 9.3)

NVT: DistCC RCE Vulnerability (CVE-2004-2687)

Summary
DistCC is prone to a remote code execution (RCE) vulnerability.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
It was possible to execute the "id" command.
Result: uid=1(daemon) gid=1(daemon)

Impact
... continues on next page ...

... continued from previous page ...

DistCC by default trusts its clients completely that in turn could allow a malicious client to execute arbitrary commands on the server.

Solution:
Solution type: VendorFix
Vendor updates are available. Please see the references for more information.
For more information about DistCC's security see the references.

Vulnerability Insight
DistCC 2.x, as used in XCode 1.5 and others, when not configured to restrict access to the server port, allows remote attackers to execute arbitrary commands via compilation jobs, which are executed by the server without authorization checks.

Vulnerability Detection Method
Details: `DistCC RCE Vulnerability (CVE-2004-2687)`
OID:1.3.6.1.4.1.25623.1.0.103553
Version used: `2022-07-07T10:16:06Z`

References
`cve: CVE-2004-2687`
`url: https://distcc.github.io/security.html`
`url: https://web.archive.org/web/20150511045306/http://archives.neohapsis.com:80/archives/bugtraq/2005-03/0183.html`
`dfn-cert: DFN-CERT-2019-0381`

[return to 192.168.153.133]

2.1.4 Critical 5900/tcp

Critical (CVSS: 9.0)

NVT: VNC Brute Force Login

Summary
The VNC service is prone to default credentials.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
`It was possible to connect to the VNC server with the password: password`

Solution:
Solution type: Mitigation
Change the password to something hard to guess or enable password protection at all.

Affected Software/OS
Various products (e.g. HIPASE-250) and misconfigurations.

Vulnerability Insight
This script tries to authenticate to a VNC server with the passwords set in the password preference. It will also test and report if no authentication / password is required at all.
Note: Some VNC servers have a blacklisting scheme that blocks IP addresses after five unsuccessful connection attempts for a period of time. The script will abort the brute force attack if it encounters that it gets blocked.
Note as well that passwords can be max. 8 characters long.

Vulnerability Detection Method
Tries to log in with given passwords via VNC protocol.
Details: `VNC Brute Force Login`
OID:1.3.6.1.4.1.25623.1.0.106056
Version used: `2026-08-18T05:48:51Z`

References
`cve: CVE-2026-65313`

[return to 192.168.153.133]

2.1.5 Critical 513/tcp

Critical (CVSS: 10.0)

NVT: rlogin Passwordless Login

Summary
The rlogin service allows root access without a password.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`It was possible to gain root access without a password.`

Impact
This vulnerability allows an attacker to gain complete control over the target system.

Solution:
Solution type: Mitigation
Disable the rlogin service and use alternatives like SSH instead.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `rlogin Passwordless Login`
OID:1.3.6.1.4.1.25623.1.0.113766
Version used: `2020-09-30T09:30:12Z`

[return to 192.168.153.133]

2.1.6 Critical 8787/tcp

Critical (CVSS: 10.0)

NVT: Distributed Ruby (dRuby/DRb) Multiple RCE Vulnerabilities

Summary
Systems using Distributed Ruby (dRuby/DRb), which is available in Ruby versions 1.6 and later, may permit unauthorized systems to execute distributed commands.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
```
The service is running in $SAFE >= 1 mode. However it is still possible to run a
↪rbitrary syscall commands on the remote host. Sending an invalid syscall the s
↪ervice returned the following response:
Flo:Errno::ENOSYS:bt["3/usr/lib/ruby/1.8/drb/drb.rb:1555:in `syscall'"0/usr/lib/
↪ruby/1.8/drb/drb.rb:1555:in `send'"4/usr/lib/ruby/1.8/drb/drb.rb:1555:in `__se
↪nd__'"A/usr/lib/ruby/1.8/drb/drb.rb:1555:in `perform_without_block'"3/usr/lib/
↪ruby/1.8/drb/drb.rb:1515:in `perform'"5/usr/lib/ruby/1.8/drb/drb.rb:1589:in `m
↪ain_loop'"0/usr/lib/ruby/1.8/drb/drb.rb:1585:in `loop'"5/usr/lib/ruby/1.8/drb/
↪drb.rb:1585:in `main_loop'"1/usr/lib/ruby/1.8/drb/drb.rb:1581:in `start'"5/usr
↪/lib/ruby/1.8/drb/drb.rb:1581:in `main_loop'"//usr/lib/ruby/1.8/drb/drb.rb:143
↪0:in `run'"1/usr/lib/ruby/1.8/drb/drb.rb:1427:in `start'"//usr/lib/ruby/1.8/dr
↪b/drb.rb:1427:in `run'"6/usr/lib/ruby/1.8/drb/drb.rb:1347:in `initialize'"//us
↪r/lib/ruby/1.8/drb/drb.rb:1627:in `new'"9/usr/lib/ruby/1.8/drb/drb.rb:1627:in
↪`start_service'"%/usr/sbin/druby_timeserver.rb:12:errnoi+:mesg"Function not im
↪plemented
```

Impact
By default, Distributed Ruby does not impose restrictions on allowed hosts or set the $SAFE environment variable to prevent privileged activities. If other controls are not in place, especially if the Distributed Ruby process runs with elevated privileges, an attacker could execute arbitrary system commands or Ruby scripts on the Distributed Ruby server. An attacker may need to know only the URI of the listening Distributed Ruby server to submit Ruby commands.

... continues on next page ...

... continued from previous page ...

Solution:
Solution type: Mitigation
Administrators of environments that rely on Distributed Ruby should ensure that appropriate controls are in place. Code-level controls may include:
- Implementing taint on untrusted input
- Setting $SAFE levels appropriately (>=2 is recommended if untrusted hosts are allowed to submit Ruby commands, and >=3 may be appropriate)
- Including drb/acl.rb to set ACLEntry to restrict access to trusted hosts

Vulnerability Detection Method
Send a crafted command to the service and check for a remote command execution via the instance_eval or syscall requests.
Details: `Distributed Ruby (dRuby/DRb) Multiple RCE Vulnerabilities`
OID:1.3.6.1.4.1.25623.1.0.108010
Version used: `2024-06-28T05:05:33Z`

References
`url:` https://tools.cisco.com/security/center/viewAlert.x?alertId=22750
`url:` http://www.securityfocus.com/bid/47071
`url:` http://blog.recurity-labs.com/archives/2011/05/12/druby_for_penetration_testers/
`url:` http://www.ruby-doc.org/stdlib-1.9.3/libdoc/drb/rdoc/DRb.html

[return to 192.168.153.133]

2.1.7 Critical 512/tcp

Critical (CVSS: 10.0)

NVT: The rexec service is running

Summary
This remote host is running a rexec service.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`The rexec service was detected on the target system.`

Solution:
Solution type: Mitigation
Disable the rexec service and use alternatives like SSH instead.

Vulnerability Insight
rexec (remote execution client for an exec server) has the same kind of functionality that rsh has: you can execute shell commands on a remote computer.
The main difference is that rexec authenticate by reading the username and password *unencrypted* from the socket.

Vulnerability Detection Method
Checks whether an rexec service is exposed on the target host.
Details: `The rexec service is running`
OID:1.3.6.1.4.1.25623.1.0.100111
Version used: `2023-09-12T05:05:19Z`

References
`cve:` CVE-1999-0618

[return to 192.168.153.133]

2.1.8 Critical 1524/tcp

Critical (CVSS: 10.0)

NVT: Possible Backdoor: Ingreslock

Summary
A backdoor is installed on the remote host.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
```
The service is answering to an 'id;' command with the following response: uid=0(
↪root) gid=0(root)
```

Impact
Attackers can exploit this issue to execute arbitrary commands in the context of the application. Successful attacks will compromise the affected isystem.

Solution:
Solution type: Workaround
A whole cleanup of the infected system is recommended.

Vulnerability Detection Method
Details: `Possible Backdoor: Ingreslock`
OID:1.3.6.1.4.1.25623.1.0.103549
Version used: `2023-07-25T05:05:58Z`

[return to 192.168.153.133]

2.1.9 Critical 8009/tcp

Critical (CVSS: 9.8)

NVT: Apache Tomcat AJP RCE Vulnerability (Ghostcat) - Active Check

Summary
Apache Tomcat is prone to a remote code execution (RCE) vulnerability in the AJP connector dubbed 'Ghostcat'.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
```
It was possible to read the file "/WEB-INF/web.xml" through the AJP connector.
Result:
AB 8\x0004 Ã\x0088 \x0002OK  \x0001 \x000CContent-Type  \x001Ctext/html;charset=
↪ISO-8859-1 AB\x001FÃ¼\x0003\x001FÃ¸<!--
  Licensed to the Apache Software Foundation (ASF) under one or more
  contributor license agreements.  See the NOTICE file distributed with
  this work for additional information regarding copyright ownership.
  The ASF licenses this file to You under the Apache License, Version 2.0
  (the "License"); you may not use this file except in compliance with
  the License.  You may obtain a copy of the License at
      http://www.apache.org/licenses/LICENSE-2.0
  Unless required by applicable law or agreed to in writing, software
  distributed under the License is distributed on an "AS IS" BASIS,
  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
  See the License for the specific language governing permissions and
  limitations under the License.
-->
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
   "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
    <head>
    <title>Apache Tomcat/5.5</title>
    <style type="text/css">
    /*<![CDATA[*/
      body {
```

... continues on next page ...

...continued from previous page ...

```
          color: #000000;
          background-color: #FFFFFF;
   font-family: Arial, "Times New Roman", Times, serif;
          margin: 10px 0px;
      }
    img {
       border: none;
    }

    a:link, a:visited {
        color: blue
    }
    th {
        font-family: Verdana, "Times New Roman", Times, serif;
        font-size: 110%;
        font-weight: normal;
        font-style: italic;
        background: #D2A41C;
        text-align: left;
    }
    td {
        color: #000000;
 font-family: Arial, Helvetica, sans-serif;
    }

    td.menu {
        background: #FFDC75;
    }
    .center {
        text-align: center;
    }
    .code {
        color: #000000;
        font-family: "Courier New", Courier, monospace;
        font-size: 110%;
        margin-left: 2.5em;
    }

     #banner {
        margin-bottom: 12px;
     }
     p#congrats {
         margin-top: 0;
         font-weight: bold;
         text-align: center;
     }
     p#footer {
         text-align: right;
         font-size: 80%;
     }
     /*]]>*/
   </style>
</head>
<body>
<!-- Header -->
<table id="banner" width="100%">
    <tr>
      <td align="left" style="width:130px">
        <a href="http://tomcat.apache.org/">
   <img src="tomcat.gif" height="92" width="130" alt="The Mighty Tomcat - MEOW!"
↪/>
 </a>
      </td>
      <td align="left" valign="top"><b>Apache Tomcat/5.5</b></td>
      <td align="right">
        <a href="http://www.apache.org/">
   <img src="asf-logo-wide.gif" height="51" width="537" alt="The Apache Software
↪ Foundation"/>
 </a>
       </td>
     </tr>
</table>
```

...continues on next page ...

...continued from previous page ...

```
<table>
    <tr>
        <!-- Table of Contents -->
        <td valign="top">
            <table width="100%" border="1" cellspacing="0" cellpadding="3">
                <tr>
    <th>Administration</th>
                </tr>
                <tr>
    <td class="menu">
      <a href="manager/status">Status</a><br/>
                    <a href="admin">Tomcat Administration</a><br/>
                    <a href="manager/html">Tomcat Manager</a><br/>
                     
                  </td>
                </tr>
            </table>
     <br />
            <table width="100%" border="1" cellspacing="0" cellpadding="3">
                <tr>
    <th>Documentation</th>
                </tr>
                <tr>
                  <td class="menu">
                    <a href="RELEASE-NOTES.txt">Release Notes</a><br/>
                    <a href="tomcat-docs/changelog.html">Change Log</a><br/
↪>
                    <a href="tomcat-docs">Tomcat Documentation</a><br/>
↪                      
                     
      </td>
                </tr>
            </table>

            <br/>
            <table width="100%" border="1" cellspacing="0" cellpadding="3">
                <tr>
                  <th>Tomcat Online</th>
                </tr>
                <tr>
                  <td class="menu">
                    <a href="http://tomcat.apache.org/">Home Page</a><br/>
      <a href="http://tomcat.apache.org/faq/">FAQ</a><br/>
                    <a href="http://tomcat.apache.org/bugreport.html">Bug D
↪atabase</a><br/>
                    <a href="http://issues.apache.org/bugzilla/buglist.cgi?bug_s
↪tatus=UNCONFIRMED&amp;bug_status=NEW&amp;bug_status=ASSIGNED&amp;bug_status=RE
↪OPENED&amp;bug_status=RESOLVED&amp;resolution=LATER&amp;resolution=REMIND&amp;
↪resolution=---&amp;bugidtype=include&amp;product=Tomcat+5&amp;cmdtype=doit&amp
↪;order=Importance">Open Bugs</a><br/>
                    <a href="http://mail-archives.apache.org/mod_mbox/tomcat-use
↪rs/">Users Mailing List</a><br/>
                    <a href="http://mail-archives.apache.org/mod_mbox/tomcat-dev
↪/">Developers Mailing List</a><br/>
                    <a href="irc://irc.freenode.net/#tomcat">IRC</a><br/>
       
                  </td>
                </tr>
            </table>

            <br/>
            <table width="100%" border="1" cellspacing="0" cellpadding="3">
                <tr>
                  <th>Examples</th>
                </tr>
                <tr>
                  <td class="menu">
                    <a href="jsp-examples/">JSP Examples</a><br/>
                    <a href="servlets-examples/">Servlet Examples</a><br/>
                    <a href="webdav/">WebDAV capabilities</a><br/>
            
                  </td>
```

...continues on next page ...

...continued from previous page ...

```
                </tr>
            </table>

            <br/>
            <table width="100%" border="1" cellspacing="0" cellpadding="3">
                <tr>
    <th>Miscellaneous</th>
                </tr>
                <tr>
                  <td class="menu">
                    <a href="http://java.sun.com/products/jsp">Sun's Java&n
↪bsp;Server Pages Site</a><br/>
                    <a href="http://java.sun.com/products/servlet">Sun's Se
↪rvlet Site</a><br/>
           
                  </td>
                </tr>
            </table>
        </td>
        <td style="width:20px"> </td>

        <!-- Body -->
        <td align="left" valign="top">
          <p id="congrats">If you're seeing this page via a web browser, it mean
↪s you've setup Tomcat successfully. Congratulations!</p>

          <p>As you may have guessed by now, this is the default Tomcat home pag
↪e. It can be found on the local filesystem at:</p>
          <p class="code">$CATALINA_HOME/webapps/ROOT/index.jsp</p>

          <p>where "$CATALINA_HOME" is the root of the Tomcat installation direc
↪tory. If you're seeing this page, and you don't think you should be, then eith
↪er you're either a user who has arrived at new installation of Tomcat, or you'
↪re an administrator who hasn't got his/her setup quite right. Providing the la
↪tter is the case, please refer to the <a href="tomcat-docs">Tomcat Documentati
↪on</a> for more detailed setup and administration information than is found in
↪ the INSTALL file.</p>
            <p><b>NOTE:</b> This page is precompiled. If you change it, this pag
↪e will not change since
                it was compiled into a servlet at build time.
                (See <tt>$CATALINA_HOME/webapps/ROOT/WEB-INF/web.xml</tt> as t
↪o how it was mapped.)
            </p>
            <p><b>NOTE: For security reasons, using the administration webapp
            is restricted to users with role "admin". The manager webapp
            is restricted to users with role "manager".</b>
            Users are defined in <code>$CATALINA_HOME/conf/tomcat-users.xml</cod
↪e>.</p>
            <p>Included with this release are a host of sample Servlets and JSPs
↪ (with associated source code), extensive documentation (including the Servlet
↪ 2.4 and JSP 2.0 API JavaDoc), and an introductory guide to developing web app
↪lications.</p>
            <p>Tomcat mailing lists are available at the Tomcat project web site
↪:</p>
          <ul>
              <li><b><a href="mailto:users@tomcat.apache.org">users@tomc
```

Solution:
Solution type: VendorFix
- Update Apache Tomcat to version 7.0.100, 8.5.51, 9.0.31 or later
- For other products using Tomcat please contact the vendor for more information on fixed versions

Affected Software/OS
Apache Tomcat versions prior 7.0.100, 8.5.51 or 9.0.31 when the AJP connector is enabled.
Other products like JBoss or Wildfly which are using Tomcat might be affected as well.

Vulnerability Insight
Apache Tomcat server has a file containing vulnerability, which can be used by an attacker to read or include any files in all webapp directories on Tomcat, such as webapp configuration files or source code.

Vulnerability Detection Method

...continues on next page ...

... continued from previous page ...

Sends a crafted AJP request and checks the response.
Details: Apache Tomcat AJP RCE Vulnerability (Ghostcat) - Active Check
OID:1.3.6.1.4.1.25623.1.0.143545
Version used: 2026-03-18T05:59:10Z

References
cve: CVE-2020-1938
url: https://lists.apache.org/thread/bnys5lvg1875dsslkkx2vmwxv833135x
url: https://tomcat.apache.org/security-9.html#Fixed_in_Apache_Tomcat_9.0.31
url: https://tomcat.apache.org/security-8.html#Fixed_in_Apache_Tomcat_8.5.51
url: https://tomcat.apache.org/security-7.html#Fixed_in_Apache_Tomcat_7.0.100
url: https://web.archive.org/web/20250114042903/https://www.chaitin.cn/en/ghostcat
url: https://www.cnvd.org.cn/flaw/show/CNVD-2020-10487
url: https://github.com/YDHCUI/CNVD-2020-10487-Tomcat-Ajp-lfi
url: https://securityboulevard.com/2020/02/patch-your-tomcat-and-jboss-instances-to-protect-from-ghostcat-vulnerability-cve-2020-1938-
url: https://www.cisa.gov/known-exploited-vulnerabilities-catalog
cisa: Known Exploited Vulnerability (KEV) catalog
cert-bund: WID-SEC-2024-0528
cert-bund: WID-SEC-2023-2480
cert-bund: CB-K20/0711
cert-bund: CB-K20/0705
cert-bund: CB-K20/0693
cert-bund: CB-K20/0555
cert-bund: CB-K20/0543
cert-bund: CB-K20/0154
dfn-cert: DFN-CERT-2021-1736
dfn-cert: DFN-CERT-2020-1508
dfn-cert: DFN-CERT-2020-1413
dfn-cert: DFN-CERT-2020-1276
dfn-cert: DFN-CERT-2020-1134
dfn-cert: DFN-CERT-2020-0850
dfn-cert: DFN-CERT-2020-0835
dfn-cert: DFN-CERT-2020-0821
dfn-cert: DFN-CERT-2020-0569
dfn-cert: DFN-CERT-2020-0557
dfn-cert: DFN-CERT-2020-0501
dfn-cert: DFN-CERT-2020-0381

[return to 192.168.153.133]

2.1.10 Critical 5432/tcp

Critical (CVSS: 9.0)
NVT: PostgreSQL Default Credentials (PostgreSQL Protocol)

Product detection result
cpe:/a:postgresql:postgresql:8.3.1
Detected by PostgreSQL Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.12802
↪5)

Summary
It was possible to login into the remote PostgreSQL as user postgres using weak credentials.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
It was possible to login as user postgres with password "postgres".

Solution:
Solution type: Mitigation
Change the password as soon as possible.

Vulnerability Detection Method
Details: PostgreSQL Default Credentials (PostgreSQL Protocol)

... continues on next page ...

... continued from previous page ...

OID:1.3.6.1.4.1.25623.1.0.103552
Version used: 2024-07-19T15:39:06Z

Product Detection Result
Product: cpe:/a:postgresql:postgresql:8.3.1
Method: PostgreSQL Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.128025

[return to 192.168.153.133]

2.1.11 Critical 3306/tcp

Critical (CVSS: 9.8)

NVT: MySQL / MariaDB Default Credentials (MySQL Protocol)

Product detection result
cpe:/a:mysql:mysql:5.0.51a
Detected by MariaDB / Oracle MySQL Detection (MySQL Protocol) (OID: 1.3.6.1.4.1.
↪25623.1.0.100152)

Summary
It was possible to login into the remote MySQL using default credentials.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
It was possible to login as user "root" with an empty password.

Solution:
Solution type: Mitigation
- Change the password as soon as possible
- Contact the vendor for other possible fixes / updates

Affected Software/OS
The following products are know to use such weak credentials:
- CVE-2001-0645: Symantec/AXENT NetProwler 3.5.x
- CVE-2002-1809: Windows binary release of MySQL 3.23.2 through 3.23.52
- CVE-2004-1532: AppServ 2.5.x and earlier
- CVE-2004-2357: Proofpoint Protection Server
- CVE-2006-1451: MySQL Manager in Apple Mac OS X 10.3.9 and 10.4.6
- CVE-2007-2554: Associated Press (AP) Newspower 4.0.1 and earlier
- CVE-2007-6081: AdventNet EventLog Analyzer build 4030
- CVE-2009-0919: XAMPP
- CVE-2014-3419: Infoblox NetMRI before 6.8.5
- CVE-2015-4669: Xsuite 2.x
- CVE-2016-6531, CVE-2018-15719: Open Dental before version 18.4
- CVE-2024-22901: Vinchin Backup & Recovery 7.2 and prior
- CVE-2026-47847: Bitnami MariaDB Galera container images and Helm chart
- No CVE / GHSA-g38h-mr9p-fjmf: Vvveb CMS 1.0.8 and prior
Other products might be affected as well.

Vulnerability Detection Method
Details: MySQL / MariaDB Default Credentials (MySQL Protocol)
OID:1.3.6.1.4.1.25623.1.0.103551
Version used: 2026-07-22T06:26:54Z

Product Detection Result
Product: cpe:/a:mysql:mysql:5.0.51a
Method: MariaDB / Oracle MySQL Detection (MySQL Protocol)
OID: 1.3.6.1.4.1.25623.1.0.100152

References
cve: CVE-2001-0645
cve: CVE-2002-1809

... continues on next page ...

... continued from previous page ...

cve: CVE-2004-1532
cve: CVE-2004-2357
cve: CVE-2006-1451
cve: CVE-2007-2554
cve: CVE-2007-6081
cve: CVE-2009-0919
cve: CVE-2014-3419
cve: CVE-2015-4669
cve: CVE-2016-6531
cve: CVE-2018-15719
cve: CVE-2024-22901
cve: CVE-2026-47847

[return to 192.168.153.133]

2.1.12 High 2121/tcp

High (CVSS: 7.5)

NVT: FTP Brute Force Logins With Default Credentials Reporting

Summary
It was possible to login into the remote FTP server using weak/known credentials.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
It was possible to login with the following credentials <User>:<Password>
msfadmin:msfadmin
postgres:postgres
service:service
user:user

Impact
This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.

Solution:
Solution type: Mitigation
Change the password as soon as possible.

Vulnerability Insight
The following devices are / software is known to be affected:
- CVE-2001-1594: Codonics printer FTP service as used in GE Healthcare eNTEGRA P&R
- CVE-2013-7404: GE Healthcare Discovery NM 750b
- CVE-2014-9198: Schneider Electric ETG3000 FactoryCast HMI gateways
- CVE-2015-7261: QNAP iArtist Lite distributed with QNAP Signage Station
- CVE-2016-8731: Foscam C1 devices
- CVE-2017-8218: vsftpd on TP-Link C2 and C20i devices
- CVE-2018-9068: IMM2 for IBM and Lenovo System x
- CVE-2018-17771: Ingenico Telium 2 PoS terminals
- CVE-2018-19063, CVE-2018-19064: Foscam C2 and Opticam i5 devices
- CVE-2018-25147: Microhard Systems IPn4G
- CVE-2020-36915: Adtec Digital SignEdje Digital Signage Player
Note: As the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.

Vulnerability Detection Method
Reports weak/known credentials detected by the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717).
Details: FTP Brute Force Logins With Default Credentials Reporting
OID:1.3.6.1.4.1.25623.1.0.108718
Version used: 2026-01-16T15:42:49Z

References
cve: CVE-1999-0501

... continues on next page ...

... continued from previous page ...

cve: CVE-1999-0502
cve: CVE-1999-0507
cve: CVE-1999-0508
cve: CVE-2001-1594
cve: CVE-2013-7404
cve: CVE-2014-9198
cve: CVE-2015-7261
cve: CVE-2016-8731
cve: CVE-2017-8218
cve: CVE-2018-9068
cve: CVE-2018-17771
cve: CVE-2018-19063
cve: CVE-2018-19064
cve: CVE-2018-25147
cve: CVE-2020-36915

[return to 192.168.153.133]

2.1.13 High 514/tcp

High (CVSS: 7.5)

NVT: rsh Unencrypted Cleartext Login

Summary
This remote host is running a rsh service.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The rsh service is misconfigured so it is allowing connections without a passwor
↪d or with default root:root credentials.

Solution:
Solution type: Mitigation
Disable the rsh service and use alternatives like SSH instead.

Vulnerability Insight
rsh (remote shell) is a command line computer program which can execute shell commands as another user, and on another computer across a computer network.
Remark: NIST don't see 'configuration issues' as software flaws so the referenced CVE has a severity of 0.0. The severity of this VT has been raised by Greenbone to still report a configuration issue on the target.

Vulnerability Detection Method
Details: rsh Unencrypted Cleartext Login
OID:1.3.6.1.4.1.25623.1.0.100080
Version used: 2021-10-20T09:03:29Z

References
cve: CVE-1999-0651

[return to 192.168.153.133]

2.1.14 High 80/tcp

High (CVSS: 7.5)

NVT: EasyPHP Webserver <= 12.1 Multiple Vulnerabilities (HTTP) - Active Check

Summary

... continues on next page ...

... continued from previous page ...

EasyPHP Webserver is prone to multiple vulnerabilities.

Quality of Detection (QoD): 99%

Vulnerability Detection Result

```
Vulnerable URL: http://192.168.153.133/phpinfo.php
Concluded from:
  <title>phpinfo()</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIV
↪E" /></head>
  <tr><td class="e">Configuration File (php.ini) Path </td><td class="v">/etc/ph
↪p5/cgi </td></tr>
  <h2>PHP Core</h2>
  <h2>PHP Variables</h2>
```

Impact
Successful exploitation will allow attackers to gain administrative access, disclose the information, inject PHP code/shell and execute a remote PHP Code.

Solution:
Solution type: WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

Affected Software/OS
EasyPHP version 12.1 and prior.

Vulnerability Insight
The bug in EasyPHP WebServer Manager, its skipping authentication for certain requests. Which allows to bypass the authentication, disclose the information or execute a remote PHP code.

Vulnerability Detection Method
Sends a crafted HTTP GET request and checks the response.
Note: It is currently expected that a result of this VT is reported if the system is generally exposing a phpinfo() output on the relevant URL / endpoint (independent from the running product). Exposing such sensitive information is generally seen as a security misconfiguration and should be avoided.
Details: `EasyPHP Webserver <= 12.1 Multiple Vulnerabilities (HTTP) - Active Check`
OID:1.3.6.1.4.1.25623.1.0.803189
Version used: `2026-10-08T05:49:09Z`

References
url: https://cxsecurity.com/issue/WLB-2013040069

High (CVSS: 7.5)

NVT: Test HTTP dangerous methods

Summary
Misconfigured web servers allows remote clients to perform dangerous HTTP methods such as PUT and DELETE.

Quality of Detection (QoD): 99%

Vulnerability Detection Result

```
We could upload the following files via the PUT method at this web server:
http://192.168.153.133/dav/puttest1667870033.html
We could delete the following files via the DELETE method at this web server:
http://192.168.153.133/dav/puttest1667870033.html
```

Impact
- Enabled PUT method: This might allow an attacker to upload and run arbitrary code on this web server.
- Enabled DELETE method: This might allow an attacker to delete additional files on this web server.

Solution:
Solution type: Mitigation
Use access restrictions to these dangerous HTTP methods or disable them completely.

Affected Software/OS

... continues on next page ...

... continued from previous page ...

Web servers with enabled PUT and/or DELETE methods.

Vulnerability Detection Method
Checks if dangerous HTTP methods such as PUT and DELETE are enabled and can be misused to upload or delete files.
Details: `Test HTTP dangerous methods`
OID:1.3.6.1.4.1.25623.1.0.10498
Version used: `2023-08-01T13:29:10Z`

References
`url:` http://www.securityfocus.com/bid/12141
`owasp:` OWASP-CM-001

High (CVSS: 7.5)

NVT: PHP < 5.3.13, 5.4.x < 5.4.3 Multiple Vulnerabilities - Active Check

Summary
PHP is prone to multiple vulnerabilities.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
```
By doing the following HTTP POST request:
"HTTP POST" body : <?php phpinfo();?>
URL              : http://192.168.153.133/cgi-bin/php?%2D%64+%61%6C%6C%6F%77%5F%
↪75%72%6C%5F%69%6E%63%6C%75%64%65%3D%6F%6E+%2D%64+%73%61%66%65%5F%6D%6F%64%65%3
↪D%6F%66%66+%2D%64+%73%75%68%6F%73%69%6E%2E%73%69%6D%75%6C%61%74%69%6F%6E%3D%6F
↪%6E+%2D%64+%64%69%73%61%62%6C%65%5F%66%75%6E%63%74%69%6F%6E%73%3D%22%22+%2D%64
↪+%6F%70%65%6E%5F%62%61%73%65%64%69%72%3D%6E%6F%6E%65+%2D%64+%61%75%74%6F%5F%70
↪%72%65%70%65%6E%64%5F%66%69%6C%65%3D%70%68%70%3A%2F%2F%69%6E%70%75%74+%2D%64+%
↪63%67%69%2E%66%6F%72%63%65%5F%72%65%64%69%72%65%63%74%3D%30+%2D%64+%63%67%69%2
↪E%72%65%64%69%72%65%63%74%5F%73%74%61%74%75%73%5F%65%6E%76%3D%30+%2D%6E
it was possible to execute the "<?php phpinfo();?>" command.
Result:
  <title>phpinfo()</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIV
↪E" /></head>
  <tr><td class="e">Configuration File (php.ini) Path </td><td class="v">/etc/ph
↪p5/cgi </td></tr>
  <h2>PHP Core</h2>
  <h2>PHP Variables</h2>
```

Impact
Exploiting this issue allows remote attackers to view the source code of files in the context of the server process. This may allow the attacker to obtain sensitive information and to run arbitrary PHP code on the affected computer. Other attacks are also possible.

Solution:
Solution type: VendorFix
PHP: Update to version 5.3.13, 5.4.3 or later
- Other products / applications: Please contact the vendor for a solution

Affected Software/OS
PHP versions prior to 5.3.13 and 5.4.x prior to 5.4.3.
Other products / applications might be affected by the tested CVE-2012-1823 as well.

Vulnerability Insight
When PHP is used in a CGI-based setup (such as Apache's mod_cgid), the php-cgi receives a processed query string parameter as command line arguments which allows command-line switches, such as -s, -d or -c to be passed to the php-cgi binary, which can be exploited to disclose source code and obtain arbitrary code execution.
An example of the -s command, allowing an attacker to view the source code of index.php is below:
http://example.com/index.php?-s

Vulnerability Detection Method
Send multiple a crafted HTTP POST requests and checks the responses.
Notes:
- This script checks for the presence of CVE-2012-1823 which indicates that the system is also affected by the other included CVEs.

... continues on next page ...

... continued from previous page ...

- It is currently expected that a result of this VT is reported if the system is generally exposing a phpinfo() output on the relevant URL / endpoint (independent from the running product). Exposing such sensitive information is generally seen as a security misconfiguration and should be avoided.
Details: PHP < 5.3.13, 5.4.x < 5.4.3 Multiple Vulnerabilities - Active Check
OID:1.3.6.1.4.1.25623.1.0.103482
Version used: 2026-09-17T05:45:41Z

References
cve: CVE-2012-1823
cve: CVE-2012-2311
cve: CVE-2012-2336
cve: CVE-2012-2335
url: https://web.archive.org/web/20190212080415/http://eindbazen.net/2012/05/php-cgi-advisory-cve-2012-1823/
url: https://www.kb.cert.org/vuls/id/520827
url: https://bugs.php.net/bug.php?id=61910
url: https://www.php.net/manual/en/security.cgi-bin.php
url: https://web.archive.org/web/20210121223743/http://www.securityfocus.com/bid/53388
url: https://web.archive.org/web/20120709064615/http://www.h-online.com/open/news/item/Critical-open-hole-in-PHP-creates-risks-Update-2-1567532.html
url: https://www.cisa.gov/known-exploited-vulnerabilities-catalog
cisa: Known Exploited Vulnerability (KEV) catalog
dfn-cert: DFN-CERT-2013-1494
dfn-cert: DFN-CERT-2012-1316
dfn-cert: DFN-CERT-2012-1276
dfn-cert: DFN-CERT-2012-1268
dfn-cert: DFN-CERT-2012-1267
dfn-cert: DFN-CERT-2012-1266
dfn-cert: DFN-CERT-2012-1173
dfn-cert: DFN-CERT-2012-1101
dfn-cert: DFN-CERT-2012-0994
dfn-cert: DFN-CERT-2012-0993
dfn-cert: DFN-CERT-2012-0992
dfn-cert: DFN-CERT-2012-0920
dfn-cert: DFN-CERT-2012-0915
dfn-cert: DFN-CERT-2012-0914
dfn-cert: DFN-CERT-2012-0913
dfn-cert: DFN-CERT-2012-0907
dfn-cert: DFN-CERT-2012-0906
dfn-cert: DFN-CERT-2012-0900
dfn-cert: DFN-CERT-2012-0880
dfn-cert: DFN-CERT-2012-0878

[return to 192.168.153.133]

2.1.15 High 513/tcp

High (CVSS: 7.5)

NVT: The rlogin service is running

Summary
This remote host is running a rlogin service.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The rlogin service is running on the target system.

Solution:
Solution type: Mitigation
Disable the rlogin service and use alternatives like SSH instead.

Vulnerability Insight
rlogin has several serious security problems,
- all information, including passwords, is transmitted unencrypted.

... continues on next page ...

... continued from previous page ...

- .rlogin (or .rhosts) file is easy to misuse (potentially allowing anyone to login without a password)

Vulnerability Detection Method
Details: The rlogin service is running
OID:1.3.6.1.4.1.25623.1.0.901202
Version used: 2025-03-05T05:38:53Z

References
cve: CVE-1999-0651

[return to 192.168.153.133]

2.1.16 High 1099/tcp

High (CVSS: 7.5)

NVT: Java RMI Server Insecure Default Configuration RCE Vulnerability - Active Check

Summary
Multiple Java products that implement the RMI Server contain a vulnerability that could allow an unauthenticated, remote attacker to execute arbitrary code (remote code execution/RCE) on a targeted system with elevated privileges.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
By doing an RMI request it was possible to trigger the vulnerability and make th
↪e remote host send a request back to the scanner host (Details on the received
↪ packet follows).
Destination IP: 192.168.153.128 (receiving IP on scanner host side)
Destination port: 23009/tcp (receiving port on scanner host side)
Originating IP: 192.168.153.133 (originating IP from target host side)

Impact
An unauthenticated, remote attacker could exploit the vulnerability by transmitting crafted packets to the affected software. When the packets are processed, the attacker could execute arbitrary code on the system with elevated privileges.

Solution:
Solution type: Workaround
Disable class-loading. Please contact the vendor of the affected system for additional guidance.

Vulnerability Insight
The vulnerability exists because of an incorrect default configuration of the Remote Method Invocation (RMI) Server in the affected software.

Vulnerability Detection Method
Sends a crafted JRMI request and checks if the target is connecting back to the scanner host.
Note: For a successful detection of this flaw the target host needs to be able to reach the scanner host on a TCP port randomly generated during the runtime of the VT (currently in the range of 10000-32000).
Details: Java RMI Server Insecure Default Configuration RCE Vulnerability - Active Check
OID:1.3.6.1.4.1.25623.1.0.140051
Version used: 2026-04-17T15:51:27Z

References
cve: CVE-2011-3556
url: https://web.archive.org/web/20211208040855/http://www.securitytracker.com/id?1026215
url: https://web.archive.org/web/20110824060234/http://download.oracle.com/javase/1.3/docs/guide/rmi/spec/rmi-protocol.html
url: https://tools.cisco.com/security/center/viewAlert.x?alertId=23665
dfn-cert: DFN-CERT-2012-1829
dfn-cert: DFN-CERT-2012-1380
dfn-cert: DFN-CERT-2012-1377
dfn-cert: DFN-CERT-2012-1156
dfn-cert: DFN-CERT-2012-1155
dfn-cert: DFN-CERT-2012-0956

... continues on next page ...

... continued from previous page ...

```
dfn-cert: DFN-CERT-2012-0828
dfn-cert: DFN-CERT-2012-0815
dfn-cert: DFN-CERT-2012-0638
dfn-cert: DFN-CERT-2012-0451
dfn-cert: DFN-CERT-2012-0418
dfn-cert: DFN-CERT-2012-0354
dfn-cert: DFN-CERT-2012-0146
dfn-cert: DFN-CERT-2012-0142
dfn-cert: DFN-CERT-2012-0126
dfn-cert: DFN-CERT-2012-0095
dfn-cert: DFN-CERT-2012-0047
dfn-cert: DFN-CERT-2011-1844
dfn-cert: DFN-CERT-2011-1826
dfn-cert: DFN-CERT-2011-1804
dfn-cert: DFN-CERT-2011-1743
dfn-cert: DFN-CERT-2011-1738
dfn-cert: DFN-CERT-2011-1706
dfn-cert: DFN-CERT-2011-1628
dfn-cert: DFN-CERT-2011-1627
dfn-cert: DFN-CERT-2011-1619
```

[return to 192.168.153.133]

2.1.17 High 21/tcp

High (CVSS: 7.5)

NVT: FTP Brute Force Logins With Default Credentials Reporting

Summary
It was possible to login into the remote FTP server using weak/known credentials.

Quality of Detection (QoD): 95%

Vulnerability Detection Result
```
It was possible to login with the following credentials <User>:<Password>
msfadmin:msfadmin
postgres:postgres
service:service
user:user
```

Impact
This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.

Solution:
Solution type: Mitigation
Change the password as soon as possible.

Vulnerability Insight
The following devices are / software is known to be affected:
- CVE-2001-1594: Codonics printer FTP service as used in GE Healthcare eNTEGRA P&R
- CVE-2013-7404: GE Healthcare Discovery NM 750b
- CVE-2014-9198: Schneider Electric ETG3000 FactoryCast HMI gateways
- CVE-2015-7261: QNAP iArtist Lite distributed with QNAP Signage Station
- CVE-2016-8731: Foscam C1 devices
- CVE-2017-8218: vsftpd on TP-Link C2 and C20i devices
- CVE-2018-9068: IMM2 for IBM and Lenovo System x
- CVE-2018-17771: Ingenico Telium 2 PoS terminals
- CVE-2018-19063, CVE-2018-19064: Foscam C2 and Opticam i5 devices
- CVE-2018-25147: Microhard Systems IPn4G
- CVE-2020-36915: Adtec Digital SignEdje Digital Signage Player
Note: As the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.

Vulnerability Detection Method

... continues on next page ...

. . . continued from previous page . . .

Reports weak/known credentials detected by the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717).
Details: FTP Brute Force Logins With Default Credentials Reporting
OID:1.3.6.1.4.1.25623.1.0.108718
Version used: 2026-01-16T15:42:49Z

References
cve: CVE-1999-0501
cve: CVE-1999-0502
cve: CVE-1999-0507
cve: CVE-1999-0508
cve: CVE-2001-1594
cve: CVE-2013-7404
cve: CVE-2014-9198
cve: CVE-2015-7261
cve: CVE-2016-8731
cve: CVE-2017-8218
cve: CVE-2018-9068
cve: CVE-2018-17771
cve: CVE-2018-19063
cve: CVE-2018-19064
cve: CVE-2018-25147
cve: CVE-2020-36915

[return to 192.168.153.133]

2.1.18 High 6697/tcp

High (CVSS: 8.1)
NVT: UnrealIRCd Authentication Spoofing Vulnerability

Product detection result
cpe:/a:unrealircd:unrealircd:3.2.8.1
Detected by UnrealIRCd Detection (OID: 1.3.6.1.4.1.25623.1.0.809884)

Summary
UnrealIRCd is prone to authentication spoofing vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
Installed version: 3.2.8.1
Fixed version: 3.2.10.7

Impact
Successful exploitation of this vulnerability will allow remote attackers to spoof certificate fingerprints and consequently log in as another user.

Solution:
Solution type: VendorFix
Update to version 3.2.10.7, 4.0.6 or later.

Affected Software/OS
UnrealIRCd before 3.2.10.7 and 4.x before 4.0.6.

Vulnerability Insight
The flaw exists due to an error in the 'm_authenticate' function in 'modules/m_sasl.c' script.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: UnrealIRCd Authentication Spoofing Vulnerability
OID:1.3.6.1.4.1.25623.1.0.809883
Version used: 2025-12-17T05:46:28Z

. . . continues on next page . . .

... continued from previous page ...

Product Detection Result
Product: cpe:/a:unrealircd:unrealircd:3.2.8.1
Method: UnrealIRCd Detection
OID: 1.3.6.1.4.1.25623.1.0.809884

References
cve: CVE-2016-7144
url: http://seclists.org/oss-sec/2016/q3/420
url: http://www.securityfocus.com/bid/92763
url: http://www.openwall.com/lists/oss-security/2016/09/05/8
url: https://github.com/unrealircd/unrealircd/commit/f473e355e1dc422c4f019dbf86bc50ba1a34a766
url: https://bugs.unrealircd.org/main_page.php

High (CVSS: 7.5)

NVT: UnrealIRCd Backdoor

Product detection result
cpe:/a:unrealircd:unrealircd:3.2.8.1
Detected by UnrealIRCd Detection (OID: 1.3.6.1.4.1.25623.1.0.809884)

Summary
Detection of backdoor in UnrealIRCd.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Solution:
Solution type: VendorFix
Install latest version of unrealircd and check signatures of software you're installing.

Affected Software/OS
The issue affects Unreal 3.2.8.1 for Linux. Reportedly package Unreal3.2.8.1.tar.gz downloaded in November 2009 and later is affected. The MD5 sum of the affected file is 752e46f2d873c1679fa99de3f52a274d. Files with MD5 sum of 7b741e94e867c0a7370553fd01506c66 are not affected.

Vulnerability Insight
Remote attackers can exploit this issue to execute arbitrary system commands within the context of the affected application.

Vulnerability Detection Method
Details: UnrealIRCd Backdoor
OID:1.3.6.1.4.1.25623.1.0.80111
Version used: 2025-03-21T05:38:29Z

Product Detection Result
Product: cpe:/a:unrealircd:unrealircd:3.2.8.1
Method: UnrealIRCd Detection
OID: 1.3.6.1.4.1.25623.1.0.809884

References
cve: CVE-2010-2075
url: http://www.unrealircd.com/txt/unrealsecadvisory.20100612.txt
url: http://seclists.org/fulldisclosure/2010/Jun/277
url: http://www.securityfocus.com/bid/40820

[return to 192.168.153.133]

2.1.19 High 5432/tcp

High (CVSS: 7.4)

NVT: SSL/TLS: OpenSSL CCS Man in the Middle Security Bypass Vulnerability

Summary
OpenSSL is prone to a security bypass vulnerability.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
Successfully exploiting this issue may allow attackers to obtain sensitive information by conducting a man-in-the-middle attack. This may lead to other attacks.

Solution:
Solution type: VendorFix
Updates are available. Please see the references for more information.

Affected Software/OS
OpenSSL before 0.9.8za, 1.0.0 before 1.0.0m and 1.0.1 before 1.0.1h.

Vulnerability Insight
OpenSSL does not properly restrict processing of ChangeCipherSpec messages, which allows man-in-the-middle attackers to trigger use of a zero-length master key in certain OpenSSL-to-OpenSSL communications, and consequently hijack sessions or obtain sensitive information, via a crafted TLS handshake, aka the 'CCS Injection' vulnerability.

Vulnerability Detection Method
Send two SSL ChangeCipherSpec request and check the response.
Details: `SSL/TLS: OpenSSL CCS Man in the Middle Security Bypass Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.105042
Version used: `2025-01-17T15:39:18Z`

References
`cve: CVE-2014-0224`
`url: https://www.openssl.org/news/secadv/20140605.txt`
`url: http://www.securityfocus.com/bid/67899`
`cert-bund: WID-SEC-2026-0180`
`cert-bund: WID-SEC-2023-0500`
`cert-bund: CB-K15/0567`
`cert-bund: CB-K15/0415`
`cert-bund: CB-K15/0384`
`cert-bund: CB-K15/0080`
`cert-bund: CB-K15/0079`
`cert-bund: CB-K15/0074`
`cert-bund: CB-K14/1617`
`cert-bund: CB-K14/1537`
`cert-bund: CB-K14/1299`
`cert-bund: CB-K14/1297`
`cert-bund: CB-K14/1294`
`cert-bund: CB-K14/1202`
`cert-bund: CB-K14/1174`
`cert-bund: CB-K14/1153`
`cert-bund: CB-K14/0876`
`cert-bund: CB-K14/0756`
`cert-bund: CB-K14/0746`
`cert-bund: CB-K14/0736`
`cert-bund: CB-K14/0722`
`cert-bund: CB-K14/0716`
`cert-bund: CB-K14/0708`
`cert-bund: CB-K14/0684`
`cert-bund: CB-K14/0683`
`cert-bund: CB-K14/0680`
`dfn-cert: DFN-CERT-2016-0388`
`dfn-cert: DFN-CERT-2015-0593`
`dfn-cert: DFN-CERT-2015-0427`
`dfn-cert: DFN-CERT-2015-0396`
`dfn-cert: DFN-CERT-2015-0082`
`dfn-cert: DFN-CERT-2015-0079`
`dfn-cert: DFN-CERT-2015-0078`

... continues on next page ...

... continued from previous page ...

```
dfn-cert: DFN-CERT-2014-1717
dfn-cert: DFN-CERT-2014-1632
dfn-cert: DFN-CERT-2014-1364
dfn-cert: DFN-CERT-2014-1357
dfn-cert: DFN-CERT-2014-1350
dfn-cert: DFN-CERT-2014-1265
dfn-cert: DFN-CERT-2014-1209
dfn-cert: DFN-CERT-2014-0917
dfn-cert: DFN-CERT-2014-0789
dfn-cert: DFN-CERT-2014-0778
dfn-cert: DFN-CERT-2014-0768
dfn-cert: DFN-CERT-2014-0752
dfn-cert: DFN-CERT-2014-0747
dfn-cert: DFN-CERT-2014-0738
dfn-cert: DFN-CERT-2014-0715
dfn-cert: DFN-CERT-2014-0714
dfn-cert: DFN-CERT-2014-0709
```

[return to 192.168.153.133]

2.1.20 Medium 2121/tcp

Medium (CVSS: 4.8)

NVT: FTP Unencrypted Cleartext Login

Summary
The remote host is running a FTP service that allows cleartext logins over unencrypted connections.

Quality of Detection (QoD): 70%

Vulnerability Detection Result

```
The remote FTP service accepts logins without a previous sent 'AUTH TLS' command
↪. Response(s):
Non-anonymous sessions: 331 Password required for openvasvt
Anonymous sessions:     331 Password required for anonymous
```

Impact
An attacker can uncover login names and passwords by sniffing traffic to the FTP service.

Solution:
Solution type: Mitigation
Enable FTPS or enforce the connection via the 'AUTH TLS' command. Please see the manual of the FTP service for more information.

Vulnerability Detection Method
Tries to login to a non FTPS enabled FTP service without sending a 'AUTH TLS' command first and checks if the service is accepting the login without enforcing the use of the 'AUTH TLS' command.
Details: `FTP Unencrypted Cleartext Login`
OID:1.3.6.1.4.1.25623.1.0.108528
Version used: `2023-12-20T05:05:58Z`

[return to 192.168.153.133]

2.1.21 Medium 80/tcp

Medium (CVSS: 6.8)

NVT: TWiki Cross-Site Request Forgery Vulnerability (Sep 2010)

Summary

... continues on next page ...

. . . continued from previous page . . .

TWiki is prone to a cross-site request forgery (CSRF) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`Installed version: 01.Feb.2003`
`Fixed version: 4.3.2`

Impact
Successful exploitation will allow attacker to gain administrative privileges on the target application and can cause CSRF attack.

Solution:
Solution type: VendorFix
Upgrade to TWiki version 4.3.2 or later.

Affected Software/OS
TWiki version prior to 4.3.2

Vulnerability Insight
Attack can be done by tricking an authenticated TWiki user into visiting a static HTML page on another side, where a Javascript enabled browser will send an HTTP POST request to TWiki, which in turn will process the request as the TWiki user.

Vulnerability Detection Method
Details: `TWiki Cross-Site Request Forgery Vulnerability (Sep 2010)`
OID:1.3.6.1.4.1.25623.1.0.801281
Version used: `2024-03-01T14:37:10Z`

References
`cve: CVE-2009-4898`
`url:` http://www.openwall.com/lists/oss-security/2010/08/03/8
`url:` http://www.openwall.com/lists/oss-security/2010/08/02/17
`url:` http://twiki.org/cgi-bin/view/Codev/SecurityAuditTokenBasedCsrfFix
`url:` http://twiki.org/cgi-bin/view/Codev/DownloadTWiki

Medium (CVSS: 6.1)

NVT: TWiki < 6.1.0 XSS Vulnerability

Summary
bin/statistics in TWiki 6.0.2 allows XSS via the webs parameter.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`Installed version: 01.Feb.2003`
`Fixed version: 6.1.0`

Solution:
Solution type: VendorFix
Update to version 6.1.0 or later.

Affected Software/OS
TWiki version 6.0.2 and probably prior.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `TWiki < 6.1.0 XSS Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.141830
Version used: `2023-07-14T16:09:27Z`

References
`cve: CVE-2018-20212`
`url:` https://seclists.org/fulldisclosure/2019/Jan/7
`url:` http://twiki.org/cgi-bin/view/Codev/DownloadTWiki

Medium (CVSS: 6.1)

NVT: jQuery < 1.9.0 XSS Vulnerability

Summary
jQuery is prone to a cross-site scripting (XSS) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Installed version: 1.3.2
Fixed version:     1.9.0
Installation
path / port:       /mutillidae/javascript/ddsmoothmenu/jquery.min.js
Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info):
- Identified file: http://192.168.153.133/mutillidae/javascript/ddsmoothmenu/jqu
↪ery.min.js
- Referenced at:   http://192.168.153.133/mutillidae/
```

Solution:
Solution type: VendorFix
Update to version 1.9.0 or later.

Affected Software/OS
jQuery prior to version 1.9.0.

Vulnerability Insight
The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '<' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '<' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `jQuery < 1.9.0 XSS Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.141636
Version used: `2023-07-14T05:06:08Z`

References
```
cve: CVE-2012-6708
url: https://bugs.jquery.com/ticket/11290
cert-bund: WID-SEC-2026-3721
cert-bund: WID-SEC-2026-3720
cert-bund: WID-SEC-2026-1752
cert-bund: WID-SEC-2022-0673
cert-bund: CB-K22/0045
cert-bund: CB-K18/1131
dfn-cert: DFN-CERT-2025-1803
dfn-cert: DFN-CERT-2023-1197
dfn-cert: DFN-CERT-2020-0590
```

Medium (CVSS: 6.0)

NVT: TWiki CSRF Vulnerability

Summary
TWiki is prone to a cross-site request forgery (CSRF) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Installed version: 01.Feb.2003
Fixed version:     4.3.1
```

Impact
Successful exploitation will allow attacker to gain administrative privileges on the target application and can cause CSRF attack.

. . . continues on next page . . .

...continued from previous page ...

Solution:
Solution type: VendorFix
Upgrade to version 4.3.1 or later.

Affected Software/OS
TWiki version prior to 4.3.1

Vulnerability Insight
Remote authenticated user can create a specially crafted image tag that, when viewed by the target user, will update pages on the target system with the privileges of the target user via HTTP requests.

Vulnerability Detection Method
Details: `TWiki CSRF Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.800400
Version used: `2024-06-28T05:05:33Z`

References
`cve: CVE-2009-1339`
`url:` http://secunia.com/advisories/34880
`url:` http://bugs.debian.org/cgi-bin/bugreport.cgi?bug=526258
`url:` http://twiki.org/p/pub/Codev/SecurityAlert-CVE-2009-1339/TWiki-4.3.0-c-diff-cve-2009-1339.txt

Medium (CVSS: 5.8)

NVT: HTTP Debugging Methods (TRACE/TRACK) Enabled

Summary
The remote web server supports the TRACE and/or TRACK methods. TRACE and TRACK are HTTP methods which are used to debug web server connections.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
`The web server has the following HTTP methods enabled: TRACE`

Impact
An attacker may use this flaw to trick your legitimate web users to give him their credentials.

Solution:
Solution type: Mitigation
Disable the TRACE and TRACK methods in your web server configuration.
Please see the manual of your web server or the references for more information.

Affected Software/OS
Web servers with enabled TRACE and/or TRACK methods.

Vulnerability Insight
It has been shown that web servers supporting this methods are subject to cross-site-scripting attacks, dubbed XST for Cross-Site-Tracing, when used in conjunction with various weaknesses in browsers.

Vulnerability Detection Method
Checks if HTTP methods such as TRACE and TRACK are enabled and can be used.
Details: `HTTP Debugging Methods (TRACE/TRACK) Enabled`
OID:1.3.6.1.4.1.25623.1.0.11213
Version used: `2023-08-01T13:29:10Z`

References
`cve: CVE-2003-1567`
`cve: CVE-2004-2320`
`cve: CVE-2004-2763`
`cve: CVE-2005-3398`
`cve: CVE-2006-4683`
`cve: CVE-2007-3008`
`cve: CVE-2008-7253`
`cve: CVE-2009-2823`
`cve: CVE-2010-0386`

...continues on next page ...

... continued from previous page ...

cve: CVE-2012-2223
cve: CVE-2014-7883
url: http://www.kb.cert.org/vuls/id/288308
url: http://www.securityfocus.com/bid/11604
url: http://www.securityfocus.com/bid/15222
url: http://www.securityfocus.com/bid/19915
url: http://www.securityfocus.com/bid/24456
url: http://www.securityfocus.com/bid/33374
url: http://www.securityfocus.com/bid/36956
url: http://www.securityfocus.com/bid/36990
url: http://www.securityfocus.com/bid/37995
url: http://www.securityfocus.com/bid/9506
url: http://www.securityfocus.com/bid/9561
url: http://www.kb.cert.org/vuls/id/867593
url: https://httpd.apache.org/docs/current/en/mod/core.html#traceenable
url: https://techcommunity.microsoft.com/t5/iis-support-blog/http-track-and-trace-verbs/ba-p/784482
url: https://owasp.org/www-community/attacks/Cross_Site_Tracing
cert-bund: CB-K14/0981
dfn-cert: DFN-CERT-2021-1825
dfn-cert: DFN-CERT-2014-1018
dfn-cert: DFN-CERT-2010-0020

Medium (CVSS: 5.3)

NVT: phpinfo() Output Reporting (HTTP)

Summary
Reporting of files containing the output of the phpinfo() PHP function previously detected via HTTP.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The following files are calling the function phpinfo() which disclose potentiall
↪y sensitive information:
http://192.168.153.133/mutillidae/phpinfo.php
Concluded from:
  <title>phpinfo()</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIV
↪E" /></head>
  <tr><td class="e">Configuration File (php.ini) Path </td><td class="v">/etc/ph
↪p5/cgi </td></tr>
  <h2>PHP Core</h2>
  <h2>PHP Variables</h2>
http://192.168.153.133/phpinfo.php
Concluded from:
  <title>phpinfo()</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIV
↪E" /></head>
  <tr><td class="e">Configuration File (php.ini) Path </td><td class="v">/etc/ph
↪p5/cgi </td></tr>
  <h2>PHP Core</h2>
  <h2>PHP Variables</h2>
```

Impact
Some of the information that can be gathered from this file includes:
The username of the user running the PHP process, if it is a sudo user, the IP address of the host, the web server version, the system version (Unix, Linux, Windows, ...), and the root directory of the web server.

Solution:
Solution type: Workaround
Delete the listed files or restrict access to them.

Affected Software/OS
All systems exposing a file containing the output of the phpinfo() PHP function.
This VT is also reporting if an affected endpoint for the following products have been identified:
- CVE-2008-0149: TUTOS
- CVE-2023-49282, CVE-2023-49283: Microsoft Graph PHP SDK
- CVE-2024-10486: Google for WooCommerce plugin for WordPress

Vulnerability Insight

... continues on next page ...

...continued from previous page ...

Many PHP installation tutorials instruct the user to create a file called phpinfo.php or similar containing the phpinfo() statement. Such a file is often left back in the webserver directory.

Vulnerability Detection Method
This script reports files identified by the following separate VT: 'phpinfo() Output Detection (HTTP)' (OID: 1.3.6.1.4.1.25623.1.0.108474).
Details: `phpinfo() Output Reporting (HTTP)`
OID:1.3.6.1.4.1.25623.1.0.11229
Version used: `2025-07-09T05:43:50Z`

References
`cve: CVE-2008-0149`
`cve: CVE-2023-49282`
`cve: CVE-2023-49283`
`cve: CVE-2024-10486`
`url: https://www.php.net/manual/en/function.phpinfo.php`
`url: https://beaglesecurity.com/blog/vulnerability/revealing-phpinfo.html`

Medium (CVSS: 5.0)

NVT: /doc directory browsable

Summary
The /doc directory is browsable. /doc shows the content of the /usr/doc directory and therefore it shows which programs and - important! - the version of the installed programs.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`Vulnerable URL: http://192.168.153.133/doc/`

Solution:
Solution type: Mitigation
Use access restrictions for the /doc directory. If you use Apache you might use this in your access.conf:
<Directory /usr/doc> AllowOverride None order deny, allow deny from all allow from localhost </Directory>

Vulnerability Detection Method
Details: `/doc directory browsable`
OID:1.3.6.1.4.1.25623.1.0.10056
Version used: `2023-08-01T13:29:10Z`

References
`cve: CVE-1999-0678`
`url: http://www.securityfocus.com/bid/318`

Medium (CVSS: 5.0)

NVT: QWikiwiki directory traversal vulnerability

Summary
The remote host is running QWikiwiki, a Wiki application written in PHP.
The remote version of this software contains a validation input flaw which may allow an attacker to use it to read arbitrary files on the remote host with the privileges of the web server.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
`Vulnerable URL: http://192.168.153.133/mutillidae/index.php?page=../../../../../`
`↪../../../../../../etc/passwd%00`

Solution:
Solution type: WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

...continues on next page ...

. . . continued from previous page . . .

Vulnerability Detection Method
Details: QWikiwiki directory traversal vulnerability
OID:1.3.6.1.4.1.25623.1.0.16100
Version used: 2025-04-15T05:54:49Z

References
cve: CVE-2005-0283
url: http://www.securityfocus.com/bid/12163

Medium (CVSS: 5.0)

NVT: awiki <= 20100125 Multiple LFI Vulnerabilities - Active Check

Summary
awiki is prone to multiple local file include (LFI) vulnerabilities because it fails to properly sanitize user-supplied input.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
Vulnerable URL: http://192.168.153.133/mutillidae/index.php?page=/etc/passwd

Impact
An attacker can exploit this vulnerability to obtain potentially sensitive information and execute arbitrary local scripts in the context of the webserver process. This may allow the attacker to compromise the application and the host.

Solution:
Solution type: WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

Affected Software/OS
awiki version 20100125 and prior.

Vulnerability Detection Method
Sends a crafted HTTP GET request and checks the response.
Details: awiki <= 20100125 Multiple LFI Vulnerabilities - Active Check
OID:1.3.6.1.4.1.25623.1.0.103210
Version used: 2025-04-15T05:54:49Z

References
url: https://www.exploit-db.com/exploits/36047/
url: http://www.securityfocus.com/bid/49187

Medium (CVSS: 4.8)

NVT: Cleartext Transmission of Sensitive Information via HTTP

Summary
The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The following input fields were identified (URL:input name):
http://192.168.153.133/dvwa/login.php:password
http://192.168.153.133/phpMyAdmin/:pma_password
http://192.168.153.133/phpMyAdmin/?D=A:pma_password
http://192.168.153.133/tikiwiki/tiki-install.php:pass
http://192.168.153.133/twiki/bin/view/TWiki/TWikiUserAuthentication:oldpassword

Impact
. . . continues on next page . . .

... continued from previous page ...

An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.

Solution:
Solution type: Workaround
Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.

Affected Software/OS
Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.

Vulnerability Detection Method
Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection.
The script is currently checking the following:
- HTTP Basic Authentication (Basic Auth)
- HTTP Forms (e.g. Login) with input field of type 'password'
Details: `Cleartext Transmission of Sensitive Information via HTTP`
OID:1.3.6.1.4.1.25623.1.0.108440
Version used: `2023-09-07T05:05:21Z`

References
`url:` https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management
`url:` https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure
`url:` https://cwe.mitre.org/data/definitions/319.html

Medium (CVSS: 4.3)

NVT: jQuery < 1.6.3 XSS Vulnerability

Summary
jQuery is prone to a cross-site scripting (XSS) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Installed version: 1.3.2
Fixed version:     1.6.3
Installation
path / port:       /mutillidae/javascript/ddsmoothmenu/jquery.min.js
Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info):
- Identified file: http://192.168.153.133/mutillidae/javascript/ddsmoothmenu/jqu
↪ery.min.js
- Referenced at:   http://192.168.153.133/mutillidae/
```

Solution:
Solution type: VendorFix
Update to version 1.6.3 or later.

Affected Software/OS
jQuery prior to version 1.6.3.

Vulnerability Insight
Cross-site scripting (XSS) vulnerability in jQuery before 1.6.3, when using location.hash to select elements, allows remote attackers to inject arbitrary web script or HTML via a crafted tag.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `jQuery < 1.6.3 XSS Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.141637
Version used: `2023-07-14T05:06:08Z`

References
`cve:` CVE-2011-4969
`url:` https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/
`cert-bund:` WID-SEC-2026-3721

... continues on next page ...

. . . continued from previous page . . .

cert-bund: WID-SEC-2026-3720
cert-bund: WID-SEC-2026-1752
cert-bund: CB-K17/0195
dfn-cert: DFN-CERT-2017-0199
dfn-cert: DFN-CERT-2016-0890

Medium (CVSS: 4.3)

NVT: phpMyAdmin 'error.php' Cross Site Scripting Vulnerability

Summary
phpMyAdmin is prone to a cross-site scripting (XSS) vulnerability.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
Successful exploitation will allow attackers to inject arbitrary HTML code within the error page and conduct phishing attacks.

Solution:
Solution type: WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

Affected Software/OS
phpMyAdmin version 3.3.8.1 and prior.

Vulnerability Insight
The flaw is caused by input validation errors in the 'error.php' script when processing crafted BBcode tags containing '@' characters, which could allow attackers to inject arbitrary HTML code within the error page and conduct phishing attacks.

Vulnerability Detection Method
Details: phpMyAdmin 'error.php' Cross Site Scripting Vulnerability
OID:1.3.6.1.4.1.25623.1.0.801660
Version used: 2023-10-17T05:05:34Z

References
cve: CVE-2010-4480
url: http://www.exploit-db.com/exploits/15699/
url: http://www.vupen.com/english/advisories/2010/3133
dfn-cert: DFN-CERT-2011-0467
dfn-cert: DFN-CERT-2011-0451
dfn-cert: DFN-CERT-2011-0016
dfn-cert: DFN-CERT-2011-0002

Medium (CVSS: 4.3)

NVT: Apache HTTP Server 'httpOnly' Cookie Information Disclosure Vulnerability

Product detection result
cpe:/a:apache:http_server:2.2.8
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)

Summary
Apache HTTP Server is prone to a cookie information disclosure vulnerability.

Quality of Detection (QoD): 99%

. . . continues on next page . . .

... continued from previous page ...

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
Successful exploitation will allow attackers to obtain sensitive information that may aid in further attacks.

Solution:
Solution type: VendorFix
Update to Apache HTTP Server version 2.2.22 or later.

Affected Software/OS
Apache HTTP Server versions 2.2.0 through 2.2.21.

Vulnerability Insight
The flaw is due to an error within the default error response for status code 400 when no custom ErrorDocument is configured, which can be exploited to expose 'httpOnly' cookies.

Vulnerability Detection Method
Details: Apache HTTP Server 'httpOnly' Cookie Information Disclosure Vulnerability
OID:1.3.6.1.4.1.25623.1.0.902830
Version used: 2026-02-24T05:57:09Z

Product Detection Result
Product: cpe:/a:apache:http_server:2.2.8
Method: Apache HTTP Server Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.117232

References
cve: CVE-2012-0053
url: http://secunia.com/advisories/47779
url: http://www.securityfocus.com/bid/51706
url: http://www.exploit-db.com/exploits/18442
url: http://rhn.redhat.com/errata/RHSA-2012-0128.html
url: http://httpd.apache.org/security/vulnerabilities_22.html
url: http://svn.apache.org/viewvc?view=revision&revision=1235454
url: http://lists.opensuse.org/opensuse-security-announce/2012-02/msg00026.html
cert-bund: CB-K15/0080
cert-bund: CB-K14/1505
cert-bund: CB-K14/0608
dfn-cert: DFN-CERT-2015-0082
dfn-cert: DFN-CERT-2014-1592
dfn-cert: DFN-CERT-2014-0635
dfn-cert: DFN-CERT-2013-1307
dfn-cert: DFN-CERT-2012-1276
dfn-cert: DFN-CERT-2012-1112
dfn-cert: DFN-CERT-2012-0928
dfn-cert: DFN-CERT-2012-0758
dfn-cert: DFN-CERT-2012-0744
dfn-cert: DFN-CERT-2012-0568
dfn-cert: DFN-CERT-2012-0425
dfn-cert: DFN-CERT-2012-0424
dfn-cert: DFN-CERT-2012-0387
dfn-cert: DFN-CERT-2012-0343
dfn-cert: DFN-CERT-2012-0332
dfn-cert: DFN-CERT-2012-0306
dfn-cert: DFN-CERT-2012-0264
dfn-cert: DFN-CERT-2012-0203
dfn-cert: DFN-CERT-2012-0188

[return to 192.168.153.133]

2.1.22 Medium 22/tcp

Medium (CVSS: 5.3)

NVT: Weak Host Key Algorithm(s) (SSH)

Product detection result
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)

Summary
The remote SSH server is configured to allow / support weak host key algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The remote SSH server supports the following weak host key algorithm(s):
host key algorithm | Description

↪---
ssh-dss | Digital Signature Algorithm (DSA) / Digital Signature Stand
↪ard (DSS)

Solution:
Solution type: Mitigation
Disable the reported weak host key algorithm(s).

Vulnerability Detection Method
Checks the supported host key algorithms of the remote SSH server.
Currently weak host key algorithms are defined as the following:
- ssh-dss: Digital Signature Algorithm (DSA) / Digital Signature Standard (DSS)
Details: Weak Host Key Algorithm(s) (SSH)
OID:1.3.6.1.4.1.25623.1.0.117687
Version used: 2024-06-14T05:05:48Z

Product Detection Result
Product: cpe:/a:ietf:secure_shell_protocol
Method: SSH Protocol Algorithms Supported
OID: 1.3.6.1.4.1.25623.1.0.105565

References
url: https://www.rfc-editor.org/rfc/rfc8332
url: https://www.rfc-editor.org/rfc/rfc8709
url: https://www.rfc-editor.org/rfc/rfc4253#section-6.6

Medium (CVSS: 5.3)

NVT: Weak Key Exchange (KEX) Algorithm(s) Supported (SSH)

Product detection result
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)

Summary
The remote SSH server is configured to allow / support weak key exchange (KEX) algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The remote SSH server supports the following weak KEX algorithm(s):
KEX algorithm | Reason

↪---
diffie-hellman-group-exchange-sha1 | Using SHA-1
diffie-hellman-group1-sha1 | Using Oakley Group 2 (a 1024-bit MODP group
↪) and SHA-1

. . . continues on next page . . .

...continued from previous page ...

Impact
An attacker can quickly break individual connections.

Solution:
Solution type: Mitigation
Disable the reported weak KEX algorithm(s)
- 1024-bit MODP group / prime KEX algorithms:
Alternatively use elliptic-curve Diffie-Hellmann in general, e.g. Curve 25519.

Vulnerability Insight
- 1024-bit MODP group / prime KEX algorithms:
Millions of HTTPS, SSH, and VPN servers all use the same prime numbers for Diffie-Hellman key exchange. Practitioners believed this was safe as long as new key exchange messages were generated for every connection. However, the first step in the number field sieve-the most efficient algorithm for breaking a Diffie-Hellman connection-is dependent only on this prime.
A nation-state can break a 1024-bit prime.

Vulnerability Detection Method
Checks the supported KEX algorithms of the remote SSH server.
Currently weak KEX algorithms are defined as the following:
- non-elliptic-curve Diffie-Hellmann (DH) KEX algorithms with 1024-bit MODP group / prime
- ephemerally generated key exchange groups uses SHA-1
- using RSA 1024-bit modulus key
Details: `Weak Key Exchange (KEX) Algorithm(s) Supported (SSH)`
OID:1.3.6.1.4.1.25623.1.0.150713
Version used: `2024-06-14T05:05:48Z`

Product Detection Result
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`
OID: 1.3.6.1.4.1.25623.1.0.105565

References
url: https://weakdh.org/sysadmin.html
url: https://www.rfc-editor.org/rfc/rfc9142
url: https://www.rfc-editor.org/rfc/rfc9142#name-summary-guidance-for-implem
url: https://www.rfc-editor.org/rfc/rfc6194
url: https://www.rfc-editor.org/rfc/rfc4253#section-6.5

Medium (CVSS: 4.3)

NVT: Weak Encryption Algorithm(s) Supported (SSH)

Product detection result
```
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)
```

Summary
The remote SSH server is configured to allow / support weak encryption algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The remote SSH server supports the following weak client-to-server encryption al
↪gorithm(s):
3des-cbc
aes128-cbc
aes192-cbc
aes256-cbc
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

...continues on next page ...

... continued from previous page ...

```
The remote SSH server supports the following weak server-to-client encryption al
↪gorithm(s):
3des-cbc
aes128-cbc
aes192-cbc
aes256-cbc
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

Solution:
Solution type: Mitigation
Disable the reported weak encryption algorithm(s).

Vulnerability Insight
- The 'arcfour' cipher is the Arcfour stream cipher with 128-bit keys. The Arcfour cipher is believed to be compatible with the RC4 cipher [SCHNEIER]. Arcfour (and RC4) has problems with weak keys, and should not be used anymore.
- The 'none' algorithm specifies that no encryption is to be done. Note that this method provides no confidentiality protection, and it is NOT RECOMMENDED to use it.
- A vulnerability exists in SSH messages that employ CBC mode that may allow an attacker to recover plaintext from a block of ciphertext.

Vulnerability Detection Method
Checks the supported encryption algorithms (client-to-server and server-to-client) of the remote SSH server.
Currently weak encryption algorithms are defined as the following:
- Arcfour (RC4) cipher based algorithms
- 'none' algorithm
- CBC mode cipher based algorithms
Details: `Weak Encryption Algorithm(s) Supported (SSH)`
OID:1.3.6.1.4.1.25623.1.0.105611
Version used: `2024-06-14T05:05:48Z`

Product Detection Result
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`
OID: 1.3.6.1.4.1.25623.1.0.105565

References
url: https://www.rfc-editor.org/rfc/rfc8758
url: https://www.kb.cert.org/vuls/id/958563
url: https://www.rfc-editor.org/rfc/rfc4253#section-6.3

[return to 192.168.153.133]

2.1.23 Medium 23/tcp

Medium (CVSS: 4.8)

NVT: Telnet Unencrypted Cleartext Login

Summary
The remote host is running a Telnet service that allows cleartext logins over unencrypted connections.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
An attacker can uncover login names and passwords by sniffing traffic to the Telnet service.

Solution:
Solution type: Mitigation

... continues on next page ...

... continued from previous page ...

Replace Telnet with a protocol like SSH which supports encrypted connections.

Vulnerability Detection Method
Details: `Telnet Unencrypted Cleartext Login`
OID:1.3.6.1.4.1.25623.1.0.108522
Version used: `2023-10-13T05:06:09Z`

[return to 192.168.153.133]

2.1.24 Medium 5900/tcp

Medium (CVSS: 4.8)

NVT: VNC Server Unencrypted Data Transmission

Summary
The remote host is running a VNC server providing one or more insecure or cryptographically weak Security Type(s) not intended for use on untrusted networks.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
```
The VNC server provides the following insecure or cryptographically weak Securit
↪y Type(s):
2 (VNC authentication)
```

Impact
An attacker can uncover sensitive data by sniffing traffic to the VNC server.

Solution:
Solution type: Mitigation
Run the session over an encrypted channel provided by IPsec [RFC4301] or SSH [RFC4254]. Some VNC server vendors are also providing more secure Security Types within their products.

Vulnerability Detection Method
Details: `VNC Server Unencrypted Data Transmission`
OID:1.3.6.1.4.1.25623.1.0.108529
Version used: `2023-07-12T05:05:04Z`

References
`url`: https://tools.ietf.org/html/rfc6143#page-10

[return to 192.168.153.133]

2.1.25 Medium 445/tcp

Medium (CVSS: 6.0)

NVT: Samba 3.0.0 <= 3.0.25rc3 MS-RPC Remote Shell Command Execution Vulnerability - Active Check

Product detection result
```
cpe:/a:samba:samba:3.0.20
Detected by SMB NativeLanMan (OID: 1.3.6.1.4.1.25623.1.0.102011)
```

Summary
Samba is prone to a vulnerability that allows attackers to execute arbitrary shell commands because the software fails to sanitize user-supplied input.

... continues on next page ...

. . . continued from previous page . . .

Quality of Detection (QoD): 99%

Vulnerability Detection Result

```
By sending a special crafted SMB request it was possible to execute ‘‘ping -p 5f
↪4f70656e564153565433303137315f -c50 192.168.153.128‘‘ on the remote host.
Received answer (ICMP "Data" field):
0x00:  48 6C EE 6A 0F EE 0B 00 56 54 33 30 31 37 31 5F    Hl.j....VT30171_
0x10:  5F 4F 70 65 6E 56 41 53 56 54 33 30 31 37 31 5F    _OpenVASVT30171_
0x20:  5F 4F 70 65 6E 56 41 53 56 54 33 30 31 37 31 5F    _OpenVASVT30171_
0x30:  5F 4F 70 65 6E 56 41 53                            _OpenVAS
```

Impact
An attacker may leverage this issue to execute arbitrary shell commands on an affected system with the privileges of the application.

Solution:
Solution type: VendorFix
Updates are available. Please see the referenced vendor advisory.

Affected Software/OS
Samba versions 3.0.0 through 3.0.25rc3.

Vulnerability Detection Method
Sends a crafted SMB request and checks if the target is sending an ICMP Echo Request back to the scanner host.
Note: For a successful detection of this flaw the scanner host needs to be able to directly receive ICMP Echo Requests (Type 8) from the target.
Details: `Samba 3.0.0 <= 3.0.25rc3 MS-RPC Remote Shell Command Execution Vulnerability - .`
`↪..`
OID:1.3.6.1.4.1.25623.1.0.108011
Version used: `2026-03-12T05:56:11Z`

Product Detection Result
Product: `cpe:/a:samba:samba:3.0.20`
Method: `SMB NativeLanMan`
OID: 1.3.6.1.4.1.25623.1.0.102011

References
`cve: CVE-2007-2447`
`url:` https://www.samba.org/samba/security/CVE-2007-2447.html
`url:` https://web.archive.org/web/20210121173708/http://www.securityfocus.com/bid/23972

[return to 192.168.153.133]

2.1.26 Medium 25/tcp

Medium (CVSS: 6.8)

NVT: Multiple Vendors STARTTLS Implementation Plaintext Arbitrary Command Injection Vulnerability

Summary
Multiple vendors' implementations of 'STARTTLS' are prone to a vulnerability that lets attackers inject arbitrary commands.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
An attacker can exploit this issue to execute arbitrary commands in the context of the user running the application. Successful exploits can allow attackers to obtain email usernames and passwords.

Solution:
Solution type: VendorFix

. . . continues on next page . . .

...continued from previous page ...

Updates are available. Please see the references for more information.

Affected Software/OS
The following vendors are known to be affected:
Ipswitch
Kerio
Postfix
Qmail-TLS
Oracle
SCO Group
spamdyke
ISC

Vulnerability Detection Method
Send a special crafted 'STARTTLS' request and check the response.
Details: Multiple Vendors STARTTLS Implementation Plaintext Arbitrary Command Injection .
↪..
OID:1.3.6.1.4.1.25623.1.0.103935
Version used: 2023-10-31T05:06:37Z

References
cve: CVE-2011-0411
cve: CVE-2011-1430
cve: CVE-2011-1431
cve: CVE-2011-1432
cve: CVE-2011-1506
cve: CVE-2011-1575
cve: CVE-2011-1926
cve: CVE-2011-2165
url: http://www.securityfocus.com/bid/46767
url: http://kolab.org/pipermail/kolab-announce/2011/000101.html
url: http://bugzilla.cyrusimap.org/show_bug.cgi?id=3424
url: http://cyrusimap.org/mediawiki/index.php/Bugs_Resolved_in_2.4.7
url: http://www.kb.cert.org/vuls/id/MAPG-8D9M4P
url: http://files.kolab.org/server/release/kolab-server-2.3.2/sources/release-notes.txt
url: http://www.postfix.org/CVE-2011-0411.html
url: http://www.pureftpd.org/project/pure-ftpd/news
url: http://www.watchguard.com/support/release-notes/xcs/9/en-US/EN_ReleaseNotes_XCS_9_1_1/EN_ReleaseNotes_WG_XCS_9_1_TLS_Hotfix.pdf
url: http://www.spamdyke.org/documentation/Changelog.txt
url: http://datatracker.ietf.org/doc/draft-josefsson-kerberos5-starttls/?include_text=1
url: http://www.securityfocus.com/archive/1/516901
url: http://support.avaya.com/css/P8/documents/100134676
url: http://support.avaya.com/css/P8/documents/100141041
url: http://www.oracle.com/technetwork/topics/security/cpuapr2011-301950.html
url: http://inoa.net/qmail-tls/vu555316.patch
url: http://www.kb.cert.org/vuls/id/555316
cert-bund: CB-K15/1514
dfn-cert: DFN-CERT-2011-0917
dfn-cert: DFN-CERT-2011-0912
dfn-cert: DFN-CERT-2011-0897
dfn-cert: DFN-CERT-2011-0844
dfn-cert: DFN-CERT-2011-0818
dfn-cert: DFN-CERT-2011-0808
dfn-cert: DFN-CERT-2011-0771
dfn-cert: DFN-CERT-2011-0741
dfn-cert: DFN-CERT-2011-0712
dfn-cert: DFN-CERT-2011-0673
dfn-cert: DFN-CERT-2011-0597
dfn-cert: DFN-CERT-2011-0596
dfn-cert: DFN-CERT-2011-0519
dfn-cert: DFN-CERT-2011-0516
dfn-cert: DFN-CERT-2011-0483
dfn-cert: DFN-CERT-2011-0434
dfn-cert: DFN-CERT-2011-0393
dfn-cert: DFN-CERT-2011-0381

Medium (CVSS: 5.9)

NVT: SSL/TLS: Deprecated SSLv2 and SSLv3 Protocol Detection

Product detection result
cpe:/a:ietf:transport_layer_security:1.0
Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)

Summary
It was possible to detect the usage of the deprecated SSLv2 and/or SSLv3 protocol on this system.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
In addition to TLSv1.0+ the service is also providing the deprecated SSLv2 and S
↪SLv3 protocols and supports one or more ciphers. Those supported ciphers can b
↪e found in the 'SSL/TLS: Report Supported Cipher Suites' (OID: 1.3.6.1.4.1.256
↪23.1.0.802067) VT.

Impact
An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection.
Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.

Solution:
Solution type: Mitigation
It is recommended to disable the deprecated SSLv2 and/or SSLv3 protocols in favor of the TLSv1.2+ protocols.
Please see the references for more resources supporting you with this task.

Affected Software/OS
All services providing an encrypted communication using the SSLv2 and/or SSLv3 protocols.

Vulnerability Insight
The SSLv2 and SSLv3 protocols contain known cryptographic flaws like:
- CVE-2014-3566: Padding Oracle On Downgraded Legacy Encryption (POODLE)
- CVE-2016-0800: Decrypting RSA with Obsolete and Weakened eNcryption (DROWN)

Vulnerability Detection Method
Checks the used SSL protocols of the services provided by this system.
Details: SSL/TLS: Deprecated SSLv2 and SSLv3 Protocol Detection
OID:1.3.6.1.4.1.25623.1.0.111012
Version used: 2026-06-03T07:18:10Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security:1.0
Method: SSL/TLS: Version Detection
OID: 1.3.6.1.4.1.25623.1.0.105782

References
cve: CVE-2016-0800
cve: CVE-2014-3566
url: https://configurator.tlsref.org/
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
url: https://drownattack.com
url: https://www.imperialviolet.org/2014/10/14/poodle.html
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2025-1658
cert-bund: WID-SEC-2023-0431
cert-bund: WID-SEC-2023-0427
cert-bund: CB-K18/0094
cert-bund: CB-K17/1198
cert-bund: CB-K17/1196

... continues on next page ...

... continued from previous page ...

cert-bund: CB-K16/1828
cert-bund: CB-K16/1438
cert-bund: CB-K16/1384
cert-bund: CB-K16/1141
cert-bund: CB-K16/1107
cert-bund: CB-K16/1102
cert-bund: CB-K16/0792
cert-bund: CB-K16/0599
cert-bund: CB-K16/0597
cert-bund: CB-K16/0459
cert-bund: CB-K16/0456
cert-bund: CB-K16/0433
cert-bund: CB-K16/0424
cert-bund: CB-K16/0415
cert-bund: CB-K16/0413
cert-bund: CB-K16/0374
cert-bund: CB-K16/0367
cert-bund: CB-K16/0331
cert-bund: CB-K16/0329
cert-bund: CB-K16/0328
cert-bund: CB-K16/0156
cert-bund: CB-K15/1514
cert-bund: CB-K15/1358
cert-bund: CB-K15/1021
cert-bund: CB-K15/0972
cert-bund: CB-K15/0637
cert-bund: CB-K15/0590
cert-bund: CB-K15/0525
cert-bund: CB-K15/0393
cert-bund: CB-K15/0384
cert-bund: CB-K15/0287
cert-bund: CB-K15/0252
cert-bund: CB-K15/0246
cert-bund: CB-K15/0237
cert-bund: CB-K15/0118
cert-bund: CB-K15/0110
cert-bund: CB-K15/0108
cert-bund: CB-K15/0080
cert-bund: CB-K15/0078
cert-bund: CB-K15/0077
cert-bund: CB-K15/0075
cert-bund: CB-K14/1617
cert-bund: CB-K14/1581
cert-bund: CB-K14/1537
cert-bund: CB-K14/1479
cert-bund: CB-K14/1458
cert-bund: CB-K14/1342
cert-bund: CB-K14/1314
cert-bund: CB-K14/1313
cert-bund: CB-K14/1311
cert-bund: CB-K14/1304
cert-bund: CB-K14/1296
dfn-cert: DFN-CERT-2018-0096
dfn-cert: DFN-CERT-2017-1238
dfn-cert: DFN-CERT-2017-1236
dfn-cert: DFN-CERT-2016-1929
dfn-cert: DFN-CERT-2016-1527
dfn-cert: DFN-CERT-2016-1468
dfn-cert: DFN-CERT-2016-1216
dfn-cert: DFN-CERT-2016-1174
dfn-cert: DFN-CERT-2016-1168
dfn-cert: DFN-CERT-2016-0884
dfn-cert: DFN-CERT-2016-0841
dfn-cert: DFN-CERT-2016-0644
dfn-cert: DFN-CERT-2016-0642
dfn-cert: DFN-CERT-2016-0496
dfn-cert: DFN-CERT-2016-0495
dfn-cert: DFN-CERT-2016-0465
dfn-cert: DFN-CERT-2016-0459
dfn-cert: DFN-CERT-2016-0453
dfn-cert: DFN-CERT-2016-0451
dfn-cert: DFN-CERT-2016-0415

... continues on next page ...

... continued from previous page ...

```
dfn-cert: DFN-CERT-2016-0403
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2016-0360
dfn-cert: DFN-CERT-2016-0359
dfn-cert: DFN-CERT-2016-0357
dfn-cert: DFN-CERT-2016-0171
dfn-cert: DFN-CERT-2015-1431
dfn-cert: DFN-CERT-2015-1075
dfn-cert: DFN-CERT-2015-1026
dfn-cert: DFN-CERT-2015-0664
dfn-cert: DFN-CERT-2015-0548
dfn-cert: DFN-CERT-2015-0404
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0259
dfn-cert: DFN-CERT-2015-0254
dfn-cert: DFN-CERT-2015-0245
dfn-cert: DFN-CERT-2015-0118
dfn-cert: DFN-CERT-2015-0114
dfn-cert: DFN-CERT-2015-0083
dfn-cert: DFN-CERT-2015-0082
dfn-cert: DFN-CERT-2015-0081
dfn-cert: DFN-CERT-2015-0076
dfn-cert: DFN-CERT-2014-1717
dfn-cert: DFN-CERT-2014-1680
dfn-cert: DFN-CERT-2014-1632
dfn-cert: DFN-CERT-2014-1564
dfn-cert: DFN-CERT-2014-1542
dfn-cert: DFN-CERT-2014-1414
dfn-cert: DFN-CERT-2014-1366
dfn-cert: DFN-CERT-2014-1354
```

Medium (CVSS: 5.3)

NVT: SSL/TLS: Server Certificate / Certificate in Chain with RSA keys less than 2048 bits

Summary
The remote SSL/TLS server certificate and/or any of the certificates in the certificate chain is using a RSA key with less than 2048 bits.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The remote SSL/TLS server is using the following certificate(s) with a RSA key w
↪ith less than 2048 bits (public-key-size:public-key-algorithm:serial:issuer):
1024:RSA:00FAF93A4C7FB6B9CC:1.2.840.113549.1.9.1=#726F6F74407562756E74753830342D
↪626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office for C
↪omplication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is no su
↪ch thing outside US,C=XX (Server certificate)
```

Impact
Using certificates with weak RSA key size can lead to unauthorized exposure of sensitive information.

Solution:
Solution type: Mitigation
Replace the certificate with a stronger key and reissue the certificates it signed.

Vulnerability Insight
SSL/TLS certificates using RSA keys with less than 2048 bits are considered unsafe.

Vulnerability Detection Method
Checks the RSA keys size of the server certificate and all certificates in chain for a size < 2048 bit.
Details: `SSL/TLS: Server Certificate / Certificate in Chain with RSA keys less than 2048.`
`↪..`
OID:1.3.6.1.4.1.25623.1.0.150710
Version used: `2021-12-10T12:48:00Z`

References
`url:` https://www.cabforum.org/wp-content/uploads/Baseline_Requirements_V1.pdf

Medium (CVSS: 5.0)

NVT: SSL/TLS: Certificate Expired

Product detection result
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Collect and Report Certificate Details (OID: 1.3.6.1.4.1.25
↪623.1.0.103692)

Summary
The remote server's SSL/TLS certificate has already expired.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
The certificate of the remote service expired on 2010-04-16 14:07:45.
Certificate details:
fingerprint (SHA-1) | ED093088706603BFD5DC237399B498DA2D4D31C6
fingerprint (SHA-256) | E7A7FA0D63E457C7C4A59B38B70849C6A70BDA6F830C7A
↪F1E32DEE436DE813CC
issued by | 1.2.840.113549.1.9.1=#726F6F74407562756E747538
↪30342D626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office
↪ for Complication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is
↪ no such thing outside US,C=XX
public key algorithm | RSA
public key size (bits) | 1024
serial | 00FAF93A4C7FB6B9CC
signature algorithm | sha1WithRSAEncryption
subject | 1.2.840.113549.1.9.1=#726F6F74407562756E747538
↪30342D626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office
↪ for Complication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is
↪ no such thing outside US,C=XX
subject alternative names (SAN) | None
valid from | 2010-03-17 14:07:45 UTC
valid until | 2010-04-16 14:07:45 UTC

Solution:
Solution type: Mitigation
Replace the SSL/TLS certificate by a new one.

Vulnerability Insight
This script checks expiry dates of certificates associated with SSL/TLS-enabled services on the target and reports whether any have already expired.

Vulnerability Detection Method
Details: SSL/TLS: Certificate Expired
OID:1.3.6.1.4.1.25623.1.0.103955
Version used: 2026-03-13T05:54:58Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security
Method: SSL/TLS: Collect and Report Certificate Details
OID: 1.3.6.1.4.1.25623.1.0.103692

Medium (CVSS: 5.0)

NVT: SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094)

Summary
The remote SSL/TLS service is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
The following indicates that the remote SSL/TLS service is affected:
Protocol Version | Successful re-done SSL/TLS handshakes (Renegotiation) over an
↪ existing / already established SSL/TLS connection

... continues on next page ...

...continued from previous page ...

```
------------------------------------------------------------------------------
↪--------------------------------------------------
TLSv1.0          | 10
```

Impact
The flaw might make it easier for remote attackers to cause a DoS (CPU consumption) by performing many renegotiations within a single connection.

Solution:
Solution type: VendorFix
Users should contact their vendors for specific patch information.
A general solution is to remove/disable renegotiation capabilities altogether from/in the affected SSL/TLS service.

Affected Software/OS
Every SSL/TLS service which does not properly restrict client-initiated renegotiation.

Vulnerability Insight
The flaw exists because the remote SSL/TLS service does not properly restrict client-initiated renegotiation within the SSL and TLS protocols.
Note: The referenced CVEs are affecting OpenSSL and Mozilla Network Security Services (NSS) but both are in a DISPUTED state with the following rationale:
> It can also be argued that it is the responsibility of server deployments, not a security library, to prevent or limit renegotiation when it is inappropriate within a specific environment.
Both CVEs are still kept in this VT as a reference to the origin of this flaw.

Vulnerability Detection Method
Checks if the remote service allows to re-do the same SSL/TLS handshake (Renegotiation) over an existing / already established SSL/TLS connection.
Details: `SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094)`
OID:1.3.6.1.4.1.25623.1.0.117761
Version used: `2026-03-13T05:54:58Z`

References
`cve: CVE-2011-1473`
`cve: CVE-2011-5094`
`url: https://web.archive.org/web/20211201133213/https://orchilles.com/ssl-renegotiation-dos/`
`url: https://mailarchive.ietf.org/arch/msg/tls/wdg46VE_jkYBbgJ5yE4P9nQ-8IU/`
`url: https://vincent.bernat.ch/en/blog/2011-ssl-dos-mitigation`
`url: https://www.openwall.com/lists/oss-security/2011/07/08/2`
`cert-bund: WID-SEC-2026-2904`
`cert-bund: WID-SEC-2026-0180`
`cert-bund: WID-SEC-2024-1591`
`cert-bund: WID-SEC-2024-0796`
`cert-bund: WID-SEC-2023-1435`
`cert-bund: CB-K17/0980`
`cert-bund: CB-K17/0979`
`cert-bund: CB-K14/0772`
`cert-bund: CB-K13/0915`
`cert-bund: CB-K13/0462`
`dfn-cert: DFN-CERT-2025-0933`
`dfn-cert: DFN-CERT-2017-1013`
`dfn-cert: DFN-CERT-2017-1012`
`dfn-cert: DFN-CERT-2014-0809`
`dfn-cert: DFN-CERT-2013-1928`
`dfn-cert: DFN-CERT-2012-1112`

Medium (CVSS: 5.0)

NVT: Check if Mailserver answer to VRFY and EXPN requests

Summary
The Mailserver on this host answers to VRFY and/or EXPN requests.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
`'VRFY root' produces the following answer: 252 2.0.0 root`

...continues on next page ...

...continued from previous page ...

Solution:
Solution type: Workaround
Disable VRFY and/or EXPN on your Mailserver.
For postfix add 'disable_vrfy_command=yes' in 'main.cf'.
For Sendmail add the option 'O PrivacyOptions=goaway'.
It is suggested that, if you really want to publish this type of information, you use a mechanism that legitimate users actually know about, such as Finger or HTTP.

Vulnerability Insight
VRFY and EXPN ask the server for information about an address. They are inherently unusable through firewalls, gateways, mail exchangers for part-time hosts, etc.

Vulnerability Detection Method
Details: `Check if Mailserver answer to VRFY and EXPN requests`
OID:1.3.6.1.4.1.25623.1.0.100072
Version used: `2023-10-31T05:06:37Z`

References
`url:` http://cr.yp.to/smtp/vrfy.html

Medium (CVSS: 4.3)

NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection

Product detection result
`cpe:/a:ietf:transport_layer_security:1.0`
`Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)`

Summary
It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
```
The service is only providing the deprecated TLSv1.0 protocol and supports one o
↪r more ciphers. Those supported ciphers can be found in the 'SSL/TLS: Report S
↪upported Cipher Suites' (OID: 1.3.6.1.4.1.25623.1.0.802067) VT.
```

Impact
An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection.
Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.

Solution:
Solution type: Mitigation
It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols.
Please see the references for more resources supporting you with this task.

Affected Software/OS
- All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols
- CVE-2023-41928: Kiloview P1 4G and P2 4G Video Encoder
- CVE-2024-41270: Gorush v1.18.4
- CVE-2025-3200: Multiple products from Wiesemann & Theis

Vulnerability Insight
The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like:
- CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST)
- CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)

Vulnerability Detection Method
Checks the used TLS protocols of the services provided by this system.
Details: `SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection`
OID:1.3.6.1.4.1.25623.1.0.117274
Version used: `2026-06-03T07:18:10Z`

...continues on next page ...

... continued from previous page ...

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security:1.0
Method: SSL/TLS: Version Detection
OID: 1.3.6.1.4.1.25623.1.0.105782

References
cve: CVE-2011-3389
cve: CVE-2015-0204
cve: CVE-2023-41928
cve: CVE-2024-41270
cve: CVE-2025-3200
url: https://configurator.tlsref.org/
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
url: https://datatracker.ietf.org/doc/rfc8996/
url: https://vnhacker.blogspot.com/2011/09/beast.html
url: https://web.archive.org/web/20201108095603/https://censys.io/blog/freak
url: https://certvde.com/en/advisories/VDE-2025-031/
url: https://gist.github.com/nyxfqq/cfae38fada582a0f576d154be1aeb1fc
url: https://advisories.ncsc.nl/advisory?id=NCSC-2024-0273
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2023-1435
cert-bund: CB-K18/0799
cert-bund: CB-K16/1289
cert-bund: CB-K16/1096
cert-bund: CB-K15/1751
cert-bund: CB-K15/1266
cert-bund: CB-K15/0850
cert-bund: CB-K15/0764
cert-bund: CB-K15/0720
cert-bund: CB-K15/0548
cert-bund: CB-K15/0526
cert-bund: CB-K15/0509
cert-bund: CB-K15/0493
cert-bund: CB-K15/0384
cert-bund: CB-K15/0365
cert-bund: CB-K15/0364
cert-bund: CB-K15/0302
cert-bund: CB-K15/0192
cert-bund: CB-K15/0079
cert-bund: CB-K15/0016
cert-bund: CB-K14/1342
cert-bund: CB-K14/0231
cert-bund: CB-K13/0845
cert-bund: CB-K13/0796
cert-bund: CB-K13/0790
dfn-cert: DFN-CERT-2020-0177
dfn-cert: DFN-CERT-2020-0111
dfn-cert: DFN-CERT-2019-0068
dfn-cert: DFN-CERT-2018-1441
dfn-cert: DFN-CERT-2018-1408
dfn-cert: DFN-CERT-2016-1372
dfn-cert: DFN-CERT-2016-1164
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2015-1853
dfn-cert: DFN-CERT-2015-1332
dfn-cert: DFN-CERT-2015-0884
dfn-cert: DFN-CERT-2015-0800
dfn-cert: DFN-CERT-2015-0758
dfn-cert: DFN-CERT-2015-0567
dfn-cert: DFN-CERT-2015-0544
dfn-cert: DFN-CERT-2015-0530
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0375

... continues on next page ...

... continued from previous page ...

```
dfn-cert: DFN-CERT-2015-0374
dfn-cert: DFN-CERT-2015-0305
dfn-cert: DFN-CERT-2015-0199
dfn-cert: DFN-CERT-2015-0079
dfn-cert: DFN-CERT-2015-0021
dfn-cert: DFN-CERT-2014-1414
dfn-cert: DFN-CERT-2013-1847
dfn-cert: DFN-CERT-2013-1792
dfn-cert: DFN-CERT-2012-1979
dfn-cert: DFN-CERT-2012-1829
dfn-cert: DFN-CERT-2012-1530
dfn-cert: DFN-CERT-2012-1380
dfn-cert: DFN-CERT-2012-1377
dfn-cert: DFN-CERT-2012-1292
dfn-cert: DFN-CERT-2012-1214
dfn-cert: DFN-CERT-2012-1213
dfn-cert: DFN-CERT-2012-1180
dfn-cert: DFN-CERT-2012-1156
dfn-cert: DFN-CERT-2012-1155
dfn-cert: DFN-CERT-2012-1039
dfn-cert: DFN-CERT-2012-0956
dfn-cert: DFN-CERT-2012-0908
dfn-cert: DFN-CERT-2012-0868
dfn-cert: DFN-CERT-2012-0867
dfn-cert: DFN-CERT-2012-0848
dfn-cert: DFN-CERT-2012-0838
dfn-cert: DFN-CERT-2012-0776
dfn-cert: DFN-CERT-2012-0722
dfn-cert: DFN-CERT-2012-0638
dfn-cert: DFN-CERT-2012-0627
dfn-cert: DFN-CERT-2012-0451
dfn-cert: DFN-CERT-2012-0418
dfn-cert: DFN-CERT-2012-0354
dfn-cert: DFN-CERT-2012-0234
dfn-cert: DFN-CERT-2012-0221
dfn-cert: DFN-CERT-2012-0177
dfn-cert: DFN-CERT-2012-0170
dfn-cert: DFN-CERT-2012-0146
dfn-cert: DFN-CERT-2012-0142
dfn-cert: DFN-CERT-2012-0126
dfn-cert: DFN-CERT-2012-0123
dfn-cert: DFN-CERT-2012-0095
dfn-cert: DFN-CERT-2012-0051
dfn-cert: DFN-CERT-2012-0047
dfn-cert: DFN-CERT-2012-0021
dfn-cert: DFN-CERT-2011-1953
dfn-cert: DFN-CERT-2011-1946
dfn-cert: DFN-CERT-2011-1844
dfn-cert: DFN-CERT-2011-1826
dfn-cert: DFN-CERT-2011-1774
dfn-cert: DFN-CERT-2011-1743
dfn-cert: DFN-CERT-2011-1738
dfn-cert: DFN-CERT-2011-1706
dfn-cert: DFN-CERT-2011-1628
dfn-cert: DFN-CERT-2011-1627
dfn-cert: DFN-CERT-2011-1619
dfn-cert: DFN-CERT-2011-1482
```

Medium (CVSS: 4.3)

NVT: SSL/TLS: RSA Temporary Key Handling 'RSA_EXPORT' Downgrade Issue (FREAK)

Product detection result

```
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↪802067)
```

Summary

... continues on next page ...

... continued from previous page ...

This host is accepting 'RSA_EXPORT' cipher suites and is prone to a man-in-the-middle (MITM) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
'RSA_EXPORT' cipher suites accepted by this service via the SSLv3 protocol:
TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA
TLS_RSA_EXPORT_WITH_DES40_CBC_SHA
TLS_RSA_EXPORT_WITH_RC2_CBC_40_MD5
TLS_RSA_EXPORT_WITH_RC4_40_MD5
'RSA_EXPORT' cipher suites accepted by this service via the TLSv1.0 protocol:
TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA
TLS_RSA_EXPORT_WITH_DES40_CBC_SHA
TLS_RSA_EXPORT_WITH_RC2_CBC_40_MD5
TLS_RSA_EXPORT_WITH_RC4_40_MD5
```

Impact

Successful exploitation will allow remote attacker to downgrade the security of a session to use 'RSA_EXPORT' cipher suites, which are significantly weaker than non-export cipher suites. This may allow a man-in-the-middle attacker to more easily break the encryption and monitor or tamper with the encrypted stream.

Solution:

Solution type: VendorFix

- Remove support for 'RSA_EXPORT' cipher suites from the service. Please see the references for more resources supporting you with this task.
- If the service is using OpenSSL: Update to version 0.9.8zd, 1.0.0p, 1.0.1k or later.

Affected Software/OS

- Hosts accepting 'RSA_EXPORT' cipher suites.
- OpenSSL versions prior to 0.9.8zd, 1.0.0 prior to 1.0.0p and 1.0.1 prior to 1.0.1k.

Vulnerability Insight

Flaw is due to improper handling RSA temporary keys in a non-export RSA key exchange cipher suite.

Vulnerability Detection Method

Checks previous collected cipher suites.

Details: `SSL/TLS: RSA Temporary Key Handling 'RSA_EXPORT' Downgrade Issue (FREAK)`

OID:1.3.6.1.4.1.25623.1.0.805142

Version used: `2026-06-03T07:18:10Z`

Product Detection Result

Product: `cpe:/a:ietf:transport_layer_security`

Method: `SSL/TLS: Report Supported Cipher Suites`

OID: 1.3.6.1.4.1.25623.1.0.802067

References

cve: CVE-2015-0204
url: https://freakattack.com
url: https://openssl-library.org/news/secadv/20150108.txt
url: https://web.archive.org/web/20210122095002/http://www.securityfocus.com/bid/71936
url: https://www.secpod.com/blog/freak-attack
url: https://blog.cryptographyengineering.com/2015/03/03/attack-of-week-freak-or-factoring-nsa
url: https://configurator.tlsref.org/
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
cert-bund: WID-SEC-2026-0180
cert-bund: CB-K18/0799
cert-bund: CB-K16/1289
cert-bund: CB-K16/1096
cert-bund: CB-K15/1751
cert-bund: CB-K15/1266
cert-bund: CB-K15/0850
cert-bund: CB-K15/0764

... continues on next page ...

... continued from previous page ...

```
cert-bund: CB-K15/0720
cert-bund: CB-K15/0548
cert-bund: CB-K15/0526
cert-bund: CB-K15/0509
cert-bund: CB-K15/0493
cert-bund: CB-K15/0384
cert-bund: CB-K15/0365
cert-bund: CB-K15/0364
cert-bund: CB-K15/0302
cert-bund: CB-K15/0192
cert-bund: CB-K15/0016
dfn-cert: DFN-CERT-2018-1408
dfn-cert: DFN-CERT-2016-1372
dfn-cert: DFN-CERT-2016-1164
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2015-1853
dfn-cert: DFN-CERT-2015-1332
dfn-cert: DFN-CERT-2015-0884
dfn-cert: DFN-CERT-2015-0800
dfn-cert: DFN-CERT-2015-0758
dfn-cert: DFN-CERT-2015-0567
dfn-cert: DFN-CERT-2015-0544
dfn-cert: DFN-CERT-2015-0530
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0375
dfn-cert: DFN-CERT-2015-0374
dfn-cert: DFN-CERT-2015-0305
dfn-cert: DFN-CERT-2015-0199
dfn-cert: DFN-CERT-2015-0021
```

Medium (CVSS: 4.0)

NVT: SSL/TLS: Diffie-Hellman Key Exchange Insufficient DH Group Strength Vulnerability

Summary
The SSL/TLS service uses Diffie-Hellman groups with insufficient strength (key size < 2048).

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`Server Temporary Key Size: 1024 bits`

Impact
An attacker might be able to decrypt the SSL/TLS communication offline.

Solution:
Solution type: Workaround
- Deploy (Ephemeral) Elliptic-Curve Diffie-Hellman (ECDHE) or use a 2048-bit or stronger Diffie-Hellman group. Please see the references for more resources supporting you with this task.
- For Apache Web Servers: Beginning with version 2.4.7, mod_ssl will use DH parameters which include primes with lengths of more than 1024 bits.

Affected Software/OS
All services providing an encrypted communication using Diffie-Hellman groups with insufficient strength.

Vulnerability Insight
The Diffie-Hellman group are some big numbers that are used as base for the DH computations. They can be, and often are, fixed. The security of the final secret depends on the size of these parameters. It was found that 512 and 768 bits to be weak, 1024 bits to be breakable by really powerful attackers like governments.

Vulnerability Detection Method
Checks the DHE temporary public key size.
Details: `SSL/TLS: Diffie-Hellman Key Exchange Insufficient DH Group Strength Vulnerabili.`
`↪..`
OID:1.3.6.1.4.1.25623.1.0.106223
Version used: `2026-06-03T07:18:10Z`

References

... continues on next page ...

... continued from previous page ...

url: https://weakdh.org
url: https://weakdh.org/sysadmin.html
url: https://configurator.tlsref.org/
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
url: https://httpd.apache.org/docs/2.4/mod/mod_ssl.html#sslcertificatefile

Medium (CVSS: 4.0)

NVT: SSL/TLS: Certificate Signed Using A Weak Signature Algorithm

Summary
The remote service is using a SSL/TLS certificate in the certificate chain that has been signed using a cryptographically weak hashing algorithm.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The following certificates are part of the certificate chain but using insecure
↪signature algorithms:
Subject:              1.2.840.113549.1.9.1=#726F6F74407562756E74753830342D626173
↪652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office for Complic
↪ation of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is no such thi
↪ng outside US,C=XX
Signature Algorithm:  sha1WithRSAEncryption
```

Solution:
Solution type: Mitigation
Servers that use SSL/TLS certificates signed with a weak SHA-1, MD5, MD4 or MD2 hashing algorithm will need to obtain new SHA-2 signed SSL/TLS certificates to avoid web browser SSL/TLS certificate warnings.

Vulnerability Insight
The following hashing algorithms used for signing SSL/TLS certificates are considered cryptographically weak and not secure enough for ongoing use:
- Secure Hash Algorithm 1 (SHA-1)
- Message Digest 5 (MD5)
- Message Digest 4 (MD4)
- Message Digest 2 (MD2)

Beginning as late as January 2017 and as early as June 2016, browser developers such as Microsoft and Google will begin warning users when visiting web sites that use SHA-1 signed Secure Socket Layer (SSL) certificates.
NOTE: The script preference allows to set one or more custom SHA-1 fingerprints of CA certificates which are trusted by this routine. The fingerprints needs to be passed comma-separated and case-insensitive:
Fingerprint1
or
fingerprint1, Fingerprint2

Vulnerability Detection Method
Check which hashing algorithm was used to sign the remote SSL/TLS certificate.
Details: SSL/TLS: Certificate Signed Using A Weak Signature Algorithm
OID:1.3.6.1.4.1.25623.1.0.105880
Version used: 2021-10-15T11:13:32Z

References
url: https://blog.mozilla.org/security/2014/09/23/phasing-out-certificates-with-sha-1-based-signature-algorithms/

[return to 192.168.153.133]

2.1.27 Medium 21/tcp

Medium (CVSS: 6.4)

NVT: Anonymous FTP Login Reporting

Summary
Reports if the remote FTP Server allows anonymous logins.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
It was possible to login to the remote FTP service with the following anonymous
↪account(s):
anonymous:anonymous@example.com
ftp:anonymous@example.com
```

Impact
Based on the files accessible via this anonymous FTP login and the permissions of this account an attacker might be able to:
- gain access to sensitive files
- upload or delete files.

Solution:
Solution type: Mitigation
If you do not want to share files, you should disable anonymous logins.

Vulnerability Insight
A host that provides an FTP service may additionally provide Anonymous FTP access as well. Under this arrangement, users do not strictly need an account on the host. Instead the user typically enters 'anonymous' or 'ftp' when prompted for username. Although users are commonly asked to send their email address as their password, little to no verification is actually performed on the supplied data.
Remark: NIST don't see 'configuration issues' as software flaws so the referenced CVE has a severity of 0.0. The severity of this VT has been raised by Greenbone to still report a configuration issue on the target.

Vulnerability Detection Method
Details: `Anonymous FTP Login Reporting`
OID:1.3.6.1.4.1.25623.1.0.900600
Version used: `2021-10-20T09:03:29Z`

References
`cve: CVE-1999-0497`

Medium (CVSS: 4.8)

NVT: FTP Unencrypted Cleartext Login

Summary
The remote host is running a FTP service that allows cleartext logins over unencrypted connections.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
```
The remote FTP service accepts logins without a previous sent 'AUTH TLS' command
↪. Response(s):
Non-anonymous sessions: 331 Please specify the password.
Anonymous sessions:     331 Please specify the password.
```

Impact
An attacker can uncover login names and passwords by sniffing traffic to the FTP service.

Solution:
Solution type: Mitigation
Enable FTPS or enforce the connection via the 'AUTH TLS' command. Please see the manual of the FTP service for more information.

Vulnerability Detection Method
Tries to login to a non FTPS enabled FTP service without sending a 'AUTH TLS' command first and checks if the service is accepting the login without enforcing the use of the 'AUTH TLS' command.

...continues on next page ...

... continued from previous page ...

Details: FTP Unencrypted Cleartext Login
OID:1.3.6.1.4.1.25623.1.0.108528
Version used: 2023-12-20T05:05:58Z

[return to 192.168.153.133]

2.1.28 Medium 5432/tcp

Medium (CVSS: 5.9)

NVT: SSL/TLS: Deprecated SSLv2 and SSLv3 Protocol Detection

Product detection result
cpe:/a:ietf:transport_layer_security:1.0
Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)

Summary
It was possible to detect the usage of the deprecated SSLv2 and/or SSLv3 protocol on this system.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
In addition to TLSv1.0+ the service is also providing the deprecated SSLv3 proto
↪col and supports one or more ciphers. Those supported ciphers can be found in
↪the 'SSL/TLS: Report Supported Cipher Suites' (OID: 1.3.6.1.4.1.25623.1.0.8020
↪67) VT.

Impact
An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection.
Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.

Solution:
Solution type: Mitigation
It is recommended to disable the deprecated SSLv2 and/or SSLv3 protocols in favor of the TLSv1.2+ protocols.
Please see the references for more resources supporting you with this task.

Affected Software/OS
All services providing an encrypted communication using the SSLv2 and/or SSLv3 protocols.

Vulnerability Insight
The SSLv2 and SSLv3 protocols contain known cryptographic flaws like:
- CVE-2014-3566: Padding Oracle On Downgraded Legacy Encryption (POODLE)
- CVE-2016-0800: Decrypting RSA with Obsolete and Weakened eNcryption (DROWN)

Vulnerability Detection Method
Checks the used SSL protocols of the services provided by this system.
Details: SSL/TLS: Deprecated SSLv2 and SSLv3 Protocol Detection
OID:1.3.6.1.4.1.25623.1.0.111012
Version used: 2026-06-03T07:18:10Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security:1.0
Method: SSL/TLS: Version Detection
OID: 1.3.6.1.4.1.25623.1.0.105782

References
cve: CVE-2016-0800
cve: CVE-2014-3566
url: https://configurator.tlsref.org/
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html

... continues on next page ...

...continued from previous page ...

url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
url: https://drownattack.com
url: https://www.imperialviolet.org/2014/10/14/poodle.html
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2025-1658
cert-bund: WID-SEC-2023-0431
cert-bund: WID-SEC-2023-0427
cert-bund: CB-K18/0094
cert-bund: CB-K17/1198
cert-bund: CB-K17/1196
cert-bund: CB-K16/1828
cert-bund: CB-K16/1438
cert-bund: CB-K16/1384
cert-bund: CB-K16/1141
cert-bund: CB-K16/1107
cert-bund: CB-K16/1102
cert-bund: CB-K16/0792
cert-bund: CB-K16/0599
cert-bund: CB-K16/0597
cert-bund: CB-K16/0459
cert-bund: CB-K16/0456
cert-bund: CB-K16/0433
cert-bund: CB-K16/0424
cert-bund: CB-K16/0415
cert-bund: CB-K16/0413
cert-bund: CB-K16/0374
cert-bund: CB-K16/0367
cert-bund: CB-K16/0331
cert-bund: CB-K16/0329
cert-bund: CB-K16/0328
cert-bund: CB-K16/0156
cert-bund: CB-K15/1514
cert-bund: CB-K15/1358
cert-bund: CB-K15/1021
cert-bund: CB-K15/0972
cert-bund: CB-K15/0637
cert-bund: CB-K15/0590
cert-bund: CB-K15/0525
cert-bund: CB-K15/0393
cert-bund: CB-K15/0384
cert-bund: CB-K15/0287
cert-bund: CB-K15/0252
cert-bund: CB-K15/0246
cert-bund: CB-K15/0237
cert-bund: CB-K15/0118
cert-bund: CB-K15/0110
cert-bund: CB-K15/0108
cert-bund: CB-K15/0080
cert-bund: CB-K15/0078
cert-bund: CB-K15/0077
cert-bund: CB-K15/0075
cert-bund: CB-K14/1617
cert-bund: CB-K14/1581
cert-bund: CB-K14/1537
cert-bund: CB-K14/1479
cert-bund: CB-K14/1458
cert-bund: CB-K14/1342
cert-bund: CB-K14/1314
cert-bund: CB-K14/1313
cert-bund: CB-K14/1311
cert-bund: CB-K14/1304
cert-bund: CB-K14/1296
dfn-cert: DFN-CERT-2018-0096
dfn-cert: DFN-CERT-2017-1238
dfn-cert: DFN-CERT-2017-1236
dfn-cert: DFN-CERT-2016-1929
dfn-cert: DFN-CERT-2016-1527
dfn-cert: DFN-CERT-2016-1468
dfn-cert: DFN-CERT-2016-1216

...continues on next page ...

... continued from previous page ...

dfn-cert: DFN-CERT-2016-1174
dfn-cert: DFN-CERT-2016-1168
dfn-cert: DFN-CERT-2016-0884
dfn-cert: DFN-CERT-2016-0841
dfn-cert: DFN-CERT-2016-0644
dfn-cert: DFN-CERT-2016-0642
dfn-cert: DFN-CERT-2016-0496
dfn-cert: DFN-CERT-2016-0495
dfn-cert: DFN-CERT-2016-0465
dfn-cert: DFN-CERT-2016-0459
dfn-cert: DFN-CERT-2016-0453
dfn-cert: DFN-CERT-2016-0451
dfn-cert: DFN-CERT-2016-0415
dfn-cert: DFN-CERT-2016-0403
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2016-0360
dfn-cert: DFN-CERT-2016-0359
dfn-cert: DFN-CERT-2016-0357
dfn-cert: DFN-CERT-2016-0171
dfn-cert: DFN-CERT-2015-1431
dfn-cert: DFN-CERT-2015-1075
dfn-cert: DFN-CERT-2015-1026
dfn-cert: DFN-CERT-2015-0664
dfn-cert: DFN-CERT-2015-0548
dfn-cert: DFN-CERT-2015-0404
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0259
dfn-cert: DFN-CERT-2015-0254
dfn-cert: DFN-CERT-2015-0245
dfn-cert: DFN-CERT-2015-0118
dfn-cert: DFN-CERT-2015-0114
dfn-cert: DFN-CERT-2015-0083
dfn-cert: DFN-CERT-2015-0082
dfn-cert: DFN-CERT-2015-0081
dfn-cert: DFN-CERT-2015-0076
dfn-cert: DFN-CERT-2014-1717
dfn-cert: DFN-CERT-2014-1680
dfn-cert: DFN-CERT-2014-1632
dfn-cert: DFN-CERT-2014-1564
dfn-cert: DFN-CERT-2014-1542
dfn-cert: DFN-CERT-2014-1414
dfn-cert: DFN-CERT-2014-1366
dfn-cert: DFN-CERT-2014-1354

Medium (CVSS: 5.9)

NVT: SSL/TLS: Report Weak Cipher Suites

Product detection result
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↪802067)

Summary
This routine reports all weak SSL/TLS cipher suites accepted by a service.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
'Weak' cipher suites accepted by this service via the SSLv3 protocol:
TLS_RSA_WITH_RC4_128_SHA
'Weak' cipher suites accepted by this service via the TLSv1.0 protocol:
TLS_RSA_WITH_RC4_128_SHA

Impact
This could allow remote attackers to obtain sensitive information or have other, unspecified impacts.

Solution:

... continues on next page ...

... continued from previous page ...

Solution type: Mitigation
The configuration of this services should be changed so that it does not accept the listed weak cipher suites anymore. Please see the references for more resources supporting you with this task.

Affected Software/OS
All services providing an encrypted communication using weak SSL/TLS cipher suites.

Vulnerability Insight
These rules are applied for the evaluation of the cryptographic strength:
- RC4 is considered to be weak (CVE-2013-2566, CVE-2015-2808)
- Ciphers using 64 bit or less are considered to be vulnerable to brute force methods and therefore considered as weak (CVE-2015-4000)
- 1024 bit RSA authentication is considered to be insecure and therefore as weak
- Any cipher considered to be secure for only the next 10 years is considered as medium
- Any other cipher is considered as strong

Vulnerability Detection Method
Checks previous collected cipher suites.
NOTE: No severity for SMTP services with 'Opportunistic TLS' and weak cipher suites on port 25/tcp is reported. If too strong cipher suites are configured for this service the alternative would be to fall back to an even more insecure cleartext communication.
Details: `SSL/TLS: Report Weak Cipher Suites`
OID:1.3.6.1.4.1.25623.1.0.103440
Version used: `2026-06-03T07:18:10Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Report Supported Cipher Suites`
OID: 1.3.6.1.4.1.25623.1.0.802067

References
`cve:` CVE-2013-2566
`cve:` CVE-2015-2808
`cve:` CVE-2015-4000
`url:` https://configurator.tlsref.org/
`url:` https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
`url:` https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
`url:` https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
`url:` https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
`url:` https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
`url:` https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
`cert-bund:` WID-SEC-2026-0180
`cert-bund:` CB-K21/0067
`cert-bund:` CB-K19/0812
`cert-bund:` CB-K17/1750
`cert-bund:` CB-K16/1593
`cert-bund:` CB-K16/1552
`cert-bund:` CB-K16/1102
`cert-bund:` CB-K16/0617
`cert-bund:` CB-K16/0599
`cert-bund:` CB-K16/0168
`cert-bund:` CB-K16/0121
`cert-bund:` CB-K16/0090
`cert-bund:` CB-K16/0030
`cert-bund:` CB-K15/1751
`cert-bund:` CB-K15/1591
`cert-bund:` CB-K15/1550
`cert-bund:` CB-K15/1517
`cert-bund:` CB-K15/1514
`cert-bund:` CB-K15/1464
`cert-bund:` CB-K15/1442
`cert-bund:` CB-K15/1334
`cert-bund:` CB-K15/1269
`cert-bund:` CB-K15/1136
`cert-bund:` CB-K15/1090
`cert-bund:` CB-K15/1059
`cert-bund:` CB-K15/1022
`cert-bund:` CB-K15/1015

... continues on next page ...

... continued from previous page ...

cert-bund: CB-K15/0986
cert-bund: CB-K15/0964
cert-bund: CB-K15/0962
cert-bund: CB-K15/0932
cert-bund: CB-K15/0927
cert-bund: CB-K15/0926
cert-bund: CB-K15/0907
cert-bund: CB-K15/0901
cert-bund: CB-K15/0896
cert-bund: CB-K15/0889
cert-bund: CB-K15/0877
cert-bund: CB-K15/0850
cert-bund: CB-K15/0849
cert-bund: CB-K15/0834
cert-bund: CB-K15/0827
cert-bund: CB-K15/0802
cert-bund: CB-K15/0764
cert-bund: CB-K15/0733
cert-bund: CB-K15/0667
cert-bund: CB-K14/0935
cert-bund: CB-K13/0942
dfn-cert: DFN-CERT-2023-2939
dfn-cert: DFN-CERT-2021-0775
dfn-cert: DFN-CERT-2020-1561
dfn-cert: DFN-CERT-2020-1276
dfn-cert: DFN-CERT-2017-1821
dfn-cert: DFN-CERT-2016-1692
dfn-cert: DFN-CERT-2016-1648
dfn-cert: DFN-CERT-2016-1168
dfn-cert: DFN-CERT-2016-0665
dfn-cert: DFN-CERT-2016-0642
dfn-cert: DFN-CERT-2016-0184
dfn-cert: DFN-CERT-2016-0135
dfn-cert: DFN-CERT-2016-0101
dfn-cert: DFN-CERT-2016-0035
dfn-cert: DFN-CERT-2015-1853
dfn-cert: DFN-CERT-2015-1679
dfn-cert: DFN-CERT-2015-1632
dfn-cert: DFN-CERT-2015-1608
dfn-cert: DFN-CERT-2015-1542
dfn-cert: DFN-CERT-2015-1518
dfn-cert: DFN-CERT-2015-1406
dfn-cert: DFN-CERT-2015-1341
dfn-cert: DFN-CERT-2015-1194
dfn-cert: DFN-CERT-2015-1144
dfn-cert: DFN-CERT-2015-1113
dfn-cert: DFN-CERT-2015-1078
dfn-cert: DFN-CERT-2015-1067
dfn-cert: DFN-CERT-2015-1038
dfn-cert: DFN-CERT-2015-1016
dfn-cert: DFN-CERT-2015-1012
dfn-cert: DFN-CERT-2015-0980
dfn-cert: DFN-CERT-2015-0977
dfn-cert: DFN-CERT-2015-0976
dfn-cert: DFN-CERT-2015-0960
dfn-cert: DFN-CERT-2015-0956
dfn-cert: DFN-CERT-2015-0944
dfn-cert: DFN-CERT-2015-0937
dfn-cert: DFN-CERT-2015-0925
dfn-cert: DFN-CERT-2015-0884
dfn-cert: DFN-CERT-2015-0881
dfn-cert: DFN-CERT-2015-0879
dfn-cert: DFN-CERT-2015-0866
dfn-cert: DFN-CERT-2015-0844
dfn-cert: DFN-CERT-2015-0800
dfn-cert: DFN-CERT-2015-0737
dfn-cert: DFN-CERT-2015-0696
dfn-cert: DFN-CERT-2014-0977

Medium (CVSS: 5.3)

NVT: SSL/TLS: Server Certificate / Certificate in Chain with RSA keys less than 2048 bits

Summary
The remote SSL/TLS server certificate and/or any of the certificates in the certificate chain is using a RSA key with less than 2048 bits.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The remote SSL/TLS server is using the following certificate(s) with a RSA key w
↪ith less than 2048 bits (public-key-size:public-key-algorithm:serial:issuer):
1024:RSA:00FAF93A4C7FB6B9CC:1.2.840.113549.1.9.1=#726F6F74407562756E74753830342D
↪626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office for C
↪omplication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is no su
↪ch thing outside US,C=XX (Server certificate)
```

Impact
Using certificates with weak RSA key size can lead to unauthorized exposure of sensitive information.

Solution:
Solution type: Mitigation
Replace the certificate with a stronger key and reissue the certificates it signed.

Vulnerability Insight
SSL/TLS certificates using RSA keys with less than 2048 bits are considered unsafe.

Vulnerability Detection Method
Checks the RSA keys size of the server certificate and all certificates in chain for a size $<$ 2048 bit.
Details: `SSL/TLS: Server Certificate / Certificate in Chain with RSA keys less than 2048.`
`↪..`
OID:1.3.6.1.4.1.25623.1.0.150710
Version used: `2021-12-10T12:48:00Z`

References
`url:` https://www.cabforum.org/wp-content/uploads/Baseline_Requirements_V1.pdf

Medium (CVSS: 5.0)

NVT: SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094)

Summary
The remote SSL/TLS service is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
```
The following indicates that the remote SSL/TLS service is affected:
Protocol Version | Successful re-done SSL/TLS handshakes (Renegotiation) over an
↪ existing / already established SSL/TLS connection
-------------------------------------------------------------------------------
↪-------------------------------------------------
TLSv1.0          | 10
```

Impact
The flaw might make it easier for remote attackers to cause a DoS (CPU consumption) by performing many renegotiations within a single connection.

Solution:
Solution type: VendorFix
Users should contact their vendors for specific patch information.
A general solution is to remove/disable renegotiation capabilities altogether from/in the affected SSL/TLS service.

Affected Software/OS
Every SSL/TLS service which does not properly restrict client-initiated renegotiation.

. . . continues on next page . . .

...continued from previous page ...

Vulnerability Insight
The flaw exists because the remote SSL/TLS service does not properly restrict client-initiated renegotiation within the SSL and TLS protocols.
Note: The referenced CVEs are affecting OpenSSL and Mozilla Network Security Services (NSS) but both are in a DISPUTED state with the following rationale:
> It can also be argued that it is the responsibility of server deployments, not a security library, to prevent or limit renegotiation when it is inappropriate within a specific environment.
Both CVEs are still kept in this VT as a reference to the origin of this flaw.

Vulnerability Detection Method
Checks if the remote service allows to re-do the same SSL/TLS handshake (Renegotiation) over an existing / already established SSL/TLS connection.
Details: SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094)
OID:1.3.6.1.4.1.25623.1.0.117761
Version used: 2026-03-13T05:54:58Z

References
cve: CVE-2011-1473
cve: CVE-2011-5094
url: https://web.archive.org/web/20211201133213/https://orchilles.com/ssl-renegotiation-dos/
url: https://mailarchive.ietf.org/arch/msg/tls/wdg46VE_jkYBbgJ5yE4P9nQ-8IU/
url: https://vincent.bernat.ch/en/blog/2011-ssl-dos-mitigation
url: https://www.openwall.com/lists/oss-security/2011/07/08/2
cert-bund: WID-SEC-2026-2904
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2024-1591
cert-bund: WID-SEC-2024-0796
cert-bund: WID-SEC-2023-1435
cert-bund: CB-K17/0980
cert-bund: CB-K17/0979
cert-bund: CB-K14/0772
cert-bund: CB-K13/0915
cert-bund: CB-K13/0462
dfn-cert: DFN-CERT-2025-0933
dfn-cert: DFN-CERT-2017-1013
dfn-cert: DFN-CERT-2017-1012
dfn-cert: DFN-CERT-2014-0809
dfn-cert: DFN-CERT-2013-1928
dfn-cert: DFN-CERT-2012-1112

Medium (CVSS: 5.0)

NVT: SSL/TLS: Certificate Expired

Product detection result
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Collect and Report Certificate Details (OID: 1.3.6.1.4.1.25
↪623.1.0.103692)

Summary
The remote server's SSL/TLS certificate has already expired.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
The certificate of the remote service expired on 2010-04-16 14:07:45.
Certificate details:
fingerprint (SHA-1) | ED093088706603BFD5DC237399B498DA2D4D31C6
fingerprint (SHA-256) | E7A7FA0D63E457C7C4A59B38B70849C6A70BDA6F830C7A
↪F1E32DEE436DE813CC
issued by | 1.2.840.113549.1.9.1=#726F6F74407562756E747538
↪30342D626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office
↪ for Complication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is
↪ no such thing outside US,C=XX
public key algorithm | RSA
public key size (bits) | 1024
serial | 00FAF93A4C7FB6B9CC
signature algorithm | sha1WithRSAEncryption

...continues on next page ...

...continued from previous page ...

```
subject                         | 1.2.840.113549.1.9.1=#726F6F74407562756E747538
↪30342D626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office
↪ for Complication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is
↪ no such thing outside US,C=XX
subject alternative names (SAN) | None
valid from                      | 2010-03-17 14:07:45 UTC
valid until                     | 2010-04-16 14:07:45 UTC
```

Solution:
Solution type: Mitigation
Replace the SSL/TLS certificate by a new one.

Vulnerability Insight
This script checks expiry dates of certificates associated with SSL/TLS-enabled services on the target and reports whether any have already expired.

Vulnerability Detection Method
Details: `SSL/TLS: Certificate Expired`
OID:1.3.6.1.4.1.25623.1.0.103955
Version used: `2026-03-13T05:54:58Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Collect and Report Certificate Details`
OID: 1.3.6.1.4.1.25623.1.0.103692

Medium (CVSS: 4.3)

NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection

Product detection result

```
cpe:/a:ietf:transport_layer_security:1.0
Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)
```

Summary
It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
The service is only providing the deprecated TLSv1.0 protocol and supports one o
↪r more ciphers. Those supported ciphers can be found in the 'SSL/TLS: Report S
↪upported Cipher Suites' (OID: 1.3.6.1.4.1.25623.1.0.802067) VT.
```

Impact
An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection.
Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.

Solution:
Solution type: Mitigation
It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols.
Please see the references for more resources supporting you with this task.

Affected Software/OS
- All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols
- CVE-2023-41928: Kiloview P1 4G and P2 4G Video Encoder
- CVE-2024-41270: Gorush v1.18.4
- CVE-2025-3200: Multiple products from Wiesemann & Theis

Vulnerability Insight
The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like:
- CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST)
- CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)

...continues on next page ...

...continued from previous page ...

Vulnerability Detection Method
Checks the used TLS protocols of the services provided by this system.
Details: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection
OID:1.3.6.1.4.1.25623.1.0.117274
Version used: 2026-06-03T07:18:10Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security:1.0
Method: SSL/TLS: Version Detection
OID: 1.3.6.1.4.1.25623.1.0.105782

References
cve: CVE-2011-3389
cve: CVE-2015-0204
cve: CVE-2023-41928
cve: CVE-2024-41270
cve: CVE-2025-3200
url: https://configurator.tlsref.org/
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
url: https://datatracker.ietf.org/doc/rfc8996/
url: https://vnhacker.blogspot.com/2011/09/beast.html
url: https://web.archive.org/web/20201108095603/https://censys.io/blog/freak
url: https://certvde.com/en/advisories/VDE-2025-031/
url: https://gist.github.com/nyxfqq/cfae38fada582a0f576d154be1aeb1fc
url: https://advisories.ncsc.nl/advisory?id=NCSC-2024-0273
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2023-1435
cert-bund: CB-K18/0799
cert-bund: CB-K16/1289
cert-bund: CB-K16/1096
cert-bund: CB-K15/1751
cert-bund: CB-K15/1266
cert-bund: CB-K15/0850
cert-bund: CB-K15/0764
cert-bund: CB-K15/0720
cert-bund: CB-K15/0548
cert-bund: CB-K15/0526
cert-bund: CB-K15/0509
cert-bund: CB-K15/0493
cert-bund: CB-K15/0384
cert-bund: CB-K15/0365
cert-bund: CB-K15/0364
cert-bund: CB-K15/0302
cert-bund: CB-K15/0192
cert-bund: CB-K15/0079
cert-bund: CB-K15/0016
cert-bund: CB-K14/1342
cert-bund: CB-K14/0231
cert-bund: CB-K13/0845
cert-bund: CB-K13/0796
cert-bund: CB-K13/0790
dfn-cert: DFN-CERT-2020-0177
dfn-cert: DFN-CERT-2020-0111
dfn-cert: DFN-CERT-2019-0068
dfn-cert: DFN-CERT-2018-1441
dfn-cert: DFN-CERT-2018-1408
dfn-cert: DFN-CERT-2016-1372
dfn-cert: DFN-CERT-2016-1164
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2015-1853
dfn-cert: DFN-CERT-2015-1332
dfn-cert: DFN-CERT-2015-0884
dfn-cert: DFN-CERT-2015-0800

...continues on next page ...

... continued from previous page ...

dfn-cert: DFN-CERT-2015-0758
dfn-cert: DFN-CERT-2015-0567
dfn-cert: DFN-CERT-2015-0544
dfn-cert: DFN-CERT-2015-0530
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0375
dfn-cert: DFN-CERT-2015-0374
dfn-cert: DFN-CERT-2015-0305
dfn-cert: DFN-CERT-2015-0199
dfn-cert: DFN-CERT-2015-0079
dfn-cert: DFN-CERT-2015-0021
dfn-cert: DFN-CERT-2014-1414
dfn-cert: DFN-CERT-2013-1847
dfn-cert: DFN-CERT-2013-1792
dfn-cert: DFN-CERT-2012-1979
dfn-cert: DFN-CERT-2012-1829
dfn-cert: DFN-CERT-2012-1530
dfn-cert: DFN-CERT-2012-1380
dfn-cert: DFN-CERT-2012-1377
dfn-cert: DFN-CERT-2012-1292
dfn-cert: DFN-CERT-2012-1214
dfn-cert: DFN-CERT-2012-1213
dfn-cert: DFN-CERT-2012-1180
dfn-cert: DFN-CERT-2012-1156
dfn-cert: DFN-CERT-2012-1155
dfn-cert: DFN-CERT-2012-1039
dfn-cert: DFN-CERT-2012-0956
dfn-cert: DFN-CERT-2012-0908
dfn-cert: DFN-CERT-2012-0868
dfn-cert: DFN-CERT-2012-0867
dfn-cert: DFN-CERT-2012-0848
dfn-cert: DFN-CERT-2012-0838
dfn-cert: DFN-CERT-2012-0776
dfn-cert: DFN-CERT-2012-0722
dfn-cert: DFN-CERT-2012-0638
dfn-cert: DFN-CERT-2012-0627
dfn-cert: DFN-CERT-2012-0451
dfn-cert: DFN-CERT-2012-0418
dfn-cert: DFN-CERT-2012-0354
dfn-cert: DFN-CERT-2012-0234
dfn-cert: DFN-CERT-2012-0221
dfn-cert: DFN-CERT-2012-0177
dfn-cert: DFN-CERT-2012-0170
dfn-cert: DFN-CERT-2012-0146
dfn-cert: DFN-CERT-2012-0142
dfn-cert: DFN-CERT-2012-0126
dfn-cert: DFN-CERT-2012-0123
dfn-cert: DFN-CERT-2012-0095
dfn-cert: DFN-CERT-2012-0051
dfn-cert: DFN-CERT-2012-0047
dfn-cert: DFN-CERT-2012-0021
dfn-cert: DFN-CERT-2011-1953
dfn-cert: DFN-CERT-2011-1946
dfn-cert: DFN-CERT-2011-1844
dfn-cert: DFN-CERT-2011-1826
dfn-cert: DFN-CERT-2011-1774
dfn-cert: DFN-CERT-2011-1743
dfn-cert: DFN-CERT-2011-1738
dfn-cert: DFN-CERT-2011-1706
dfn-cert: DFN-CERT-2011-1628
dfn-cert: DFN-CERT-2011-1627
dfn-cert: DFN-CERT-2011-1619
dfn-cert: DFN-CERT-2011-1482

Medium (CVSS: 4.0)

NVT: SSL/TLS: Diffie-Hellman Key Exchange Insufficient DH Group Strength Vulnerability

Summary

... continues on next page ...

... continued from previous page ...

The SSL/TLS service uses Diffie-Hellman groups with insufficient strength (key size < 2048).

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`Server Temporary Key Size: 1024 bits`

Impact
An attacker might be able to decrypt the SSL/TLS communication offline.

Solution:
Solution type: Workaround
- Deploy (Ephemeral) Elliptic-Curve Diffie-Hellman (ECDHE) or use a 2048-bit or stronger Diffie-Hellman group. Please see the references for more resources supporting you with this task.
- For Apache Web Servers: Beginning with version 2.4.7, mod_ssl will use DH parameters which include primes with lengths of more than 1024 bits.

Affected Software/OS
All services providing an encrypted communication using Diffie-Hellman groups with insufficient strength.

Vulnerability Insight
The Diffie-Hellman group are some big numbers that are used as base for the DH computations. They can be, and often are, fixed. The security of the final secret depends on the size of these parameters. It was found that 512 and 768 bits to be weak, 1024 bits to be breakable by really powerful attackers like governments.

Vulnerability Detection Method
Checks the DHE temporary public key size.
Details: `SSL/TLS: Diffie-Hellman Key Exchange Insufficient DH Group Strength Vulnerabili.`
`↪..`
OID:1.3.6.1.4.1.25623.1.0.106223
Version used: `2026-06-03T07:18:10Z`

References
url: https://weakdh.org
url: https://weakdh.org/sysadmin.html
url: https://configurator.tlsref.org/
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
url: https://httpd.apache.org/docs/2.4/mod/mod_ssl.html#sslcertificatefile

Medium (CVSS: 4.0)

NVT: SSL/TLS: Certificate Signed Using A Weak Signature Algorithm

Summary
The remote service is using a SSL/TLS certificate in the certificate chain that has been signed using a cryptographically weak hashing algorithm.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The following certificates are part of the certificate chain but using insecure
↪signature algorithms:
Subject:              1.2.840.113549.1.9.1=#726F74407562756E74753830342D626173
↪652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office for Complic
↪ation of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is no such thi
↪ng outside US,C=XX
Signature Algorithm:  sha1WithRSAEncryption
```

Solution:
Solution type: Mitigation

... continues on next page ...

... continued from previous page ...

Servers that use SSL/TLS certificates signed with a weak SHA-1, MD5, MD4 or MD2 hashing algorithm will need to obtain new SHA-2 signed SSL/TLS certificates to avoid web browser SSL/TLS certificate warnings.

Vulnerability Insight
The following hashing algorithms used for signing SSL/TLS certificates are considered cryptographically weak and not secure enough for ongoing use:
- Secure Hash Algorithm 1 (SHA-1)
- Message Digest 5 (MD5)
- Message Digest 4 (MD4)
- Message Digest 2 (MD2)
Beginning as late as January 2017 and as early as June 2016, browser developers such as Microsoft and Google will begin warning users when visiting web sites that use SHA-1 signed Secure Socket Layer (SSL) certificates.
NOTE: The script preference allows to set one or more custom SHA-1 fingerprints of CA certificates which are trusted by this routine. The fingerprints needs to be passed comma-separated and case-insensitive:
Fingerprint1
or
fingerprint1, Fingerprint2

Vulnerability Detection Method
Check which hashing algorithm was used to sign the remote SSL/TLS certificate.
Details: `SSL/TLS: Certificate Signed Using A Weak Signature Algorithm`
OID:1.3.6.1.4.1.25623.1.0.105880
Version used: `2021-10-15T11:13:32Z`

References
`url:` https://blog.mozilla.org/security/2014/09/23/phasing-out-certificates-with-sha-1-based-signature-algorithms/

[return to 192.168.153.133]

2.1.29 Low general/tcp

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary
The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 174459
Packet 2: 174569
```

Impact
A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:
Solution type: Mitigation
To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'
Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.
The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

Affected Software/OS
TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight

... continues on next page ...

... continued from previous page ...

The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: `TCP Timestamps Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: `2023-12-15T16:10:08Z`

References
url: https://datatracker.ietf.org/doc/html/rfc1323
url: https://datatracker.ietf.org/doc/html/rfc7323
url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152
url: https://www.fortiguard.com/psirt/FG-IR-16-090

[return to 192.168.153.133]

2.1.30 Low 22/tcp

Low (CVSS: 2.6)
NVT: Weak MAC Algorithm(s) Supported (SSH)

Product detection result
`cpe:/a:ietf:secure_shell_protocol`
`Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565`
`↪)`

Summary
The remote SSH server is configured to allow / support weak MAC algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The remote SSH server supports the following weak client-to-server MAC algorithm
↪(s):
hmac-md5
hmac-md5-96
hmac-sha1-96
umac-64@openssh.com
The remote SSH server supports the following weak server-to-client MAC algorithm
↪(s):
hmac-md5
hmac-md5-96
hmac-sha1-96
umac-64@openssh.com
```

Solution:
Solution type: Mitigation
Disable the reported weak MAC algorithm(s).

Vulnerability Detection Method
Checks the supported MAC algorithms (client-to-server and server-to-client) of the remote SSH server.
Currently weak MAC algorithms are defined as the following:
- MD5 based algorithms
- 96-bit based algorithms
- 64-bit based algorithms
- 'none' algorithm
Details: `Weak MAC Algorithm(s) Supported (SSH)`
OID:1.3.6.1.4.1.25623.1.0.105610
Version used: `2024-06-14T05:05:48Z`

Product Detection Result
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`

... continues on next page ...

... continued from previous page ...

OID: 1.3.6.1.4.1.25623.1.0.105565

References
url: https://www.rfc-editor.org/rfc/rfc6668
url: https://www.rfc-editor.org/rfc/rfc4253#section-6.4

[return to 192.168.153.133]

2.1.31 Low 25/tcp

Low (CVSS: 3.7)

NVT: SSL/TLS: 'DHE_EXPORT' MITM Security Bypass Vulnerability (LogJam)

Product detection result
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↪802067)

Summary
This host is accepting 'DHE_EXPORT' cipher suites and is prone to a man-in-the-middle (MITM) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
'DHE_EXPORT' cipher suites accepted by this service via the SSLv3 protocol:
TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA
TLS_DH_anon_EXPORT_WITH_DES40_CBC_SHA
TLS_DH_anon_EXPORT_WITH_RC4_40_MD5
'DHE_EXPORT' cipher suites accepted by this service via the TLSv1.0 protocol:
TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA
TLS_DH_anon_EXPORT_WITH_DES40_CBC_SHA
TLS_DH_anon_EXPORT_WITH_RC4_40_MD5

Impact
Successful exploitation will allow a man-in-the-middle attacker to downgrade the security of a TLS session to 512-bit export-grade cryptography, which is significantly weaker, allowing the attacker to more easily break the encryption and monitor or tamper with the encrypted stream.

Solution:
Solution type: VendorFix
- Remove support for 'DHE_EXPORT' cipher suites from the service. Please see the references for more resources supporting you with this task.
- If the service is using OpenSSL: Update to version 1.0.1n, 1.0.2b or later.

Affected Software/OS
- Hosts accepting 'DHE_EXPORT' cipher suites.
- OpenSSL versions prior to 1.0.1n and 1.0.2 prior to 1.0.2b.

Vulnerability Insight
Flaw is triggered when handling Diffie-Hellman key exchanges defined in the 'DHE_EXPORT' cipher suites.

Vulnerability Detection Method
Checks previous collected cipher suites.
Details: SSL/TLS: 'DHE_EXPORT' MITM Security Bypass Vulnerability (LogJam)
OID:1.3.6.1.4.1.25623.1.0.805188
Version used: 2026-06-03T07:18:10Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security
Method: SSL/TLS: Report Supported Cipher Suites
OID: 1.3.6.1.4.1.25623.1.0.802067

References

... continues on next page ...

... continued from previous page ...

cve: CVE-2015-4000
url: https://weakdh.org
url: https://weakdh.org/sysadmin.html
url: https://web.archive.org/web/20210122160144/http://www.securityfocus.com/bid/74733
url: https://weakdh.org/imperfect-forward-secrecy.pdf
url: https://openwall.com/lists/oss-security/2015/05/20/8
url: https://blog.cloudflare.com/logjam-the-latest-tls-vulnerability-explained
url: https://openssl-library.org/post/2015-05-20-logjam-freak-upcoming-changes/index.html
url: https://configurator.tlsref.org/
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
cert-bund: WID-SEC-2026-0180
cert-bund: CB-K21/0067
cert-bund: CB-K19/0812
cert-bund: CB-K16/1593
cert-bund: CB-K16/1552
cert-bund: CB-K16/0617
cert-bund: CB-K16/0599
cert-bund: CB-K16/0168
cert-bund: CB-K16/0121
cert-bund: CB-K16/0090
cert-bund: CB-K16/0030
cert-bund: CB-K15/1591
cert-bund: CB-K15/1550
cert-bund: CB-K15/1517
cert-bund: CB-K15/1464
cert-bund: CB-K15/1442
cert-bund: CB-K15/1334
cert-bund: CB-K15/1269
cert-bund: CB-K15/1136
cert-bund: CB-K15/1090
cert-bund: CB-K15/1059
cert-bund: CB-K15/1022
cert-bund: CB-K15/1015
cert-bund: CB-K15/0964
cert-bund: CB-K15/0932
cert-bund: CB-K15/0927
cert-bund: CB-K15/0926
cert-bund: CB-K15/0907
cert-bund: CB-K15/0901
cert-bund: CB-K15/0896
cert-bund: CB-K15/0877
cert-bund: CB-K15/0834
cert-bund: CB-K15/0802
cert-bund: CB-K15/0733
dfn-cert: DFN-CERT-2023-2939
dfn-cert: DFN-CERT-2021-0775
dfn-cert: DFN-CERT-2020-1561
dfn-cert: DFN-CERT-2020-1276
dfn-cert: DFN-CERT-2016-1692
dfn-cert: DFN-CERT-2016-1648
dfn-cert: DFN-CERT-2016-0665
dfn-cert: DFN-CERT-2016-0642
dfn-cert: DFN-CERT-2016-0184
dfn-cert: DFN-CERT-2016-0135
dfn-cert: DFN-CERT-2016-0101
dfn-cert: DFN-CERT-2016-0035
dfn-cert: DFN-CERT-2015-1679
dfn-cert: DFN-CERT-2015-1632
dfn-cert: DFN-CERT-2015-1608
dfn-cert: DFN-CERT-2015-1542
dfn-cert: DFN-CERT-2015-1518
dfn-cert: DFN-CERT-2015-1406
dfn-cert: DFN-CERT-2015-1341
dfn-cert: DFN-CERT-2015-1194

... continues on next page ...

... continued from previous page ...

dfn-cert: DFN-CERT-2015-1144
dfn-cert: DFN-CERT-2015-1113
dfn-cert: DFN-CERT-2015-1078
dfn-cert: DFN-CERT-2015-1067
dfn-cert: DFN-CERT-2015-1016
dfn-cert: DFN-CERT-2015-0980
dfn-cert: DFN-CERT-2015-0977
dfn-cert: DFN-CERT-2015-0976
dfn-cert: DFN-CERT-2015-0960
dfn-cert: DFN-CERT-2015-0956
dfn-cert: DFN-CERT-2015-0944
dfn-cert: DFN-CERT-2015-0925
dfn-cert: DFN-CERT-2015-0879
dfn-cert: DFN-CERT-2015-0844
dfn-cert: DFN-CERT-2015-0737

Low (CVSS: 3.4)

NVT: SSL/TLS: SSLv3 Protocol CBC Cipher Suites Information Disclosure Vulnerability (POODLE)

Product detection result
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↪802067)

Summary
This host is prone to an information disclosure vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
Successful exploitation will allow a man-in-the-middle attackers gain access to the plain text data stream.

Solution:
Solution type: Mitigation
Possible Mitigations are:
- Disable SSLv3
- Disable cipher suites supporting CBC cipher modes
- Enable TLS_FALLBACK_SCSV if the service is providing TLSv1.0+

Vulnerability Insight
The flaw is due to the block cipher padding not being deterministic and not covered by the Message Authentication Code

Vulnerability Detection Method
Evaluate previous collected information about this service.
Details: SSL/TLS: SSLv3 Protocol CBC Cipher Suites Information Disclosure Vulnerability .
↪..
OID:1.3.6.1.4.1.25623.1.0.802087
Version used: 2026-03-13T05:54:58Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security
Method: SSL/TLS: Report Supported Cipher Suites
OID: 1.3.6.1.4.1.25623.1.0.802067

References
cve: CVE-2014-3566
url: https://www.openssl.org/~bodo/ssl-poodle.pdf
url: http://www.securityfocus.com/bid/70574
url: https://www.imperialviolet.org/2014/10/14/poodle.html
url: https://www.dfranke.us/posts/2014-10-14-how-poodle-happened.html
url: http://googleonlinesecurity.blogspot.in/2014/10/this-poodle-bites-exploiting-ssl-30.html
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2025-1658

... continues on next page ...

... continued from previous page ...

cert-bund: WID-SEC-2023-0431
cert-bund: CB-K17/1198
cert-bund: CB-K17/1196
cert-bund: CB-K16/1828
cert-bund: CB-K16/1438
cert-bund: CB-K16/1384
cert-bund: CB-K16/1102
cert-bund: CB-K16/0599
cert-bund: CB-K16/0156
cert-bund: CB-K15/1514
cert-bund: CB-K15/1358
cert-bund: CB-K15/1021
cert-bund: CB-K15/0972
cert-bund: CB-K15/0637
cert-bund: CB-K15/0590
cert-bund: CB-K15/0525
cert-bund: CB-K15/0393
cert-bund: CB-K15/0384
cert-bund: CB-K15/0287
cert-bund: CB-K15/0252
cert-bund: CB-K15/0246
cert-bund: CB-K15/0237
cert-bund: CB-K15/0118
cert-bund: CB-K15/0110
cert-bund: CB-K15/0108
cert-bund: CB-K15/0080
cert-bund: CB-K15/0078
cert-bund: CB-K15/0077
cert-bund: CB-K15/0075
cert-bund: CB-K14/1617
cert-bund: CB-K14/1581
cert-bund: CB-K14/1537
cert-bund: CB-K14/1479
cert-bund: CB-K14/1458
cert-bund: CB-K14/1342
cert-bund: CB-K14/1314
cert-bund: CB-K14/1313
cert-bund: CB-K14/1311
cert-bund: CB-K14/1304
cert-bund: CB-K14/1296
dfn-cert: DFN-CERT-2017-1238
dfn-cert: DFN-CERT-2017-1236
dfn-cert: DFN-CERT-2016-1929
dfn-cert: DFN-CERT-2016-1527
dfn-cert: DFN-CERT-2016-1468
dfn-cert: DFN-CERT-2016-1168
dfn-cert: DFN-CERT-2016-0884
dfn-cert: DFN-CERT-2016-0642
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2016-0171
dfn-cert: DFN-CERT-2015-1431
dfn-cert: DFN-CERT-2015-1075
dfn-cert: DFN-CERT-2015-1026
dfn-cert: DFN-CERT-2015-0664
dfn-cert: DFN-CERT-2015-0548
dfn-cert: DFN-CERT-2015-0404
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0259
dfn-cert: DFN-CERT-2015-0254
dfn-cert: DFN-CERT-2015-0245
dfn-cert: DFN-CERT-2015-0118
dfn-cert: DFN-CERT-2015-0114
dfn-cert: DFN-CERT-2015-0083
dfn-cert: DFN-CERT-2015-0082
dfn-cert: DFN-CERT-2015-0081
dfn-cert: DFN-CERT-2015-0076
dfn-cert: DFN-CERT-2014-1717
dfn-cert: DFN-CERT-2014-1680
dfn-cert: DFN-CERT-2014-1632
dfn-cert: DFN-CERT-2014-1564
dfn-cert: DFN-CERT-2014-1542
dfn-cert: DFN-CERT-2014-1414

... continues on next page ...

... continued from previous page ...

dfn-cert: DFN-CERT-2014-1366
dfn-cert: DFN-CERT-2014-1354

[return to 192.168.153.133]

2.1.32 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: ICMP Timestamp Reply Information Disclosure
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: 2025-01-21T05:37:33Z

References
cve: CVE-1999-0524
url: https://datatracker.ietf.org/doc/html/rfc792
url: https://datatracker.ietf.org/doc/html/rfc2780
cert-bund: CB-K15/1514
cert-bund: CB-K14/0632
dfn-cert: DFN-CERT-2014-0658

[return to 192.168.153.133]

2.1.33 Low 5432/tcp

Low (CVSS: 3.4)

NVT: SSL/TLS: SSLv3 Protocol CBC Cipher Suites Information Disclosure Vulnerability (POODLE)

Product detection result
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.

... continues on next page ...

... continued from previous page ...

↪802067)

Summary
This host is prone to an information disclosure vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
Vulnerability was detected according to the Vulnerability Detection Method.

Impact
Successful exploitation will allow a man-in-the-middle attackers gain access to the plain text data stream.

Solution:
Solution type: Mitigation
Possible Mitigations are:
- Disable SSLv3
- Disable cipher suites supporting CBC cipher modes
- Enable TLS_FALLBACK_SCSV if the service is providing TLSv1.0+

Vulnerability Insight
The flaw is due to the block cipher padding not being deterministic and not covered by the Message Authentication Code

Vulnerability Detection Method
Evaluate previous collected information about this service.
Details: SSL/TLS: SSLv3 Protocol CBC Cipher Suites Information Disclosure Vulnerability .
↪..
OID:1.3.6.1.4.1.25623.1.0.802087
Version used: 2026-03-13T05:54:58Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security
Method: SSL/TLS: Report Supported Cipher Suites
OID: 1.3.6.1.4.1.25623.1.0.802067

References
cve: CVE-2014-3566
url: https://www.openssl.org/~bodo/ssl-poodle.pdf
url: http://www.securityfocus.com/bid/70574
url: https://www.imperialviolet.org/2014/10/14/poodle.html
url: https://www.dfranke.us/posts/2014-10-14-how-poodle-happened.html
url: http://googleonlinesecurity.blogspot.in/2014/10/this-poodle-bites-exploiting-ssl-30.html
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2025-1658
cert-bund: WID-SEC-2023-0431
cert-bund: CB-K17/1198
cert-bund: CB-K17/1196
cert-bund: CB-K16/1828
cert-bund: CB-K16/1438
cert-bund: CB-K16/1384
cert-bund: CB-K16/1102
cert-bund: CB-K16/0599
cert-bund: CB-K16/0156
cert-bund: CB-K15/1514
cert-bund: CB-K15/1358
cert-bund: CB-K15/1021
cert-bund: CB-K15/0972
cert-bund: CB-K15/0637
cert-bund: CB-K15/0590
cert-bund: CB-K15/0525
cert-bund: CB-K15/0393
cert-bund: CB-K15/0384
cert-bund: CB-K15/0287
cert-bund: CB-K15/0252
cert-bund: CB-K15/0246
cert-bund: CB-K15/0237
cert-bund: CB-K15/0118
cert-bund: CB-K15/0110
cert-bund: CB-K15/0108

... continues on next page ...

... continued from previous page ...

```
cert-bund: CB-K15/0080
cert-bund: CB-K15/0078
cert-bund: CB-K15/0077
cert-bund: CB-K15/0075
cert-bund: CB-K14/1617
cert-bund: CB-K14/1581
cert-bund: CB-K14/1537
cert-bund: CB-K14/1479
cert-bund: CB-K14/1458
cert-bund: CB-K14/1342
cert-bund: CB-K14/1314
cert-bund: CB-K14/1313
cert-bund: CB-K14/1311
cert-bund: CB-K14/1304
cert-bund: CB-K14/1296
dfn-cert: DFN-CERT-2017-1238
dfn-cert: DFN-CERT-2017-1236
dfn-cert: DFN-CERT-2016-1929
dfn-cert: DFN-CERT-2016-1527
dfn-cert: DFN-CERT-2016-1468
dfn-cert: DFN-CERT-2016-1168
dfn-cert: DFN-CERT-2016-0884
dfn-cert: DFN-CERT-2016-0642
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2016-0171
dfn-cert: DFN-CERT-2015-1431
dfn-cert: DFN-CERT-2015-1075
dfn-cert: DFN-CERT-2015-1026
dfn-cert: DFN-CERT-2015-0664
dfn-cert: DFN-CERT-2015-0548
dfn-cert: DFN-CERT-2015-0404
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0259
dfn-cert: DFN-CERT-2015-0254
dfn-cert: DFN-CERT-2015-0245
dfn-cert: DFN-CERT-2015-0118
dfn-cert: DFN-CERT-2015-0114
dfn-cert: DFN-CERT-2015-0083
dfn-cert: DFN-CERT-2015-0082
dfn-cert: DFN-CERT-2015-0081
dfn-cert: DFN-CERT-2015-0076
dfn-cert: DFN-CERT-2014-1717
dfn-cert: DFN-CERT-2014-1680
dfn-cert: DFN-CERT-2014-1632
dfn-cert: DFN-CERT-2014-1564
dfn-cert: DFN-CERT-2014-1542
dfn-cert: DFN-CERT-2014-1414
dfn-cert: DFN-CERT-2014-1366
dfn-cert: DFN-CERT-2014-1354
```

[return to 192.168.153.133]