


④ Subsequences of strings

→ Using recursion:-



→ The base case will be as soon as $i \geq n$, we will push the string to our vector of string.

```
#include <bits/stdc++.h>

void getTheSubsequence(vector<string> &ans, string str, int i, int n, string s) {
    if(i >= n) {
        if(s != "") {
            ans.push_back(s);
            return;
        }
        getTheSubsequence(ans, str, i + 1, n, s);
        s = s + str[i];
        getTheSubsequence(ans, str, i + 1, n, s);
    }
}

vector<string> subsequences(string str){
    vector<string> ans;
    string s = "";
    int i = 0, n = str.length();
    getTheSubsequence(ans, str, i, n, s);

    return ans;
}
```

Time Complexity	$O(2^n)$
Space Complexity	$O(2^n)$

→ Bitwise

0 0 0	→ " "
0 0 1	→ "c"
0 1 0	→ "b"
0 1 1	→ "bc"
1 0 0	→ "a"
1 0 1	→ "ac"
1 1 0	→ "ab"
1 1 1	→ "abc"

```
#include <bits/stdc++.h>
vector<string> subsequences(string str) {
    vector<string> ans;
    int length = str.length();
    int endIndex = 1 << length;
    for (int i = 1; i < endIndex; i++) { → 2N
        int j = length - 1, no = i;
        string output = "";
        while (no) { → log 2N = N * log 2
            if ((no & 1)) {
                output = str[j] + output;
            }
            j--;
            no >>= 1;
        }
        if (output != "") {
            ans.push_back(output);
        }
    }
    return ans;
}
```

Time Complexity	$O(N * 2^N)$
Space Complexity	$O(N)$