HOW TO PUBLISH SHINY APP

or=input$color)

et_

ets

Install Required Packages   ?   ✕

Publishing content requires updated versions of the following packages: PKI,
packrat, rsconnect.

Do you want to install these packages now?

Yes   No

Publish to Server

Publish Files From: ~~████████deploy~~ **shiny**

☑ ® server.R
☑ ® ui.R

Publish From Account: Add New Account

☁ ~~████████~~ shinyapps.io

Title:

deploy shiny

The title must contain 3 - 64 alphanumeric characters.

FIRST TIME YOU FIND 'CONNECT ACCOUNT' →

☑ Launch browser

Publish   Cancel

Dashboard

Applications »

Account »

Profile

Tokens

Log out

GETTING STARTED

Hi! You must be new here...

Thanks for trying out shinyapps.io! You'll need to install the `rsconnect` R package to get started. The `rsconnect` package enables you to deploy and manage your Shiny applications directly from your R console. To get started, fire up your favorite IDE, and follow the directions below.

STEP 1 – INSTALL RSCONNECT

The `rsconnect` package can be installed directly from CRAN. To make sure you have the latest version run following code in your R console:

```
install.packages('rsconnect')
```

STEP 2 – AUTHORIZE ACCOUNT

The `rsconnect` package must be authorized to your account using a token and secret. To do this, click the copy button below and we'll copy the whole command you need to your clipboard. Just paste it into your console to authorize your account. Once you've entered the command successfully in R, that computer is now authorized to deploy applications to your shinyapps.io account.

```
rsconnect::setAccountInfo(name='unexcitingdev',
                          token='9BD8925FA3138E0281F9B18BACC07DB0',
                          secret='<SECRET>')
```

Show secret

Copy to clipboard

In the future, you can manage your tokens from the Tokens page the settings menu.

click Here

The `shinyapps` package must be authorized to your account using a token and secret. To do this, click the copy button below and we'll copy the whole command you need to your clipboard. Just paste it into your console to authorize your account. Once you've entered the command successfully in R, that computer is now authorized to deploy applications to your shinyapps.io account.

```
rsconnect::setAccountInfo(name='unexcitingdev',
                          token='██████████████████████████',
                          secret='<SECRET>')
```

Show Secret

Copy to clipboard

OK

The `shinyapps` package must be authorized to your account using a token and secret. To do this, click the copy button below and we'll copy the whole command you need to your clipboard. Just paste it into your console to authorize your account. Once you've entered the command successfully in R, that computer is now authorized to deploy applications to your shinyapps.io account.

```
rsconnect::setAccountInfo(name='unexcitingdev',
                          token=█████████████████
                          secret=██████████████████)
```

Hide secret

Copy to clipboard

OK

ctrl + c

Connect Account

Back

Connect ShinyApps.io Account

Go to your account on ShinyApps and log in.

Click your name, then choose **Tokens** from your account menu.

Click **Show** on the token you want to use, then **Show Secret** and **Copy to Clipboard.** Paste the result here:

```
rsconnect::setAccountInfo(name='aagarw30',
token='6902F2C2E6FF7E2D0F2E0112721C12D0',
secret='aGYCtQiysM/XRJd7hDE0OCpo2re1oRHqBKRueg
yR')
```

Need a ShinyApps.io account? Get started here.

1

ctrl +

∨

2

Connect Account   Cancel

Publish to Server

Publish Files From: ████████████████████████████

☑ ⓡ server.R
☑ ⓡ ui.R

Publish From Account: *Add New Account*

████████████████████████

████████████████████████

Title:

shinyTest

☑ Launch browser

The END ➜ **Publish**   Cancel