

Metanoia: when your agent becomes the buyer

Metanoia is a storefront for **agent-led subscription commerce**. You hand an AI agent a spending *mandate* instead of your card. It shops a marketplace of API and software subscriptions, and Juspay Hyperswitch settles the real payment in the sandbox. The agent proposes. Deterministic server code decides and pays. Written by Aayush Shrestha.

1 The industry, and why I picked it

Vertical: developer and SaaS subscriptions, bought by an agent. I picked this because it is where payments are about to change shape. The interesting question in US commerce is no longer how a human checks out. It is **what happens when software does the buying**. Subscriptions are the ideal first surface. They are recurring, priced, comparable, and machine-describable, with a price, a throughput number, an uptime number, and feature flags. That is exactly what an agent can reason over and a deterministic ranker can score.

Why the US market shaped the choices. US SaaS is card-first and mandate-friendly. The Hyperswitch US connectors (Stripe, Adyen, Braintree) support `setup_future_usage` and customer-acceptance mandates for off-session recurring, with no local-rail complexity such as UPI or iDEAL to model. So the integration centers on **cards plus a saved-card mandate**, which is the real US subscription pattern.

The thesis in one line:

*the model proposes, the server decides, Hyperswitch settles.
An LLM can research and recommend. It can never set a price or move money.*

Why an agent and a mandate together? Because an agent good enough to buy for you is also good enough to be talked into overspending. So authority never lives in the model.

2 The flows this industry needs




FIG 1. END-TO-END FLOW. GREEN IS DETERMINISTIC AUTHORITY; RED DASHED IS DEFERRED OR REFUSED, WHERE THE CARD IS NEVER TOUCHED.

A subscription business needs a chain of flows, and here is where I focused. First, **discovery and comparison**. Then **mandate-gated selection**. Then a **customer-initiated checkout (CIT)**. Then **proof that the thing works**. After that, **off-session recurring (MIT)**, plus **webhooks and reconciliation**, and finally **refunds and cancellation**. I built the spine from discovery through checkout end to end against the live sandbox. Recurring and MIT are designed and coded, but connector-blocked (see section 4).

3 What I built, what I deferred, and why

CAPABILITY	STATE	REASONING
Mandate, deterministic decide() , and SpendGuard	LIVE	A budget guarantee is only real if the server enforces it before any charge. An over-budget purchase is impossible through the app, and a refusal is a first-class, audited outcome.
Deterministic ranking over a 30-offer catalog (10 capabilities)	LIVE	Scoring is reproducible and auditable, computed on server-owned numbers rather than model opinion. Same inputs give the same ranking.
CIT checkout through Hyperswitch Unified Checkout (Fauxpay)	LIVE	A real sandbox payment settles. The card is entered in Hyperswitch's iframe and never touches my server.
Capability proof and a live payment record on the receipt	LIVE	After paying, an authenticated call returns 200, and I pull the real payment record from the Hyperswitch API, the same fields the dashboard shows. Nothing is faked.
Refunds, cancellation, resubscribe, and per-session isolation	LIVE	Refunds are server-side, idempotent, and owned-only, verified by retrieval. Each browser is its own tenant.
Deployed on Cloud Run, Cloud SQL, Vertex, and Secret Manager	LIVE	Hosted and sharable. Secrets live in Secret Manager, never in code.
Webhook receiver (HMAC verify, atomic settle)	LIVE	A valid signature returns 200; a bad or missing one returns 401. Verified on the deployed endpoint.
Off-session MIT and saved-card recurring	BLOCKED	Coded with <code>setup_future_usage</code> , <code>customer_acceptance</code> , and <code>recurring_details</code> . Routing the card to Stripe returns <code>UE_9000</code> , because the account needs raw-card API access, a Stripe-side grant. Fauxpay returns no reusable payment method. So MIT is proven in code, not yet in settlement.
Automatic renewal scheduler	DEFERRED	Renewal is manual and on demand today, and it re-runs SpendGuard. A background scheduler is the next step once MIT clears.
Webhook delivery and settlement	LIVE	Signed Hyperswitch <code>payment_succeeded</code> events reach an HMAC-verifying Vercel ingress, which forwards the untouched body to the Cloud Run receiver; Cloud Run verifies the HMAC again and settles the known payment in Cloud SQL (deduped by <code>event_id</code> , marked processed). Confirmed in the Vercel and Cloud Run logs and the events table. Direct <code>*.run.app</code> delivery does not land and the low-level transport reason is unconfirmed; unknown-payment events are retained, not dropped.
AP2 cryptographic mandate signatures, and x402	DEFERRED	The AP2 Intent and Cart shapes are modeled and enforced app-side. Signed JWT mandates are on the roadmap.

4 Integration and payment-method choices, with the reasoning

Unified Checkout, not raw card fields. The card is collected inside Hyperswitch's iframe, so the PAN and CVV never touch my server and I stay outside PCI scope. My server only ever holds the **publishable key** and a per-payment `client_secret`. The secret key stays server-side.

Connectors are processors, not payment methods. I never show Stripe, Adyen, or Fauxpay as a customer choice. The customer picks a *card*, and routing to a processor is a server decision. For US subscriptions the payment method that matters is a **card plus a saved-card mandate** for recurring.

Fauxpay for CIT, Stripe reserved for MIT. Fauxpay is a reliable dummy connector, so checkout always settles for a clean demo. Real off-session recurring needs a reusable `payment_method_id`, which only a real connector such as Stripe-test returns. That is why Stripe is wired for the mandate path.

Idempotency is a property of the payment id. I mint `pay_ = sha256(customer:plan:period)`, so a retry reuses the same intent instead of charging twice. A duplicate-id error self-heals: it reuses a live intent, or mints a fresh id for a dead one. Confirming twice records *one* subscription.

Webhooks: verify, then settle atomically. I check the raw-body HMAC (SHA-512/256, timing-safe), then run one DB transaction: dedupe by `event_id`, settle, upsert the subscription, and issue the credential. Unknown-payment events are retained, never dropped, so out-of-order delivery stays safe.

US subscription integration is Unified Checkout for cards, off-session mandates for recurring, stable-id idempotency, and signed webhooks as the source of truth.




FIG 2. THE AUTHORITY BOUNDARY. A PROPOSAL IS THE ONLY THING THAT CROSSES FROM MODEL TO SERVER, AND MONEY ONLY CROSSES FROM SERVER TO HYPERSWITCH.

5 How the prototype fits together, end to end




FIG 3. THE CUSTOMER-INITIATED PAYMENT SEQUENCE. SPENDGUARD RUNS AGAIN ON THE SERVER BEFORE HYPERSWITCH IS EVER CALLED.

The stack. Next.js 16 (App Router) runs on **Cloud Run**. Gemini 3.1 Pro and 2.5 Flash run on **Vertex AI** through the AI SDK tool loop. **Cloud SQL** Postgres is reached through the IAM connector, with no public IP. Secrets live in **Secret Manager**. Juspay **Hyperswitch** settles in the sandbox. A dual-backend Store (in-memory for dev and tests, Postgres in production) makes correctness a database property: an idempotent `payment_id` primary key, one credential per plan, and webhook `event_id` dedupe.

Safety and trust. Untrusted input, meaning the request and public GitHub metadata, is wrapped and labeled “data, not instructions.” The agent has no payment tool. The GitHub fetch is SSRF-guarded and only accepts `github.com/owner/repo`. Preference memory lives in a separate, consent-gated schema, never mixed with payments.

If a reviewer trusts one thing, trust this: the number that gets charged is computed by deterministic, unit-tested server code, on data the model never authored.

How I would finish it. First, get raw-card API access on the Stripe test account, or self-host Hyperswitch, to unblock the reusable `payment_method_id` and prove off-session MIT. Second, add the renewal scheduler on top of the already-tested, pending-first, idempotent renewal path, now that the webhook settlement loop is closed. Third, sign the AP2 Intent and Cart mandates.

91 tests green. Type-check and lint clean. A real sandbox payment completes end to end on the live URL.

APPENDIX

Hand-written notes

FROM MY IPAD, WHILE BUILDING METANOIA

The next pages are the raw study and design notes I sketched on my iPad as I worked through the Hyperswitch integration, the mandate model, and the propose-versus-decide split. They are unedited, and included to show how the architecture actually came together.

Aayush Shrestha · Metanoia · Juspay Hyperswitch prototype

Agents Subscription → JusPay (Hyperswitch Sandbox)

Comparing -
Cancel / auto renew -
Profile / type -

AI agent
→ Buys for you
mathematical mandate

AI driven commerce
Forward deployed PM (Build bridges)
↳ clients / core / Scouts

30 years online payment
→ AI shopping for you x402 → visa/mastercard
→ Human psychology (Agent Payment Role)
AP2 → Angus pay

Corporate card
→ instead of spending
→ it manages well

Budget / Handle
↳ No. opensource version
Empty spot in the MAP

300 m transaction of India / Day

Open source - Hyperswitch
↳ integrate once
→ Figure out the protocol
→ Adaptor
→ smart Routing
↳ per transaction (Aiden / Stripe)

→ fail over
↳ auto retries (Backup processing) M's recovered

Payment Intent, your server
Client secret
CC → server? NOX
Browser talk to payment proc
Secret key (NO Database)
Auth vs. Capture
↓
\$50? check
↓
Take money out
mandate →
CIT - Human in loop

MIT - merchant auto renewals
Web hooks: Hyperswitch → URL → web hook with signature (auth)

Idempotency: Tag attached to a request (Re-try of transaction)
Take Dropped network connection

HTTP 402

x402
↳ AI agent
↓
402 code w/ price

AP2:

intent mandate
↓
cart mandate

Pays
HTTP 200 / unlock service

Hyperswitch

↳ no crypto
↳ fiat rails

99% business uses

Execution / DEMO

Next.js

Public https / vercel

↳ secure web hooks

Reuse AI SDK

Hyperswitch mandate sandbox
HYPERLOADER SDK

Act 1: Grant via AP2
Act 2: Shops / reason / buys
Act 3: Assemble if over budget

CIT → you approve

MIT → merchant auto

Hyperswitch takes Backup processing

AI handles

Recruiter? →
Standard retail →?

walk in AP2 protocol

Deep grasps web hook discipline

Agents are becoming customer

- shift is coming

V1 Metanoia Recap

Autonomous

line to cross?

Raw unfiltered CC

→ Security Nightmare (Makes up API)
→ (Prompt injection failure)
→ (loop hole (keep buying))

Tuning of mind

Machine checkable budget

MANDATE

Agent loop
Spend guard vault
Juspay Hyperswitch
Drizzle DB schema

Why not Physical goods?

→ safely execute financial

(Return) Customer problem

→ Developer API

(Digital)
(Recurring)
(Definable)
(Priced well)

Machine

Describeable

Model proposes →
Server Decides →

Model

Research
Read
Recommendation

Consultant

can't buy cheque

Server

Authority
Math
Payment Orch

Has access

Mandate: Homepage

Up to 5 project URLs

Public metadata

Not for private Repo


CI/CD & Unit Test

AST parsing
(agent has no access to payment orch level.)

abstract Syntax Tree

Code level
Air Gaped

Dependencies
import to enforce security
Boundaries



AI SDK

while loop

3 Tools access

list services → it finds

Check mandate → communicate / check

Recommend →

↓

JSON proposal

4 Scouts

- Price / Operating Cost
- Value
- Quality
- Market Signal

How do you Rank?

Spend Guard?

CIT

→ customer initiated

→ Receipt screen

2.5 flash 4 Scouts
in parallel

Market Search Scout → Google Search Tool

Research
KYC →
Merchant ID →
Prevent agent from these recom

Onboarded
Payment
Connector?

Deterministic Ranking Phase

Server approved Guest list

Math > Opinion

Fit	35 %
price	30 %
reliability	20 %
throughput	15 %

→ Gives the services a score ranking

Contextual Constraint

Prompt Injection

- ↳ fails to steal money
- ↳ AI might be confused

Catalog prices

Server extract ID from JSON

Go to Catalog & extract price

Idempotency

SHA-256 Algo

hash → 30 char Alpha numerical ID

Built in self healing

AGOL payment error

Bitwise comparison for mismatch

Success - Record to DB
API to User
SHA256 to user

NO → external vendor
Authenticated sandbox mock
Just a prototype

Interview Arsenal

5min framing

budget not card
model propose
server decides
hyperswitch settles

Retrieve Don't Retrain

Q&A over spending
→ Spend guard (AST test)

Show constraints

re-run Over budget

Spend Guard Denied

Serverside
NO API called

NO Fake product

Show Receipts - internal mock
not real vendor

No live Yet! CI/MTI

→ Double change
→ 30 char string
SHA-256
HGOL error

→ web hook, raw buffer, SHA512 sig / AI don't touch money / Memory?

18 Fixed API

Hyperswitch looks for approved list of merchant

Server has final deterministic things

6x3

Curated sandbox

AI opinion out of scope

web sockets (Hard constraint)
(Do this thing)

Spending (Speed)

Constitution (Up time awake)

For agent (price)
Guardrail

Spend Guard

- market data
quote stream, Tickstream, realtime HUI
- news
breakdown cost, newfeed AI, SignalDesk
- vector search
Vector tile, retrieval ops, vector search
- Geocoding
lat, stream, global
- Compute
Inference edge, GPU Burst, Compute cluster pro
- Transcription
Scribe lite
Voxstream
Transcribe Ultra

- LLM Inference
- Transactional email
- Observability
- Authentication

Missed Cloudflare Auth

Spend Guard

→ Mandate (expired)?

→ item price

→ monthly cap checking
(Double spend)??

→ allow list

→ merchant

→ active subscription exceed?

Spend Guard

Deny (Before Touching Hyperswitch)

Hyperswitch (Fauxpay)

CIT - customer ini. checkout flow

MIT - merchant ini. user not present

Fauxpay lacks
Storing Card
↓
stripe test
PCI compliance

Where does Data lives

Drizzle
Cloud SQL (postgres)
Memory

IAM auth socket / no public IP

Schema separation

↳ Public

Financial data

Payment

Memory

AI Context

Preferences

Deterministic preference learning

lean → ranking map

Basic statistic to adjust choices

Unit Tests

Idempotency

Spend Guard

Service decides

Limitation

- Drizzle / GCP DB instance

- signed webhook in public URL

- pending first renewal audit
Server crash

AP2 → agent payment protocol

JSON - mandate

- base 64 URL
JWT token
verification

Metanoia V2 Recap / Pre Demo

Stripe rejected Raw Card
with UE_9000 so, off session renewal
Blocked

Secret manager
cloud Run
Vertex AI
PostgreSQL

Real estate agent
Find a house
You buy house

CIT Fauxpay (Pho-pay)
ORM Drizzle schemas (security)

IDOR Bugs - ?
→ Payment ID / patched (Browser session)

Ownership guard

Pull ID / verifies session cookies

Server Returns Not found

Honest ledger

↳ web hooks

↓ (async messages)

Incoming web hooks verifies

↓

shared secret $\equiv$ metanoia hash

HTTP is not landing in Cloud Run / for web hooks

Recurring MIT

Fauxpay

→ Single Use checkout

NO Saved

AP2 :-

Intent mandate (JSON boundaries)

↳ Spend Guard, Deterministic

Signet / JWT

Inspired.