




uOttawa



ELG 5142:
Ubiquitous Sensing / Smart Cities
Assignment 2

Dr. Burak Kantarci



GROUP 14

Table of Contents

1. Code:	3
2. Test Results:	5
1. RandomForest model results:.....	5
2. Adaboost model results:	6
3. Naïve Bayes model results:	7
4. Ensemble voting model results:.....	8
5. Ensemble weighted model results:.....	9
3. Accuracy Comparison:	10

Table of Figures

Figure 1 Classification report of Random Forest model	5
Figure 2 Confusion matrix of Random Forest model	5
Figure 3 Classification report of Adaboost model	6
Figure 4 Confusion matrix of Adaboost model	6
Figure 5 Classification report of Naive Bayes model	7
Figure 6 Confusion matrix of Naive Bayes model	7
Figure 7 Classification report of Ensemble voting model	8
Figure 8 Confusion matrix of Ensemble voting model	8
Figure 9 Train Accuracies and weights that are used to make Ensemble weighted model	9
Figure 10 Classification report of Ensemble weighted model	9
Figure 11 Confusion matrix of Ensemble weighted model	9
Figure 12 Bar plot to compare accuracies of different models	10

1. Code:

```
# Import Libraries
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import classification_report
import matplotlib.pyplot as plt
from sklearn.metrics import confusion_matrix, ConfusionMatrixDisplay, accuracy_score
from sklearn.ensemble import AdaBoostClassifier
from sklearn.naive_bayes import GaussianNB
import seaborn as sns # for data visualization
sns.reset_defaults()

# Loading the data
df = pd.read_csv('MCSDatasetNEXTCONLab.csv')
df.head()

# Splitting
X = df.iloc[:, :-1]
y = df.iloc[:, -1]
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
random_state=42, stratify=y)
print(X_train.shape)
print(X_test.shape)

# Random Forest model training
rf = RandomForestClassifier().fit(X_train, y_train)

# Adaboost model training
adaboost = AdaBoostClassifier(n_estimators=100, random_state=0).fit(X_train, y_train)

# Gaussian Naive Bayes
gnb = GaussianNB().fit(X_train, y_train)

# Function to show classification report and plot the confusion matrix
def report_and_confusion(y_test, y_pred):
    labels1 = ['Fake', 'Legitimate']
    print(classification_report(y_test, y_pred))
    cm = confusion_matrix(y_test, y_pred)
    disp = ConfusionMatrixDisplay(confusion_matrix=cm, display_labels=labels1)
    disp.plot()

    plt.show()

# Random Forest model testing
```

```

y_pred1 = rf.predict(X_test)
report_and_confusion(y_test, y_pred1)

# Adaboost model testing
y_pred2 = adaboost.predict(X_test)
report_and_confusion(y_test, y_pred2)

# Gaussian Naive testing
y_pred3 = gnb.predict(X_test)
report_and_confusion(y_test, y_pred3)

# Agrregator based on majority voting rule
y_pred4 = (y_pred1 + y_pred2 + y_pred3) >= 2
report_and_confusion(y_test, y_pred4)

# Agrregator based on weighted sum of classifiers decisions
pred1 = rf.predict(X_train)
acc1 = accuracy_score(y_train, pred1)
pred2 = adaboost.predict(X_train)
acc2 = accuracy_score(y_train, pred2)
pred3 = gnb.predict(X_train)
acc3 = accuracy_score(y_train, pred3)
wrf = acc1/(acc1 + acc2 + acc3)
wada = acc2/(acc1 + acc2 + acc3)
wgnb = acc3/(acc1 + acc2 + acc3)
y_pred5 = (y_pred1 * wrf + y_pred2 * wada + y_pred3 * wgnb) > 0.5
print("Train Accuracies: ", acc1, acc2, acc3)
print("Weights: ", wrf, wada, wgnb)
report_and_confusion(y_test, y_pred5)

# Calculating accuracies and plotting the bar plot
test_acc1 = accuracy_score(y_test, y_pred1)
test_acc2 = accuracy_score(y_test, y_pred2)
test_acc3 = accuracy_score(y_test, y_pred3)
test_acc4 = accuracy_score(y_test, y_pred4)
test_acc5 = accuracy_score(y_test, y_pred5)
test_acc_ls=[test_acc1,test_acc2,test_acc3,test_acc4,test_acc5]
print(test_acc_ls)
sns.set()
plt.figure(figsize=(10,5))
g=sns.barplot(x = ['RF', 'Adaboost', 'NB', 'Ensemble-vote', 'Ensemble-weighted'], y =
test_acc_ls)
g.set(ylim=(0.82, 1));
counter=0
for va in test_acc_ls:

```

```

v=str(round(va,4)*100)+' %'
g.text(counter,va,v, color='black', ha="center")
counter+=1
plt.show()

```

2. Test Results:

1. RandomForest model results:

	precision	recall	f1-score	support
0	1.00	0.97	0.98	379
1	0.99	1.00	1.00	2518
accuracy			1.00	2897
macro avg	1.00	0.98	0.99	2897
weighted avg	1.00	1.00	1.00	2897

Figure 1 Classification report of Random Forest model




Figure 2 Confusion matrix of Random Forest model

2. Adaboost model results:

	precision	recall	f1-score	support
0	0.88	0.81	0.84	379
1	0.97	0.98	0.98	2518
accuracy			0.96	2897
macro avg	0.93	0.90	0.91	2897
weighted avg	0.96	0.96	0.96	2897

Figure 3 Classification report of Adaboost model




Figure 4 Confusion matrix of Adaboost model

3. Naïve Bayes model results:

	precision	recall	f1-score	support
0	0.67	0.01	0.01	379
1	0.87	1.00	0.93	2518
accuracy			0.87	2897
macro avg	0.77	0.50	0.47	2897
weighted avg	0.84	0.87	0.81	2897

Figure 5 Classification report of Naive Bayes model




Figure 6 Confusion matrix of Naive Bayes model

4. Ensemble voting model results:

	precision	recall	f1-score	support
0	1.00	0.80	0.89	379
1	0.97	1.00	0.99	2518
accuracy			0.97	2897
macro avg	0.98	0.90	0.94	2897
weighted avg	0.97	0.97	0.97	2897

Figure 7 Classification report of Ensemble voting model




Figure 8 Confusion matrix of Ensemble voting model

5. Ensemble weighted model results:

Train Accuracies: 1.0 0.974885647708639 0.8691637179597825

Weights: 0.3516113370152334 0.34278084602779635 0.30560781695697037

Figure 9 Train Accuracies and weights that are used to make Ensemble weighted model

	precision	recall	f1-score	support
0	1.00	0.80	0.89	379
1	0.97	1.00	0.99	2518
accuracy			0.97	2897
macro avg	0.98	0.90	0.94	2897
weighted avg	0.97	0.97	0.97	2897

Figure 10 Classification report of Ensemble weighted model




Figure 11 Confusion matrix of Ensemble weighted model

3. Accuracy Comparison:




Figure 12 Bar plot to compare accuracies of different models

It's concluded that Random Forest model has the highest accuracy. Ensemble voting and Ensemble weighted models have the same accuracy as the accuracies of used base estimators are high. The accuracy of Ensemble models is near to the accuracy of Adaboost model as its accuracy is higher than Naïve Bayes accuracy and lower than Random Forest accuracy (median accuracy).