data

adam okulicz-kozaryn
adam.okulicz.kozaryn@gmail.com

this version: Wednesday 24th January, 2018 11:00

<u>outline</u>

ps2 Spring2016 comments

old ps2

regular (not gis) data gis data (has shapes, can make a map from it)

the 'join'

Example: New Jersey Home Values

data management takes time! value your time!

- producing maps and spatial statistics is fast
- omost time (i'd say 50-95%) is data management:
- · figuring out, cleaning, documenting, combining, etc
- so we start with data management
- ♦ but only about 20% of class is dat mgmt
- ·but it'll be about 80% of your time
- ♦ spend it on data you care about and will use in your career!

data

- ♦a lot of data here:
- ·http://geocommons.com/search.html
- · just search for what you are interested in, say 'road'
- ·and see https://www.policymap.com/maps

open govt, especially city data

- ojust few examples
- trend is that more and more local, state, fed opens up
- ♦ http://phlapi.com/ , https://data.cityofchicago.org/ , http://opencityapps.org/ ,

https://www.metrochicagodata.org/, http://www.opendataphilly.org/,

http://www.phila.gov/data/Pages/data.aspx

<u>outline</u>

ps2 Spring2016 comments

old ps2

regular (not gis) data

gis data (has shapes, can make a map from it)

the 'join

Example: New Jersey Home Values


general comments

- oplease no ms word! txt or pdf
- ⋄remember to specify u/a and num of obs
- ♦ need to email me *all* data you've used
- · (incl data you used for joining (toady's class))
- eg do not assume i have NJ countiessend me the whole thing! you can just zip the whole project
- folder
- or share good drive, dropbox.com etc
- .prj, etc)

 again, in journal you can ask me questions!

·if you just send me one .shp file, it won't run! (need .dbf

ps2 Spring2016 comments




healthy corner stores

- makes sense to label zipcodes; right proportions
- ♦ these aren't sq miles! sq ft or meters!
- · colors denote polygon sizes—so same info twice
- · better could map educ, inc, age, bmi, etc
- $\cdot \, \text{dots}$ could be little smaller or hollow so they overlap less
- ♦ make goog map and zoom in: show more detail

see environ: other businesses, pub transpo, sch, etc

- wonder about big healthy stores like wholefoods
- ·could dentote big ones with big dots
- ♦ usually may want to put year on a map
- · (at very least in metadata/journal)

Contaminations Sites in New Jersey 1992



contaminations

ps2 spring 2016 samples schoround

- perfect size and color for contaminated sites!
 doesn't overlap much but big enough to see
- · and grayish good for contamination
- ♦ informative— NYC and Philly the worst
- ⋄excellent idea to relate poverty to contamination∙there is lit linking them! so nice test! [also can do race]
- could do poverty at municipal or census tract levels
- use space better! NJ should be bigger like Philly stores mapthousands must be set off by commas in legend
- very good to match contaminations and poverty by year!
 "poverty status" –guess counts: better %

⋄ "poverty status" –guess counts; better %⋄ as in Philly map: zoom to Camden or Newark, have goog

contaminations

- ♦http://www.nytimes.com/interactive/2015/07/08/us/ census-race-map.html?_r=0
- ♦ in couple classes we'll be making online maps like this
- ♦ but already now you can do sth similar
- ·see footnote: census and socialexplorer.com: download data
- map in qgis and bring in background from googmaps
- · with openlayers plugin

<u>outline</u>

2 Spring2016 comments

old ps2

regular (not gis) data


gis data (has shapes,

the 'ioir

Example: New Jersey Home Values

old ps2 14/

ps2: open space



New Jersey Preserved Open Space

Legend
County Owned Open Space
State Owned Open Space
New Jersey Population

15/50

66083- 233890 233890 - 401696 401696 - 569503

569503 - 737309 737309 - 905116

ps2

- excellent idea for map—open space related to population
- great use of multiple layers
- great non-cluttered borders
- ⋄can use space better-portrait orientation, bigger NJ
- use commas for population
- say for which year it is
- opop den probably more meaningful
- on the other hand, we already see size from map
- · and so we can sort out density

old ps2 16/50

<u>outline</u>

s2 Spring2016 comments

old ps2

regular (not gis) data

gis data (has shapes, can make a map from it)

the 'ioin

Example: New Jersey Home Values

regular (not gis) data 17/50

files

- \diamond .xls(x)
- ♦.CSV
- ♦etc etc
- obut also .dbf! (part of shapefile)

regular (not gis) data 18/50

◊u/a: unit of analysis: what do you study?

what are data?

- ⋄u/a=# of obs=# of rows=sample size
- ·dataset has variables, which are the attributes of u/as
- ♦ say students: age; counties: water area
 ♦ if several layers: may have several u/as
- ♦ eg counties: #18; hospitals:#700
- dataset is a matrix/spreadsheet/2D object
- ♦ cols are vars, rows are obs♦ vars are characteristics of obs
- ♦ eg: edu, age, inc are vars
- and persons are obs—each row is a different person

storage type: numeric v string

- string format is characters, eg "Camden"
- ⋄numeric is a number, eg "22"
- · real (can have decimals), eg "22.01"
- ·integer (no decimals), eg "22"
- ⋄cannot do any math with strings; eg no thematic map
- ♦ it is a storage format, not data recognition
- storage type=how computer sees it, not you (human)
- · numbers can be stored as strings; strings cannot be stored as numbers (this is how computer sees it)

regular (not gis) data 20/50

storage type: numeric v string

- strings are safer; eg string "0821" made into a number results in 821", which is a mistake!
- · that's why many software packages, incl qgis often store numbers as strings
- · but then we often need to make them into numeric to do the math or mapping
- be careful about it, triple check, there are often problems and it's non-intuitive

regular (not gis) data 21/50

metadata

- ♦ it's data about data, ie documentation of data
- ♦ have it, use it
- · most basic and important: u/a, # of obs, source/url
- · all ps require you have these "metadata"
- but there's also other metadata
- · eg codebook and variable definitions
- ·it's important stuff for science:
- critical to have thorough and organized documentation of data

regular (not gis) data 22/50

<u>outline</u>

ps2 Spring2016 comments

old ps2

egular (not gis) data

gis data (has shapes, can make a map from it)

the 'join

Example: New Jersey Home Values

files

- ♦.shp
- ♦.kml

shapefiles

- probably most popular
- actually 3 (or more) files:
- ·.shp spatial data/coordinates ("main one" load this one)
- ·.dbf attribute data
- · .shx other stuff
- ·.prj projection
- · just manage it with gis soft, eg qgis

kml

- ♦ another popular format: google .kml
- ♦ this is Google Maps format

other gis data

- ♦there's much more
- we'll cover them on "as is" basis
- · if you bump into something else-let me know-we'll cover it

spatial and attribute data

- ⋄spatial=location: where ?
- ·coordinates, lat/lon
- ◇ attribute
- ·what, how much, when
- · these are characteristics of a location
- ·so the unit of analysis (U/A) is a location

raster and vector

- oraster (has resolution)
- · area covered by cells/pixels
- ·each cell/pixel have values/colors
- vector (no resolution): all real world features:
- · points (dots/nodes): airports, cities, trees
- ·lines (arcs): rivers, roads
- · polygons (areas): counties, cities

raster and vector

X

gis or spatial data

- opoint: X,Y
- ♦line: at least 2 X,Y
- ⋄polygon: at least 3 X,Y
- ♦ draw

layers

- data is organized by *layers* covering themes, eg roads, admin boundaries, etc etc
- show example/draw a picture

data, layers

- \diamond gis data is (always) location info (lat/long)+(usually) some regular data
- there always must be a data table with location info/shapes that underlies a map (and the data table usually contains some regular data, too)
- some regular data, too)

 omost of the time you want to superimpose different layers
 of gis data
- eg roads, cities, state boundaries, schools

 often you want to produce thematic (choropleth) maps
 thematic maps use different symbols/colors to show
 variation in data

<u>outline</u>

2 Spring2016 comments

old ps2

regular (not gis) data

gis data (has shapes, can make a map from it)

the 'join'

Example: New Jersey Home Values

the 'join' 34/!

anybody can load a shapefile and make a map dealing with real data, you'll typically have to do a join ♦ again, you'll spend most time on data management • even say over 90% of the time this is where the real value come from: • to bring different vars together to produce new insight ♦ if you just map one or few similar vars from same or similar data.

some real skills

it has probably been already done!
just goog: "what you study, map" and see images;
but combining creatively variety of vars:
there is no such map in the world!

the delimbet the control of the delimbet the delimbet the control of the delimbet the del

howto map it

- ♦ ok you have some data—it would likely have geo id:
- ·ISD name/code, county name/id, etc
- · codes/ids are great: unique! (as opposed to names)
- then google a shapefile that you can join with your data
- ⋄google "geo in you data, shapefile" eg "NJ counties, shapefile"
- ♦ and then join the two to produce a map
- ♦ beware of representativeness of your data for areas
- ·i spent months coding provinces from WVS
- then emailed them and found out that they are not representative...

the 'join' 36/50

the "merging" problems; some examples

- \diamond "Camden county" \neq "Camden"
- ⋄ "Congo" ≠ "Congo, Republic of"
- \diamond "Great Britain" \neq "United Kingdom"
- \diamond "Camden" \neq "CAMDEN"
- \diamond "Camden" \neq "Camden" (space is a character !)
- ♦ "08012" ≠ "8012"
- be very careful; check the tables to see if it merged right
- odoes it make sense? eg Camden richer than Cherry Hill?

the 'join'

<u>outline</u>

ps2 Spring2016 comments

old ps2

regular (not gis) data

gis data (has shapes, can make a map from it)

the 'ioin

Example: New Jersey Home Values

figuring things out

- you got housing prices for NJ counties
- and we've found matching gis data (shapefile) with NJ
 counties
- ♦ both have county variable so you can join
- ♦ but both keys/ids need to be coded in exactly the same way
- ·characters and storage!
- and you need to figure this out

```
Zillow housing prices

the "traditional" (non-gis) data in excel from
  http://www.zillow.com/research/data/
⋄i reposted on my website
  https://sites.google.com/site/adamokuliczkozaryn/gis_
  int/NJ-counties-Zillow-Home-Value-Index-TimeSeries.xls
and cleaned up: dropped first row, excessive columns,$ and
  ","; cnty names upcase, saved as csv (first sheet)
```

int/all_homes.csv
.note missing val for Morris; think abt missing data!

♦ https://sites.google.com/site/adamokuliczkozaryn/gis_

♦ nj counties data (same as alaways)

Example: New Jersey Home Values

https://docs.google.com/uc?id=

1xJDhcRCkgv7k4tNCa72Oog5bohV6dTB2&export=download

adjusting and cleaning up spreadsheets ⋄adjust ID: make counties uppercase

- · (or could drop 'County' from COUNTY LABEL variable)
- ♦ always clean up the spreadsheet:
- one row header (I dropped first row)
- $\cdot\,\text{make}$ col (variable) names brief: say $<\!5$ alphanumeric chars
- drop excessive columns you wont need, keep it clean
- ·important! leave only plain numbers!
- · drop all special chars from vals: "#" "\$" "," etc
- ♦ save as csv (just one sheet); reposted:
- int/all_homes.csv

https://sites.google.com/site/adamokuliczkozaryn/gis_

• note missing value! and save in project folder

Example: New Jersey Home Values

install MMQGIS (just once) if not there already

- ♦ Plugins-Manage and Install Plugins:
- ·Search: MMQGIS
- · and install
- onow we can use MMQGIS to join and fix the data!
- · [another way to do joins:

http://www.qgistutorials.com/en/docs/performing_table_joins.html]

MMQGIS: join; and text to float

- MMQGIS-Combine-Attributes Join From CSV File
- ♦ Input CSV: all_homes.csv
 ♦ CSV File Field: UPPER
- ♦ Join Layer: nj_counties
- ♦ Join Layer Attribute: COUNTY
- omake sure notfound.csv is where you want it
- L L C L L L LINEW IEDO
- check notfound.csv: header and 'NEW JERSEY': makes sense!
- shock the tables to see if it is ined right: he were carefull
- check the tables to see if it joined right; be very careful!
- ♦ MMQGIS-Modify-Text to Float (almost always need this!)
 ♦ highlight "Dec 2012" only (others are not clean: "\$",",")

missing value

- ⋄right click layer-Open Attribute Table
- onote that now MORRIS has 0 for "Dec 2012"
- this is incorrect!
- hit pen icon at top left: "Toggle Editing Mode"
- · and remove zero from that cell
- hit "Toggle Editing Mode" again and Save

and the thematic map

- onj_counties-Properties-Style and from drop-down: "Graduated"
- ♦ Column: "Dec 2012"
- ♦ Color ramp: can just leave Blues
- omany ways to classify [if time, discuss later]
- ousually good: 'natural breaks/jenks' say 3-7
- ♦ and hit "Classify" button
- ♦ and hit "OK" to see the map—viola!
- ⋄zoom in as much as needed

print a map: Print Composer ⋄ Project-New Print Composer

♦ NJ is tall: on the right "Composition" and do "portrait" ♦ left: blank icon "Add New Map" and draw a rectangle

oright: "Item properties" change scale to adjust zoom

- ♦ left: icon with arrows "Move Item Content" to adjust view
- ♦left: legend button "Add new legend"
- $\cdot \ normally \ legend \ requires \ lots \ of \ editing$
- · right: **uncheck** auto-update and beautify it: · drop items with minus sign
- · and edit by double clicking it
- ♦ top: on the left: Composer-Export as Image

don't trust anybody!

⋄remember, always be critical

http://www.trulia.com/home_prices/New_Jersey/

·but it is just tourists!

- triangulate your results: compare with other source
- · just goog picture, eg 'nj counties property values map'
- ♦ looks about right (they have some other definition of the prices, but correlation is important)
- ♦ show to others, ask for comments, present locally or at a conference
- ♦i mistakengly thought a lot of aclohol problems in Cape May

Example: New Jersey Home Values 47/50

tip1

- merging (joining) data is tedious and tricky
- ♦ be careful, double, triple check
- ⋄easy to make mistake

tip2: missing vals

- tricky! pay extra attention to it!
- ⋄sometimes qgis makes " to 0! esp MMQGIS: str to float
- sometimes qgis colors it yellow sometimes transparent:
- · (i guess: "=transparent, 'NULL'=yellow)
- to make it stand out can change color ramp
- · eg if NULL is white, make even number of classes on 2 color ramp (say BlueRed)

tip3: what if traditional data is in weird format

- ♦ same as with gis data
- ·if you see something else than .shp or .kml, email me!
- $\cdot \, \text{there}$ are many data formats, and we cannot cover them all
- · we'll do them if we bump into them—do let us know what you've found!