

Spring 2022

Q1: Sort (Arr, n) {

int countR, countG, countB = 0;
n+1 ← for (int i=0; i < n; i++) {

if (Arr[i] == 'R') {
countR++;

}
else if (Arr[i] == 'G') {
countG++;

}
else if (Arr[i] == 'B') {
countB++;


}
countR ← for (int i=0; i < countR; i++) {
Arr[i] = 'R';

}
countG ← for (int j=countR; j < countG; j++) {
Arr[j] = 'G';

}
countB ← for (int k=countG; k < countB; k++) {
Arr[k] = 'B';

}
 $O(n)$

① No 2:
BFS:



Source Node is '5'.

π	Nil	5	5	5	1
Node	5	1	2	4	3
d	0	1	1	1	2

b) When 117 executed for the 4th Time: Vertices in the Q are:

π	5	5	1
Node	2	4	3
d	1	1	2
C	G	G	G

a) Tree Edges


0 → 1
0 → 2
0 → 4
1 → 2

Cross Edges


1 → 2
2 → 3
4 → 5
3 → 1
3 → 4
3 → 5

Q No 3:

Dijkstra:



Line 10 executed 3 time.



Min Heap

a=0

b=3

c=1

d=2


e=6

f=5.4

g=4

h=8.6

L10 executed 5th time.



~~U = b~~

~~U.d = 3~~


~~U.π = 0~~

~~V = e~~


~~V.d = 6~~

~~V.π = b~~

(b)



F changed 2nd Time.




F changed for 3rd time.

(a)

$$\begin{aligned} U &= g \\ U \cdot \pi &= c \\ U \cdot d &= 4 \end{aligned}$$

$$\begin{aligned} V &= f \\ V \cdot \pi &= g \\ V \cdot d &= 4 \end{aligned}$$



(b)

π	Nil	A	A
Node	A	C	B
d	0	1	3

	π	Nil	a	a	a	b	g	c	f
	Node	a	b	c	d	e	f	g	h
		0	∞	∞	∞	∞	∞	∞	∞
(a)		0	3	1	2	∞	∞	∞	∞
(c)		0	3	1	2	∞	6	4	∞
(d)		0	3	1	2	∞	6	4	∞
(b)		0	3	1	2	6	5	4	∞
(g)		0	3	1	2	6	4	4	8
(f)		0	3	1	2	6	4	4	6
(e)		0	3	1	2	6	4	4	6

||—————||