

# Assignment 7

Joshua Graham

April 30, 2018

## **Abstract**

All Scripts used in the assignment can be found in the A9 folder, if needed.

## 0.1 Problem 1 Process

I had a lot of trouble with this assignment. The first hard part I tackled was figuring out how I was going to link name and index. I cannot remember where I saw it, it was probably online but I cannot find the reference I used. I figured out I could do it with:

Linking by index

```
1 #print(blogs.index("F-Measure"))
```

The second tackle I had was fixing numpredict to stop throwing errors on strings. After reading the error dialog, I found I just had to get rid of the section argument in the list inside of numpredict.py. Below is the changed function: **I believe all that changed was `vec2=data[i]`**. This previously had a ["title"] argument beside it.

Linking by index

```
1 def getdistances(data, vec1):
2     distancelist=[]
3
4     # Loop over every item in the dataset
5     for i in range(len(data)):
6         vec2=data[i]
7
8         # Add the distance and the index
9         distancelist.append((cosine(vec1, vec2), i))
10
11    # Sort by distance
12    distancelist.sort()
13    return distancelist
```

I implemented the cosine function manually instead of using one of the many math packages because it was a short method and I'm running off a Virtual Machine after my laptop died. I am not happy with this method, this is where I thought I could get rid of the title matching itself as a neighbor. If the distance on the bottom equaled zero, I believe the entries would all be the same. I assumed from this that the blogs would be the same entry, so I set the distance high. The function is shown below:

Linking by index

```
1
2 def cosine(v1, v2):
3     sumTop=0.0
4     for i in range(len(v1)):
5         sumTop += v1[i]*v2[i]
6     sumBottom1 = 0.0
7     sumBottom2 = 0.0
8     for i in range(len(v1)):
9         sumBottom1 += v1[i] ** 2
10        sumBottom2 += v2[i] ** 2
11    if(sumBottom1 * sumBottom2 == 0):
12        return 100
13    else:
14        return (sumTop)/((sumBottom1 * sumBottom2)**0.5)
```

Lastly, the code can be run with the run.py script, shown below. I went through several iterations of this trying to figure out what worked best. In the end I went for readability.

```

1 import clusters
2 import numpredict
3 def findNeigh(i, data, k):
4     testing = data[i]
5     neighbors = numpredict.knnestimate(data, testing, k)
6     for i in neighbors:
7         print(blogs[i[1]])
8
9
10 blogs, text, data = clusters.readfile("blogdata1.txt")
11 #print(blogs.index("F-Measure"))
12 #findNeigh(blogs.index("F-Measure"), data, 5)
13 for name in "F-Measure", "Web_Science_and_Digital_Libraries_Research_Group":
14     for k in 1, 2, 5, 10, 20:
15         print("Running", name, "against_k=", k)
16         findNeigh(blogs.index(name), data, k)
17         print("\n\n")

```

## 0.2 Problems with the code

The code for every example I found, found itself as a neighbor. I could not figure out why it was happening, I understand why in theory, but I could not figure out a way around it. Beyond this, both examples found the same nearest neighbor, other than themselves. I believe this is because the data is bad, not because the code is. If I had to do it again, I'd grab a new dataset.

## 0.3 Example Output

I've left the entire output in the file output.txt. However, I clipped F-Measure's neighbors with k=5 below.

Running F-Measure against k = 5

The World's First Internet Baby

CardrossManiac2

SPIN IT RECORDS Moncton 467A Main Street Moncton NB CANADA

F-Measure

Abu Everyday