

Interface Capability Brief

EDI 837P → QCare · Stakeholder overview · 2026-08-13

1. Executive summary

Directory-poll X12 837P professional claims, parse with PilotFish EDI TableData (837-Q1), and map each ST to QCare's 2100-byte outpatient (OT / B837) flat-file record. Demo only — golden-path fidelity against client samples, not full WTX/ITX parity.

2. Who this is for

- Source: operator dropping .txt / .edi / *.837 into input/inbound - Destinations: QCare text under output/qcare/; archived EDI under output/archive/; debug EDI XML under output/debug/ - Demo vs production: synthetic/client sample PHI; no SNIP gate; REPOSHDR claim numbering is a demo-stable header, not byte-identical to staged WTX

- Source: operator dropping .txt / .edi / *.837 into input/inbound
- Destinations: QCare text under output/qcare/; archived EDI under output/archive/; debug EDI XML under output/debug/
- Demo vs production: synthetic/client sample PHI; no SNIP gate; REPOSHDR claim numbering is a demo-stable header, not byte-identical to staged WTX

3. What the interface can do

Capabilities below are drawn from the working design and, when present, the published CapabilityStatement — not from aspirational roadmap items.

- Transport: Directory / File (DirectoryListener)
- Format: X12 837P (005010X222A1), TableData IG 837-Q1
- Identity: CLM01 patient control; ST02 transaction control
- Samples: samples/MCQRQ74837PS801.TXT, ...802.TXT, ...803.TXT (803 = STONE / SHARON / procedure 70487)

Integration highlights

FQCN sources: edi-278-prior-auth DirectoryListener + DirectoryTransport; edi-835-payment-integrity Split 835 format (IG swapped to 837-Q1). Image: pilotfish-eip:23R1.

Stage	Module	Notes
Listener	DirectoryListener	Poll \$\$EDI_INBOUND_DIRECTORY; Move → archive
Format	EDI TableData 837-Q1 + XPath fork //Transaction	UseInternalData=false; USE_ENHANCED_CONTEXT=true
Target	XPath Extract Claim Identity (after fork)	Source processors see raw EDI — do not extract on the source
Target	XML Formatting → FileWrite debug XML	Pretty-print before the XML write
Target	XSLT transform-837p-to-qcare.xslt method=text	No XML Formatting after the text map
Transport	DirectoryTransport	{CLM01}_qcare.txt

4. Honest boundaries (not claimed yet)

- Production hardening (HA, disaster recovery, full audit workflows) is outside this demo brief
- Anything not listed in §3 should be treated as future work unless confirmed in DESIGN.md

5. What you can verify in a walkthrough

Use these as checklist items when reviewing the demo with business stakeholders. They describe outcomes, not module names.

- Exercise route “1 - Map 837P To QCare” from the Web UI or documented smoke path
- Confirm outputs land in the documented folders / queues and appear in the Web UI status views

6. How it works (plain language)

7. Validation

EDI parses via TableData; outbound record length 2100; golden-path slices in automated tests. Not checked: SNIP 1–7; full 336-field WTX parity; REPOSHDR identity vs staged.

6. State & idempotency

File presence only (no SQL). Listener Moves inbound to archive after pick-up; QCare overwrite by basename.

8. Dual-write / side effects

Archive Move (listener) then debug XML + QCare. Accepted demo risk: archive can succeed while map/write fails.

3. Inbound contract

- Transport: Directory / File (DirectoryListener) - Format: X12 837P (005010X222A1), TableData IG 837-Q1 - Identity: CLM01 patient control; ST02 transaction control - Samples: samples/MCQRQ74837PS801.TXT, ...802.TXT, ...803.TXT (803 = STONE / SHARON / procedure 70487)

Routes in this interface

Each route is a configured PilotFish flow. Technical wiring appears in the Route Diagrams PDF; here is the stakeholder reading.

1 - Map 837P To QCare: runs steps such as Poll EDI 837P Files, Fork - XPath, Write QCare Record.

1 - Map 837P To QCare: runs steps such as Poll EDI 837P Files, Fork - XPath, Extract Claim Identity, Write QCare Record.

1 - Map 837P To QCare: runs steps such as Poll EDI 837P Files, Fork - XPath, Extract Claim Identity, Pretty-Print EDI XML.

1 - Map 837P To QCare: runs steps such as Poll EDI 837P Files, Fork - XPath, Extract Claim Identity, Pretty-Print EDI XML.

1 - Map 837P To QCare: runs steps such as Poll EDI 837P Files, Fork - XPath, Extract Claim Identity, Pretty-Print EDI XML.

1 - Map 837P To QCare: runs steps such as Poll EDI 837P Files, Fork - XPath, Extract Claim Identity, Pretty-Print EDI XML.

1 - Map 837P To QCare: runs steps such as Poll EDI 837P Files, Fork - XPath, Extract Claim Identity, Pretty-Print EDI XML.

7. Security & trust posture

- X12 SNIP validation is used where configured to reject bad EDI before downstream work

-
- Credentials and passwords in this package are demo-only — not production secrets
 - Risk noted in design: High — Not full WTX parity — Golden-path subset
 - Risk noted in design: Med — REPOSHDR claim numbering — Demo-stable header; tests exclude exact header match
 - Risk noted in design: Med — Archive-before-QCare — Accepted demo risk
 - Risk noted in design: Med — Multi-LX claims — Fork is //Transaction only; samples are 1 LX
 - Risk noted in design: Low — PHI in samples — Demo-only; do not publish

8. Seeing it work

- - Ports: EIP 8123, Web UI 8125 (no SQL) - LAN: <http://192.168.68.62:8125/> - Heap: 512M–2G - TableData: `../../../../EDI/TableData/x12` → `edi-tabledata`
- `docker compose --profile full up -d --build`
- | Web UI | <http://127.0.0.1:8125/> |
- | EIP | <http://127.0.0.1:8123/eip/> |

9. Related technical documents

- DESIGN.md — working engineering specification for this interface
- README.md — how to run, ports, and smoke commands
- This Capability Brief — shareable stakeholder summary (regenerate after design changes)

This document is generated from the interface sources listed above. If design and runtime diverge, believe the smoke-tested runtime and update DESIGN.md.