

Interface Capability Brief

SQL Server PilotFish XML Export · Stakeholder overview · 2026-08-13

1. Executive summary

Poll SQL Server PilotFishDemo.dbo.Captures on a timer and write the current result set as one pretty-printed XML file.
Demo-only: no business transform, no SNIP, no dual-write.

2. Who this is for

- Sources: SQL Server 2022 (PilotFishDemo.dbo.Captures) - Destinations: XML file captures_export.xml on the EIP output volume - Demo vs production: Demo only (SA login, encrypt=true;trustServerCertificate=true, overwrite the same file each poll)

- Sources: SQL Server 2022 (PilotFishDemo.dbo.Captures)
- Destinations: XML file captures_export.xml on the EIP output volume
- Demo vs production: Demo only (SA login, encrypt=true;trustServerCertificate=true, overwrite the same file each poll)

3. What the interface can do

Capabilities below are drawn from the working design and, when present, the published CapabilityStatement — not from aspirational roadmap items.

- Transport: Database Polling (SQL) listener, JDBC, every 15 seconds
- Format / envelope: SQL-XML (SelectCapturesSQL.xml) → XML result document (Execute into="records" as="Capture" + XMLOut)
- Identity fields: CaptureId (int, identity)
- Samples path: seed rows in sql/01_init.sql (1001–1003); Demo tab can insert more

Integration highlights

Stage	Module / mechanism	Notes
Listener	com.pilotfish.eip.modules.db.DatabaseSqlListener (Database Polling (SQL))	Docs: 26R1.11; runtime pilotfish-eip:23R1. PollingInterval=15, UseSingleOutputStream=true, InputFile=SelectCapturesSQL.xml. JDBC via \$\$\$sqlserver.*. Skeleton: edi-837-snip-sqlserver poll route.
Listener processors	none	Do not put XML Formatting here — listener-side has no effect on the file write (§1.4).
Router	com.pilotfish.eip.modules.routing.XPathRoutingModule (shown as Conditional Node Router in V2)	`count(//CAPTURE \
Target processors	com.pilotfish.eip.modules.transform.XMLFormattingProcessor	On the transport, before Directory File. Indent is hardcoded to 2 spaces.

Stage	Module / mechanism	Notes
Transports	com.pilotfish.eip.modules.file.DirectoryTransport	TargetDirectory=\$XML_OUTPUT_DIRECTORY, FileName=captures_export, AppendToFile=Overwrite. Skeleton: edi-999-ta1-ack-triage Directory File transport.

4. Honest boundaries (not claimed yet)

- None for this demo scope.

5. What you can verify in a walkthrough

Use these as checklist items when reviewing the demo with business stakeholders. They describe outcomes, not module names.

- Exercise route “1 - Export Captures to XML” from the Web UI or documented smoke path
- Confirm outputs land in the documented folders / queues and appear in the Web UI status views

6. How it works (plain language)

7. Validation

- What is checked: JDBC query must return well-formed XML or XML Formatting throws - What is NOT checked: SNIP, schema XSD, business rules - Does failure block outbound? (yes/no): yes — no file write if the processor throws

6. State & idempotency

- Status model: table Status is display-only (COMPLETE / PENDING). Poll does not claim or update rows. - When state advances: n/a — each poll re-exports the whole table - Dedup keys: CaptureId in SQL; file overwrite (last poll wins) - Retry / poison: none; failed poll logs in EIP. No kickout directory.

8. Dual-write / side effects

- Order of commits: SQL is read-only from EIP; Web UI inserts are a separate demo side effect - Compensation: none - Demo shortcuts (if any): SA password in compose; trust server cert; overwrite one file

3. Inbound contract

- Transport: Database Polling (SQL) listener, JDBC, every 15 seconds - Format / envelope: SQL-XML (SelectCapturesSQL.xml) → XML result document (Execute into="records" as="Capture" + XMLOut) - Identity fields: CaptureId (int, identity) - Samples path: seed rows in sql/01_init.sql (1001–1003); Demo tab can insert more

Routes in this interface

Each route is a configured PilotFish flow. Technical wiring appears in the Route Diagrams PDF; here is the stakeholder reading.

1 - Export Captures to XML: runs steps such as Poll Captures Table, Conditional Router, Pretty-Print XML, Write Captures XML.

7. Security & trust posture

- X12 SNIP validation is used where configured to reject bad EDI before downstream work
- Credentials and passwords in this package are demo-only — not production secrets
- Risk noted in design: High — SA login on the LAN port — Demo SQL is published on 14342
- Risk noted in design: Med — Overwrite semantics — Each poll replaces captures_export.xml

-
- Risk noted in design: Med — Docs 26R1.11 vs image 23R1 — Config tag names could drift
 - Risk noted in design: Low — Unbounded poll — 15s is light (one SELECT)

8. Seeing it work

- - Ports: EIP 8136, Web UI 8137, SQL Server 14342 - Volumes: ./output → /opt/pilotfish/output; ./sql into init container
- - Heap / special JVM: default G1, 256–1024M - Dependencies / cold start: SQL healthy → sql/01_init.sql → EIP. JDBC driver mssql-jdbc-12.8.1.jre11.jar in EIP image (same as csv-sftp-to-sql).
- - Local Web UI: http://127.0.0.1:8137/
- - EIP: http://127.0.0.1:8136/eip/
- - SQL Server: 127.0.0.1:14342 (sa / PilotFish_Demo1! · PilotFishDemo)
- docker compose --profile stage up -d --build
- docker compose --profile full up -d --build

9. Related technical documents

- DESIGN.md — working engineering specification for this interface
- README.md — how to run, ports, and smoke commands
- This Capability Brief — shareable stakeholder summary (regenerate after design changes)

This document is generated from the interface sources listed above. If design and runtime diverge, believe the smoke-tested runtime and update DESIGN.md.