

Facility Onboarding Plan — NHL Catholic Medical & IRL N Gainesville (Expense)

Implementation plan for adding two expanded-Expense facilities into MedReceivables / eiPlatform (Flat File to HL7 and Kickout Reports). Covers sample-format validation, H2 database updates, route 1 listeners (no new message path), strip/split config, and ADT/DFT mapping rules.

Scope: NHL – Catholic Medical Center (CLIENT CAT) and IRL N – HCA FL Gainesville Hospital (CLIENT GAN). Samples under *data/archive/Expanded expense/NHL-Catholic* and *.../IRL N-Gainesville* (plus facility workbooks).

1. Summary of the request

Add CAT and GAN to the **existing** Expense expanded-CDM intake path so the same PTH5 flat-file feed is picked up, converted to canonical XML in route 1, stripped/split via CLIENT_SPLITS + CLIENT_CODES, then ADT/DFT generated with the new mapping rules. **No separate upfront message/transform is needed** — sample files match peer Expanded Expense feeds.

SOFTWAREID decision: Request listed **513** for Catholic Medical, but 513 is already used by FPS / Central Lab (CLIENT CNL). **Use SOFTWAREID 524 for CAT** instead. IRL Gainesville keeps requested SOFTWAREID **523** (free).

2. Target database records (from request)

2.1 CLIENT_SPLITS (facility / partition registry)

Table columns in current H2 DB: SOFTWAREID, CLIENTNAME, PARTITION, CLIENT, FACILITY, FACILITY_CODE, DEFAULT_PERF_DR, ACCOUNT_NUM_ALPHA, DATE_RANGE, IS_DEFAULT. FILE_HEADER_FACILITY_NAME from the email is **not** a CLIENT_SPLITS column — it maps to route 1 listener attribute **FacilityNameShouldBe**.

Field	NHL Catholic Medical	IRL N Gainesville
SOFTWAREID	524 (assigned; was 513 in request)	523
CLIENTNAME	Catholic Medical	HCA FL Gainesville Hospital
FILE HEADER / FacilityNameShouldBe	Catholic Medical Center	HCA FL Gainesville Hospital
PARTITION	NHL	IRL
CLIENT	CAT	GAN
FACILITY	CAT	GAN
FACILITY_CODE	HK	PT
DEFAULT_PERF_DR	CP9	CN1
ACCOUNT_NUM_ALPHA	HK	PT
DATE_RANGE	20260611	20260505
IS_DEFAULT	1 (recommended)	1 (recommended)

NHL note: Exclude locations Monodock and Huggins (X.HH) from split/strip config when loading CLIENT_CODES / strip tables from the Catholic feed workbook.

2.2 CLIENT_CODES (split codes)

CLIENT_CODES columns: FACILITY, CODE, COMPARATOR, SOFTWARE_ID. These define how one input file forks into multiple related output sets in route 3. Source the location/code rows from the request workbooks (excluding Monodock / Huggins for NHL). Mirror recent Expense inserts (e.g. IRL GUX/CAX or NHL POT/FRK/PAT) for structure.

- Insert one CLIENT_SPLITS default row per facility (above).
- Insert CLIENT_CODES rows for each included split location for that SOFTWARE_ID.

- Optional / if used by strip logic: STRIP_LOCATIONS, STRIP_PERFORMING_SITES already has LC (LabCorp) globally; verify apply-list includes CAT/GAN.
- Preferred ops path already in eiConsole: route **88a – Add New Facility** + Excel *MedReceivables_NewFacilityInfo.xlsx* via format New Facility SQLXML.

3. Sample-file validation (Expanded Expanse — confirmed)

Compared Catholic (*PTH5.CMC..*) and Gainesville (*PTH5.GA.1.*) samples against peer Expanded Expanse files (Chippenhams *PTH5.CC.2.*, Henrico *PTH5.HR.2.*, Spotsylvania, TriCities, etc. under *Other expanded expanse samples*).

Check	New samples (CMC / GA)	Peer Expanded Expanse
Format	Fixed-width PTH5, CRLF, .txt	Same
Record types present	H, P, I, G, C, Q, D, T	Same set
Dominant record lengths	H=169, P=1641, I=550, C=546, G=331, Q=466	Identical modes on peers
Field alignment (H/P/I/C)	Facility header, account, admit/disch, CDM, NEW/ASB/CAM	Same column layout
File-name family	PTH5.CMC..MMDD... / PTH5.GA.1.MMDD...	PTH5.<site>.[n.]MMDD... (e.g. CC.2, HR.2)

Conclusion: Reuse the existing *Transform Flat File to XML-New-Expanse-Expanded-CDM* processor (*raw-flat-file-specification-expanded-cdm.xml*). Do **not** build a new FlatFileProcessor spec or a facility-specific “massage” path. Work remaining is wiring: listeners, ClientName allowlists, and DB splits — not a new parser.

- Sample H lines already match FacilityNameShouldBe targets: *Catholic Medical Center / HCA FL Gainesville Hospital*.
- Facility workbooks present beside samples: *MedReceivables_NewFacilityInfo_NHL Catholic Medical.xlsx* and *..._IRL N Gainesville.xlsx* (use with route 88a when loading splits/codes).
- NHL still excludes Monodock and Huggins (X.HH) when loading CLIENT_CODES / strip rows.

4. End-to-end flow (after DB + wiring)

Route	Purpose for new facilities
1 – Incoming Flat Files...	Listener + attribute stamp + existing Expanded-CDM → canonical XML
2 – Stripping and Tweaking	Loads CLIENT_SPLITS; resolves SoftwareID; strip rules incl. PerfSite LC
3 – Splitting Records by Facility	Uses CLIENT_SPLITS + CLIENT_CODES to fork output streams
3b – Generate HL7 Files	ADT (Generate ADT A04) + DFT (Generate DFT DPT P03) XSLTs

5. Route 1 work — listeners only (reuse Expanded-CDM)

SOFTWAREID is **not** set in route 1 — route 2 looks it up from CLIENT_SPLITS (Partition + Client). Route 1 only needs DirectoryListeners for the new file-name patterns, attribute stamps (PartitionName / ClientName / FacilityNameShouldBe), and the **existing** Expanded-CDM transform allowlist. No new massaging processors.

5.1 Copy-from templates

New facility	Best copy-from	Sample FileNameRestriction
NHL CAT	NHL POT / FRK / PAT (or PTH5.CC-style listener)	PTH5.CMC.* (ext: txt)
IRL GAN	IRL GUX / CAX (or PTH5.HR/CC-style listener)	PTH5.GA.* (ext: txt)

Peers already listening for Expanded Expanse PTH5 feeds include *PTH5.CC.**, *PTH5.HR.**, *PTH5.SAA.**, etc. **PTH5.CMC** and **PTH5.GA** have **zero** listeners today — add them.

5.2 Checklist per new client

- **Source listener:** Clone an Expanded Expanse PTH5 listener.
PollingDirectory=\$\$FLAT_FILE_INPUT_DIRECTORY; archive=\$\$FLAT_FILE_ARCHIVE_DIRECTORY;
FileExtensionRestriction=**txt**. FileNameRestriction: **PTH5.CMC.*** (CAT) and **PTH5.GA.*** (GAN).
- **Set Facility Name – {CLIENT}:** FacilityNameShouldBe = *Catholic Medical Center / HCA FL Gainesville Hospital*;
PartitionName=NHL|IRL; ClientName=CAT|GAN.
- **Target processors:** Add *Set Partition and Client Name-NHL-CAT* and *...-IRL-GAN* (ExecuteProcessor on PartitionName+ClientName → Partition/Client).
- **Expanded-CDM allowlist:** Add CAT and GAN to OGNL on *Transform Flat File to XML-New-Expanse-Expanded-CDM* (current allowlist has POT/FRK/PAT/GUX/CAX/... — not CAT/GAN). Keep them excluded from the legacy Flat File to XML processor.
- **Do not:** add a new FlatFileProcessor XML spec, CSV transform, or client-specific pre-canonical massage — layout already matches Expanded-CDM.

6. Route 2 / 3 work

- Route 2 already reads all CLIENT_SPLITS and XPath SoftwareID / DefaultPerfDr / DateRange — no SQL change if DB rows are correct.
- Add CAT and GAN to *Apply Stripping – SPECIFIC CLIENTS ONLY – Site Locations* OGNL so PerfSite kickouts (including strip **LC**) apply.
- Confirm strip location tables / secondary strip rows for excluded NHL locations (Monodock, Huggins X.HH).
- Route 3 split query uses partition + client; CAT/GAN rows must exist so SplitCount > 0 when expected.

7. ADT / DFT XSLT updates (route 3b)

Most rules already exist for peer Expanse facilities. Prefer copying the IRL softwareID / facility guard lists and NHL partition branches rather than inventing new logic.

Rule from request	Where it lives today	Action for CAT / GAN
PerfSite kickout — strip LC	STRIP_PERFORMING_SITES + route 2 site-location	Add CAT/GAN to Apply Stripping Site Locations list
PID marital status default U	ADT — IRL/FPS/GLF softwareID lists; NHL not for CAT	Add GAN software ID to marital-U; decide CAT
PV1-8 Attending (NPI/Name)	ADT — NHL uses 1st-charge ordering MD; IRL by facility	Copy partition=NHL; add GAN to IRL facility list
PV1-44/45 admit & discharge	ADT PV1.44; blank-admit also GLF-only in route 2	Verify inpatient path; clone GLF blank-admit if needed upstream
PV2-28 ARSA (blank admit → 1st charge)	ADT PV2.28	Reuse admit/first-charge once CAT/GAN are wired
Guarantor name blank → patient	ADT GT1 — global	No change expected

Rule from request	Where it lives today	Action for CAT / GAN
Subscriber name blank → patient	ADT IN1 — NHL empty-subscriber handling	CAT inherits NHL; confirm GAN vs IRL peers
Relationship blank → SE / CH / UN	ADT GT1/IN1 — partial IRL softwareID lists	Extend for GAN; decide NHL CAT

DFT template mainly carries charge/MUE logic; demographic/PV1 rules are predominantly in **Generate ADT A04 HL7/transform.xslt**. Still scan **Generate DFT DPT P03 HL7/transform.xslt** for any partition/client/softwareID allowlists that need CAT/GAN or the new IDs.

8. Suggested implementation sequence

- **0. SOFTWAREIDs locked:** CAT=524, GAN=523 (513 left with FPS CNL).
- **1. Samples validated** — Expanded Expanse match confirmed (section 3). Use FileNameRestriction **PTH5.CMC.*** / **PTH5.GA.***; load split/codes from the NewFacilityInfo workbooks beside the samples.
- **2. Database:** insert CLIENT_SPLITS + CLIENT_CODES (+ strip tables) via 88a Excel path or SQL; backup H2 first. Exclude Monodock / Huggins for NHL.
- **3. Route 1:** clone PTH5 Expanded Expanse listeners for CMC/GA; stamp CAT/GAN; add both to Expanded-CDM OGNL only (no new parser).
- **4. Route 2:** add CAT/GAN to PerfSite strip client list.
- **5. ADT/DFT XSLT:** extend guard lists per section 7.
- **6. Rebuild/redeploy** Docker / server eip-root + DB.
- **7. Test:** drop one CMC and one GA sample; verify canonical attrs, splits, ADT PID/PV1/PV2/GT1/IN1, DFT charges, LC kickouts, Monodock/Huggins exclusion.

9. Test plan (acceptance)

- Listener picks only PTH5.CMC.* (CAT) / PTH5.GA.* (GAN); peers untouched.
- Messages take Expanded-CDM path (not legacy Flat File → XML).
- Route 2 attributes: SoftwareID / DefaultPerfDr / DateRange match CLIENT_SPLITS.
- Split outputs only for included CLIENT_CODES (no Monodock / Huggins for NHL).
- ADT: PID-16 = U when required; PV1-8 from attending/ordering rules; admit/discharge/PV2-28 follow inpatient + blank-admit rules; guarantor/subscriber name & relationship defaults match request.
- PerfSite LC charges stripped / reported as kickouts.
- No regressions for NHL POT/FRK/PAT and IRL GUX/CAX (and PTH5.CC/HR peers).

10. Open questions

- Full CLIENT_CODES / strip-location lists from the NewFacilityInfo workbooks.
- Whether NHL CAT must force marital U and SE/CH/UN the same way later IRL expanses do.
- Whether blank-admit → first charge date must be applied in route 1 (GLF-style) or only in ADT PV1/PV2.
- Confirm ops is OK that request's 513 for CAT will not be used (524 instead).

Generated for PilotFish Sandbox / MedReceivables eiPlatform planning. Validated against eip-root Expanded-CDM wiring, H2 CLIENT_SPLITS schema, and archive samples under Expanded expanse (NHL-Catholic, IRL N-Gainesville, Other samples).