

Interface Capability Brief

EDI 837P → QCare Flat File · Stakeholder overview · 2026-08-12

1. Executive summary

Demo that polls a drop folder for X12 837P professional claims, parses them with PilotFish EDI TableData (837-Q1), and maps each transaction to QCare's 2100-byte fixed-width outpatient (OT/B837) flat-file record for downstream claims systems. Demo only — golden-path fidelity against client samples, not full WTX/ITX parity.

2. Who this is for

- Sources: Clearinghouse / operator dropping .txt / .edi 837P into input/inbound - Destinations: QCare flat files under output/qcare/; archived EDI under output/archive/; debug EDI XML under output/debug/ - Demo vs production: Demo only — synthetic/client sample PHI; no SNIP gate; REPOSHDR claim numbering approximated

- Sources: Clearinghouse / operator dropping .txt / .edi 837P into input/inbound
- Destinations: QCare flat files under output/qcare/; archived EDI under output/archive/; debug EDI XML under output/debug/
- Demo vs production: Demo only — synthetic/client sample PHI; no SNIP gate; REPOSHDR claim numbering approximated

3. What the interface can do

Capabilities below are drawn from the working design and, when present, the published CapabilityStatement — not from aspirational roadmap items.

- Transport: Directory / File (DirectoryListener)
- Format / envelope: X12 837P (005010X222A1), TableData IG 837-Q1
- Identity fields: CLM01 patient control number; ST02 transaction control
- Samples path: samples/MCQRQ74837PS801.TXT, ...802.TXT, ...803.TXT
- Golden expected: samples/expected/qcare...SEQF.staged (3 × 2100-byte records)

Integration highlights

FQCN sources: Sandbox edi-835-payment-integrity FormatProfile + csv-to-json directory skeleton + playbook §3.6. Image: pilotfish-eip:23R1.

Stage	Module / mechanism	Notes
Listener	com.pilotfish.eip.modules.file.DirectoryListener	Poll \$\$EDI_INBOUND_DIRECTORY; Move → archive
Format	com.pilotfish.eip.modules.transform.edi.EDITransformationModule + XPathForkingModule //Transaction	UseInternalData=false, USE_ENHANCED_CONTEXT=true, TransactionDataWithVersion → edi-tabledata/837-Q1 @ 5010
Target processors	FileWriteProcessor → XSLTProcessor (transform-837p-to-qcare.xslt, method=text)	Fixed-width partner format (not X12 generation)
Transport	com.pilotfish.eip.modules.file.DirectoryTransport	\$\$QCARE_OUTPUT_DIRECTORY

4. Honest boundaries (not claimed yet)

- Fork per LX / 2400 service line for multi-line claims?
- Port remaining Excel map rows after golden-path acceptance?

5. What you can verify in a walkthrough

Use these as checklist items when reviewing the demo with business stakeholders. They describe outcomes, not module names.

- Exercise route “1 - Map 837P To QCare” from the Web UI or documented smoke path
- Confirm outputs land in the documented folders / queues and appear in the Web UI status views

6. How it works (plain language)

7. Validation

- What is checked: EDI parses via TableData; outbound record length 2100; golden-path field slices in automated tests
- What is NOT checked: SNIP Types 1–7; full 336-field WTX parity; REPOSHDR / RecordSequence# claim-number identity vs staged; custom UB4_* / prepaid CAS lookups - Does failure block outbound? Yes for unparseable EDI

6. State & idempotency

- Status model: file presence only (no SQL) - When state advances: listener Moves inbound to archive after pick-up; QCare overwrite by basename - Dedup keys: none (demo overwrite) - Retry / poison: unparseable EDI fails the transaction (see logs/eip.log); no separate kickout router in v1

8. Dual-write / side effects

- Order of commits: archive Move (listener) then QCare + debug writes - Compensation: none — accepted demo risk that archive can succeed while map/write fails - Demo shortcuts: claim-site / claim-number block (pos 7–25) derived from BHT/GS + demo sequence, not byte-identical to staged REPOSHDR values

3. Inbound contract

- Transport: Directory / File (DirectoryListener) - Format / envelope: X12 837P (005010X222A1), TableData IG 837-Q1
- Identity fields: CLM01 patient control number; ST02 transaction control - Samples path: samples/MCQRQ74837PS801.TXT, ...802.TXT, ...803.TXT - Golden expected: samples/expected/qcare...SEQF.staged (3 × 2100-byte records)

Routes in this interface

Each route is a configured PilotFish flow. Technical wiring appears in the Route Diagrams PDF; here is the stakeholder reading.

- 1 - Map 837P To QCare: runs steps such as Poll EDI 837P Files, Fork - XPath, Extract Claim Identity, Debug Write EDI XML.

7. Security & trust posture

- X12 SNIP validation is used where configured to reject bad EDI before downstream work
- Credentials and passwords in this package are demo-only — not production secrets
- Risk noted in design: High — Not full WTX parity — 336 leaf fields + undocumented custom funcs
- Risk noted in design: Med — REPOSHDR claim numbering — Not present on 837 wire
- Risk noted in design: Med — Archive-before-QCare — Listener Move
- Risk noted in design: Med — Multi-LX claims — Fork is //Transaction only
- Risk noted in design: Low — PHI in samples — Client zip content

8. Seeing it work

- - Ports: EIP 8123, Web UI 8125 (no SQL) - Compose project: edi-837p-qcare - LAN:
LAN_HINT=http://192.168.68.62:8125/ (re-detect on spin-up) - Volumes: ./input, ./output, ./logs, EDI/TableData/x12
→ edi-tabledata - Heap: 512M–2G - Cold start: EIP ~60–90s
- - Local: http://localhost:8125/
- docker compose up -d --build

9. Related technical documents

- DESIGN.md — working engineering specification for this interface
- README.md — how to run, ports, and smoke commands
- EDI837P_QCare_V2_Route_Diagrams.pdf — detailed PilotFish route wiring diagrams
- This Capability Brief — shareable stakeholder summary (regenerate after design changes)

This document is generated from the interface sources listed above. If design and runtime diverge, believe the smoke-tested runtime and update DESIGN.md.