

Med Rec — Karen Batch Change Diff

Readable summary of implemented requests #2–#5 (skipping #6 MUEs). Generated 2026-08-07.

#1 NHL CAT go-live is Done (prior live deploy) and has no code delta in this batch.

Overview

#	Item	What changed	Primary file(s)
2	HAL split crosswalk (HAX)	Replaced limited LOCATION_ABBR choose() with Karen's 71-entry LocationAbbreviation → FAC crosswalk. Kept legacy EMSHM/EMSHC/HPO. Unknown → HAX.	transform-halifax-flatfilexml-to-canonical.xml.xslt (+ SQL/mock)
3	NGP Healthfirst IN1.4	admlnsName prefers PRIMARY_PAYER, falls back to PRIMARY_CVG_PAYER (fixes blank Primary Cvg Payer rows).	transform-ngp-healthfirst-flatfilexml-to-canonical.xml.xslt
4	Ariana IN1.16 subscriber	LigoLab transform hardens InsuredName (+ patient fallback). ADT ARA empty IN1.16 uses XCN patient name (not XPN).	transform.xslt, transform.xslt
5	NTX Frisco end date	FRI moved from strip-before to strip-after (MED pattern). CLIENT_SPLITS DATE_RANGE → 20260802 via SQL.	route.xml, CLIENT_SPLITS_full.csv (+ SQL/mock)

Also included (status / samples)

- Clients/Med Rec/create_karen_requests_status_pdf.py (living status tracker generator)
- Clients/Med Rec/MedRec_Karen_Requests_Status.pdf (regenerated status overview)
- Clients/Med Rec/data/Karen-Requests-Aug7th2026/ (Karen drop + Halifax mock)

How to read: green = added, red = removed, grey = hunk headers. Halifax crosswalk expansion is large — that section may truncate; use git diff for the full dump.

#2 — HAL split crosswalk (HAX)

Replaced limited LOCATION_ABBR choose() with Karen's 71-entry LocationAbbreviation → FAC crosswalk. Kept legacy EMSHM/EMSHC/HPO. Unknown → HAX.

Related

- Mock regression files: data/Karen-Requests-Aug7th2026/New mapping/Halifax/mock-hax-mis-split/

Diff: transform-halifax-flatfilexml-to-canonicalxml.xslt

Clients/Med Rec/eip-root/interfaces/Flat File to HL7 and Kickout Reports/routes/1 - Incoming Flat Files
by Partition and Client/transform-halifax-flatfilexml-to-canonicalxml.xslt

```
@@ -1,695 +1,910 @@
-<?xml version="1.0" encoding="UTF-8"?>
-<xsl:stylesheet xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:dtFormatter="xalan://com.pilotfish.eip.gui.mapper.util.DateTimeFormatter"
  xmlns:pf="http://pilotfishtechnology.com" xmlns:xs="http://www.w3.org/2001/XMLSchema" exclude-result-
  prefixes="dtFormatter" version="3.1">
-  <xsl:output encoding="UTF-8" indent="yes" method="xml" version="1.0" />
-  <xsl:template match="/">
-    <XCSDData>
-      <Group key="">
-        <Unknown />
-        <Header>
-          <FacilityName>Halifax Med Ctr</FacilityName>
-        </Header>
-      </Group>
-      <!-- Process each Group element from the input -->
-      <xsl:for-each select="//Group">
-        <Group key="{@key}">
-          <!-- Patient Demographics -->
-          <PatientDemographics>
-            <absadmitdiag>
-              <xsl:value-of select="Demographics/XCSRecord[1]/PRIM_DIAGNOSIS_CODE" />
-            </absadmitdiag>
-            <admpatstate>
-              <!--ALREADY STATE CODE ABBR-->
-              <xsl:value-of select="Demographics/XCSRecord[1]/PAT_STATE" />
-            </admpatstate>
-            <absAdmitdate>
-              <xsl:value-of select="pf:formatToYyyyMmDd(Demographics/XCSRecord[1]/ADM_DATE)" />
-            </absAdmitdate>
-            <absattendingdocupin />
-            <absdischargedate>
-              <xsl:value-of select="pf:formatToYyyyMmDd(Demographics/XCSRecord[1]/DISCH_DATE_TIME)" />
-            </absdischargedate>
-            <admemplname />
-            <admzipcode>
-              <xsl:value-of select="Demographics/XCSRecord[1]/PAT_ZIP" />
-            </admzipcode>
-            <absattendingdocnmn />
-            <absattendingdocname>
-              <xsl:value-of select="Demographics/XCSRecord[1]/ATTEND_PROV_NAME" />
-            </absattendingdocname>
-            <admemplstreet />
-            <admAcctNum>
-              <xsl:value-of select="Demographics/XCSRecord[1]/HSP_CSN" />
-            </admAcctNum>
-            <admbirthdate>
-              <xsl:variable name="PatDOB">
-                <xsl:choose>
-                  <xsl:when test="string-length(Demographics/XCSRecord[1]/PAT_DOB) != 10">
-                    <!--WE KNOW WE NEED TO PAD WITH ZERO-->
-                    <xsl:value-of select="pf:padDate(Demographics/XCSRecord[1]/PAT_DOB)" />
-                  </xsl:when>
-                  <xsl:otherwise>
-                    <xsl:value-of select="Demographics/XCSRecord[1]/PAT_DOB" />
-                  </xsl:otherwise>
-                </xsl:choose>
-              </xsl:variable>
-              <xsl:if test="string-length($PatDOB) != 0 and not(contains($PatDOB,'NaN'))">
-                <xsl:choose>
-                  <xsl:when test="contains($PatDOB, '-')">
-                    <xsl:value-of select="translate($PatDOB, '-', ' ')" />
-                  </xsl:when>
-                  <xsl:when test="string-length(translate($PatDOB, '/', ' ')) != 0">
-                    <xsl:value-of select="dtFormatter:format(translate($PatDOB, '/', ' '), 'MMddyyyy',
-                      'yyyyMMdd')" />
-                  </xsl:when>
-                </xsl:choose>
-              </xsl:if>
-            </admbirthdate>
-          </PatientDemographics>
-        </Group>
-      </xsl:for-each>
-    </XCSDData>
  </template>
</stylesheet>
```

```

-      </admbirthdate>
-      <admLocation>
-        <xsl:variable name="deptAbbr" select="Demographics/XCSRecord[1]/DEPARTMENT_ABBR" />
-        <xsl:variable name="locationAbbr" select="Demographics/XCSRecord[1]/LOCATION_ABBR" />
-        <xsl:choose>
-          <xsl:when test="$locationAbbr = 'EMSHM' and $deptAbbr = 'ND FSED ED'">
-            <xsl:value-of select="'HED'" />
-          </xsl:when>
-          <xsl:when test="$locationAbbr = 'EMSHM' and $deptAbbr = 'PO FSED ED'">
-            <xsl:value-of select="'PXE'" />
-          </xsl:when>
-          <xsl:when test="$locationAbbr = 'HMC'">
-            <xsl:value-of select="'HAX'" />
-          </xsl:when>
-          <xsl:when test="$locationAbbr = 'MCD'">
-            <xsl:value-of select="'DEX'" />
-          </xsl:when>
-          <xsl:when test="$locationAbbr = 'HPO'">
-            <xsl:value-of select="'POX'" />
-          </xsl:when>
-          <xsl:when test="$locationAbbr = 'EMSHC'">
-            <xsl:value-of select="'PXE'" />
-          </xsl:when>
-          <xsl:otherwise>
-            <xsl:value-of select="'HAX'" />
-          </xsl:otherwise>
-        </xsl:choose>
-      </admLocation>
-      <admpatsex>
-        <xsl:value-of select="Demographics/XCSRecord[1]/PAT_SEX" />
-      </admpatsex>
-      <admpatphone>
-        <xsl:value-of select="Demographics/XCSRecord[1]/PAT_HOME_PHONE" />
-      </admpatphone>
-      <admssn>
-        <xsl:value-of select="Demographics/XCSRecord[1]/PAT_SSN" />
-      </admssn>
-      <admname>
-        <xsl:value-of select="Demographics/XCSRecord[1]/HSP_ACCOUNT_NAME" />
-      </admname>
-      <admemplcity />
-      <admpatcity>
-        <xsl:value-of select="Demographics/XCSRecord[1]/PAT_CITY" />
-      </admpatcity>
-      <admFinClass>
-        <xsl:value-of select="Demographics/XCSRecord[1]/ACCT_FIN_CLASS" />
-      </admFinClass>
-      <AttendDrNPI>
-        <xsl:value-of select="Demographics/XCSRecord[1]/ATTENDING_PROV_NPI" />
-      </AttendDrNPI>
-      <absPatientUnit />
-      <admpatienttype>
-        <xsl:variable name="class" select="Demographics/XCSRecord[1]/PAT_CLASS" />
-        <xsl:value-of select="substring($class,0,23)" />
-        <!--<xsl:choose-->
-        <!--<xsl:when test="$baseClass = ('Billing Encounter','Erroneous Encounter','Lab
Requisition','Outpatient','Outpatient Surgery','Pre-Admission Testing','Treatment
Series','Radiation/Oncology Series')">-->
-        <!--<xsl:value-of select="'0'" />-->
-        <!--</xsl:when-->
-        <!--<xsl:when test="$baseClass = ('Inpatient','Inpatient Psych','Inpatient
Rehab','Newborn','Observation','Surgery Admit','Hospice - Inpatient')">-->
-        <!--<xsl:value-of select="'I'" />-->
-        <!--</xsl:when-->
-        <!--<xsl:when test="$baseClass = ('Emergency')">-->
-        <!--<xsl:value-of select="'E'" />-->
-        <!--</xsl:when-->
-        <!--<xsl:otherwise-->
-        <!--<xsl:value-of select="'NA'" />-->
-        <!--</xsl:otherwise-->
-        <!--</xsl:choose-->
-      </admpatienttype>
-      <admstreet>
-        <xsl:value-of select="Demographics/XCSRecord[1]/PAT_STREET" />
-      </admstreet>
-      <admstreet2>
-        <xsl:value-of select="Demographics/XCSRecord[1]/PAT_STREET_2" />
-      </admstreet2>
-      <admemplzip />
-      <ChiefComplaint />
-      <admaccidentdate />
-      <Filler2 />
-      <admmaritalstatus>
-        <xsl:variable name="status" select="Demographics/XCSRecord[1]/PAT_MARITAL_STAT" />
-        <xsl:choose>

```

```

-      <xsl:when test="$status = 'Divorced'">
-        <xsl:value-of select="'D'" />
-      </xsl:when>
-      <xsl:when test="$status = 'Married'">
-        <xsl:value-of select="'M'" />
-      </xsl:when>
-      <xsl:when test="$status = 'Separated'">
-        <xsl:value-of select="'X'" />
-      </xsl:when>
-      <xsl:when test="$status = 'Significant Other'">
-        <xsl:value-of select="'U'" />
-      </xsl:when>
-      <xsl:when test="$status = 'Single'">
-        <xsl:value-of select="'S'" />
-      </xsl:when>
-      <xsl:when test="$status = 'Unknown'">
-        <xsl:value-of select="'U'" />
-      </xsl:when>
-      <xsl:when test="$status = 'Widowed'">
-        <xsl:value-of select="'W'" />
-      </xsl:when>
-      <xsl:otherwise>
-        <xsl:value-of select="'U'" />
-      </xsl:otherwise>
-    </xsl:choose>
-  </admmaritalstatus>
- </PatientDemographics>
- <!-- Process each charge record in the group -->
- <xsl:for-each select="Charges/XCSRecord[QUANTITY]">
-   <Charge>
-     <radNumOfTimes>
-       <xsl:value-of select="QUANTITY" />
-     </radNumOfTimes>
-     <radExamServDate>
-       <!-- Accept MM/dd/yyyy (daily) and yyyy-MM-dd (historical HAL exports). -->
-       <xsl:value-of select="pf:formatToYyyyMmDd(SERVICE_DATE)" />
-     </radExamServDate>
-     <radPatientName>
-       <xsl:value-of select="HSP_ACCOUNT_NAME" />
-     </radPatientName>
-     <radAcctNum>
-       <xsl:value-of select="HSP_CSN" />
-     </radAcctNum>
-     <radExamBillingCode>
-       <xsl:value-of select="CPT_CODE" />
-     </radExamBillingCode>
-     <CDM>
-       <xsl:value-of select="*[local-name()='PROC_CODE_CDM']" />
-     </CDM>
-     <radExamCPT>
-       <xsl:value-of select="CPT_CODE" />
-     </radExamCPT>
-     <examdesc>
-       <xsl:value-of select="PROCEDUREDESCRIPTION" />
-     </examdesc>
-     <radOrderingPhyLic>
-       <xsl:value-of select="BILLINGPROVIDERNPI" />
-     </radOrderingPhyLic>
-     <absPatientUnit />
-     <radOrderingPhyMne>
-       <xsl:value-of select="BILLINGPROVIDERNAME" />
-     </radOrderingPhyMne>
-     <ExamHCPCCode />
-     <orderingDrNPI>
-       <xsl:value-of select="BILLINGPROVIDERNPI" />
-     </orderingDrNPI>
-     <misOrderingPhyCity />
-     <radOrderingPhyUPIN />
-     <misOrderingPhyName>
-       <xsl:value-of select="BILLINGPROVIDERNAME" />
-     </misOrderingPhyName>
-     <misOrderingPhyAddr />
-   </Charge>
- </xsl:for-each>
- <!-- Guarantor Information -->
- <Guarantor>
-   <admGuarCity>
-     <xsl:value-of select="Demographics/XCSRecord[1]/GUAR_CITY" />
-   </admGuarCity>
-   <admGuarEmployer />
-   <admGuarAddr1>
-     <xsl:value-of select="Demographics/XCSRecord[1]/GUAR_STREET" />
-   </admGuarAddr1>
-   <admGuarAddr2>
-     <xsl:value-of select="Demographics/XCSRecord[1]/GUAR_STREET_2" />

```

```

-      </admGuarAddr2>
-      <admGuarHomePhone>
-        <xsl:value-of select="Demographics/XCSRecord[1]/GUAR_HOME_PHONE" />
-      </admGuarHomePhone>
-      <admGuarZip>
-        <xsl:value-of select="Demographics/XCSRecord[1]/GUAR_ZIP" />
-      </admGuarZip>
-      <admPatientUnit />
-      <admGuarEmplCity />
-      <admGuarEmplState />
-      <admGuarEmplZip />
-      <admGuarRel>
-        <xsl:variable name="guarRel" select="Demographics/XCSRecord[1]/GUAR_RELATION" />
-        <xsl:value-of select="substring(upper-case($guarRel),1,2)" />
-      </admGuarRel>
-      <admGuarName>
-        <xsl:choose>
-          <xsl:when test="not(contains(Demographics/XCSRecord[1]/GUAR_NAME','))">
-            <xsl:choose>
-              <xsl:when test="string-length(Demographics/XCSRecord[1]/GUAR_NAME) != 0">
-                <xsl:value-of select="concat(',',Demographics/XCSRecord[1]/GUAR_NAME)" />
-              </xsl:when>
-              <xsl:otherwise>
-                <xsl:value-of select="'" />
-              </xsl:otherwise>
-            </xsl:choose>
-          </xsl:when>
-          <xsl:otherwise>
-            <xsl:value-of select="Demographics/XCSRecord[1]/GUAR_NAME" />
-          </xsl:otherwise>
-        </xsl:choose>
-      </admGuarName>
-      <npr1 />
-      <admGuarState>
-        <xsl:value-of select="pf:GetStateAbbreviation(Demographics/XCSRecord[1]/GUAR_STATE)" />
-      </admGuarState>
-      <admAcctNum />
-      <admGuarEmplAddr1 />
-      <admGuarSSN>
-        <xsl:value-of select="Demographics/XCSRecord[1]/GUAR_SSN" />
-      </admGuarSSN>
-      <admGuarEmplPhone />
-    </Guarantor>
-    <!-- Diagnosis Codes -->
-    <DiagnosisCodes>
-      <xsl:if test="Demographics/XCSRecord[1]/PRIM_DIAGNOSIS_CODE">
-        <Diag>
-          <xsl:value-of select="Demographics/XCSRecord[1]/PRIM_DIAGNOSIS_CODE" />
-        </Diag>
-      </xsl:if>
-      <xsl:if test="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_1">
-        <Diag>
-          <xsl:value-of select="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_1" />
-        </Diag>
-      </xsl:if>
-      <xsl:if test="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_2">
-        <Diag>
-          <xsl:value-of select="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_2" />
-        </Diag>
-      </xsl:if>
-      <xsl:if test="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_3">
-        <Diag>
-          <xsl:value-of select="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_3" />
-        </Diag>
-      </xsl:if>
-      <xsl:if test="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_4">
-        <Diag>
-          <xsl:value-of select="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_4" />
-        </Diag>
-      </xsl:if>
-      <xsl:if test="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_5">
-        <Diag>
-          <xsl:value-of select="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_5" />
-        </Diag>
-      </xsl:if>
-      <xsl:if test="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_6">
-        <Diag>
-          <xsl:value-of select="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_6" />
-        </Diag>
-      </xsl:if>
-      <xsl:if test="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_7">
-        <Diag>
-          <xsl:value-of select="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_7" />
-        </Diag>
-      </xsl:if>

```

```
-      <xsl:if test="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_8">
-      <Diag>
-      <xsl:value-of select="Demographics/XCSRecord[1]/SECONDARY_DIAG_CODE_8" />
```

... truncated after 320 lines. Full diff: `git diff -- path`

#3 — NGP Healthfirst IN1.4

admInsName prefers PRIMARY_PAYER, falls back to PRIMARY_CVG_PAYER (fixes blank Primary Cvg Payer rows).

Diff: transform-ngp-healthfirst-flatfilexml-to-canonicalxml.xslt

Clients/Med Rec/eip-root/interfaces/Flat File to HL7 and Kickout Reports/routes/1 - Incoming Flat Files
by Partition and Client/transform-ngp-healthfirst-flatfilexml-to-canonicalxml.xslt

@@ -415,7 +415,15 @@

```
<adminsPaCode />
<absPatientUnit />
<admInsName>
-   <xsl:value-of select="PRIMARY_CVG_PAYER" />
+   <!-- Prefer Primary Payer; fall back to Primary Cvg Payer when blank (Karen IN1.4). -->
+   <xsl:choose>
+     <xsl:when test="string-length(normalize-space(PRIMARY_PAYER)) != 0">
+       <xsl:value-of select="normalize-space(PRIMARY_PAYER)" />
+     </xsl:when>
+     <xsl:otherwise>
+       <xsl:value-of select="normalize-space(PRIMARY_CVG_PAYER)" />
+     </xsl:otherwise>
+   </xsl:choose>
</admInsName>
<admAcctNum />
<adminsinsuredrel>
```

#4 — Ariana IN1.16 subscriber

LigoLab transform hardens InsuredName (+ patient fallback). ADT ARA empty IN1.16 uses XCN patient name (not XPN).

Diff: transform.xslt

Clients/Med Rec/eip-root/interfaces/Flat File to HL7 and Kickout Reports/routes/1 - Incoming Flat Files
by Partition and Client/transform.xslt

```
@@ -125,9 +125,18 @@
    <xsl:value-of select="xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:SubscriberId |
InsuranceInfo[PayorPriority='1']/SubscriberId" />
    </adminspolicy>
    <subscribername>
-      <xsl:if
test="concat(xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:LastName |
InsuranceInfo[PayorPriority='1']/InsuredName/LastName,
',',xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:FirstName |
InsuranceInfo[PayorPriority='1']/InsuredName/FirstName) != ','">
-        <xsl:value-of
select="concat(xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:LastName |
InsuranceInfo[PayorPriority='1']/InsuredName/LastName,
',',xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:FirstName |
InsuranceInfo[PayorPriority='1']/InsuredName/FirstName)" />
-      </xsl:if>
+      <xsl:variable name="ins1Last" select="normalize-
space((xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:LastName |
InsuranceInfo[PayorPriority='1']/InsuredName/types:LastName |
InsuranceInfo[PayorPriority='1']/InsuredName/LastName)[1])" />
+      <xsl:variable name="ins1First" select="normalize-
space((xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:FirstName |
InsuranceInfo[PayorPriority='1']/InsuredName/types:FirstName |
InsuranceInfo[PayorPriority='1']/InsuredName/FirstName)[1])" />
+      <xsl:variable name="patLast" select="normalize-
space((xfin:PatientInfo/xfin:Person/types:Name/types:LastName | PatientInfo/Person/Name/types:LastName |
PatientInfo/Person/Name/LastName)[1])" />
+      <xsl:variable name="patFirst" select="normalize-
space((xfin:PatientInfo/xfin:Person/types:Name/types:FirstName | PatientInfo/Person/Name/types:FirstName
| PatientInfo/Person/Name/FirstName)[1])" />
+      <xsl:choose>
+        <xsl:when test="string-length($ins1Last) != 0 or string-length($ins1First) != 0">
+          <xsl:value-of select="concat($ins1Last, ',', $ins1First)" />
+        </xsl:when>
+        <xsl:when test="string-length($patLast) != 0 or string-length($patFirst) != 0">
+          <xsl:value-of select="concat($patLast, ',', $patFirst)" />
+        </xsl:when>
+      </xsl:choose>
    </subscribername>
    <adminzip>
    <xsl:value-of select="xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:Address/types:ZIP |
InsuranceInfo[PayorPriority='1']/Address/ZIP" />
@@ -151,9 +160,19 @@
    <xsl:value-of select="xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:PayorId |
InsuranceInfo[PayorPriority='1']/PayorId" />
    </adminsmne>
    <admininsuredname>
-      <xsl:if
test="concat(xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:LastName |
InsuranceInfo[xfin:PayorPriority='1']/InsuredName/LastName,
',',xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:FirstName |
InsuranceInfo[xfin:PayorPriority='1']/InsuredName/FirstName
) != ','">
-        <xsl:value-of
select="concat(xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:LastName |
InsuranceInfo[xfin:PayorPriority='1']/InsuredName/LastName,
',',xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:FirstName |
InsuranceInfo[xfin:PayorPriority='1']/InsuredName/FirstName
)" />
-      </xsl:if>
+      <!-- Map InsuredName; if blank, use patient name (Cerner needs IN1.16 for SELFPAID). -->
+      <xsl:variable name="ins1Last" select="normalize-
space((xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:LastName |
InsuranceInfo[PayorPriority='1']/InsuredName/types:LastName |
InsuranceInfo[PayorPriority='1']/InsuredName/LastName)[1])" />
+      <xsl:variable name="ins1First" select="normalize-
space((xfin:InsuranceInfo[xfin:PayorPriority='1']/xfin:InsuredName/types:FirstName |
InsuranceInfo[PayorPriority='1']/InsuredName/types:FirstName |
InsuranceInfo[PayorPriority='1']/InsuredName/FirstName)[1])" />
+      <xsl:variable name="patLast" select="normalize-
space((xfin:PatientInfo/xfin:Person/types:Name/types:LastName | PatientInfo/Person/Name/types:LastName |
PatientInfo/Person/Name/LastName)[1])" />
+      <xsl:variable name="patFirst" select="normalize-
space((xfin:PatientInfo/xfin:Person/types:Name/types:FirstName | PatientInfo/Person/Name/types:FirstName
| PatientInfo/Person/Name/FirstName)[1])" />
+      <xsl:choose>
```



```

+         <xsl:when test="string-length($ins1Last) != 0 or string-length($ins1First) != 0">
+             <xsl:value-of select="concat($ins1Last, ', ', $ins1First)" />
+         </xsl:when>
+         <xsl:when test="string-length($patLast) != 0 or string-length($patFirst) != 0">
+             <xsl:value-of select="concat($patLast, ', ', $patFirst)" />
+         </xsl:when>
+     </xsl:choose>
    </adminsinsuredname>
    <admInsPhone>
        <xsl:value-of
select="xifin:InsuranceInfo[xifin:PayorPriority='1']/xifin:Phone/types:HomePhone |
InsuranceInfo[xifin:PayorPriority='1']/Phone/HomePhone" />

```

Diff: transform.xslt

Clients/Med Rec/eip-root/interfaces/Flat File to HL7 and Kickout Reports/formats/Generate ADT A04
HL7/transform.xslt

@@ -1095,7 +1095,7 @@

```

        </XPN.1>
        <XPN.2 />
    </xsl:when>
-     <xsl:when test="$partitionName = ('SPG','ARA') and string-
length(Insurance1/adminsinsuredname) = 0">
+     <xsl:when test="$partitionName = 'SPG' and string-length(normalize-
space(Insurance1/adminsinsuredname)) = 0">
        <XPN.1>
            <xsl:value-of select="normalize-space(substring-
before(PatientDemographics/admname, ','))" />
        </XPN.1>

```

@@ -1103,6 +1103,15 @@

```

        <xsl:value-of select="normalize-space(substring-
after(PatientDemographics/admname, ','))" />
    </XPN.2>
    </xsl:when>
+     <!-- ARA: use XCN (not XPN) so HL7TransformationProcessor emits IN1.16; fall back
to patient name when blank. -->
+     <xsl:when test="$partitionName = 'ARA' and string-length(normalize-
space(Insurance1/adminsinsuredname)) = 0">
+         <XCN.1>
+             <xsl:value-of select="normalize-space(substring-
before(PatientDemographics/admname, ','))" />
+         </XCN.1>
+         <XCN.2>
+             <xsl:value-of select="normalize-space(substring-
after(PatientDemographics/admname, ','))" />
+         </XCN.2>
+     </xsl:when>
    <xsl:otherwise>
        <XCN.1>
            <xsl:value-of select="normalize-space(substring-
before(Insurance1/adminsinsuredname, ','))" />

```

#5 — NTX Frisco end date

FRI moved from strip-before to strip-after (MED pattern). CLIENT_SPLITS DATE_RANGE → 20260802 via SQL.

Related

- NEW SQL: Clients/Med Rec/deploy/sql/02_update_NTX_FRI_end_date.sql

Diff: route.xml

Clients/Med Rec/eip-root/interfaces/Flat File to HL7 and Kickout Reports/routes/2 - Stripping and Tweaking/route.xml

```
@@ -308,7 +308,8 @@
</Processor>
<Processor class="com.pilotfish.eip.modules.transform.XSLTProcessor" name="Strip Charges If
radExamServeDate Before DATE_RANGE from DB">
  <ModuleConfig>
-    <ExecuteProcessor>{ognl:(getAttribute('Partition') == 'NTX' && getAttribute('Client') ==
'ANC') || (getAttribute('Partition') == 'NTX' && getAttribute('Client') == 'FTW') ||
(getAttribute('Partition') == 'NTX' && getAttribute('Client') == 'ARL') ||
(getAttribute('Partition') == 'NTX' && getAttribute('Client') == 'NOH') ||
(getAttribute('Partition') == 'NTX' && getAttribute('Client') == 'PLA') ||
(getAttribute('Partition') == 'NTX' && getAttribute('Client') == 'FRI') ||
(getAttribute('Partition') == 'NTX' && getAttribute('Client') == 'SAC') ||
(getAttribute('Partition') == 'PPA') || (getAttribute('Partition') == 'IRL' &&
getAttribute('Client') == 'COX') || (getAttribute('Partition') == 'IRL' && getAttribute('Client')
== 'JFX') || (getAttribute('Partition') == 'IRL' && getAttribute('Client') == 'LWX') ||
(getAttribute('Partition') == 'IRL' && getAttribute('Client') == 'PWX') || getAttribute('Client')
== 'ARA' || (getAttribute('Partition') == 'NTX' && getAttribute('Client') ==
'DEC')}}</ExecuteProcessor>
+    <!-- NTX FRI removed from strip-before: end-date only (strip-after) as of 2026-08-07 Karen #5 -->
+    <ExecuteProcessor>{ognl:(getAttribute('Partition') == 'NTX' && getAttribute('Client') ==
'ANC') || (getAttribute('Partition') == 'NTX' && getAttribute('Client') == 'FTW') ||
(getAttribute('Partition') == 'NTX' && getAttribute('Client') == 'ARL') ||
(getAttribute('Partition') == 'NTX' && getAttribute('Client') == 'NOH') ||
(getAttribute('Partition') == 'NTX' && getAttribute('Client') == 'PLA') ||
(getAttribute('Partition') == 'NTX' && getAttribute('Client') == 'SAC') ||
(getAttribute('Partition') == 'PPA') || (getAttribute('Partition') == 'IRL' &&
getAttribute('Client') == 'COX') || (getAttribute('Partition') == 'IRL' && getAttribute('Client')
== 'JFX') || (getAttribute('Partition') == 'IRL' && getAttribute('Client') == 'LWX') ||
(getAttribute('Partition') == 'IRL' && getAttribute('Client') == 'PWX') || getAttribute('Client')
== 'ARA' || (getAttribute('Partition') == 'NTX' && getAttribute('Client') ==
'DEC')}}</ExecuteProcessor>
    <XSLTPath>transform-strip-before-date-range.xslt</XSLTPath>
    <CacheXSLTToXML>false</CacheXSLTToXML>
    <XSLTEngine>Saxon</XSLTEngine>
@@ -319,7 +320,8 @@
</Processor>
<Processor class="com.pilotfish.eip.modules.transform.XSLTProcessor" name="Strip Charges If
radExamServDate After DATE_RANGE from DB">
  <ModuleConfig>
-    <ExecuteProcessor>{ognl:getAttribute('Partition') == 'WCH' || (getAttribute('Partition') == 'NTX'
&& getAttribute('Client') == 'MED')}}</ExecuteProcessor>
+    <!-- NTX FRI end-date (Karen #5): same pattern as NTX MED – strip DOS after
CLIENT_SPLITS.DATE_RANGE -->
+    <ExecuteProcessor>{ognl:getAttribute('Partition') == 'WCH' || (getAttribute('Partition') == 'NTX'
&& getAttribute('Client') == 'MED') || (getAttribute('Partition') == 'NTX' &&
getAttribute('Client') == 'FRI')}}</ExecuteProcessor>
    <XSLTPath>transform-strip-after-date-range.xslt</XSLTPath>
    <CacheXSLTToXML>false</CacheXSLTToXML>
    <XSLTEngine>Saxon</XSLTEngine>
```

Diff: CLIENT_SPLITS_full.csv

Clients/Med Rec/reports/CLIENT_SPLITS_full.csv

```
@@ -74,7 +74,7 @@
"170","IRL","FAW","Fawcett","FAW","WG","WC4","WG","20141102","1"
"170","IRL","FAW","Fawcett","FAX","WZ","WC4","WZ","20141102"
"170","IRL","FAW","Fawcett","FAY","XA","WC4","XA","20141102"
- "406","NTX","FRI","Medcity Frisco","FRI","TU","CP2","TU","20250113","1"
+ "406","NTX","FRI","Medcity Frisco","FRI","TU","CP2","TU","20260802","1"
"501","NHL","FRJ","Frisbie Hospital","FRJ","HC","HC2","HC","20201001","1"
"501","NHL","FRJ","Frisbie Hospital","FRP","HE","HC2","HE","20201001"
"510","NHL","FRK","Frisbie Hospital","FRK","HC","HC2","HC","20201001","1"
```

New file: 02_update_NTX_FRI_end_date.sql

Clients/Med Rec/deploy/sql/02_update_NTX_FRI_end_date.sql

```
+-- NTX Frisco (FRI) software 406 – END date by DOS (Karen request #5, 2026-08-07)
+-- Mirror NTX MED strip-after pattern: only send radExamServDate <= DATE_RANGE.
+-- Route change: FRI removed from strip-before; added to strip-after in route 2.
```

```
+
+UPDATE CLIENT_SPLITS
+  SET DATE_RANGE = '20260802'
+ WHERE SOFTWAREID = 406
+   AND PARTITION = 'NTX';
+
+-- Verify (optional):
+-- SELECT SOFTWAREID, PARTITION, SPLIT_CODE, CLIENT, FACILITY, DATE_RANGE, IS_DEFAULT
+--   FROM CLIENT_SPLITS
+--  WHERE SOFTWAREID = 406;
```

Deploy checklist (ready items)

- #2 Copy updated transform-halifax-flatfilexml-to-canonicalxml.xslt; smoke mock-hax-mis-split.
- #3 Copy transform-ngp-healthfirst-...xslt; smoke Primary Payer accounts.
- #4 Copy Ariana LigoLab transform.xslt + Generate ADT A04 transform.xslt; smoke SELFPAY IN1.16.
- #5 Copy route 2 Stripping and Tweaking/route.xml; run deploy/sql/02_update_NTX_FRI_end_date.sql on target DB.
- #6 Still skipped — waiting on PilotFish\MUE examples.
- Living status: regenerate MedRec_Karen_Requests_Status.pdf after status updates.

Regenerate this PDF: `python3 "Clients/Med Rec/create_karen_batch_diff_pdf.py"`