

Facility Onboarding Plan — NHL Catholic Medical & IRL N Gainesville (Expanse)

Implementation plan for adding two expanded-Expanse facilities into MedReceivables / eiPlatform (Flat File to HL7 and Kickout Reports). Covers H2 database updates, route 1 listeners/processors, downstream strip/split config, and ADT/DFT mapping rules from the request.

Scope: NHL – Catholic Medical Center (CLIENT CAT) and IRL N – HCA FL Gainesville Hospital (CLIENT GAN). Source folders referenced in request: *Expanded expanse\NHL-Catholic* and *Expanded expanse\IRL N-Gainesville*.

1. Summary of the request

Add new facilities to the Expanse expanded-CDM intake path so the same flat-file feed can be picked up, converted to canonical XML in route 1, stripped/split using CLIENT_SPLITS + CLIENT_CODES, then generate ADT/DFT with the new mapping rules.

Important conflict: The request lists SOFTWAREID **513** for Catholic Medical, but SOFTWAREID **513 is already taken** in the current H2 DB by FPS / Central Lab (CLIENT CNL). SOFTWAREID **523** (requested for Gainesville) is free. Confirm with MedRec/ops whether CAT should receive a new free software ID (e.g. 524) or whether FPS CNL will be remapped before using 513.

2. Target database records (from request)

2.1 CLIENT_SPLITS (facility / partition registry)

Table columns in current H2 DB: SOFTWAREID, CLIENTNAME, PARTITION, CLIENT, FACILITY, FACILITY_CODE, DEFAULT_PERF_DR, ACCOUNT_NUM_ALPHA, DATE_RANGE, IS_DEFAULT. FILE_HEADER_FACILITY_NAME from the email is **not** a CLIENT_SPLITS column — it maps to route 1 listener attribute **FacilityNameShouldBe**.

Field	NHL Catholic Medical	IRL N Gainesville
SOFTWAREID	513 (CONFLICT — see above)	523 (free)
CLIENTNAME	Catholic Medical	HCA FL Gainesville Hospital
FILE HEADER / FacilityNameShouldBe	Catholic Medical Center	HCA FL Gainesville Hospital
PARTITION	NHL	IRL
CLIENT	CAT	GAN
FACILITY	CAT	GAN
FACILITY_CODE	HK	PT
DEFAULT_PERF_DR	CP9	CN1
ACCOUNT_NUM_ALPHA	HK	PT
DATE_RANGE	20260611	20260505
IS_DEFAULT	1 (recommended)	1 (recommended)

NHL note: Exclude locations Monodock and Huggins (X.HH) from split/strip config when loading CLIENT_CODES / strip tables from the Catholic feed workbook.

2.2 CLIENT_CODES (split codes)

CLIENT_CODES columns: FACILITY, CODE, COMPARATOR, SOFTWARE_ID. These define how one input file forks into multiple related output sets in route 3. Source the location/code rows from the request workbooks (excluding Monodock / Huggins for NHL). Mirror recent Expanse inserts (e.g. IRL GUX/CAX or NHL POT/FRK/PAT) for structure.

- Insert one CLIENT_SPLITS default row per facility (above).
- Insert CLIENT_CODES rows for each included split location for that SOFTWARE_ID.

- Optional / if used by strip logic: STRIP_LOCATIONS, STRIP_PERFORMING_SITES already has LC (LabCorp) globally; verify apply-list includes CAT/GAN.
- Preferred ops path already in eiConsole: route **88a – Add New Facility** + Excel *MedReceivables_NewFacilityInfo.xlsx* via format New Facility SQLXML.

3. End-to-end flow (what happens after DB is wired)

Route	Purpose for new facilities
1 – Incoming Flat Files...	Listener + attribute stamp + expanded-CDM flatfile→canonical XML
2 – Stripping and Tweaking	Loads CLIENT_SPLITS; resolves SoftwareID; applying strip rules incl. PerfSite LC
3 – Splitting Records by Facility	Uses CLIENT_SPLITS + CLIENT_CODES to fork output streams
3b – Generate HL7 Files	ADT (Generate ADT A04) + DFT (Generate DFT DPT P03) XSLTs

4. Route 1 work — listeners & canonical conversion

In route 1, each pickup is a DirectoryListener. SOFTWAREID is **not** set here — route 2 looks it up from CLIENT_SPLITS using Partition + Client. Route 1 must set PartitionName/ClientName (then Partition/Client) and convert the flat file into canonical XML via the **Transform Flat File to XML-New-Expense-Expanded-CDM** path (raw-flat-file-specification-expanded-cdm.xml).

4.1 Copy-from templates

New facility	Best copy-from	Why
NHL CAT	NHL POT / FRK / PAT	Same NHL Expance expanded-CDM listener pattern
IRL GAN	IRL GUX / CAX	Most recent IRL EXP Expance listeners

4.2 Checklist per new software / client

- **Source listener:** Clone *Pickup Flat Files – {PARTITION} – {CLIENT}* with *1 – Incoming Raw File – Dir Listener – {PARTITION} – {CLIENT}*. PollingDirectory=\$\$FLAT_FILE_INPUT_DIRECTORY; archive=\$\$FLAT_FILE_ARCHIVE_DIRECTORY; FileExtensionRestriction per feed (txt for NHL-style). Set FileNameRestriction from sample file names in the Expanded expance folders (TBD from samples).
- **Set Facility Name – {CLIENT}:** TransactionAttributePopulationProcessor setting FacilityNameShouldBe, PartitionName, ClientName (use FILE_HEADER values / CAT / GAN).
- **Target processors:** Add *Set Partition and Client Name-NHL-CAT* and *...-IRL-GAN* (ExecuteProcessor on PartitionName+ClientName; set Partition/Client).
- **Expanded-CDM processor allowlist:** Add CAT and GAN to OGNL on *Transform Flat File to XML-New-Expance-Expanded-CDM*; keep them excluded from the legacy Flat File to XML processor.
- If SOFTWAREID is brand-new (yes for 523; maybe for CAT if not reusing 513): new listener is required. If it were an existing software ID with only a new split facility, listener may already exist — not the case for CAT/GAN today.

5. Route 2 / 3 work

- Route 2 already reads all CLIENT_SPLITS and XPath SoftwareID / DefaultPerfDr / DateRange — no SQL change if DB rows are correct.
- Add CAT and GAN to *Apply Stripping – SPECIFIC CLIENTS ONLY – Site Locations* OGNL so PerfSite kickouts (including strip LC) apply.
- Confirm strip location tables / secondary strip rows for excluded NHL locations (Monodock, Huggins X.HH).
- Route 3 split query uses partition + client; CAT/GAN rows must exist so SplitCount > 0 when expected.

6. ADT / DFT XSLT updates (route 3b)

Most rules already exist for peer Expance facilities. Prefer copying the IRL softwareID / facility guard lists and NHL partition branches rather than inventing new logic.

Rule from request	Where it lives today	Action for CAT / GAN
PerfSite kickout — strip LC	STRIP_PERFORMING_SITES + route 2 transform	Add CAT/GAN to Apply Stripping Site Locations client list
PID marital status default U	ADT transform — IRL softwareID list (514–522...)	Add IRL software ID for CAT to IRL marital-U list; decide whether NHL
PV1-8 Attending (NPI/Name)	ADT — NHL partition branch uses first charge or attending physician	Verify NPI/Name by facility GAN (+ split facility codes) to
PV1-44 / PV1-45 admit & discharge (blank admit)	ADT (PV1-44) related blank admit is first charge	Verify admitting physician by facility GAN
PV2-28 ARSA date (blank admit → ADT PV2-28 date)	ADT (PV2-28) date with admit / first DOS logic	Reuse same admit/first-charge sourcing once CAT/GAN are in the right
Guarantor name blank → patient name	ADT GT1 — already global	No change expected
Subscriber name blank → patient name	ADT IN1 — NHL has special empty-subscriber handling	CAT inherits NHL; confirm IRL GAN expected behavior vs peers

Rule from request	Where it lives today	Action for CAT / GAN
Relationship blank → SE / CH / UNADT GT1/IN1 — IRL list today only includes some softwareIDs (e.g. 514/541), lists for GAN exclude	Expanded CDM	Exclude NHL CAT inclusion

DFT template mainly carries charge/MUE logic; demographic/PV1 rules are predominantly in **Generate ADT A04 HL7/transform.xslt**. Still scan **Generate DFT DPT P03 HL7/transform.xslt** for any partition/client/softwareID allowlists that need CAT/GAN or the new IDs.

7. Suggested implementation sequence

- **0. Confirm SOFTWAREID for CAT** (513 conflict vs assign new ID).
- **1. Gather sample files** from Expanded expanse folders; lock FileNameRestriction patterns and validate expanded-CDM columns.
- **2. Database:** insert CLIENT_SPLITS + CLIENT_CODES (+ strip tables as needed) via 88a Excel path or SQL; export/backup H2 first.
- **3. Route 1:** clone listeners/processors; update expanded-CDM OGNL allowlists.
- **4. Route 2:** add CAT/GAN to PerfSite strip client list.
- **5. ADT/DFT XSLT:** extend guard lists per section 6.
- **6. Rebuild/redeploy** local Docker image (or server eip-root) with updated eip-root + DB.
- **7. Test:** drop one NHL Catholic file and one IRL Gainesville file; verify canonical attrs (Partition/Client/SoftwareID), split outputs, ADT PID/PV1/PV2/GT1/IN1, DFT charges, LC kickouts, and that Monodock/Huggins are excluded.

8. Test plan (acceptance)

- Listener picks files by FileNameRestriction only for the intended facility.
- Route 2 attributes: SoftwareID / DefaultPerfDr / DateRange match CLIENT_SPLITS.
- Split outputs created only for included CLIENT_CODES (no Monodock / Huggins for NHL).
- ADT: PID-16 = U when required; PV1-8 populated from attending/ordering rules; admit/discharge/PV2-28 follow inpatient + blank-admit rules; guarantor/subscriber name & relationship defaults match request.
- PerfSite LC charges stripped / reported as kickouts.
- No regressions for existing NHL POT/FRK/PAT and IRL GUX/CAX peers.

9. Open questions

- Final SOFTWAREID for Catholic Medical given 513 collision with FPS CNL.
- Exact FileNameRestriction regexes from sample feed names.
- Full CLIENT_CODES / strip-location row lists from the workbooks (beyond the single default CLIENT_SPLITS row).
- Whether NHL CAT must force marital U and SE/CH/UN the same way later IRL expanses do.
- Whether blank-admit → first charge date must be applied in route 1 (GLF-style) or only in ADT PV1/PV2.

Generated for PilotFish Sandbox / MedReceivables eiPlatform planning. Validated against current eip-root-fromTEST and H2 medreceivables.mv.db schema.