Techno-economic validation of distributed grain monitoring

"Techno-economic validation of "Distributed Predictive Grain Monitoring." Tech: Compare CO2/VOC vs Temp (lead-time), Distributed vs Point sensing (hotspots), and LoRa vs WiFi penetration through grain. Validate "Rate of Change" logic. Econ: Contrast industrial costs vs small-farmer budgets. Find avg loss per ton & estimated ROI. Verdict: Is this solved or is there a cost/accuracy gap? Provide the technical & financial justification for a low-cost prototype." *Generated by LeapSpace, Sat Oct 10 2026*

Distributed Predictive Grain Monitoring at a Glance

Key Findings Table

Question	Evidence-based finding	Relevant context	Citations
CO2/VOC vs temperature for earliest warning	CO2 usually rises before temperature becomes informative in localized wet/spoilage conditions, and VOCs can provide additional lead time for biochemical deterioration; however, reliability is crop-dependent and formal alarm metrics are scarce.	Wheat/corn evidence is favorable; rapeseed evidence is less supportive.	[1] [2] [3] [4] [5] [6]
Rate-of-change vs static thresholds	Trend-based logic is technically well motivated because respiration and VOC signals evolve dynamically; static thresholds alone are likely weaker, but derivative alarms are not yet strongly validated with sensitivity/specificity data.	Strong rationale, weak formal validation.	[5] [7] [8] [9] [10] [11]
Distributed vs point sensing for hotspots	Sparse point probes can miss distant hotspots until they grow, while distributed sensing or richer spatial reconstruction improves anomaly localization and coverage.	Direct missed-hotspot-rate comparisons are still rare.	[1] [12] [13] [14] [15] [16] [17] [18]

Question	Evidence-based finding	Relevant context	Citations
LoRa vs WiFi through grain	No direct grain-bulk comparison was found, but surrogate obstruction studies consistently favor LoRa for low-power, long-duration, obstruction-tolerant sensing; WiFi may be useful where power and throughput matter more.	Verdict is extrapolated, not directly proven in grain bins.	[19] [20] [21] [22] [23] [24] [25]
Economic case	The prevention opportunity is clearly large: storage losses are often reported at 10%-20% globally and higher in poor storage, while grain discounts of $0.10-$0.85 per bushel are documented.	Exact per-bin ROI and per-ton averages are underreported.	[26] [27] [28] [29] [30] [31]
Industrial vs smallholder fit	The literature supports a two-tier market: industrial systems emphasize dense/full-field monitoring, while low-budget users need simpler RH/temperature/moisture tools and low-cost probes.	Different tiers appear more realistic than one universal system.	[14] [32] [33] [34] [35] [36]
Overall verdict	The concept is technically credible but not fully solved; the remaining gap is field-validated, affordable, low-maintenance deployment with quantified false alarms and ROI.	Best justification is for a low-cost prototype, not a claim of commercial closure.	[6] [12] [19] [37] [38]

Direct Answer

Verdict: distributed predictive grain monitoring is **not fully solved**. The strongest technical evidence supports **CO2 + temperature + RH** as a better early-warning stack than temperature-only monitoring, especially for localized wet pockets or spoilage that temperature cables may miss; VOCs may add lead time in some cases, but are less deployment-mature [1] [4] [5] [13].

For **hotspot detection**, distributed or spatially richer sensing addresses a genuine weakness of point probes: conventional cables have limited spatial sensitivity, so distant hotspots may remain invisible until they become large [15] [16]. For **wireless**, the evidence does **not** include direct LoRa-vs-WiFi tests through bulk grain, but the best available obstruction studies make **LoRa the more defensible prototype choice** because it is repeatedly preferred for low-power, long-duration sensing under attenuating conditions [19] [21] [22] [23].

Economically, the prototype case is strong even though commercial ROI data are thin: reported storage losses are often large, and even low-cost preventive practices can avoid discounts of **$0.10-$0.85 per bushel** [26] [31]. However, the evidence does **not** support a single defensible "average loss per ton" across crops and storage types without adding external price assumptions [26] [27] [28] [29] [30].

Best prototype justification: build a **low-cost distributed system with sparse nodes measuring CO2, temperature, and RH, communicating by LoRa, using rate-of-change plus simple multivariate anomaly scoring**. That directly targets the main unresolved gap: affordable early warning with better hotspot sensitivity than temperature-only cables, without the cost/complexity of industrial imaging systems [11] [16] [22] [36] [38].

Confidence level: High - the broad direction is well supported across multiple sources, though exact performance and ROI magnitudes remain under-quantified [6] [37].

Study Scope

This report synthesizes evidence on stored-grain spoilage sensing, hotspot localization, wireless communication in obstructed/agricultural settings, and storage economics, primarily from studies spanning roughly **2010-2025**, with emphasis on pilot silos, grain bins, storage reviews, sensing experiments, and agricultural IoT deployment literature [6] [14] [39] [40].

Assumptions & Limitations

- No direct **LoRa vs WiFi through grain bulk** experiment was retrieved, so the radio comparison is an extrapolation from surrogate obstruction studies rather than a grain-specific benchmark [19] [24].
- The literature provided does not support a universal **average loss per ton** or a universal **per-bin CAPEX/OPEX/payback** figure for distributed predictive systems [6] [37] [41].
- Rate-of-change logic is strongly motivated, but the retrieved studies rarely report **ROC/AUC, sensitivity, specificity, or false-alarm rates** under full field conditions [6] [10] [11].

Suggested Further Research

- Direct full-bin trials comparing **CO2/VOC vs temperature-only** with numeric lead-time and false-alarm metrics [6].
- Head-to-head **LoRa, WiFi, Zigbee, sub-GHz** propagation tests through grain vs fill depth, moisture, and antenna placement [19].

- Controlled validation of **rate-of-change alarms** against static thresholds during aeration and ambient swings [9] [10].
- Techno-economic studies with **per-bin CAPEX, OPEX, calibration labor, and avoided-loss ROI** by storage scale [37] [41].
- Smallholder willingness-to-pay studies for predictive spoilage monitoring beyond moisture-only tools [34] [42].

Full Report

Introduction and Decision Framing

Stored grain monitoring matters because spoilage can develop locally, spread before it becomes visually obvious, and impose both quantity losses and market-quality discounts [31] [43]. The decision here is not whether monitoring is useful in general, but whether a **distributed predictive** approach adds enough technical value over simpler alternatives to justify a **low-cost prototype** now [6] [12] [38].

The evaluation criteria are:

1. **Lead time**: does CO2 or VOC sensing warn earlier than temperature-only sensing? [1] [4]
2. **Spatial sensitivity**: does distributed sensing reduce hotspot-miss risk relative to sparse probes? [15] [16]
3. **Connectivity feasibility**: can a practical low-power radio architecture function in obstructed storage environments? [22] [24]
4. **Alarm logic quality**: are trend/rate-of-change methods more defensible than static thresholds? [9] [11]
5. **Economic plausibility**: are avoided losses large enough to justify a lower-cost deployment tier? [26] [31] [36]

Confidence level: High - these decision criteria directly match the retrieved literature and the user's target trade-offs [6] [38].

Foundational Context

Grain spoilage is driven by interactions among **temperature, moisture/water activity, respiration, fungal growth, and intergranular gas composition** [43]. That mechanism explains why different sensing modes behave differently:

- **Temperature** is useful but spatially local and relatively slow to spread through bulk grain [5] [15].
- **CO2** reflects respiration and microbial/metabolic activity, and is argued to diffuse much faster than heat, making it a plausible earlier bulk indicator [5].

- **VOCs** can reflect biochemical deterioration before visible spoilage or regulatory toxin thresholds are reached [4] [44] [45].
- **Distributed sensing** matters because spoilage often begins as a local wet pocket or moisture anomaly rather than a uniform bin-wide event [1] [14].

This mechanism-level view supports the core concept of predictive monitoring: use **faster-changing chemical indicators** plus **spatial coverage** to detect local deterioration sooner than conventional temperature cables alone [1] [13].

Confidence level: High - the mechanistic rationale is directly and repeatedly supported [43].

Technical Evidence

CO2/VOC versus temperature for early spoilage warning

The strongest pattern in the evidence is that **CO2 often gives earlier warning than temperature-only sensing** in stored wheat and corn contexts [1] [5] [13]. In a 2025 pilot-scale wheat wet-pocket study, CO2 rose rapidly while temperature remained relatively stable, and the authors concluded CO2 was a faster, more sensitive warning signal for spoilage and mycotoxin risk than temperature plus RH alone [1]. Related corn work reported earlier spoilage hot-spot detection with CO2 than with temperature cables [13]. A stored-wheat paper also explicitly states that CO2 monitoring can detect spoilage earlier than intergranular temperature because CO2 diffuses much faster than heat [5].

VOC evidence points in the same direction for some crops. In maize, a VOC precursor appeared **5 days before** aflatoxin B1 exceeded regulatory limits, suggesting meaningful biochemical lead time even when grain appearance had not changed [4]. VOC/colorimetric approaches also achieved strong classification performance for freshness or storage stage, including up to 100% correct identification in some datasets and 98% correctness in stage classification [44] [45].

However, this is **not universal**. A controlled rapeseed study concluded CO2 was **not** a reliable early-spoilage indicator for that crop, directly limiting any blanket claim that CO2 always dominates [3]. Just as importantly, the field still lacks robust head-to-head reporting of **numeric lead-time gain, ROC/AUC, false-alarm rates, and deployment reliability** in full-size bins [6] [46].

Taken together, these findings suggest that **CO2 is the most mature low-cost step beyond temperature**, while **VOC sensing is promising but less field-validated** for deployable grain-bin systems [6] [44].

Confidence level: High - direction of effect is consistent, but exact performance magnitude is not [1] [6] [13].

Rate-of-change logic versus static thresholds

The case for **rate-of-change** logic is stronger conceptually than statistically validated. Multiple studies show spoilage signals evolving in phases or bursts rather than crossing a single stable concentration threshold [7] [8] [9]. A mini-silo wheat experiment showed respiratory rate stayed low initially and then increased with worsening storage conditions, supporting alarms based on evolving trajectory rather than fixed concentration alone [9]. VOC emissions in maize were highest in the first four days and then declined, again favoring temporal-pattern interpretation [8].

Several papers explicitly argue that continuous CO2 monitoring is preferable because grain respiration can change suddenly and temperature sensors may miss distant hotspots [10] [11]. Machine-learning studies using CO2 with temperature and RH also point toward dynamic multivariate detection rather than single-threshold rules [11] [47] [48].

But the validation gap is clear: the retrieved studies generally **do not report sensitivity, specificity, false alarms, or robustness to ambient swings** for derivative-based alarms [7] [8] [10]. So the correct conclusion is not that rate-of-change logic is proven superior in field deployment, but that it is **the most technically defensible prototype logic to test next** [11].

A practical inference from the evidence is that the prototype should combine:

- **CO2 slope** as an early global change detector, and
- **temperature/RH level and gradient checks** as context filters to reduce false positives [11] [49].

Confidence level: Medium - rationale is strong, formal validation is limited [10] [11].

Distributed sensing versus point sensing for hotspot detection

The hotspot case for distribution is one of the strongest parts of the evidence base. Conventional probe cables have low spatial resolution, with sensor spacing around **1.2 m** and local sensitivity only about **30-60 cm**, which means distant hotspots may not be detected until they are larger [15] [16]. This directly supports the premise that point sensing has a real blind-spot problem.

Several studies then show what richer sensing can add:

- CO2 sensing detected developing spoilage hotspots earlier than temperature cables in stored corn [13].
- Pilot-silo CO2/RH/T monitoring captured a simulated wet pocket via rapid CO2 rise while temperature stayed stable [1].
- Full-scale electromagnetic imaging in an **80 t** grain bin detected localized high-moisture anomalies and tracked a moisture region over **10 days** [14].
- Sparse-sensor field reconstruction methods achieved low temperature/humidity error, including temperature MAE below **0.30 °C** and RMSE below **0.35 °C**, and another reconstruction method held deviation to **≤0.5 °C** with SSIM above **0.97** [17] [18].

What is still missing is direct reporting of **missed-anomaly rate**, **detection delay** versus conventional cables, or **actual avoided spoilage outcomes** under matched field conditions [12] [14]. Still, the available evidence is enough to support the narrower claim that **distributed or spatially enhanced monitoring solves a real sensing-geometry weakness of point probes** [16] [18].

Confidence level: High - the spatial limitation of point probes is directly evidenced, even if outcome metrics are sparse [15] [16].

LoRa versus WiFi penetration and deployment reliability

The radio evidence is the weakest on direct grain relevance, because **no retrieved study directly compares LoRa and WiFi inside grain bins or bulk grain** [19] [50]. That gap must be stated plainly.

Even so, the surrogate evidence is directionally useful. Across buried/soil, vegetation, obstructed indoor, and NLoS studies, LoRa performance degrades with depth, moisture, and obstruction, but remains workable with appropriate parameters such as lower frequencies, higher spreading factors, higher antenna placement, or relays [24] [25] [51] [52]. Some underground-to-aboveground tests reported **99.8% packet delivery ratio** despite strong attenuation [21]. LoRaWAN is repeatedly favored over WiFi when **power consumption and network lifetime** matter most [22] [23], and reviews describe multi-year battery life for low-rate sensing use [53] [54].

WiFi, by contrast, is reported as strong for connectivity, transmission precision, and coverage in some agricultural monitoring experiments, but not as the most power-efficient option [20]. For a grain-bin prototype sending periodic scalar measurements such as CO2, temperature, and RH, the literature therefore supports **LoRa over WiFi on maintenance economics**, not on grain-specific propagation proof [39] [55].

This pattern implies a practical decision:

- choose **LoRa** for embedded, battery-powered, low-duty-cycle nodes;
- use WiFi only where power is available and high-throughput/local backhaul is needed [22] [23].

Confidence level: Medium - deployment logic is well supported, but grain-bulk propagation remains untested in the retrieved evidence [19] [22].

Economic Evidence

Loss baseline and avoided-loss potential

The economic opportunity is credible because documented storage losses are large enough that even partial prevention can matter. Reviews report **10%-20% global stored-grain losses**, **20%-50%** in developing countries, and up to **40%** under poor storage/handling [26]. In smallholder maize systems, insect damage rose to **33.4%** and weight loss to **5%** over 32 weeks [27]. Traditional or non-hermetic storage often shows severe damage escalation, including cases such as **47.3%** damage in a non-lined traditional granary versus below **10%** with hermetic protection [28], and maize weevil damage rising to **9.25%** at 18% moisture in non-hermetic storage while hermetic storage kept damage below **0.3%** [29].

The most directly monetizable figure in the retrieved set is the documented market discount of **$0.10-$0.85 per bushel**, with sanitation practices costing less than **$0.001 per 27.3 kg bushel** while avoiding contamination, insect, and mold discounts [31]. That does not translate to a universal per-ton loss without crop-price assumptions, but it clearly shows that **small quality improvements can have outsized economic effect** [31].

So the evidence supports an ROI baseline framed as:

- **avoid quantity loss** from spoilage/damage, and/or
- **avoid price discounts** from contamination or downgraded quality [31] [56].

Confidence level: High - loss severity is strongly supported, though not as one unified per-ton dollar figure [26] [31].

Industrial cost and payback expectations

The literature does **not** provide a defensible universal hardware cost per bin, maintenance cost, or exact payback for distributed predictive grain monitoring [6] [41] [57]. It repeatedly says current advanced systems are constrained by equipment cost, maintenance, calibration burden, and deployment feasibility, and many remain at prototype or pilot stage [37].

The closest payback figure is from a review stating that most integrated monitoring platforms recover costs in about **8-14 months**, driven by lower spoilage, lower labor, and improved grain quality [40]. That is useful as directional evidence, but not a full commercial ROI model. More generic predictive-maintenance literature is even more optimistic, citing very short payback and high ROI, but those figures are not grain-storage-specific and should not be overgeneralized [58].

Accordingly, the industrial conclusion is narrow: **the business case is plausible, but the market still lacks transparent, field-validated techno-economic data for distributed predictive grain systems** [6] [37].

Confidence level: Medium - the barriers are well documented, the exact economics are not [37] [41].

Low-budget farmer affordability and device trade-offs

For low-budget users, the literature clearly shows that **cheap tools can be useful if expectations are matched to risk and calibration limits** [42] [59]. Examples include:

- commercial moisture meters with oven-reference differences of **0.1%-3.7%** [60];
- a low-cost hygrometer approach that distinguished maize moisture levels and was considered suitable for smallholders [61];
- RH/temperature algorithms estimating grain moisture to within **±1%** for at least **95%** of samples across 10 grains [62];
- a low-cost paddy probe meter costing about **US$100** versus **US$750 to >US$4,000** for imported brands, while showing strong calibration and low error [35].

However, affordability ceilings are also stark. In one Kenya study, traders were willing to pay only **$0.28** for hygrometer testing and **$0.39** for commercial moisture meter service, and only **15%** bought the hygrometer in a take-it-or-leave-it auction [34]. This implies that smallholder adoption depends not just on technical utility, but on **extreme price compression and low-complexity operation** [34] [42].

Taken together, this supports a **two-tier market**: industrial users may buy richer systems for spatial certainty, while smallholders need minimum-viable tools that deliver acceptable risk reduction per dollar [32] [35].

Confidence level: High - the affordability split is strongly evidenced [34] [35].

ROI logic for a low-cost prototype

Because exact prototype cost is not given in the evidence, the most defensible ROI statement is a **break-even logic**, not a fabricated percentage. The literature supports three propositions:

1. Losses and discounts can be economically meaningful even at modest percentages [26] [31].
2. Monitoring systems are believed to recover cost within months in many cases [40].
3. A minimum viable sensor stack of **temperature + RH + CO2** is specifically supported as a cost-effective field unit architecture [36] [38].

So the prototype is economically justified if it can prevent either:

- a small fraction of the documented **10%-20%** typical storage loss range, or
- even a subset of the documented **$0.10-$0.85/bushel** quality discount exposure [26] [31].

Inferred: Taken together, these findings suggest that a low-cost prototype does not need industrial full-field certainty to be worthwhile; it only needs to outperform temperature-only practice enough to trigger earlier intervention on a limited number of bins or batches [36] [38].
Confidence level: Low - this is a reasoned inference because exact prototype CAPEX/OPEX and prevented-loss values are not directly reported [37].

Verdict and Prototype Justification

Solved versus gap assessment

This problem is **technically feasible but not commercially closed**. The evidence supports the concept of predictive multimodal monitoring, especially **CO2 plus temperature/RH**, and supports richer spatial coverage for hotspot detection [1] [13] [18]. But three gaps remain:

- **validation gap**: few full-size field studies with alarm-performance metrics [6];
- **radio gap**: no direct LoRa-vs-WiFi grain-bulk penetration evidence [19];
- **economic gap**: sparse per-bin CAPEX/OPEX and quantified avoided-loss ROI [37] [41].

So the literature does **not** support saying the problem is already solved. It supports saying there is a **cost/accuracy/validation gap** that a targeted prototype could address [38].

Confidence level: High - this conclusion aligns closely with the strongest cross-source pattern [6] [37].

Minimum viable prototype recommendation

The most defensible low-cost prototype is:

- **Sensors:** temperature + RH at distributed nodes, plus fewer **CO2 anchor nodes** [36] [38] [49]
- **Logic:** rate-of-change on CO2, combined with absolute level and local T/RH context [9] [11]
- **Network: LoRa** for low-duty-cycle battery-powered nodes [22] [39] [54]
- **Deployment philosophy:** sparse distribution rather than full-field imaging, to target the point-sensing blind spot at much lower cost [16] [32]

This architecture is justified because it captures the highest-value technical features from the literature without inheriting the cost and complexity of electromagnetic imaging or dense industrial systems [32] [33] [36].

Final technical and financial justification

Technically, the prototype is justified because:

- CO2 generally gives earlier warning than temperature-only sensing in relevant storage scenarios [1] [13].

- Point probes can miss distant hotspots; sparse distribution improves spatial sensitivity [15] [16].
- Rate-of-change logic matches the dynamic nature of respiration and spoilage signals [9] [11].
- LoRa is the better low-maintenance prototype network choice despite missing grain-specific radio data [22] [23].

Financially, the prototype is justified because:

- storage losses and quality discounts are large enough that early prevention has credible value [26] [31];
- low-cost sensing tiers already show workable affordability/accuracy trade-offs for budget-constrained users [35] [62];
- current advanced systems remain too under-validated or too costly for broad low-budget adoption, leaving room for a cheaper middle ground [37] [41].

Bottom line: Go for a low-cost prototype. The evidence supports a real unmet niche: **affordable, distributed, predictive warning that improves on temperature-only cables but avoids industrial full-field system cost** [6] [38].

Overall confidence level: High - the strategic verdict is strongly supported, though precise performance and ROI numbers still require prototype-stage field validation [6] [19] [37].

References

1. Kiaitsi, E., Zanardi, S., Sulyok, M., (...), Garcia-Cela, E. (2025) Real-time CO2 monitoring for early detection of grain spoilage and mycotoxin contamination. *Journal of the Science of Food and Agriculture*. https://doi.org/10.1002/jsfa.70151
2. Raudienė, E., Rušinskas, D., Balčiūnas, G., (...), Gailius, D. (2017) Carbon dioxide respiration rates in wheat at various temperatures and moisture contents. *Mapan - Journal of Metrology Society of India*. https://doi.org/10.1007/s12647-016-0202-4
3. Raudienė, E., Gailius, D., Balčiūnas, G., (...), Dobiliene, J. (2018) Precocious rapeseed spoilage detection. *Journal of Physics: Conference Series*. https://doi.org/10.1088/1742-6596/1065/23/232001
4. Li, J., Zhang, W., Sun, Y., (...), He, L. (2025) Effective extraction of aflatoxin B1 and its three precursors by ionic liquid-impregnated covalent triazine polymer for accurately tracking their dynamic changes. *Chemical Engineering Journal*. https://doi.org/10.1016/j.cej.2025.164186
5. Kim, Y., Kang, S., Ajani, O.S., (...), Ha, Y. (2024) Predicting early mycotoxin contamination in stored wheat using machine learning. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2024.102294
6. Ramachandran, R.P. (2022) Integrated approach on stored grain quality management with CO2 monitoring-A review. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2022.101950

7. https://www.sciencedirect.com/science/article/pii/S2196564124000947
8. Żytek, Aleksandra, Rusinek, Robert, Oniszczuk, Anna, Gancarz, Marek (2023) Effect of the Consolidation Level on Organic Volatile Compound Emissions from Maize during Storage. *Materials*. https://doi.org/10.3390/ma16083066
9. Oluwakayode, A., Sulyok, M., Krska, R., Medina, A. (2024) The effect of the interactions of water activity, and temperature on OTA, OTB, and OTα produced by Penicillium verrucosum in a mini silo of natural and inoculated wheat using CO2 production as fungal activity sentinel. *Food Chemistry*. https://doi.org/10.1016/j.foodchem.2024.140590
10. Ubhi, G.S., Sadaka, S. (2015) Temporal valuation of corn respiration rates using pressure sensors. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2015.02.004
11. Cui, H., Wang, S., Yang, X., (...), Wang, S. (2022) Predictive models for assessing the risk of Fusarium pseudograminearum mycotoxin contamination in post-harvest wheat with multi-parameter integrated sensors. *Food Chemistry: X*. https://doi.org/10.1016/j.fochx.2022.100472
12. Zhang, H., Yang, J., Zhu, Y., (...), Li, B. (2026) A Thermal State Field Forecasting Framework for Intelligent Ventilation Decision-Making in Granary Based on a Hierarchical TCN-Mamba Network. *Sensors*. https://doi.org/10.3390/s26175362
13. Ileleji, K.E., Maier, D.E., Bhat, C., Woloshuk, C.P. (2006) Detection of a developing hot spot in stored corn with a CO2 sensor. *Applied Engineering in Agriculture*. https://www.scopus.com/pages/publications/33744469049
14. Asefi, M., Gilmore, C., Jeffrey, I., (...), Paliwal, J. (2017) Detection and continuous monitoring of localised high-moisture regions in a full-scale grain storage bin using electromagnetic imaging. *Biosystems Engineering*. https://doi.org/10.1016/j.biosystemseng.2017.08.015
15. Asefi, M., Jeffrey, I., LoVetri, J., (...), Paliwal, J. (2015) Grain bin monitoring via electromagnetic imaging. *Computers and Electronics in Agriculture*. https://doi.org/10.1016/j.compag.2015.10.016
16. Ramachandran, R.P. (2022) Integrated approach on stored grain quality management with CO2 monitoring-A review. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2022.101950
17. Cao, Y., Duan, S., Yang, W., (...), Wan, A. (2024) A Spatial High - Resolution Reconstruction Model for Warehouse Grain Piles' Temperature and Humidity Fields. *Journal of the Chinese Cereals and Oils Association*. https://doi.org/10.20048/j.cnki.issn.1003-0174.000747
18. Wu, Y., Zhang, J., Li, X., (...), Xu, Y. (2025) Mechanism and Data-Driven Grain Condition Information Perception Method for Comprehensive Grain Storage Monitoring. *Foods*. https://doi.org/10.3390/foods14193426
19. Sinha, S., Pradeep Reddy, G.P., Kim, S.-M., Park, S.-H. (2026) Native AI-based hybrid deep learning for wireless link quality prediction in NTN waterside scenarios. *ICT Express*. https://doi.org/10.1016/j.icte.2025.10.001

20. Hashmi, A.U.H., Mir, G.U., Sattar, K., (...), Hussain, S. (2024) Effects of IoT Communication Protocols for Precision Agriculture in Outdoor Environments. *IEEE Access*. https://doi.org/10.1109/ACCESS.2024.3381522

21. Manzil, I.I.J., Aldhaheri, L., Alshehhi, N., Saeed, N. (2024) Smart Soil Monitoring: Leveraging LoRa-based IoT for Sustainable Agriculture 4.0. *2024 7th International Conference on Signal Processing and Information Security, ICSPIS 2024*. https://doi.org/10.1109/ICSPIS63676.2024.10812616

22. Sadowski, S., Spachos, P. (2020) Wireless technologies for smart agricultural monitoring using internet of things devices with energy harvesting capabilities. *Computers and Electronics in Agriculture*. https://doi.org/10.1016/j.compag.2020.105338

23. Lova Raju, K., Veeramani, V. (2022) Wireless Communication Technologies with IoT-Based Cloud-Enabled Service for Smart Agriculture Monitoring System. *2022 International Conference on Innovative Trends in Information Technology, ICITIIT 2022*. https://doi.org/10.1109/ICITIIT54346.2022.9744230

24. Paolini, C., Komeylian, S., Raghav, R., Sarkar, M. (2023) Measurement of Attenuated LoRa Propagation in Sandy Loam. *Proceedings - IEEE Consumer Communications and Networking Conference, CCNC*. https://doi.org/10.1109/CCNC51644.2023.10060076

25. Di Renzone, G., Parrino, S., Peruzzi, G., (...), Bertoni, D. (2021) LoRaWAN Underground to Aboveground Data Transmission Performances for Different Soil Compositions. *IEEE Transactions on Instrumentation and Measurement*. https://doi.org/10.1109/TIM.2021.3061820

26. Sirohi, Ranjna, Bhat, Mohammad Ishfaq, Singh, Shikhangi, (...), Pandey, Ashok (2022) Sustainable technologies for damaged grains utilisation. *Biomass, Biofuels, Biochemicals*. https://doi.org/10.1016/B978-0-323-89855-3.00012-1

27. Ngwenyama, P., Mvumi, B.M., Stathers, T.E., (...), Siziba, S. (2022) How different hermetic bag brands and maize varieties affect grain damage and loss during smallholder farmer storage. *Crop Protection*. https://doi.org/10.1016/j.cropro.2021.105861

28. Stathers, T., Holcroft, D., Engelbert, M., (...), Marion, P. (2025) The evidence on crop postharvest loss reduction interventions for sub-Saharan African and South Asian food systems: a systematic scoping review update 2024. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2025.102727

29. Mabasso, G.A., Resende, O., Souza, D.G., (...), Leite, L.F. (2024) Physical properties and quality of corn grains stored at different initial moisture contents under hermetic and non-hermetic conditions. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2024.102463

30. Muleta, O.D., Tola, Y.B., Hofacker, W.C. (2021) Assessment of storage losses and comparison of underground and aboveground storage for better stability and quality of maize (zea mays l.) and sorghum (sorghum bicolor l.) grains in selected districts of jimma zone, Ethiopia. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2021.101847

31. Tilley, Dennis R., Casada, Mark E., Langemeier, Michael R., (...), Arthur, Frank H. (2015) Economic Analysis for Commingling Effects of Insect Activity in the Elevator Boot Area. *Journal of Economic Entomology*. https://doi.org/10.1093/jee/tov222
32. Asefi, M., Jeffrey, I., LoVetri, J., (...), Paliwal, J. (2015) Grain bin monitoring via electromagnetic imaging. *Computers and Electronics in Agriculture*. https://doi.org/10.1016/j.compag.2015.10.016
33. Gilmore, C., Asefi, M., Paliwal, J., LoVetri, J. (2017) Industrial scale electromagnetic grain bin monitoring. *Computers and Electronics in Agriculture*. https://doi.org/10.1016/j.compag.2017.03.005
34. Fuller, A.J., Ricker-Gilbert, J. (2021) Estimating Demand for Third-party Quality Testing in Rural Grain Markets: Evidence from an Experimental Auction for Measuring Moisture Content in Kenya. *Journal of African Economies*. https://doi.org/10.1093/jae/ejab002
35. Joaquin, A.C., Ramos, M.E.V., Martinez, R.C. (2019) Development and performance evaluation of a grain probe moisture meter for paddy. *International Journal of Environmental Science and Development*. https://doi.org/10.18178/ijesd.2019.10.10.1198
36. Danao, M.G.C., Zandonadi, R.S., Gates, R.S. (2015) Development of a grain monitoring probe to measure temperature, relative humidity, carbon dioxide levels and logistical information during handling and transportation of soybeans. *Computers and Electronics in Agriculture*. https://doi.org/10.1016/j.compag.2015.10.008
37. Li, X., Guo, H., Lu, Y., (...), Wu, W. (2026) A data-driven spatiotemporal scale atlas of grain temperature fields in granaries: Temporal memory and local spatial coupling. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2026.103030
38. Lutz, É., Coradi, P.C. (2022) Applications of new technologies for monitoring and predicting grains quality stored: Sensors, Internet of Things, and Artificial Intelligence. *Measurement: Journal of the International Measurement Confederation*. https://doi.org/10.1016/j.measurement.2021.110609
39. Gómez, Yesica Tatiana Beltrán, Cerquera, Manuel Ricardo Pérez, Colorado, Julian D. (2026) Smart Irrigation through IoT and Sensor Fusion: A Multiscale Review for Precision Agriculture. *Crop Design*. https://doi.org/10.1016/j.cropd.2026.100164
40. Kwadzokpui, B.A., Lin, H., Johnson, N.A.N., (...), Ekumah, J.-N. (2026) Advanced non-destructive detection methods for monitoring biological factors in post-harvest maize losses during transportation and storage. *Journal of Food Composition and Analysis*. https://doi.org/10.1016/j.jfca.2026.109212
41. https://www.sciencedirect.com/science/article/pii/S2193413426007975
42. Vera Zambrano, M., Dutta, B., Mercer, D.G., (...), Touchie, M.F. (2019) Assessment of moisture content measurement methods of dried food products in small-scale operations in developing countries: A review. *Trends in Food Science and Technology*. https://doi.org/10.1016/j.tifs.2019.04.006
43. Magan, N., Aldred, D. (2007) Post-harvest control strategies: Minimizing mycotoxins in the food chain. *International Journal of Food Microbiology*. https://doi.org/10.1016/j.ijfoodmicro.2007.07.034

44. Liu, Y., Ren, S., Sun, Q., (...), Zhang, Y. (2024) Analysis of Characteristics Volatile Organic Compounds and Quality Evaluation of Wheat Kernels Storage. *Journal of Nuclear Agricultural Sciences*. https://doi.org/10.11869/j.issn.1000-8551.2024.11.2155

45. Liang, Y., Lin, H., Kang, W., (...), Chen, Q. (2023) Application of colorimetric sensor array coupled with machine-learning approaches for the discrimination of grains based on freshness. *Journal of the Science of Food and Agriculture*. https://doi.org/10.1002/jsfa.12777

46. Leal, M.M., Rodrigues, D.M., de Moraes, R.S., (...), Coradi, P.C. (2023) Monitoring of intergranular variables for predicting technical breakage of wheat grains stored in vertical silos. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2023.102115

47. de Sousa, Inês Gonçalves, Oliveira, Jorge, Mexia, António, (...), Brites, Carla (2023) Advances in Environmentally Friendly Techniques and Circular Economy Approaches for Insect Infestation Management in Stored Rice Grains. *Foods*. https://doi.org/10.3390/foods12030511

48. https://www.sciencedirect.com/science/article/pii/S1936976X23000920

49. Mabasso, G.A., Resende, O., Souza, D.G., (...), Leite, L.F. (2024) Physical properties and quality of corn grains stored at different initial moisture contents under hermetic and non-hermetic conditions. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2024.102463

50. Aby, G.R., Maier, D.E. (2023) DISTRIBUTION OF BRICK- VERSUS SPHERICAL-SHAPED WIRELESS SENSORS AS A FUNCTION OF GRAVITY-FILLING A STORAGE SILO AND THEIR RECOVERY FROM THE CORN GRAIN MASS DURING UNLOADING. *Applied Engineering in Agriculture*. https://doi.org/10.13031/aea.15276

51. Hardie, Marcus, Hoyle, Donald (2019) Underground Wireless Data Transmission Using 433-MHz LoRa for Agriculture. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s19194232

52. Tiusanen, J. (2005) Attenuation of a soil scout radio signal. *Biosystems Engineering*. https://doi.org/10.1016/j.biosystemseng.2004.10.013

53. Thakur, A.S., Imtiaz, M.H. (2025) Long Range (LoRa) Agriculture Network in Northern New York: A Scoping Review. *2025 IEEE 16th Annual Ubiquitous Computing, Electronics and Mobile Communication Conference, UEMCON 2025*. https://doi.org/10.1109/UEMCON67449.2025.11267659

54. Tighe, M., Novais, J.J.M., Demattê, J.A.M., (...), Suarez, L.A. (2025) Sensing and geotechnologies for soil characterization. *Unlocking the Secrets of Soil*. https://doi.org/10.1016/B978-0-443-29879-0.00001-0

55. Raza, U., Kulkarni, P., Sooriyabandara, M. (2017) Low Power Wide Area Networks: An Overview. *IEEE Communications Surveys and Tutorials*. https://doi.org/10.1109/COMST.2017.2652320

56. Kotu, B.H., Abass, A.B., Hoeschle-Zeledon, I., (...), Bekunda, M. (2019) Exploring the profitability of improved storage technologies and their potential impacts on food security and income of smallholder farm households in Tanzania. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2019.04.003

57. Islam, M.S., Sadmani, S., Rostom Ali, M.R., (...), Alam, M.M. (2024) Remotely controlled smart monitoring system of hermetic paddy storage to reduce postharvest losses in Bangladesh. *Smart Agricultural Technology*. https://doi.org/10.1016/j.atech.2024.100468

58. Taylor, James I. (1988) Accurate predictive maintenance programs. *Tappi journal*. https://www.scopus.com/pages/publications/0024104692

59. Schwamback, D., Persson, M., Berndtsson, R., (...), Wendland, E.C. (2023) Automated Low-Cost Soil Moisture Sensors: Trade-Off between Cost and Accuracy. *Sensors*. https://doi.org/10.3390/s23052451

60. Jafari, A., Tumbleson, M., Rausch, K.D. (2022) Evaluation of grain moisture measurement methods suited for developing countries. *Journal of Stored Products Research*. https://doi.org/10.1016/j.jspr.2022.102001

61. Tubbs, T., Woloshuk, C., Ileleji, K.E. (2017) A simple low-cost method of determining whether it is safe to store maize. *AIMS Agriculture and Food*. https://doi.org/10.3934/agrfood.2017.1.43

62. Delahunt, C.B., Wang, W., Ghionea, S., (...), Friend, M. (2020) Algorithms to predict moisture content of grain using relative humidity time-series. *2020 IEEE Global Humanitarian Technology Conference, GHTC 2020*. https://doi.org/10.1109/GHTC46280.2020.9342933