
GENERAL NOTES UNLESS OTHERWISE NOTED:

1. REFERENCE RWWeight.STEP FOR MODEL BASE DEF
2. REMOVE ALL BURRS AND SHARP EDGES R0.050 MM MAX
3. OVERALL PROFILE TOLERANCE ⌓ | 0.1 | A | B | C | TO A MINIMUM GRID OF 5MM UNLESS OTHERWISE SPECIFIED
4. INTERNAL CORNERS RADIUS IS 0.2MM MAXIMUM



MATERIAL: **BRASS**	UNLESS OTHERWISE SPECIFIED	DRAWN BY	Hayden Reinhold	1/5/2022		
FINISH: **125**	DECIMAL: .X ± 0.1, .XX ± 0.01, .XXX ± 0.005 — ANGULAR: .X ± 0.1, .XX ± 0.01	CHECKED		1/5/2022		
WEIGHT: **29.75g**	INTERPRET PER ASME Y14.5-2018	ENG APPR.				
	DO NOT SCALE DRAWING	MFG APPR.				
		+X 3U Frame			DWG. NO. **RWWeight**	
		UNITS: **MM**	REVISION: **A**	FORMAT: **B**	SCALE: **3:1**	PAGE: **1/2**

SOLIDWORKS Educational Product. For Instructional Use Only.