
Layer Stack Legend



Material	Layer	Thickness	Dielectric Material	Type	Gerber
	Top Overlay			Legend	GTO
Surface Material	Top Solder	0.025mm	Solder Resist	Solder Mask	GTS
Copper	Top Layer	0.036mm		Signal	GTL
		1.498mm	*FR-4*	*Dielectric*	
Copper	Bottom Layer	0.036mm		Signal	GBL
Surface Material	Bottom Solder	0.025mm	Solder Resist	Solder Mask	GBS
	Bottom Overlay			Legend	GBO

Total thickness: 1.620mm

Requirements
- IPC Class 2
- Solder Type: Lead-Free
- Flux Type: Water Soluble
- Compliance: RoHS
- Bare board 100% continuity and open test
- ~1.62mm FR-4, 2-Layer stackup, 1 oz. copper all layers, ENIG, Green LPI solder mask, white legend.
- Tented vias on both sides of board.

Special Instructions
- Remove pin 7 on J1 and J5 prior to assembly.
- Pre-Bake PWBs and/or any integrated circuits (per manufacturer's guidelines) that are not in moisture barrier packaging or where humidity indicator indicates moisture.
- Assembly quantity is per Purchase Order.
- Trim leads on all through-hole components to 0.5mm to 1.5mm from PCB.
- Aqueous cleaning only, do not use alcohol.
- Inspect workmanship per IPC-601 Class 2.
- Anti-Static precautions must be observed when handling boards and components.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AUTERION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF

PROPRIETARY AND CONFIDENTIAL

NEXT ASSY	USED ON	
APPLICATION		

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL±
ANGULAR: MACH± BEND ±
TWO PLACE DECIMAL ±
THREE PLACE DECIMAL ±
INTERPRET GEOMETRIC TOLERANCING PER:
MATERIAL
FINISH
DO NOT SCALE DRAWING

	NAME	DATE
DRAWN		5/17/2020
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		

COMMENTS:

AUTERION

TITLE
PIXHAWK DEBUG ADAPTER MINI

SIZE	DWG. NO.	
	712040-500-RC01	

SCALE: 1:1	WEIGHT:	SHEET 2 OF 9