

Notes 9

grep

- Used to search the text of a file line by line.

Formula: `grep + option + search criteria + file(s)`

Example: `grep + 'dracula'`

awk

- Used to scan and format text data line by line.

Formula: `awk + options + {awk command} + file(s)`

Example: `awk + '{print $1}' + ~/Documents/Csv/cars.csv`

sed

- Used to perform operations on files and standard output.

Formula: `sed + options + sed script + file(s)`

Example: `sed + 's/false/true/g' + ~/Documents/sample_files/Json/joke.json`

How to use the pipe (|) to redirect the output of a command to another.

- Used after a command to redirect it's standard output to the standard input of another. Allows you to chain commands together so the output of one becomes the input of the next.

Usage: `command_1 | command_2 | command_3 | ... | command_N`

Examples:

- Count and list files in a directory.
 - `ls | wc -l`
- Sort and remove duplicates
 - `cat colors.txt | sort | uniq`
- Use grep to look for a string in a particular man page
 - `man ls | grep "string"`

How to save the output of a command to a file with (>).

- Used after a command to save the standard output of a command to a file.

Usage: `Command output + > + file`

Examples

- Save the output of a command to a file.
 - `ls -lA ~ > file.txt`

- Save the error generated by a command to a file.
 - `ls -lA downloads/ 2> error-of-ls`
- Save the error to a file and the success to another.
 - `ls -lA downloads/ Pictures > success.txt 2> error.txt`

How to append the output of a command to a file.

- Use **>>** after a command to add to a file instead of overwriting it's content

Usage: `command + >> + filename`

Examples

- Append a directory listing to a file.
 - `ls -lA >> allmyfiles.txt`
- Add system information to a log file.
 - `uname -a >> system_info.log`
- Add the current date and time to a log file.
 - `date >> system_info.log`