

Chinook Bill of Materials

10 pc. 4' x 8' sheet 1/2" thick lauan plywood (actually it's 7/16")
8 pc. 12' long 1" x 2-1/2" clear pine (or fir) molding for rub rail, chine log & sheer clamp
32 ft 1-1/4" x 3 1/2" clear fir for frames (random lengths)
1 pc. 4 ft. 1-1/4" x 11-1/2" clear fir for aft two frame bottoms
1 pc. 16 ft - 1-1/2" x 5 1/2" clear fir for keelson (one piece)
1 pc. 8' 1-1/2" x 11-1/2" clear fir for motor mount, gussets and well sides.
12 dozen #8 x 1 1/4" stainless steel wood screws
4 dozen #10 x 2" stainless steel wood screws
16 ea. #10 x 4" flat head stainless machine screws, washers & nuts
8 ea. 1/4" x 3" stainless steel lag screws
5 - gallon epoxy
A dozen or so inexpensive disposable paint brushes of various widths
Rubber gloves
Respirators (for sanding dust) & safety glasses

In addition, for the strongback and frame jig, you'll need the following materials:

1 - 16' fir 4x6s
3 - 8' 2x4 studs
3 - 3' fir 4x4s
6 - Metal Tee Brackets
1 sheet 1/2" shop ply
Some scraps of 1x2 furring strip
Handful of 16d box nails
Handful of 2d box nails
Woodworking (or white) glue