

I used `chmod +x q1.sh` to compile the code and then used `bash` to execute the code.

Below is shown the output of the code.

```
Alert!!
Disk usage value: 83.00
Disk usage exceeded
Alert!!
CPU usage value: 80.0
CPU usage exceeded
Alert!!
Disk usage value: 83.00
Disk usage exceeded
Alert!!
CPU usage value: 77.8
CPU usage exceeded
Alert!!
Disk usage value: 83.00
Disk usage exceeded
Alert!!
CPU usage value: 100.0
CPU usage exceeded
Alert!!
Disk usage value: 83.00
Disk usage exceeded
Alert!!
CPU usage value: 75.0
CPU usage exceeded
Alert!!
Disk usage value: 83.00
Disk usage exceeded
Alert!!
CPU usage value: 100.0
CPU usage exceeded
Alert!!
Disk usage value: 83.00
Disk usage exceeded
Alert!!
CPU usage value: 80.0
CPU usage exceeded
Alert!!
Disk usage value: 83.00
Disk usage exceeded
Alert!!
CPU usage value: 100.0
CPU usage exceeded
Alert!!
Disk usage value: 83.00
Disk usage exceeded
Alert!!
CPU usage value: 100.0
```

These alerts are also being stored in the `Arham.log` file.

```
alert() #just printing alert here
```

```
{
```

```
    message="Alert!!"
```

```
    echo "$message" | tee -a "$log_file" # i used tee -a so that the terminal also shows the echo
statements and then they are aslo written in the log file named arham.log
```

```
}
```

***** the above is the alert function which simply prints alert! On the terminal and writes it down to the log file**

setting the threshold values below

```
disk_threshold=30
```

```
cpu_threshold=30
```

```
memory_threshold=10
```

```
log_file="/home/arham/Desktop/OS thoery/Assignment # 1/arham.log"
```

```
max_log_size=10M
```

```
while true; do
```

```
    # data is stored in the file after each print in terminal
```

```
    # Disk usage calculations and then writing alert call
```

```
    disk_usage=$(df -h --output=pcent / | sed '1d' | awk '{printf "%.2f", $1}') #df displays disk usage
and used output=pcent to output the % only
```

```
    if (( $(echo "$disk_usage > $disk_threshold" | bc -l) )); then # checking the threshold using if , if
is doing the same thing throughout the code
```

```
        alert "Disk usage exceeds $disk_threshold%: $disk_usage"
```

```
        echo "Disk usage value: $disk_usage" | tee -a "$log_file"
```

```
        echo "Disk usage exceeded" | tee -a "$log_file"
```

```
fi
```

CPU Usage Monitoring and then calling alert

```
cpu_usage=$(top -bn1 | grep "Cpu(s)" | sed "s/.*, *\([0-9.]*\)%* id.*\1/")
```

```
if (( $(echo "$cpu_usage > $cpu_threshold" | bc -l) )); then
```

```
    alert "CPU usage exceeds $cpu_threshold%: $cpu_usage%"
```

```
    echo "CPU usage value: $cpu_usage" | tee -a "$log_file"
```

```
    echo "CPU usage exceeded" | tee -a "$log_file"
```

```
fi
```

Memory Usage Monitoring and then alert is called if it is below threshold, in the above we were checking if it was above threshold

```
free_mem=$(free --mega | awk '/Mem/{print $4}') # free mega displays the free memory
```

```
total_mem=$(free --mega | awk '/Mem/{print $2}')
```

```
memory_usage=$(echo "scale=2; ($total_mem - $free_mem) * 100 / $total_mem" | bc)
```

```
if (( $(echo "$memory_usage < $memory_threshold" | bc -l) )); then
```

```
    alert "Memory usage falls below $memory_threshold%: $memory_usage%"
```

```
    echo "Memory usage value: $memory_usage" | tee -a "$log_file"
```

```
    echo "Memory usage exceeded" | tee -a "$log_file"
```

```
fi
```

Log Rotation means that new file is made when old one is filled up to 10mb

```
if [ -f "$log_file" ]; then # -f tells us if the path to the file is the one we need or not
```

```
    log_size=$(du -b "$log_file" | awk '{print $1}')
```

```
    if [ "$log_size" -gt "$(( $(echo "$max_log_size" | tr -d '[:alpha:]') * 1024 ))" ]; then
```

```
        mv "$log_file" "$log_file.old"
```

```
touch "$log_file"
```

```
alert "Log file rotated: $log_file"
```

```
fi
```

```
fi
```

```
sleep 10s
```

```
done
```