

```

-- schema-additions.sql
--
-- All DB changes needed for the 8 fixes in this patch set.
-- Run in your Neon console or via drizzle migration.
-- Use CONCURRENTLY for indexes to avoid table locks in production.

-- ——— Fix #4: yt-dlp backoff persistence —————

CREATE TABLE IF NOT EXISTS yt_dlp_backoff (
  youtube_id      TEXT PRIMARY KEY,
  failure_type    TEXT NOT NULL,
  consecutive_fails INTEGER NOT NULL DEFAULT 1,
  retry_after     TIMESTAMPTZ NOT NULL,
  last_failure_at TIMESTAMPTZ NOT NULL DEFAULT NOW(),
  updated_at      TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

CREATE INDEX CONCURRENTLY IF NOT EXISTS idx_yt_dlp_backoff_retry
  ON yt_dlp_backoff (retry_after);

-- ——— Fix #5: Live gate cooldown persistence —————

CREATE TABLE IF NOT EXISTS system_settings (
  key      TEXT PRIMARY KEY,
  value    TEXT NOT NULL,
  updated_at TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

-- ——— Fix #8: Index for channels platform filter —————

CREATE INDEX CONCURRENTLY IF NOT EXISTS idx_channels_platform
  ON channels (platform);

-- ——— Fix #2: Phantom user cleanup —————
-- Inspect before running – make sure these have no data worth keeping

-- Option A: Hard delete (if confirmed safe)
-- DELETE FROM users
-- WHERE id IN ('54374239', 'tiktok_-000hfXLzkfKJGE24wvR-qZP9Pw6iwxLWyeM');

-- Option B: Soft delete (safer – leaves data intact but stops processing)
-- ALTER TABLE users ADD COLUMN IF NOT EXISTS active BOOLEAN DEFAULT true;
-- UPDATE users SET active = false
-- WHERE id IN ('54374239', 'tiktok_-000hfXLzkfKJGE24wvR-qZP9Pw6iwxLWyeM');

-- ——— Fix #6: Migrate Jrt9VPmojMA from hardcoded block to DB —————
-- Run AFTER removing the hardcoded block from the autopilot code

```

```

-- INSERT INTO content_vault_backups (youtube_id, status, error_message, resurrection_count)
-- VALUES ('Jrt9VPmojMA', 'failed', 'Cross-contaminated metadata – migrated from hardcoded', 0)
-- ON CONFLICT (youtube_id) DO UPDATE
--     SET status          = 'failed',
--         error_message    = 'Cross-contaminated metadata – migrated from hardcoded',
--         resurrection_count = 0,
--         retry_after      = NOW() + INTERVAL '48 hours';

-- ——— Fix #1: Add resurrection columns if not already present ———
-- (for tables that the Resurrection Engine targets)

ALTER TABLE youtube_push_backlog
    ADD COLUMN IF NOT EXISTS retry_after          TIMESTAMPTZ,
    ADD COLUMN IF NOT EXISTS resurrection_count    INTEGER DEFAULT 0;

ALTER TABLE pre_encoder_queue
    ADD COLUMN IF NOT EXISTS retry_after          TIMESTAMPTZ,
    ADD COLUMN IF NOT EXISTS resurrection_count    INTEGER DEFAULT 0;

ALTER TABLE shorts_clip_queue
    ADD COLUMN IF NOT EXISTS retry_after          TIMESTAMPTZ,
    ADD COLUMN IF NOT EXISTS resurrection_count    INTEGER DEFAULT 0;

ALTER TABLE content_vault_backups
    ADD COLUMN IF NOT EXISTS retry_after          TIMESTAMPTZ,
    ADD COLUMN IF NOT EXISTS resurrection_count    INTEGER DEFAULT 0;

ALTER TABLE video_metadata_sync_queue
    ADD COLUMN IF NOT EXISTS retry_after          TIMESTAMPTZ,
    ADD COLUMN IF NOT EXISTS resurrection_count    INTEGER DEFAULT 0;

-- ——— Index for resurrection engine performance ———

CREATE INDEX CONCURRENTLY IF NOT EXISTS idx_push_backlog_resurrection
    ON youtube_push_backlog (status, retry_after)
    WHERE status IN ('permanently_failed', 'failed');

CREATE INDEX CONCURRENTLY IF NOT EXISTS idx_vault_backups_resurrection
    ON content_vault_backups (status, retry_after)
    WHERE status IN ('permanently_failed', 'failed', 'download_failed');

```