

```
-- schema-history-fixes.sql (hardened)
-- Run each block manually in Neon console.
-- CREATE INDEX CONCURRENTLY must NOT be inside a transaction block.

-- =====
-- BLOCK 1: autopilot_queue additions
-- =====

-- Fix #9: CHECK STATUS TYPE BEFORE DEPLOYING TS THAT WRITES 'deferred' or 'escalated'
-- Run this first:
--   SELECT pg_typeof(status) FROM autopilot_queue LIMIT 1;
--
-- If result is 'text' → no action needed, proceed.
--
-- If result is a custom enum (e.g. 'autopilot_queue_status'), run:
--   SELECT t.typname
--   FROM pg_type t
--   JOIN pg_attribute a ON a.atttypid = t.oid
--   JOIN pg_class c ON c.oid = a.attrelid
--   WHERE c.relname = 'autopilot_queue' AND a.attname = 'status';
-- Then:
--   ALTER TYPE <enum_name> ADD VALUE IF NOT EXISTS 'deferred';
--   ALTER TYPE <enum_name> ADD VALUE IF NOT EXISTS 'escalated';
-- (These must run OUTSIDE a transaction block in Neon)
-- If app already uses 'needs_human' or 'manual_review', use that instead of 'escalated'.
```

```
ALTER TABLE autopilot_queue
  ADD COLUMN IF NOT EXISTS miss_count      INTEGER DEFAULT 0,
  ADD COLUMN IF NOT EXISTS recovered_at    TIMESTAMPTZ,
  ADD COLUMN IF NOT EXISTS escalated_at    TIMESTAMPTZ,
  ADD COLUMN IF NOT EXISTS deferred_until TIMESTAMPTZ;
```

```
-- Item 1: columns used by dead-letter-drain INSERT.
-- If these already exist, IF NOT EXISTS makes this a no-op.
-- If they do NOT exist and you prefer payload-only traceability,
-- comment these out AND remove the matching columns from the INSERT
-- in dead-letter-drain.ts (values are already embedded in enrichedPayload).
```

```
ALTER TABLE autopilot_queue
  ADD COLUMN IF NOT EXISTS platform          TEXT,
  ADD COLUMN IF NOT EXISTS target_platform   TEXT,
  ADD COLUMN IF NOT EXISTS source            TEXT,
  ADD COLUMN IF NOT EXISTS original_queue_item_id INTEGER,
  ADD COLUMN IF NOT EXISTS dead_letter_id    INTEGER;
```

```
-- =====
-- BLOCK 2: channels token backup
-- =====
```

```

ALTER TABLE channels
  ADD COLUMN IF NOT EXISTS access_token_backup TEXT,
  ADD COLUMN IF NOT EXISTS refresh_token_backup TEXT,
  ADD COLUMN IF NOT EXISTS token_expires_backup TIMESTAMPTZ,
  ADD COLUMN IF NOT EXISTS token_backed_up_at TIMESTAMPTZ,
  ADD COLUMN IF NOT EXISTS needs_reconnect BOOLEAN DEFAULT false,
  ADD COLUMN IF NOT EXISTS reconnect_reason TEXT,
  ADD COLUMN IF NOT EXISTS token_recovery_note TEXT,
  ADD COLUMN IF NOT EXISTS last_token_refresh TIMESTAMPTZ;

-- =====
-- BLOCK 3: dead_letter_queue additions
-- Fix #7: CHECK dead_letter_queue.status TYPE BEFORE DEPLOYING drain code
-- =====

-- Run this first:
--   SELECT pg_typeof(status) FROM dead_letter_queue LIMIT 1;
--
-- If result is 'text' → no action needed, proceed with ALTER TABLE below.
--
-- If result is a custom enum, find its name:
--   SELECT t.typname
--   FROM pg_type t
--   JOIN pg_attribute a ON a.atttypid = t.oid
--   JOIN pg_class c ON c.oid = a.attrelid
--   WHERE c.relname = 'dead_letter_queue' AND a.attname = 'status';
--
-- Then add needed values OUTSIDE a transaction block:
--   ALTER TYPE <enum_name> ADD VALUE IF NOT EXISTS 'expired';
--   ALTER TYPE <enum_name> ADD VALUE IF NOT EXISTS 'requeued';
--   ALTER TYPE <enum_name> ADD VALUE IF NOT EXISTS 'resolved';
--   ALTER TYPE <enum_name> ADD VALUE IF NOT EXISTS 'deferred';
-- (These must run as standalone statements, not inside BEGIN/COMMIT)
--
-- Only after confirming text type or adding enum values, run the ALTER TABLE:

ALTER TABLE dead_letter_queue
  ADD COLUMN IF NOT EXISTS requeue_count INTEGER DEFAULT 0,
  ADD COLUMN IF NOT EXISTS expired_at TIMESTAMPTZ,
  ADD COLUMN IF NOT EXISTS requeued_at TIMESTAMPTZ,
  ADD COLUMN IF NOT EXISTS next_retry_at TIMESTAMPTZ; -- prevents re-selection of
budget/channel-blocked items

CREATE INDEX CONCURRENTLY IF NOT EXISTS idx_dlq_next_retry
  ON dead_letter_queue (next_retry_at, status)
  WHERE status NOT IN ('expired', 'requeued', 'resolved');

```

```
--  
-- BLOCK 4: Security IP allowlist  
--
```

```
CREATE TABLE IF NOT EXISTS security_ip_allowlist (  
  id          SERIAL PRIMARY KEY,  
  ip_prefix   TEXT NOT NULL UNIQUE,  
  description TEXT,  
  added_at    TIMESTAMPTZ DEFAULT NOW()  
);  
  
INSERT INTO security_ip_allowlist (ip_prefix, description) VALUES  
  ('35.191.', 'Google Cloud Load Balancer health checks'),  
  ('130.211.', 'Google Cloud Load Balancer health checks'),  
  ('209.85.', 'Google crawlers'),  
  ('66.249.', 'Googlebot'),  
  ('127.',    'localhost'),  
  ('10.',     'Private network RFC 1918'),  
  ('192.168.', 'Private network RFC 1918'),  
  ('::1',     'IPv6 localhost')  
ON CONFLICT (ip_prefix) DO NOTHING;
```

```
--  
-- BLOCK 5: Indexes (run OUTSIDE any transaction)  
--
```

```
CREATE INDEX CONCURRENTLY IF NOT EXISTS idx_autopilot_stuck_recovery  
  ON autopilot_queue (status, scheduled_at)  
  WHERE status = 'scheduled';
```

```
CREATE INDEX CONCURRENTLY IF NOT EXISTS idx_dlq_active  
  ON dead_letter_queue (status, created_at)  
  WHERE status NOT IN ('expired', 'requeued', 'resolved');
```

```
CREATE INDEX CONCURRENTLY IF NOT EXISTS idx_channels_needs_reconnect  
  ON channels (platform, needs_reconnect)  
  WHERE needs_reconnect = true;
```

```
--  
-- BLOCK 6: Direct row updates – VERIFY FIRST  
-- SELECT before UPDATE. If rows don't match, skip.  
--
```

```
-- Step 1: Inspect the rows  
SELECT id, type, status, error_message, created_at  
FROM autopilot_queue  
WHERE id IN (16855, 16854, 7529);
```

```
-- Step 2: Only run the UPDATE if the SELECT shows these are the
-- verified_missing / stuck_scheduled items described in pipeline_traces.
-- If the rows don't exist or look wrong, DO NOT run the UPDATE below.
-- Instead, log a warning and stop.

-- UPDATE for verified_missing videos (run only after confirming above):
/*
UPDATE autopilot_queue
SET status = 'permanent_fail',
    error_message = 'Video verified missing from YouTube – confirmed 2026-05-24'
WHERE id IN (16855, 16854)
    AND status NOT IN ('published', 'permanent_fail', 'cancelled');

UPDATE autopilot_queue
SET status      = 'pending',
    scheduled_at = NOW(),
    miss_count   = 2,
    error_message = 'Force-recovered: missed twice by stuck-scheduler (pipeline rows 13-14)'
WHERE id = 7529
    AND status = 'scheduled';
*/
-- Uncomment the block above ONLY after verifying the SELECT matches.
```