MedRena

For better infusion

UniFusion VP50Pro+
Infusion Pump

Safety

- High accuracy :±5%
- Double air bubble detect (8 levels - 20-800 ul)
- Double pressure detect
- Anti-bolus function
- DERS (Drug error reduction system)
- IP Level: IP34
- 9 hours battery back-up time
- Waterproof embrance cover
- Anti free flow Clamp

Friendliness

- 4.3" colour touch screen
- Intuitive operation system
- Automatic calibration
- Inter-Lockable
- Custormized drug library

Shenzhen MedRena biotech Co., Ltd.
Add: 4th Floor, Office Building, Silcon Industrial Park, No.3 Kaitian Road, Pinghu Street, Longgang District, Shenzhen 518111, China
Tel: +86 18682318839 Web : www.medrena.com

MedRena

For better infusion

Unifusion VP50Pro+

Specifications and functions

Dimension	199*126*111
Weight	Approx. 1.4 kg
Display	4.3 inch color touch screen (Show - mode, rate, VTBI, Time, ETC.)
Brightness Levels	10 levels
Flow rate accuracy	±5%
Flow rate	0.01 – 2000 ml/h (range 0.01-99.99 ml/h with increment 0.01 ml/h)
Time range	1 – 99hrs59min
VTBI	0-9999 ml Adjust (up and down) 0.01ml/time (Range 0.01- 99.99 ml)
Dose rate units	More than 15 types
Concentration calculate	Automatically
Bolus setting	Manual bolus and Programmable bolus Bolus rate 0 – 2000 ml/h Bolus volume 0.1 – 1500 ml
KVO rate	KVO 0.01-5 ml/h
Infusion modes	8 infusion modes Rate mode, Time mode, Body-weight mode, Drip mode, Drug library mode, Ramp up/down mode, Loading-dose mode, Sequence mode (up to 10 modes)
Handle	Included
Drug library	Standard 16 items and Customized drug library
IV SET	More than 20 brands (15,20,60 drops/ml)
Purge	Yes (400 ml/h for micro set , 2000 ml/h for macro set)
DPS	Yes
Titration	Yes
Micro mode	Yes
Standby mode	Yes
Screen lock	Yes
Night mode	Yes
Occlusion levels	13 levels (75mmHg ~ 975 mmHg) Double pressure detect - Up-stream and Down-stream
Anti Bolus	Yes
Records	More than 5000 entries
Alarms	VTBI near end, VTBI infused, Pressure high, Battery empty, Battery nearly empty, No power supply, Reminder alarm, KVO finished, Check upstream, Drops error, Air bubble, Door open, Standby time expired, System error, Repeat alarm.
Alarms volume levels	10 levels

Unifusion VP50Pro+

Specifications and functions

Power supply	AC: 110V-240V , 50/60 Hz DC: 12 V
Battery life	Standard : 9 Hours (with 2 battery) ; 25ml/h Lithium Polymer Battery
Charging time	< 5 Hours
Classification	IEC , EC , ISO
IP Level	IP34
IrDa	Optional
Data interface	USB
Drop sensor	Supported
Wireless	Wifi (optional)
Dc input	Yes
RS232	Supported
Nurse call	Supported
Language	English , Chinese , Thai

Shenzhen MedRena biotech Co., Ltd.
Add: 4th Floor, Office Building, Silcon Industrial Park, No.3 Kaitian Road, Pinghu Street, Longgang District, Shenzhen 518111, China
Tel: +86 18682318839 Web : www.medrena.com