COMEN
Share With The World.

12-channel Electrocardiograph H12

Physical

Height:	305mm
Width:	228mm
Length:	74mm
Weight:	4.0KG (including battery)
Display:	10.4 inches LCD color touch screen
Resolution:	800×600
Display Data:	Patient ID, gender, age, waveforms, recording/sweep speed, gain, EMG filter, HR, leads status, clock, information message, network and USB, battery status
Display format:	12×1, 6×2, simultaneously 12 leads display
Brightness:	Manual from 1 to 10

Processing

ECG Analysis Sampling Rate:	1000samples/sec (sps)
Digital Sampling Rate:	1000samples/sec/channel
Acquisition Mode:	pre/post-acquisition 10 seconds instantaneous ECG acquisition

Dynamic Range:	AC differential±10mV, DC offset± 650mV
Resolution:	0.2μV/LSB@1000sps
Frequency Response:	-3dB@0.05Hz-150Hz
Baseline Drift Filter:	0.05Hz, 0.1Hz, 0.2Hz, 0.5Hz
Low Cut-off Frequency:	OFF, 75Hz, 100Hz, 150Hz
AC Filter:	50/60Hz ±0.1Hz
CMRR:	≥110dB
ADC:	24bit
Input Impedance:	≥50MΩ
Patient Leakage:	<10μA
HR Meter:	30-300 bpm ±1% or 1bpm
Startup Time:	around 10 seconds
Gain/Sensitivity:	2.5mm/mV, 5mm/mV, 10mm/mV, 20mm/mV, 20/10mm/mV,10/5mm/mV and AGC

Power

Power supply: AC input/Battery Operation

AC Power

Input Voltage:	100-240V~
AC Frequency:	50Hz/60HZ±1Hz
Input Power:	100VA

Battery

Battery Type:	Rechargeable Lithium ion Battery
Battery Capacity:	14.8V typical, 3100mAh 7 hours of continuous operation without recording/ 500 ECGs or conduct continuous recording for 2 hours
Battery Charge Time:	3.4 hours with power off

Recorder

Recording Tech:Thermal dot-matrix

Recorder Width:	210mm
Recording Paper:	210mm×140mm(20M) Z-fold ,210mm×150mm(150P) Z-fold
Valid Recording Width:	210mm
Paper Speed:	Manual: 5mm/s, 6.25mm/s, 10mm/s, 12.5mm/s, 25mm/s, 50mm/s
Auto& Rhythm:	25mm/s, 50mm/s
Recording format:	3×4, 3×4+1R, 1×12, 1×12+1R ,6×2, 6×2+1R
External printer format:	3×4, 3×4+1R, 3×4+3R, 6×2, 6×2+1R, 1×12, 1×12+T
Recorder Resolution:	Horizontal 40dots/mm, vertical 8 dots/mm @ 25mm/s

Software

Measurement & Interpretation: COMEN ECG analysis algorithm

Internal Storage: Standard 8G micro SD card for 10000 ECGs internal memory

ECG Storage Format: DAT(binary), BMP,JPG,PDF,DICOM,XML,SCP

R-R Analysis: Yes

Print out Mode: Normal, One-key, Extended

Re-print out: Re-print out last patient case

Sound: key sound & HR beep

Multi-Language: Multi-Languages

Diagnostic Review: 10 minutes review for all 12 leads waveform info.

Hardware support: Built in WIFI module/ keyboard, mouse and scanner optional

Standby : OFF, 5min,10min,15min,20min,25min,30min

Timing Power off: OFF, 10min~5hours

Patient record fuzzy search function: Patient name, ID, diagnostic time.

Environmental Specs

Temperature

Operating: 5℃ to 40℃

Transport & storage: -20℃ to 60℃

Humidity

Operating: ≤90%

Transport & storage: ≤93%

Pressure

Operating: 700hPa to 1060hPa

Transport & storage: 700hPa to 1060hPa

Shenzhen Comen Medical Instruments Co., Ltd.

Add: Floor 7, Block 5, 4th Industrial Park of Nanyou,Nanshan District, Shenzhen 518052, China
Tel:+86-755-2640 8879 Fax:+86-755-2643 1232
Web: en.comen.com E-mail: info@szcomen.com