OpticPS Fiber Model Validation Report

ITU-T G.652.D fiber model, OpticPS version 1.1.0

SIMULATION AND SPECIFICATION ANALYSIS ONLY: NO MEASURED FIBER DATA. NOTHING HERE IS EXPERIMENTALLY VALIDATED.

Configuration SHA-256 4a087b9e8662ad1bb6e71861f3002c57e0ea37e51d1bf3815fa303868036a5a8. Seed 42. Python 3.11.15, NumPy 2.4.6. Runtime 342 s.

1. Summary

OpticPS now offers a selectable fiber description with attenuation, chromatic dispersion and dispersion slope, and a third-order dispersion term in the field propagation. Presets follow Rec. ITU-T G.652 (08/2024). Each number records whether it is a specification limit, a representative simulation value, manufacturer data or a laboratory measurement.

- With no fiber selected, the link reproduces v1.0 exactly: 45 of 45 saved v1.0 fiber-sweep points were recomputed identically (symbol errors, bit errors, rates and powers).
- At the Profile A, Uniform, 40 km point, v1.0 defaults give SER 0.590072, BER 0.374823 (149850 symbol errors, -27.011 dBm received). The G.652.D representative preset at 1550 nm gives SER 0.673927, BER 0.443107 (171145 symbol errors, -30.011 dBm received).
- The simulated dispersion null agrees with theory to 3e-08 relative error in every case tested.

2. Standard and references

The model follows Rec. ITU-T G.652 (08/2024), edition 10.0, approved 2024-08-29. Its status, in force, is taken from the ITU-T recommendation page, read 2026-10-30, and not from the PDF. Used: clause 6 (fibre attributes, Equations (6-1) to (6-3)), clause 7 (cable attributes), clause 8 (Table 2, G.652.D), and Appendix I (Table I.1, representative link values). The G.652.D variant is a deliberate default for presets only: nothing forces the simulation onto G.652.D, and a custom fiber description can describe any other type.

Equation (6-2a,b,c) reached the code through an extraction in which the signs and subscripts were garbled. The signs were reconstructed, and confirmed by continuity with Equation (6-3) at 1460 nm: the reconstructed bounds equal the values of Equation (6-3), 8.625 and 12.472 ps/(nm km), and they join continuously at lambda0 min and lambda0 max. This is consistency evidence, not a reading of the printed equation, and it should be checked against the printed Recommendation.

3. Equations and assumptions

Dispersion parameter D and slope S relate to the propagation constant through:

$$\beta_2 = -\frac{D\lambda^2}{2\pi c}, \qquad \beta_3 = \frac{\lambda^4 S + 2\lambda^3 D}{4\pi^2 c^2}$$

The field envelope A of E = A exp(-i omega0 t) acquires, for an optical frequency offset omega over length L:

$$A(\omega, L) = A(\omega, 0)\exp\left[i\left(\frac{\beta_2}{2}\omega^2 + \frac{\beta_3}{6}\omega^3\right)L\right]$$

numpy's FFT kernel is exp(-i omega t), so its frequency axis is minus the optical offset. The even term is unchanged and the odd term enters as exp(-i beta3 L omega_np^3 / 6). A test checks the sign: a pulse offset in frequency is delayed by beta3 omega^2 L / 2 on either side. A slope left unset (None) selects the v1.0 second-order model, with no third-order term at all, so existing results are unchanged. Any slope that is given, including 0.0, adds the full beta3, including its 2 lambda^3 D part: 0.0 is a true zero slope, with beta3 = 2 lambda^3 D / (4 pi^2 c^2) from D

alone, and is not the v1.0 path. Each of attenuation, D and S carries its own provenance tag, so measuring D does not relabel S. Intensity detection of a double-sideband signal sees the cosine of the second-order phase, so the first null follows:

$$f_{\text{null}} = \sqrt{\frac{c}{2\lambda^2 |D| L}}$$

When D is zero or the length is zero there is no null and the code returns infinity.

The G.652 three-term Sellmeier form and the bounds for 1460 nm to 1625 nm are:

$$= \frac{S_0 \lambda}{4}\left[1 - \left(\frac{\lambda_0}{\lambda}\right)^4\right], \qquad 8.625 + 0.052(\lambda - 1460) \le D \le 12.472 + 0.068(\lambda - 1$$

The representative preset uses this form with lambda0 and S0 fitted so that D = 17 ps/(nm km) and S = 0.056 ps/(nm^2 km) at 1550 nm, the Table I.1 values. The fit gives lambda0 = 1307.6 nm and S0 = 0.0889 ps/(nm^2 km), inside Table 2. This is a model choice, not a value stated in the Recommendation. Its attenuation is the Table I.1 link value, joined linearly between bands, also an assumption.

Assumptions carried from the link model: single polarization; no polarization mode dispersion; no Kerr effect; no amplifier or laser noise; attenuation independent of power. PMD is listed in the tables and is not simulated.

4. ITU-T G.652.D attributes

Fibre attributes and cable attributes are kept apart because they apply to different things. The fibre values describe the glass; the cable values are limits for factory-length cable.

Fibre attribute	Detail	Value
Mode field diameter	1310 nm, nominal range	8.6 to 9.2 um, tolerance 0.4 um
Cladding diameter	Nominal	125.0 um, tolerance 0.7 um
Cable cut-off wavelength	Maximum	1260 nm
Macrobending loss	30 mm radius, 100 turns, 1625 nm	0.1 dB maximum
Zero-dispersion wavelength	lambda0 min, max	1300 nm, 1324 nm
Dispersion slope at lambda0	S0 min, max	0.073, 0.092 ps/(nm^2 km)
D at 1550 nm	Minimum, maximum	13.3, 18.6 ps/(nm km)
D at 1625 nm	Minimum, maximum	17.2, 23.7 ps/(nm km)

Cable attribute	Detail	Value
Attenuation coefficient	Maximum, 1310 to 1625 nm (Notes 1, 2)	0.4 dB/km
Attenuation coefficient	Maximum at 1383 ± 3 nm after hydrogen ageing (Note 3)	0.4 dB/km
Attenuation coefficient	Maximum, 1530 to 1565 nm	0.3 dB/km
PMD coefficient	PMD_Q, M = 20 cables, Q = 0.01%	0.2 ps/sqrt(km) maximum

Note 1 of Table 2 says the cable attenuation values should not be applied to short cables such as jumpers, indoor cables and drop cables. Note 2 extends the range to 1260 nm by adding 0.07 dB/km to the 1310 nm value; the Recommendation does not give the intermediate curve, so OpticPS applies the addition flat from 1260 to 1310 nm. Table I.1 gives typical values of concatenated links, which are not cable limits:

Link attribute (Table I.1)	Wavelength	Typical link value
Attenuation coefficient	1260 to 1360 nm	0.5 dB/km
Attenuation coefficient	1530 to 1565 nm	0.275 dB/km
Attenuation coefficient	1565 to 1625 nm	0.35 dB/km
Chromatic dispersion D1550	1550 nm	17 ps/(nm km)


Link attribute (Table I.1)	Wavelength	Typical link value
Dispersion slope S1550	1550 nm	0.056 ps/(nm^2 km)

The Table I.1 typical link value of 0.5 dB/km at 1310 nm is above the Table 2 cable limit of 0.40 dB/km. Table I.1 is titled "Representative values of concatenated optical fibre links" and its attenuation column is headed "Typical link value"; it is a link value and not a cable limit. Appendix I says that link attenuation is affected by factors other than the cables, such as splices, passive components and installation, and that these are not specified in the Recommendation. Inference, not stated in the Recommendation: that link-level contribution is why the link value exceeds the cable limit. The representative preset therefore reports itself outside the Table 2 cable attenuation limit at 1310 nm, and the code says so instead of hiding it. Over the 1 nm grid the Table I.1 value is above the Table 2 cable limit from 1260 to 1435 nm, with the interpolated curve crossing the limit at about 1435.6 nm. Table I.1 itself states values only for 1260 to 1360 nm in this region; beyond 1360 nm the curve, and so the upper end of this range, rests on the assumed linear interpolation.

5. Attenuation and dispersion



Attenuation, Table 2 cable limit and Table I.1 typical link value (analytical)



Dispersion bounds and representative curve, 1260 to 1625 nm (analytical)

The representative curve gives D = 17.000 ps/(nm km) at 1550 nm, inside the bounds 13.30 to 18.59, and D = 0.211 ps/(nm km) at 1310 nm. The representative curve stays inside the bounds over 1260 to 1625 nm: True. The bounds are a worst-case envelope. A limit preset sits on one bound with attenuation at the Table 2 maximum, and is not a real fiber.


6. BER and SER sensitivity

All results in this section are simulated, through the link and the full receiver, with the same waveforms and frames as the v1.0 demonstration. They are not measurements. Only the before and after comparison below is paired with v1.0, with the same excess loss, runs and noise seeds. The length sweeps and the sensitivity tests differ from v1.0 and from each other in noise seed tag, number of runs and excess loss, and each table lists its excess loss. Points with fewer than 10 symbol errors are drawn as hollow upper bounds, as in the main report.


Length at 1550 nm and 1310 nm

Representative preset, excess loss fixed at 18 dB (Profile A) and 13 dB (Profile B), mean of 4 runs. At 1310 nm, D is 0.21 ps/(nm km), so dispersion hardly matters and the attenuation of 0.5 dB/km dominates. At 1550 nm the attenuation is lower, 0.275 dB/km. Profile A is loss-limited in these sweeps: the first dispersion null at 40 km is 9.6 GHz, against a Nyquist frequency of 4 GHz and a receiver bandwidth of 8 GHz, and the attenuation-only arm of the before and after comparison accounts for the change from v1.0 at 8 of 8 points. Profile B is where dispersion can matter: its first null at 6 km is 24.7 GHz, against a Nyquist frequency of 28 GHz and a receiver bandwidth of 42 GHz. Even so, the attenuation-only arm accounts for the change from v1.0 at 6 of 6 Profile B points. For Profile B at 1550 nm the error count is not monotonic in length, which is consistent with, and not proven to be caused by, the dispersion null moving through the signal band as the length grows.

The two wavelengths differ here only in the fiber: responsivity, V_pi, the modulator and its bias are the same at 1550 nm and 1310 nm. This is an assumption for comparison and not a model of real devices, which differ between the bands, so the comparison between wavelengths is of the fiber alone.



BER and SER versus fiber length, Profile A (simulated)




BER and SER versus fiber length, Profile B (simulated)

Wavelength (nm)	Waveform	Length (km)	Excess loss (dB)	Received (dBm)	SER	BER	Errors
1550	Uniform	0	18	-15.01	0	0	0
1550	Uniform	5	18	-16.39	1.08e-03	5.39e-04	137
1550	Uniform	10	18	-17.76	1.46e-02	7.30e-03	1855
1550	Uniform	20	18	-20.51	1.60e-01	8.01e-02	20329
1550	Uniform	30	18	-23.26	3.86e-01	2.05e-01	49055
1550	Uniform	40	18	-26.01	5.47e-01	3.36e-01	69436
1550	Outer70	0	18	-15.01	0	0	0
1550	Outer70	5	18	-16.39	9.14e-04	4.57e-04	116
1550	Outer70	10	18	-17.76	1.32e-02	6.62e-03	1682
1550	Outer70	20	18	-20.51	1.30e-01	6.52e-02	16556
1550	Outer70	30	18	-23.26	2.98e-01	1.69e-01	37895
1550	Outer70	40	18	-26.01	4.09e-01	2.58e-01	51899
1310	Uniform	0	18	-15.01	0	0	0
1310	Uniform	5	18	-17.51	1.04e-02	5.21e-03	1324
1310	Uniform	10	18	-20.01	1.20e-01	5.99e-02	15199
1310	Uniform	20	18	-25.01	4.91e-01	2.87e-01	62408
1310	Uniform	30	18	-30.01	6.70e-01	4.41e-01	85103
1310	Uniform	40	18	-35.01	7.44e-01	4.96e-01	94436
1310	Outer70	0	18	-15.01	0	0	0
1310	Outer70	5	18	-17.51	9.24e-03	4.62e-03	1173
1310	Outer70	10	18	-20.01	9.93e-02	4.96e-02	12606
1310	Outer70	20	18	-25.01	3.64e-01	2.30e-01	46264
1310	Outer70	30	18	-30.01	5.43e-01	3.37e-01	68933
1310	Outer70	40	18	-35.01	6.51e-01	4.02e-01	82709

Wavelength (nm)	Waveform	Length (km)	Excess loss (dB)	Received (dBm)	SER	BER	Errors
1550	Uniform	0	13	-10.01	3.88e-06	1.94e-06	1
1550	Uniform	1	13	-10.28	7.75e-06	3.88e-06	2
1550	Uniform	2	13	-10.56	5.81e-05	2.91e-05	15
1550	Uniform	3	13	-10.83	1.46e-03	7.32e-04	378
1550	Uniform	4	13	-11.11	4.04e-02	2.02e-02	10436
1550	Uniform	5	13	-11.38	2.47e-01	1.24e-01	63673
1550	Uniform	6	13	-11.66	1.43e-01	7.13e-02	36799
1550	Outer70	0	13	-10.01	3.88e-06	1.94e-06	1
1550	Outer70	1	13	-10.29	7.75e-06	3.88e-06	2
1550	Outer70	2	13	-10.56	5.04e-05	2.52e-05	13
1550	Outer70	3	13	-10.84	1.38e-03	6.88e-04	355
1550	Outer70	4	13	-11.11	3.61e-02	1.81e-02	9327
1550	Outer70	5	13	-11.39	2.24e-01	1.15e-01	57786
1550	Outer70	6	13	-11.66	1.59e-01	7.99e-02	41157
1310	Uniform	0	13	-10.01	3.88e-06	1.94e-06	1
1310	Uniform	1	13	-10.51	7.75e-06	3.88e-06	2
1310	Uniform	2	13	-11.01	5.43e-05	2.71e-05	14
1310	Uniform	3	13	-11.51	3.22e-04	1.61e-04	83
1310	Uniform	4	13	-12.01	1.19e-03	5.93e-04	306
1310	Uniform	5	13	-12.51	3.15e-03	1.57e-03	812
1310	Uniform	6	13	-13.01	8.15e-03	4.07e-03	2102
1310	Outer70	0	13	-10.01	3.88e-06	1.94e-06	1
1310	Outer70	1	13	-10.51	7.75e-06	3.88e-06	2
1310	Outer70	2	13	-11.01	3.49e-05	1.74e-05	9
1310	Outer70	3	13	-11.51	2.83e-04	1.41e-04	73
1310	Outer70	4	13	-12.01	1.17e-03	5.83e-04	301
1310	Outer70	5	13	-12.51	2.88e-03	1.44e-03	744
1310	Outer70	6	13	-13.01	7.12e-03	3.56e-03	1837

Sensitivity to D and to attenuation

At 1550 nm, one point per profile. D is set to the lower and upper G.652.D bound with attenuation held at the representative value; then attenuation is varied with D held. These are envelope tests, not predictions for a fiber.



Sensitivity of BER to D at the bounds and to attenuation (simulated)

Profile A, 40 km, dispersion:

Case	Waveform	Excess loss (dB)	SER	BER	Symbol errors
D at lower bound	Uniform	8	5.51e-04	2.76e-04	140
D at lower bound	Outer70	8	5.47e-04	2.74e-04	139
D representative	Uniform	8	6.50e-04	3.25e-04	165
D representative	Outer70	8	6.22e-04	3.11e-04	158
D at upper bound	Uniform	8	7.13e-04	3.56e-04	181
D at upper bound	Outer70	8	6.69e-04	3.35e-04	170

Profile A, attenuation:

Case	Waveform	Excess loss (dB)	SER	BER	Symbol errors
0.2 dB/km	Uniform	8	0	0	0
0.2 dB/km	Outer70	8	0	0	0
0.275 dB/km	Uniform	8	6.50e-04	3.25e-04	165
0.275 dB/km	Outer70	8	6.22e-04	3.11e-04	158
0.3 dB/km	Uniform	8	5.98e-03	2.99e-03	1519
0.3 dB/km	Outer70	8	5.19e-03	2.60e-03	1319
0.35 dB/km	Uniform	8	6.64e-02	3.32e-02	16871
0.35 dB/km	Outer70	8	5.62e-02	2.81e-02	14267

Profile B, 4 km, dispersion:


Case	Waveform	Excess loss (dB)	SER	BER	Symbol errors
D at lower bound	Uniform	10	0	0	0
D at lower bound	Outer70	10	0	0	0
D representative	Uniform	10	5.89e-04	2.95e-04	304
D representative	Outer70	10	6.99e-04	3.50e-04	361
D at upper bound	Uniform	10	1.88e-02	9.40e-03	9707
D at upper bound	Outer70	10	2.05e-02	1.03e-02	10595

Profile B, attenuation:


Case	Waveform	Excess loss (dB)	SER	BER	Symbol errors
0.2 dB/km	Uniform	10	3.29e-04	1.65e-04	170
0.2 dB/km	Outer70	10	4.07e-04	2.03e-04	210
0.275 dB/km	Uniform	10	5.89e-04	2.95e-04	304
0.275 dB/km	Outer70	10	6.99e-04	3.50e-04	361
0.3 dB/km	Uniform	10	7.13e-04	3.57e-04	368
0.3 dB/km	Outer70	10	8.06e-04	4.03e-04	416
0.35 dB/km	Uniform	10	1.01e-03	5.05e-04	521
0.35 dB/km	Outer70	10	1.18e-03	5.89e-04	608

Before and after: v1.0 defaults and G.652.D at 1550 nm

Identical configuration, seed, waveforms, frames and per-point noise seeds as the v1.0 fiber sweep of configs/demo.yaml. The v1.0 arm re-computed 25 of 25 Profile A and 20 of 20 Profile B saved points identically, so the comparison starts from the same code. Excess loss is 22 dB (Profile A) and 14 dB (Profile B), 8 runs. Single point: Profile A, Uniform, 40 km. v1.0: SER 0.590072, BER 0.374823, 149850 symbol errors, 190374 bit errors, R_BMD 0.1959, received -27.011 dBm. G.652.D: SER 0.673927, BER 0.443107, 171145 symbol errors, 225056 bit errors, R_BMD 0.0424, received -30.011 dBm.



Profile A, v1.0 defaults against G.652.D at 1550 nm (simulated)



Profile B, v1.0 defaults against G.652.D at 1550 nm (simulated)

Profile A, Uniform:

Fiber	Length (km)	Excess loss (dB)	Received (dBm)	SER	BER	Symbol errors
v1.0 defaults	0	22	-19.01	5.89e-02	2.94e-02	14947
G.652.D representative	0	22	-19.01	5.89e-02	2.94e-02	14947
v1.0 defaults	5	22	-20.01	1.20e-01	6.01e-02	30528
G.652.D representative	5	22	-20.39	1.48e-01	7.40e-02	37565
v1.0 defaults	10	22	-21.01	1.99e-01	9.95e-02	50480
G.652.D representative	10	22	-21.76	2.61e-01	1.31e-01	66237
v1.0 defaults	20	22	-23.01	3.63e-01	1.89e-01	92208
G.652.D representative	20	22	-24.51	4.66e-01	2.63e-01	118243
v1.0 defaults	40	22	-27.01	5.90e-01	3.75e-01	149850
G.652.D representative	40	22	-30.01	6.74e-01	4.43e-01	171145

Profile B, Uniform:

Fiber	Length (km)	Excess loss (dB)	Received (dBm)	SER	BER	Symbol errors
v1.0 defaults	0	14	-11.01	4.46e-05	2.23e-05	23
G.652.D representative	0	14	-11.01	4.46e-05	2.23e-05	23
v1.0 defaults	1	14	-11.21	2.00e-04	9.98e-05	103
G.652.D representative	1	14	-11.28	2.62e-04	1.31e-04	135
v1.0 defaults	2	14	-11.41	8.02e-04	4.01e-04	414
G.652.D representative	2	14	-11.56	1.18e-03	5.92e-04	611
v1.0 defaults	4	14	-11.81	7.05e-02	3.53e-02	36405
G.652.D representative	4	14	-12.11	8.60e-02	4.30e-02	44367

Why the results differ. The attenuation of the preset is 0.275 dB/km against 0.2 dB/km, so the span loses 0.075 dB more per km. The dispersion at 1550 nm is the same 17 ps/(nm km). The only other change is that the preset supplies a slope, which switches the third-order term (beta3) on; v1.0 has no such term. That term is not "the slope" alone: beta3 = 0.1268 ps^3/km in total, of which 0.0357 ps^3/km comes from D (the 2 lambda^3 D part) and 0.0911 ps^3/km from S. Two further arms isolated the changes on Uniform and Outer70, the second being a third-order on or off test and not a test of S alone:

- Profile A: With the beta3 term switched on, symbol-error counts were identical to v1.0 at all 10 points. With only the attenuation changed, the change in symbol errors was within 10% (plus one error) of the full preset's change at 8 of 8 points with fiber.
- Profile B: With the beta3 term switched on, symbol-error counts equalled v1.0 at 6 of 8 points and differed by at most 8 symbol errors (Outer70, 4 km). With only the attenuation changed, the change in symbol errors was within 10% (plus one error) of the full preset's change at 6 of 6 points with fiber.

The beta3 arm changed symbol errors by at most 8, a small change against the attenuation effect; compare section 7 for the size of the third-order phase.

The 40 km Profile A point appears in three sections with different settings, so its values differ between tables: the excess loss, the number of runs and the noise seed tag are listed below for the same fiber, the 1550 nm representative preset, Uniform. The sections are not paired with each other, and only the before and after section is paired with v1.0.

Profile A, Uniform, 40 km:

Section	Excess loss (dB)	Runs	Noise seed tag	Received (dBm)	BER	Symbol errors
Before and after	22	8	20	-30.01	4.43e-01	171145
Length sweep	18	4	40	-26.01	3.36e-01	69436
Sensitivity (D representative)	8	8	50	-16.01	3.25e-04	165

Profile B, Uniform, 4 km:

Section	Excess loss (dB)	Runs	Noise seed tag	Received (dBm)	BER	Symbol errors
Before and after	14	8	21	-12.11	4.30e-02	44367
Length sweep	13	4	41	-11.11	2.02e-02	10436
Sensitivity (D representative)	10	8	51	-8.11	2.95e-04	304

7. Numerical validation

The first null of the simulated intensity response of a small tone through the dispersion routine is compared with theory. The grid is not aligned to the theoretical null, and the null is found by intersecting the two sides of the response. Relative error is at most 3.1e-08.

Wavelength (nm)	Variant	D (ps/(nm km))	Theory (GHz)	Simulated (GHz)	Relative error	Null shift from beta3 term (GHz)
1550	representative	17.000	19.1575	19.1575	-3.1e-08	0.0e+00
1310	representative	0.211	203.6730	203.6730	-3.1e-08	2.2e-09
1550	limit-low	13.305	21.6549	21.6549	-3.1e-08	0.0e+00
1550	limit-high	18.592	18.3190	18.3190	-3.1e-08	0.0e+00

The beta3 term changes only the phase of the sidebands of a double-sideband signal, not the magnitude of the intensity response, to first order. The largest change in response magnitude at half the null frequency, between beta3 on and off, was 9.6e-08. The size of the third-order phase at the Nyquist frequency of each profile, at the longest sweep length, against the second-order phase:

Profile	Length (km)	Baud (GBd)	beta3 total (ps^3/km)	from D	from S	2nd-order phase (rad)	3rd-order phase (rad)
profile_A	40	8	0.1268	0.0357	0.0911	0.274	1.34e-05
profile_B	6	56	0.1268	0.0357	0.0911	2.013	6.90e-04

Here beta3 is in ps^3/km, and its parts from D and from S are shown. The third-order phase is some orders of magnitude below the second-order phase, so the third-order term is expected to be negligible for these baud rates. This is consistent with the beta3 arm of the before and after comparison, which differed from v1.0 by at most 8 symbol errors. It would matter for much wider bandwidths or near the zero-dispersion wavelength.

8. Limitations and experimental data still required

- The Southampton link's fiber type and length are unconfirmed. Nothing here describes it.
- The Table 2 limits are for cable, and exclude short cables such as jumpers (Note 1). A short bench link is not covered by them.
- PMD is listed and not simulated; no polarization effects are modelled.
- No Kerr effect, no amplifier, no laser chirp. Real transmitters add chirp that interacts with dispersion.
- Connector and splice losses, and bend loss, are not modelled except through the excess loss term. Table I.1 link values may already include such contributions (Appendix I), so adding excess loss to a Table I.1 attenuation can count them twice. Here the excess loss is a sweep parameter that places the error rate in a measurable range, and not a splice budget.
- Responsivity, V_pi and the modulator are taken to be the same at 1550 nm and 1310 nm.
- The representative curves are models built from Table I.1, not a measurement of any fiber.
- Needed from Southampton: fiber type and manufacturer data sheet, link length, attenuation measured at the operating wavelength, dispersion or a group delay measurement, and the laser wavelength. Attenuation, dispersion and slope enter through apply_measurements, which marks each measured value as laboratory-measured with its own tag. The link length is set as fiber_length_km on the link, and the laser wavelength by the wavelength given when the preset or custom fiber is selected; apply_measurements does not set either.

9. What is analytical, simulated and experimentally validated

Item	Status
G.652.D limits, bounds, Table I.1 curves, third-order phase sizes	Analytical
BER and SER versus length, sensitivity, before and after, dispersion null	Simulated
Any statement about the Southampton link or any real fiber	Not experimentally validated. No measured data has been imported.

10. References

1. Recommendation ITU-T G.652 (08/2024), Characteristics of a single-mode optical fibre and cable, edition 10.0, approved 2024-08-29. Clauses 6 to 8, Tables 1 and 2, Equations (6-1) to (6-3), Appendix I and Table I.1. The status 'in force' is taken from the ITU-T recommendation page (https://www.itu.int/rec/T-REC-G.652), read 2026-10-30, and not from the PDF.

2. G. P. Agrawal, Nonlinear Fiber Optics, Academic Press. Used for the sign convention of the dispersion phase only.

3. J. Wang and K. Petermann, Small signal analysis for dispersive optical fiber communication systems, J. Lightw. Technol. 10(1):96-100, 1992. doi:10.1109/50.108743

4. Recommendations ITU-T G.650.1, G.650.2 and Supplement 39 are cited by G.652 for test methods and system design. They were not read for this work.

11. Reproducibility

Command: uv run opticps fiber-validate. Configuration: configs/fiber_validation.yaml and configs/demo.yaml. Data: results/fiber_validation/fiber_results.json. Standard: Rec. ITU-T G.652 (08/2024), edition 10.0.