

## Setting Up CONSOLE PASSWORD for a Router

```
Router>enable
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#line console 0
Router(config-line)#password fatih
Router(config-line)#login
Router(config-line)#exit
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console
exit
```

## Removing CONSOLE PASSWORD

```
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#
Router(config)#
Router(config)#line console 0
Router(config-line)#no password
Router(config-line)#exit
Router(config)#exit
```

## Setting Up SECRET PASSWORD for a Router

### = PASSWORD FOR PRIVELEGED MODE

```
Router>enable
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#
Router(config)#enable secret fatihcinar
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#exit
```

## Removing SECRET PASSWORD

```
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#no secret
      ^
% Invalid input detected at '^' marker.

Router(config)#no enable secret
Router(config)#exit
_
```