



D REF

MAX TIE WIDTH

OPTIONAL TRIMMED BASE



DISPOSABLE PRESSURE SENSITIVE ADHESIVE FIXTURE



# SADDLE MATERIAL AND FINISH DATA

CODE	MATERIAL	SPEC.	COLOR
K	PEKK	NONE	NATURAL
N	NYLON, NATURAL	ASTM D4066, D6779, OR EQUAL	NATURAL
NB	NYLON, BLACK, STABILIZED	ASTM D4066, D6779, OR EQUAL	BLACK
NH	NYLON, HEAT STABILIZED	ASTM D4066, D6779, OR EQUAL	NATURAL
Р	PEEK	NONE	NATURAL
Т	TEFZEL	FLUOROPOLYMER	BLUE
V	POLYETHERIMIDE	ULTEM 1000 OR EQUAL	NATURAL
VC	CARBON/POLYETHERIMIDE	NONE	NATURAL

#### BASEPLATE MATERIAL

CODE	MATERIAL					
С	CARBON/EPOXY, 350°F CURE GLASS/EPOXY, 350°F CURE GLASS/EPOXY, 250°F CURE 30% GLASS/PEI					
E						
G						
U						
UC	30% CARBON/PEI					
٧	40% GLASS/PEI					
VC	40% CARBON/PEI					

# DIMENSION DATA

	SIZE	D REF	SADDLE DIMENSIONS					
	CODE	D KLI	Α	В	С			
	2	.100	.56	.34	.37			
	3	.190	.67	.44	.43			
	5	5 .350		.56	.52			

#### OPTIONAL BASEPLATE PRIMER


01 11011	THE BROKE BUILT THINKER
CODE	MATERIAL SPEC.
Р	MIL-PRF-85582

RIVET MATERIAL: 300 SERIES OR A-286 CRES RIVET FINISH: PASSIVATE PER AMS 2700

MANUFACTURER'S OPTION:

300 SERIES CRES WASHER UNDER RIVET HEAD

### EXAMPLE PART NUMBER



UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.		PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.		GLICK BOND					CARSON CITY NEVADA 89706	
		APPROVALS	DATE	TITLE	<del></del>	0.4.01.5		0.01		5.465
ANGLES	±1°	DRAWNDAC	27AUG13	] M(	JUNI,	CABLE	_ IIE,	COM	POSITE	BASE
.XX	±.03	CHECKED & () (Carliforn	27AUG13	SIZE	CAGE CODE	. O	DWG. NO.	240		REV.
.XXX	±.010	RELEASED OBCITIZE	27AUG13	I A	6653	0	CB4(	) 19		24
.XXXX	±.001	REVISED DAC	27AUG13	SCALE	1/1	27AUG13			SHEET 1	of 1