

# FOX\_Checklist

**What this is:** every FoxByte feature and its sub-features — built or not, and how it was tested — so it's clear where we are and what's next. How each feature works is in `FOX_Feature_Implemented.pdf` (same ids).

**Last updated:** 22 September 2026 · **Reflects:** `main @ 2778762` (v1.0.1, exact repository path PR #1) + the FoxByte rename and brand indirection ( `chore/foxbyte` )

**Source:** `docs/FOX_Checklist.html` → `make feature-doc` → this PDF

✔ Done & tested — automated tests (unit, VM integration or CI)

🟡 Partial — gaps, or not verified end to end

⚠ Sub-features: 

✔ built

🟡 partly

! a known limit

→ planned, not built

□ not built yet

✖ broken

✔ Done — tested by hand only

✖ Known issue

□ Not started

**The badge rule**

(audit v2 G31, which found 47 rows badged done while carrying an open item): a row is *done* or *done (manual)* only when nothing in it is 🟡, □ or ✖, and `scripts/test_feature_checklist.sh` fails the build otherwise. A ! is a limit of what the feature does and a → is a planned extension — neither makes the row's own claim untrue. How thoroughly something was tested belongs in "Tested by", not in the sub-features. · "VM §n" = section of `make integration` ; "v2 §n" = `make integration-v2` ; "update" = `make integration-update`

## Where we are

| Area                                     | Features   | Done & tested | Done (manual) | Partial  | Known issue | Not started | Progress                    |
|------------------------------------------|------------|---------------|---------------|----------|-------------|-------------|-----------------------------|
| A · Install & setup                      | 9          | 4             | 3             | 2        | ·           | ·           | <div><div></div></div> 78%  |
| B · CLI & services                       | 3          | 3             | ·             | ·        | ·           | ·           | <div><div></div></div> 100% |
| C · Branching & storage                  | 8          | 7             | ·             | 1        | ·           | ·           | <div><div></div></div> 88%  |
| D · Durability                           | 6          | 5             | ·             | 1        | ·           | ·           | <div><div></div></div> 83%  |
| E · Security foundations                 | 3          | 3             | ·             | ·        | ·           | ·           | <div><div></div></div> 100% |
| F · SQL gateway                          | 7          | 6             | 1             | ·        | ·           | ·           | <div><div></div></div> 100% |
| G · Accounts & auth                      | 6          | 5             | ·             | 1        | ·           | ·           | <div><div></div></div> 83%  |
| H · Blackbox (record of schema changes)  | 18         | 16            | ·             | 2        | ·           | ·           | <div><div></div></div> 89%  |
| I · Import & migration                   | 13         | 5             | 8             | ·        | ·           | ·           | <div><div></div></div> 100% |
| J · ETL pipelines (experimental)         | 4          | 2             | 2             | ·        | ·           | ·           | <div><div></div></div> 100% |
| K · APIs, SDKs & agents                  | 6          | 4             | 2             | ·        | ·           | ·           | <div><div></div></div> 100% |
| L · Web console                          | 11         | 1             | 10            | ·        | ·           | ·           | <div><div></div></div> 100% |
| M · Build, CI & releases                 | 8          | 7             | 1             | ·        | ·           | ·           | <div><div></div></div> 100% |
| <b>Total (features built or started)</b> | <b>102</b> | <b>68</b>     | <b>27</b>     | <b>7</b> | ·           | ·           | <div><div></div></div> 93%  |
| N · Not started (roadmap)                | 7          | 1             | ·             | ·        | ·           | 6           | <div><div></div></div> 14%  |

### Storage engine — not implemented, by design

FoxByte does **not** have its own storage engine. Data is stored by **PostgreSQL's own engine** (heap tables, B-tree indexes, write-ahead log) running on local disk inside the stock `postgres:18-bookworm` image plus wal-g ( `postgres:16-bookworm` for an install created before 21 Sep 2026). This was a locked architecture decision: a Neon-style engine that separates compute from storage over the network adds latency to every transaction, and transaction speed must never be compromised.

What **is** built is a storage *layer* around Postgres: copy-on-write branch drivers — ZFS on macOS/Linux, btrfs on Windows — behind one interface in `internal/branch/storage.go` (C1), quotas (C6), capacity reporting (C7), and durability to object storage with wal-g + MinIO: WAL archiving, base backups, point-in-time restore (D1–D3). Networked storage disaggregation is listed in the README roadmap but not started (see "Not started").

## Suggested next steps

---

1. **The claims are checkable now:** a restore is proved weekly and by `fox backup verify` (D2), a tag cannot ship past a red or stale nightly (M2), every command the engine runs has a deadline so nothing hangs for ever (G30's useful half), containers restart on crash (B2), and CI runs the race detector. Before this, the most consequential thing the product claims — that the backups restore — had never been tested end to end on a real install.
2. **This checklist's own badge rule is enforced** (audit v2 G31): no row can be badged done while carrying an open sub-item, and `scripts/test_feature_checklist.sh` fails the build if one is. The 45 sub-items that broke the rule were each put somewhere honest — built, a limit (!), planned (→), or a note in "Tested by" — and nine of them turned out to be things we had already shipped and never ticked off, including automated UI tests, per-user access control, SDK contract tests and the first signed release.
3. Run on real machines what the throwaway VM cannot: `fox update` across a real release on macOS and Windows (A9); on Windows, the zstd distro image's unpack (M5), the btrfs holding area of `fox pg upgrade` (D6), and an export's copy to the host (D5).
4. Automated tests for the imports (I1–I3, I7) — the last area with none.
5. Gate release tags on the nightly suites, so a tag cannot ship past a red suite (M2).
6. Decide how this checklist shows partial work (audit v2 G31): 9 features are badged done while carrying an open sub-item ( C7, D5, D6, F5, G3, H16, H17, I13, M7 ) — down from 34. Each of those sub-items is a disclosed limit rather than unfinished work, so the remaining question is whether a limit belongs in the sub-item list at all.
7. **The object store's images are FoxByte's own** (M6): MinIO left Docker Hub in 2026 and then quay.io stopped serving it anonymously — every tag there answers 401 — so a fresh install on macOS or Linux could not start, while existing installs carried on from their cache and Windows carried on because its distro image ships them inside it. They are mirrored to `ghcr.io/thefoxbyte` by `.github/workflows/mirror-images.yml`, which takes them out of a published release's distro asset rather than from a registry that will not serve us. **Run it once and pin what it prints.** It can only be dispatched after it is on the default branch, and until the digests are pinned `release.yml` refuses to publish.
8. **Promotion is built** (H18, audit G29): a branch's recorded statements, reviewed, then applied to another branch in one transaction — attributed to whoever wrote them, with the approver beside them. Schema only. An agent can propose and cannot approve its own request.
9. **From the audit, deliberately left:** HA beyond the demo — automatic failover and fencing across hosts (D4, G21); metrics and alerts, and supervision of the background servers themselves (B2, G27 — the containers restart); splitting the branch package and running its SQL through pgx (G30 — the deadlines are in); quotas on btrfs and per-branch CPU/memory (C6, G33).

| ID                                                                                                                                                | Feature · sub-features                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Tested by                                                                            |
|---------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|  <b>A1</b> <b>One-line installer (macOS / Linux)</b>             | <ul style="list-style-type: none"> <li>✓ Detects OS / CPU, downloads the release binary</li> <li>✓ Installs to the prefix (sudo only if needed)</li> <li>✓ Stages the Linux engine for the VM on macOS</li> <li>✓ <code>FOX_VERSION</code> , <code>FOX_REPO</code> , <code>FOX_DIST</code> , <code>FOX_PREFIX</code></li> <li>✓ Verifies every download against <code>SHA256SUMS</code> ; refuses what it can't check</li> <li>✓ Release signature checked (OpenSSL 3; warns with LibreSSL)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Unit ( <code>test_install_sh.sh</code> , CI); manual                                 |
|  <b>A2</b> <b>Windows installer (install.ps1)</b>                | <ul style="list-style-type: none"> <li>✓ Installs WSL, elevates, resumes after reboot</li> <li>✓ Downloads fox.exe, engine, image build context</li> <li>✓ Ubuntu rootfs verified against Ubuntu's checksums</li> <li>✓ Adds to PATH and runs <code>fox setup</code></li> <li>✓ Prefers the prebuilt distro image, falls back to the rootfs</li> <li>✓ Verifies FoxByte's own downloads</li> <li>✓ Run on a real Windows machine (distro image downloaded and verified)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Pester (Windows CI); Windows run 16 Sep                                              |
|  <b>A3</b> <b>fox setup on macOS (Lima)</b>                      | <ul style="list-style-type: none"> <li>✓ Creates / starts the Lima VM</li> <li>✓ Installs Docker and ZFS</li> <li>✓ Reinstalls the engine on every run</li> <li>✓ Starts the stack</li> <li>✓ Repairs an interrupted provisioning on the next run (dpkg interrupted, half-installed packages)</li> <li>✓ Image builds from the copy inside fox when it cannot be pulled (C8)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Unit; run against a deliberately broken VM, 21 Sep                                   |
|  <b>A4</b> <b>fox setup on Windows (WSL2 + btrfs)</b>            | <ul style="list-style-type: none"> <li>✓ Imports a dedicated distro with systemd</li> <li>✓ Docker, btrfs and a storage mount unit</li> <li>✓ Quiet steps, detail in install.log</li> <li>✓ Waits for systemd on a cold distro</li> <li>✓ Preloaded images tagged as the engine runs them</li> <li>✓ Summary with API key and <code>sslmode</code></li> <li>✓ Fresh install from v0.8.6 on Windows: preload used, no apt, key in the summary</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Unit ( <code>host_wsl_test.go</code> ); Windows run 16 Sep                           |
|  <b>A5</b> <b>Linux native</b>                                 | <ul style="list-style-type: none"> <li>✓ Engine runs in-process, no VM</li> <li>✓ <code>fox setup</code> explains nothing is needed</li> <li>✓ Services listen on loopback by default ( <code>FOX_LISTEN</code> to expose)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | VM integration (all suites run on Linux)                                             |
|  <b>A6</b> <b>Command forwarding &amp; host file streaming</b> | <ul style="list-style-type: none"> <li>✓ macOS → Lima VM, starts the VM if stopped</li> <li>✓ Windows → WSL distro</li> <li>✓ <code>fox import</code> streams a host file over stdin → <a href="#">Stream pipeline run spec files too</a></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Unit ( <code>TestImportLocalFile</code> , <code>TestWSLArgs</code> )                 |
|  <b>A7</b> <b>Always-latest engine binary</b>                  | <ul style="list-style-type: none"> <li>✓ Downloads the newest engine into the cache (ELF check)</li> <li>✓ <code>FOX_NO_REFRESH</code> , <code>FOX_VERSION</code></li> <li>✓ Verified against <code>SHA256SUMS</code> ; keeps the staged engine if not</li> <li>✓ Seen verifying on a real Windows install</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Unit ( <code>host_test.go</code> , <code>update_test.go</code> ); Windows run 16 Sep |
|  <b>A8</b> <b>New-release notice on fox start</b>              | <ul style="list-style-type: none"> <li>✓ Background check, 1.5 s limit, printed last</li> <li>✓ Only a promoted, newer, complete release</li> <li>✓ One request per start; a found release remembered 6 h, never "up to date"</li> <li>✓ Off switch; never on dev builds; silent offline</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Unit; update §1, §1b, §2, §3, §8; real Mac check                                     |
|  <b>A9</b> <b>fox update</b>                                   | <ul style="list-style-type: none"> <li>✓ Downloads and verifies everything before changing anything</li> <li>✓ Stops servers, installs engine, restarts old one on failure</li> <li>✓ <code>up</code> , Blackbox upgrade, <code>start</code> on the new engine</li> <li>✓ Replaces host <code>fox</code> , keeps previous binaries</li> <li>✓ <code>--check</code> , <code>--yes</code> , <code>--version</code></li> <li>✓ Linux path verified end to end</li> <li>✓ macOS path run against real releases (v0.8.3 → v0.8.4 → v0.8.5)</li> <li>□ Windows path run against a real release (deferred)</li> <li>✓ Release signatures (Ed25519 over <code>SHA256SUMS</code>)</li> <li>✓ The version line stays readable by older installs, so <code>fox update</code> works from any released version</li> <li>✓ A previously released version is shown to accept each build (nightly <code>upgrade suite</code> and each release ( <code>release-verify</code> )</li> </ul> | Unit; update §4–§7; a real Mac run                                                   |

| ID   | Feature · sub-features                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Tested by                                                                   |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| ✓ B1 | <b>The fox command set</b> <ul style="list-style-type: none"> <li>✓ Stack: setup, start, stop, up, down, status, check, logs, connect, psql, demo, update</li> <li>✓ Branching, backup / restore, HA</li> <li>✓ Blackbox, policy, impact</li> <li>✓ Import, pipelines</li> <li>✓ backup export / restore, pg status / upgrade</li> <li>✓ Users, API keys, admin</li> <li>✓ <code>fox vm status / fox vm shell</code> (Lima, WSL; Linux says there is no VM)</li> <li>✓ <code>branch create --from</code></li> <li>✓ <code>fox uninstall</code> removes it all, retired installs included</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Unit ( <code>main_test.go</code> , <code>update_test.go</code> ); VM suites |
| ✓ B2 | <b>Background services (daemon)</b> <ul style="list-style-type: none"> <li>✓ Control plane :8080, gateway :6432, agent API :8088</li> <li>✓ Detached, pidfiles and logs in <code>~/ .fox</code></li> <li>✓ Stop (TERM then KILL), status, logs</li> <li>✓ Containers restart on crash and after a reboot ( <code>--restart=unless--stopped</code> ); a container stopped on purpose stays stopped</li> <li>! The three background servers themselves are not supervised ( <code>fox check</code> reports them)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Unit ( <code>TestStopTerminatesProcess</code> ); VM §1                      |
| ✓ B3 | <b>First run (sample data, check, connect)</b> <ul style="list-style-type: none"> <li>✓ Sample data seeded into <code>main</code> on a first start: <code>users</code> , <code>projects</code> , <code>events</code> , five rows each, two foreign keys</li> <li>✓ <code>fox demo seed drop sql</code> on any branch; <code>FOX_NO_DEMO=1</code> starts empty</li> <li>✓ The console opens itself, with the one-time setup token already in the link</li> <li>✓ Declines to open a browser in the VM, over SSH, with no display, or with <code>FOX_NO_BROWSER</code></li> <li>✓ <code>fox check</code> : version, console, storage, main, three servers, three ports, TLS, Blackbox, backup age, sample data — each failure with the command that fixes it</li> <li>✓ <code>fox connect [branch]</code> prints the application's connection string, then opens psql; <code>fox psql</code> takes a branch</li> <li>✓ <code>fox branch create</code> ends with the connection string and how long it took</li> <li>✓ Plain-English errors in the CLI and the console ( <code>internal/errhint</code> , <code>web/src/errhint.ts</code> )</li> </ul> | Unit; v1 §11d                                                               |

## C Branching & storage

7 of 8 done

| ID   | Feature · sub-features                                                                                                                                                                                                                                                                                                                                                                                                        | Tested by                                                                   |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| ✓ C1 | <b>Storage drivers (ZFS / btrfs)</b> <ul style="list-style-type: none"> <li>✓ ZFS snapshot + clone per branch (macOS VM, Linux)</li> <li>✓ btrfs subvolume snapshots (Windows)</li> <li>✓ Pool / filesystem created on a loopback file</li> <li>✓ One storage interface for both</li> <li>✓ Delete removes the clone's own origin snapshot, so a non-main parent can be re-used</li> </ul>                                    | Unit; VM §2, §2b (ZFS); btrfs manual on Windows                             |
| ✓ C2 | <b>Branch lifecycle</b> <ul style="list-style-type: none"> <li>✓ Create, list, delete</li> <li>✓ Reset to parent</li> <li>✓ Suspend / resume</li> <li>✓ Recreate a container from its surviving data</li> <li>✓ Create from any branch ( <code>--from</code> , REST <code>from</code> , Dashboard picker)</li> <li>✓ Names validated in the CLI and at the API boundary (one check, <code>branch.checkName</code>)</li> </ul> | Unit; VM §2, §2b, §4                                                        |
| ✓ C3 | <b>Protection of main</b> <ul style="list-style-type: none"> <li>✓ Delete and reset refused</li> <li>✓ Suspend refused for main, the HA standby and whichever container serves main</li> </ul>                                                                                                                                                                                                                                | Unit; VM §4, §6                                                             |
| ✓ C4 | <b>Private networking (no host ports)</b> <ul style="list-style-type: none"> <li>✓ Branch databases reachable only through the gateway</li> <li>✓ Published ports (object store, restore, debug) on loopback only; standby unpublished</li> <li>✓ An older install's public object store is re-created on start</li> </ul>                                                                                                    | Unit ( <code>TestParsePublishedPort</code> , <code>TestDSN</code> ); VM §1c |
| ✓ C5 | <b>Scale-to-zero &amp; wake on connect</b> <ul style="list-style-type: none"> <li>✓ Idle branches suspended automatically</li> <li>✓ Next connection wakes the branch (~0.3–0.7 s)</li> <li>✓ HA standby never suspended</li> <li>→ Idle clocks survive a gateway restart</li> </ul>                                                                                                                                          | VM §7                                                                       |
| 🔥 C6 | <b>Storage quotas</b> <ul style="list-style-type: none"> <li>✓ Space reserved for main (ZFS)</li> <li>🔥 Per-branch cap (opt-in)</li> <li>□ Quotas on btrfs</li> </ul>                                                                                                                                                                                                                                                         | Manual                                                                      |
| ✓ C7 | <b>Capacity &amp; status</b> <ul style="list-style-type: none"> <li>✓ Services, main health, backups, branches</li> <li>✓ Storage used / available</li> <li>! btrfs "used" is apparent size</li> </ul>                                                                                                                                                                                                                        | VM §1                                                                       |

|   |                                                                                                                                                                                                                                         |               |
|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| ✓ | <b>C8 Provisioning &amp; image pull</b>                                                                                                                                                                                                 | Unit; VM §11b |
| ✓ | <ul style="list-style-type: none"> <li>Docker, storage pool and image prepared on up</li> <li>Pulls from GHCR, builds locally as fallback</li> <li>The build context is built into fox, so the fallback works on any install</li> </ul> |               |

D Durability

5 of 6 done

| ID                                         | Feature · sub-features                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Tested by                                                                        |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| ✓ D1                                       | <b>WAL archiving to object storage</b> <ul style="list-style-type: none"> <li>wal-g ships main's WAL to MinIO, off the commit path</li> <li>MinIO images pinned on quay.io</li> <li>Branches are disposable by design (export one that matters)</li> <li>Remote S3 target ( fox backup target set ), keys in 0600 env files</li> <li>Object Lock reported; tested on MinIO</li> </ul>                                                                                                                                                                                                                                                                                                                            | VM §3; VM §11c; not yet run against AWS S3                                       |
| ✓ D2                                       | <b>Base backups</b> <ul style="list-style-type: none"> <li>Create and list</li> <li>Follow the primary after a failover; listing works with main stopped</li> <li>Read-only listing: GET /api/backups and a Dashboard panel</li> <li>Schedule and retention ( FOX_BACKUP_INTERVAL , FOX_BACKUP_RETAIN )</li> <li>A first backup at install</li> <li>Age shown and warned in fox status and the status API</li> <li>Proven, not assumed: fox backup verify writes a probe row, waits for its WAL segment to be archived, restores the newest base backup into a container of its own and reads the row back</li> <li>On a schedule (weekly; FOX_RESTORE_CHECK_INTERVAL ), with the result in fox check</li> </ul> | VM §3, §3b, §6; VM §11c                                                          |
| ✓ D3                                       | <b>Point-in-time restore</b> <ul style="list-style-type: none"> <li>Restore to a timestamp or latest on :5433</li> <li>Per-install credentials</li> <li>Starts from the newest base backup that precedes the target</li> <li>A point no backup precedes is refused, naming the oldest</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                 | Unit; VM §3, §3b, §6; v2 §1a                                                     |
| 🔥 D4                                       | <b>HA standby &amp; failover</b> <ul style="list-style-type: none"> <li>Streaming hot standby</li> <li>Manual failover, main rerouted</li> <li>Nothing deletes or stops the promoted standby</li> <li>fox up brings it back, not the old main</li> <li>fox ha fallback, keeping every write</li> <li>The promoted standby archives WAL, so backups and PITR cover the failover</li> <li>Automatic failover, fencing, multi-host</li> </ul>                                                                                                                                                                                                                                                                       | Unit; VM §6, §7                                                                  |
| ✓ D5                                       | <b>Portable export &amp; restore</b> <ul style="list-style-type: none"> <li>Every non-agent branch: pg_dump, its roles, the Blackbox head; SHA256SUMS over all</li> <li>Copied out of the VM and verified on the host; a copy that fails is deleted</li> <li>Damaged, incomplete or path-escaping archives refused</li> <li>Restore into a new branch, same or newer major; Blackbox checked exact</li> </ul>                                                                                                                                                                                                                                                                                                    | Unit; VM pg-upgrade §1; the host copy on macOS/Windows is unit-tested only       |
| ✓ D6                                       | <b>PostgreSQL major upgrade</b> <ul style="list-style-type: none"> <li>fox pg status : the major of the install and of each branch</li> <li>Plan with every change crossed, found-in-your-data first; refusals say what to do</li> <li>Asks, exports, then reloads every carried branch on the new major</li> <li>Data, roles, API keys and every Blackbox entry come across</li> <li>Old databases held outside the branch namespace; rollback and finalize</li> <li>Each upgraded cluster archives WAL under its own prefix</li> </ul>                                                                                                                                                                         | Unit; VM pg-upgrade (72 / 72); the btrfs (Windows) holding area has not been run |
| → Carry agent branches; upgrade with HA on |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                  |

E Security foundations

3 of 3 done

| ID   | Feature · sub-features                                                                                                                                                                                                                                                 | Tested by                       |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| ✓ E1 | <b>Per-install generated secrets</b> <ul style="list-style-type: none"> <li>Generated Postgres and MinIO passwords</li> <li>Used by restore too</li> <li>Each login role has its own derived password</li> <li>Never on a command line (docker --env-file )</li> </ul> | Unit (indirect); v2 §1a; VM §1d |

|   |                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                     |
|---|---------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| ✓ | <b>E2 TLS everywhere</b>                          | <ul style="list-style-type: none"> <li>✓ Self-signed TLS on all three services, zero setup</li> <li>✓ TLS required from other machines (loopback clients may skip it)</li> <li>✓ No plain-HTTP fallback except on loopback</li> </ul>                                                                                                                                                                                   | Unit<br>( <code>TestReadStartupUpgradesTLS</code> ) |
| ✓ | <b>E3 Keys are made by a person, not by start</b> | <ul style="list-style-type: none"> <li>✓ Start creates no account and no key, and caches none on disk</li> <li>✓ The banner shows the connection string and how to make a key</li> <li>✓ The first account created gets the admin grant on main</li> <li>✓ First account over HTTP needs the setup token ( <code>fox setup-token</code> )</li> <li>✓ Exactly one first account, however many sign up at once</li> </ul> | Integration §1                                      |

## F SQL gateway

7 of 7 done

| ID | Feature · sub-features                                                                                                                                                                          | Tested by                                                                                                                                                                    |
|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ✓  | <b>F1 Routing by database name</b> <ul style="list-style-type: none"> <li>✓ One endpoint :6432, database name = branch</li> </ul>                                                               | Unit; VM §1, §6<br>→ <a href="#">Connection pooling, rate limiting</a>                                                                                                       |
| ✓  | <b>F2 API-key authentication</b> <ul style="list-style-type: none"> <li>✓ <code>key_</code> key as the Postgres password</li> <li>✓ Bad key rejected with a Postgres error</li> </ul>           | VM §1<br><ul style="list-style-type: none"> <li>✓ Startup deadline and connection cap</li> <li>✓ An account key opens main, its own branches, or any for an admin</li> </ul> |
| ✓  | <b>F3 Backend login (SCRAM)</b> <ul style="list-style-type: none"> <li>✓ Cleartext, md5, SCRAM-SHA-256</li> </ul>                                                                               | VM §1, §6, §8 (exercised); no unit test for SCRAM yet<br><ul style="list-style-type: none"> <li>✓ Clients never see the database password</li> </ul>                         |
| ✓  | <b>F4 Per-user Postgres login roles</b> <ul style="list-style-type: none"> <li>✓ Role per user, actor can't be forged</li> <li>✓ Permissions of non-superuser <code>db_client</code></li> </ul> | Manual<br><ul style="list-style-type: none"> <li>✓ Own password per role</li> </ul>                                                                                          |
| ✓  | <b>F5 Attribution session settings</b> <ul style="list-style-type: none"> <li>✓ Actor kind, branch, session id per connection</li> </ul>                                                        | VM §8<br>! <a href="#">Kind / branch / session client-settable</a>                                                                                                           |
| ✓  | <b>F6 Ctrl-C (CancelRequest) forwarding</b> <ul style="list-style-type: none"> <li>✓ Cancel a running query through the gateway</li> </ul>                                                      | Unit                                                                                                                                                                         |
| ✓  | <b>F7 Errors &amp; insecure build tag</b> <ul style="list-style-type: none"> <li>✓ Real Postgres error responses</li> </ul>                                                                     | Unit ( <code>TestSendError</code> )<br><ul style="list-style-type: none"> <li>✓ No-auth bypass impossible in release builds</li> </ul>                                       |

## G Accounts & auth

5 of 6 done

| ID | Feature · sub-features                                                                                                                                                                                                                                                                                                                                     | Tested by                                                                                                                                                                                                                                                                                                 |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ✓  | <b>G1 Auth store (SQLite)</b> <ul style="list-style-type: none"> <li>✓ Users, keys, sessions, OAuth ids, pipelines</li> <li>✓ Safe under concurrent use (WAL, busy timeout), including a new store created by three services at once</li> </ul>                                                                                                            | Unit ( <code>TestVerifyKeyConcurrent</code> , <code>TestConcurrentFirstOpen</code> ); VM §1<br>→ <a href="#">Roles / permissions, multi-tenant projects</a>                                                                                                                                               |
| ✓  | <b>G2 Email &amp; password users</b> <ul style="list-style-type: none"> <li>✓ Create account, log in</li> <li>✓ Password change (signs out other sessions); admin reset at the CLI</li> <li>→ <a href="#">Self-service reset by email</a></li> <li>✓ List and delete users (admins)</li> <li>✓ Emails validated; at most 63 bytes (a role name)</li> </ul> | Unit; VM §1; VM §1d<br><ul style="list-style-type: none"> <li>✓ Forgotten password: <code>fox user passwd</code>, named on the login page, README and Guide</li> <li>! <a href="#">No self-service reset by email — it needs the machine, which suits a local install and not a hosted one</a></li> </ul> |
| ✓  | <b>G3 API keys</b> <ul style="list-style-type: none"> <li>✓ Create (shown once), list, revoke</li> <li>✓ Bearer / X-API-Key and gateway password</li> </ul>                                                                                                                                                                                                | Unit; VM §1<br><ul style="list-style-type: none"> <li>✓ Revoking an id that is not there is refused (404), not reported as revoked</li> </ul>                                                                                                                                                             |
| ✓  | <b>G4 Web sessions &amp; signup control</b> <ul style="list-style-type: none"> <li>✓ httpOnly session cookie</li> <li>✓ Sign-up closed by default ( <code>FOX_SIGNUP=open</code> )</li> </ul>                                                                                                                                                              | Unit ( <code>TestSessions</code> )<br><ul style="list-style-type: none"> <li>✓ Failed sign-ins throttled</li> </ul>                                                                                                                                                                                       |

|                                                                                   |                                   |                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                   |              |
|-----------------------------------------------------------------------------------|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
|  | <b>G5 OAuth (GitHub / Google)</b> | <ul style="list-style-type: none"> <li>✓ Sign-in flows built</li> <li>✓ Defaults match what the engine serves ( <code>https://localhost:8080</code> ; web origin = public URL)</li> <li>✓ Session cookie <code>Secure</code> / <code>SameSite</code> follow the origin</li> </ul> | <ul style="list-style-type: none"> <li>□ Tested with a real OAuth app</li> <li>✓ Only a provider-verified email joins or creates an account; closed sign-up respected</li> <li>✓ State cookie one-use, <code>Secure</code> , <code>SameSite=Lax</code></li> </ul> | Unit; VM §1b |
|-----------------------------------------------------------------------------------|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|

|   |                        |                                                                                                                                                                                     |                                                                                                                                                                               |              |
|---|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| ✓ | <b>G6 Security log</b> | <ul style="list-style-type: none"> <li>✓ Sign-ins, failures, keys, passwords, accounts, admin grants, refusals</li> <li>✓ Hash-chained, append-only, anchored and signed</li> </ul> | <ul style="list-style-type: none"> <li>✓ <code>fox audit</code>, <code>verify</code>, <code>GET /api/audit</code><br/>→ Included in <code>fox backup export</code></li> </ul> | Unit; VM §1d |
|---|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|

## H Blackbox (record of schema changes) 16 of 18 done

| ID   | Feature · sub-features                                                                                                                                                                                                                                                                                                                                                        | Tested by                             |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|
| ✓ H1 | <b>DDL recording</b> <ul style="list-style-type: none"><li>✓ Who, tool, branch, statement, status, risk</li><li>✓ Inherited by every branch</li><li>✓ A restart records nothing: the install script's own statements are not captured</li><li>! Role / database changes, some dropped object types</li><li>✓ Agents' UPDATE and DELETE recorded; TRUNCATE by anyone</li></ul> | VM §8; v2 §9; v2 §10                  |
| 🔥 H2 | <b>Hash chain, append-only &amp; verify</b> <ul style="list-style-type: none"><li>✓ Rows can't be edited or deleted normally</li><li>✓ fox ledger verify</li><li>🔥 Superuser rewrite caught only via anchors (H10–H12)</li></ul>                                                                                                                                              | VM §8; v2 §0, §6b                     |
| ✓ H3 | <b>Attribution</b> <ul style="list-style-type: none"><li>✓ Humans via their login role</li><li>✓ Agents via their own agent-&lt;id&gt; role</li></ul>                                                                                                                                                                                                                         | Unit; VM §8; v2 §1c                   |
| ✓ H4 | <b>Destructive-DDL guardrail</b> <ul style="list-style-type: none"><li>✓ DROP TABLE / DROP SCHEMA refused, attempt recorded</li><li>✓ Override only superusers / db_admin , use recorded</li></ul>                                                                                                                                                                            | VM §8; v2 §1b, §6b                    |
| ✓ H5 | <b>Risk flags</b> <ul style="list-style-type: none"><li>✓ Type change, drop column flagged</li><li>✓ Judged on the running statement (no comments or literals)</li></ul>                                                                                                                                                                                                      | Unit; v2 §6b                          |
| ✓ H6 | <b>Blackbox access (CLI / REST / MCP / UI / SDK)</b> <ul style="list-style-type: none"><li>✓ CLI, REST with filters, MCP, web page, SDKs</li></ul>                                                                                                                                                                                                                            | v2 §0, §5                             |
| ✓ H7 | <b>fox ledger revert --to</b> <ul style="list-style-type: none"><li>✓ Help and output say it's a point-in-time restore of main</li></ul>                                                                                                                                                                                                                                      | Unit (help text); VM §3 (the restore) |
| ✓ H8 | <b>Override permission (db_admin) &amp; upgrade</b> <ul style="list-style-type: none"><li>✓ fox admin grant revoke list</li><li>✓ First user granted automatically</li></ul>                                                                                                                                                                                                  | v2 §1b, §6                            |
| ✓ H9 | <b>Blackbox 2.0 capture</b> <ul style="list-style-type: none"><li>✓ Transaction id and WAL position per entry</li><li>✓ Task, tool-call hash, override use</li></ul>                                                                                                                                                                                                          | Unit; v2 §2                           |

|   |                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                    |
|---|------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| ✓ | <b>H10 Checkpoints &amp; anchors</b>                       | <ul style="list-style-type: none"> <li>✓ Merkle root in the database and in read-only anchor files</li> <li>✓ On a schedule and on demand</li> <li>✓ Published anchor format</li> <li>✓ Copied to the backup target (S3 Object Lock)</li> <li>✓ Anchors signed (Ed25519, key outside the databases)</li> </ul>                                                                                                                                                                                                                                                                                           | Unit; v2 §3, §3b   |
| ✓ | <b>H11 fox-verify (independent verifier)</b>               | <ul style="list-style-type: none"> <li>✓ Checks a live branch or an export</li> <li>✓ Release binaries for every platform</li> <li>✓ <code>--pubkey</code> checks signatures</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                  | Unit; v2 §3        |
| ✓ | <b>H12 Blackbox integrity &amp; export</b>                 | <ul style="list-style-type: none"> <li>✓ INTACT / TAMPERED via CLI, REST, MCP</li> <li>✓ JSON-lines export</li> <li>→ Streaming for very large ledgers</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                        | v2 §3              |
| ✓ | <b>H13 Branch from just before a Blackbox entry</b>        | <ul style="list-style-type: none"> <li>✓ Restore + replay up to the change's transaction</li> <li>✓ By transaction id or timestamp</li> <li>✓ CLI, REST, MCP, the Integrity panel, and every row of the Blackbox page</li> <li>✓ main untouched</li> <li>✓ Documented: README, the Guide's step 6, and the reference</li> </ul>                                                                                                                                                                                                                                                                          | Unit; v2 §4; VM ui |
| ✓ | <b>H14 Blackbox names &amp; aliases</b>                    | <ul style="list-style-type: none"> <li>✓ <code>fox blackbox</code>, <code>/blackbox</code> routes, MCP and SDK names</li> <li>✓ Every original name still works</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                               | Unit; v2 §5        |
| ✓ | <b>H15 Policy gate (warn / block)</b>                      | <ul style="list-style-type: none"> <li>✓ BBX02 warn / BBX01 block with JSON detail</li> <li>✓ Blocked attempts recorded</li> <li>✓ Per-rule <code>db_admin</code> override</li> <li>✓ CLI, REST, MCP, web page; custom rules</li> <li>✓ Patterns match the running statement</li> <li>✓ TRUNCATE (its own guardrail, H4)</li> </ul>                                                                                                                                                                                                                                                                      | Unit; v2 §6, §6b   |
| ✓ | <b>H16 Agent provenance &amp; execute_change</b>           | <ul style="list-style-type: none"> <li>✓ Session, task, parent session on every agent change (also through the Gateway DSN)</li> <li>✓ MCP <code>execute_change</code> with policy preview</li> <li>✓ <code>fox blackbox sessions</code>, REST</li> <li>! Provenance is what the agent says (not verified)</li> </ul>                                                                                                                                                                                                                                                                                    | Unit; v2 §7        |
| 🔗 | <b>H17 Impact analysis</b>                                 | <ul style="list-style-type: none"> <li>✓ Dependents (views, foreign keys, indexes, depth)</li> <li>✓ Other branches that have the object</li> <li>✓ Policy verdict and risk score</li> <li>✓ CLI, REST, MCP, inside <code>execute_change</code></li> <li>🔗 Functions, types, schemas not recognised from SQL</li> </ul>                                                                                                                                                                                                                                                                                  | Unit; v2 §8        |
| ✓ | <b>H18 Blackbox diff, and promoting a branch's changes</b> | <ul style="list-style-type: none"> <li>✓ Fork point, changes only on each side</li> <li>✓ Objects changed on both</li> <li>✓ Diff: CLI, REST, MCP</li> <li>✓ Promotion: a branch's recorded statements, reviewed, then applied to another branch in one transaction</li> <li>✓ Refused on a conflict (both sides changed the same object), on a statement the target's gate blocks, and when there is nothing to promote</li> <li>✓ Approving needs the right to manage the target, so an agent cannot approve its own request</li> <li>✓ Promotion: CLI, REST, MCP and the web Requests page</li> </ul> | Unit; v2 §8, §8b   |

## I Import & migration

13 of 13 done

| ID   | Feature · sub-features                                                                                                                                                                                                 | Tested by                     |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| ✓ I1 | <b>From Postgres</b> <ul style="list-style-type: none"> <li>✓ Schema and data via <code>pg_dump</code></li> <li>✓ Zero-table result reported as an error</li> </ul>                                                    | Manual; no automated test yet |
| ✓ I2 | <b>From MySQL ≤5.7 / MariaDB</b> <ul style="list-style-type: none"> <li>✓ pgloader with type mapping (multi-arch image)</li> </ul>                                                                                     | Manual; no automated test yet |
| ✓ I3 | <b>From MySQL 8.x</b> <ul style="list-style-type: none"> <li>✓ Native mysqldump path (<code>caching_sha2_auth</code>)</li> <li>✓ Types, NULLs, unicode, PK</li> <li>→ Other indexes, foreign keys, defaults</li> </ul> | Manual; no automated test yet |

|   |                                                                                                                                                                                                                                                                                                 |                      |
|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| ✓ | <b>I4 From MongoDB</b><br>✓ Collection → typed table, exact name<br>✓ Nested objects / arrays kept as jsonb                                                                                                                                                                                     | VM §9, §10           |
| ✓ | <b>I5 From a .sql dump</b><br>✓ Runs the dump into a new branch<br>✓ Fails listing every failed statement (instance kept)<br>✓ Same for Postgres imports (I1)<br>✓ Automated test                                                                                                               | Unit; VM §11         |
| ✓ | <b>I6 From JSON / NDJSON</b><br>✓ Columns inferred from top-level keys<br>✓ An invalid document fails the import, naming its element or line                                                                                                                                                    | Unit; VM §10, §11    |
| ✓ | <b>I7 From CSV</b><br>✓ Table from the header, exact column names<br>! Typed columns (all text today)                                                                                                                                                                                           | Manual               |
| ✓ | <b>I8 Continuous replication &amp; cutover</b><br>✓ Initial copy + streaming (logical replication)<br>✓ Cutover keeps data (CLI)<br>✓ Status and cutover from REST and the Import page<br>✓ A replicating branch is never auto-suspended<br>✓ Automated test (VM §5b) and driven in the browser | Unit; VM §5b         |
| ✓ | <b>I9 Guard handling during import</b><br>✓ Guardrail paused, recording stays on<br>✓ Re-armed even after a crash                                                                                                                                                                               | Manual               |
| ✓ | <b>I10 Live progress (CLI &amp; SSE)</b><br>✓ Live log and progress bar<br>! psql subprocess output not streamed                                                                                                                                                                                | Manual               |
| ✓ | <b>I11 Import REST endpoints</b><br>✓ From a connection string or an uploaded file<br>✓ Target names validated (the import creates the branch through branch.Create)<br>✓ Private, local and container sources for admins only; metadata refused                                                | Manual; unit; VM §1d |
| ✓ | <b>I12 Web Import page</b><br>✓ Database and file panels with live console<br>✓ No longer claims a SQLite loader that doesn't exist                                                                                                                                                             | Manual               |
| ✓ | <b>I13 Exact identifier fidelity</b><br>✓ Case kept ( <code>userId</code> , <code>leaseAiChats</code> )<br>! Field order of JSON sources not kept                                                                                                                                               | Unit; VM §10         |

## J ETL pipelines (experimental)

4 of 4 done

| ID | Feature · sub-features                                                                                                                                                                                                                                                                                                                                                               | Tested by   |
|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| ✓  | <b>J1 Pipeline engine</b><br>✓ Extract → raw schema → SQL models → tests, in a fresh branch<br>✓ <code>ref()</code> / <code>source()</code> templating<br>→ <a href="#">Dependency graph</a><br>→ <a href="#">Incremental models</a><br>→ <a href="#">Scheduling</a><br>✓ A run replaces only a branch the pipeline made<br>✓ API sources are connection strings, never server paths | Unit; VM §9 |
| ✓  | <b>J2 Data-quality tests</b><br>✓ <code>not_null</code> , <code>unique</code> , <code>accepted_values</code> , <code>row_count_min</code> , <code>custom</code><br>✓ Failure → exit 1, data kept                                                                                                                                                                                     | Unit; VM §9 |
| ✓  | <b>J3 Stored pipelines &amp; run history</b><br>✓ Saved per user, run over the API, history<br>→ <a href="#">Read a run's log</a><br>→ <a href="#">Mark runs whose process died</a>                                                                                                                                                                                                  | Manual      |
| ✓  | <b>J4 Pipeline editor (web)</b><br>✓ Create, edit, run, results, history<br>→ <a href="#">Confirm before delete</a>                                                                                                                                                                                                                                                                  | Manual      |

## K APIs, SDKs & agents

6 of 6 done

| ID | Feature · sub-features                                                                                                                                                                                                                                                                                                                                           | Tested by                     |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| ✓  | <b>K1 Control-plane REST API</b><br>✓ Branches, query, Blackbox, policy, impact, import, pipelines, keys<br>✓ Versioned paths: <code>/api/v1/...</code> reaches the same routes, and <code>/api/...</code> keeps working<br>✓ Exact-origin CORS, branch-name check, body limits, timeouts<br>✓ Branches owned by their maker; others 404 (owner, admin, or main) | Unit; VM §1; v2 §0–§8; VM §1d |

|   |                            |                                                                                                                                                                                                                                                                                                                                                                                                               |                         |
|---|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| ✓ | <b>K2 OpenAPI spec</b>     | <ul style="list-style-type: none"> <li>✓ Served, Blackbox 2.0 endpoints documented</li> <li>✓ Matches the code (import fields, status codes, auth routes, /blackbox aliases)</li> <li>✓ Drift check in CI</li> </ul>                                                                                                                                                                                          | Unit (drift check)      |
| ✓ | <b>K3 Python SDK</b>       | <ul style="list-style-type: none"> <li>✓ Branches, query, Blackbox</li> <li>→ <a href="#">Import, pipelines, keys, agents</a></li> <li>✓ Contract tests against a live engine (nightly sdks suite)</li> <li>→ <a href="#">Publish to PyPI</a></li> <li>✓ Contract tests against a live engine</li> </ul>                                                                                                      | Manual; VM sdks         |
| ✓ | <b>K4 TypeScript SDK</b>   | <ul style="list-style-type: none"> <li>✓ Same client for Node and browsers</li> <li>✓ Contract tests against a live engine (nightly sdks suite)</li> <li>→ <a href="#">Publish to npm</a></li> <li>✓ Compiles, and contract tests against a live engine</li> </ul>                                                                                                                                            | Manual; VM sdks         |
| ✓ | <b>K5 Agent Branch API</b> | <ul style="list-style-type: none"> <li>✓ A branch per agent, own non-superuser role</li> <li>✓ Provenance (task, parent, session)</li> <li>✓ DSN reachable from the host (gateway-routed, branch-scoped key)</li> <li>✓ Cap, listing and TTL count suspended branches</li> <li>✓ Superuser switch only in <code>-tags insecure</code> builds</li> <li>✓ Agents and their keys belong to the caller</li> </ul> | Unit; VM §5; v2 §1c, §7 |
| ✓ | <b>K6 MCP server</b>       | <ul style="list-style-type: none"> <li>✓ Branches, run_sql, Blackbox tools</li> <li>✓ policy_check, execute_change, impact, diff</li> <li>✓ Requires an API key and acts as that account; a scoped key is held to its branch</li> <li>✓ Client config &amp; 16-tool reference (docs/mcp.md)</li> <li>✓ Same ownership rule as the REST API</li> </ul>                                                         | Unit; v2 §1c–§8         |

## L Web console

11 of 11 done

| ID   | Feature · sub-features                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Tested by              |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| ✓ L1 | <b>Embedded single-origin UI</b> <ul style="list-style-type: none"> <li>✓ Served by the engine at :8080</li> <li>✓ Automated UI tests (Playwright, in the nightly ui suite)</li> <li>✓ One branch-list loader for every selector: retries a dropped request, reports one it cannot load</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Manual                 |
| ✓ L2 | <b>Login &amp; signup</b> <ul style="list-style-type: none"> <li>✓ Log in / sign up tabs, OAuth buttons</li> <li>✓ Covered by the console's Playwright tests</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Manual; VM ui          |
| ✓ L3 | <b>Dashboard</b> <ul style="list-style-type: none"> <li>✓ Live tiles</li> <li>✓ Branch table: create, suspend, resume, delete, copy DSN</li> <li>✓ Covered by the console's Playwright tests</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Manual; VM ui          |
| ✓ L4 | <b>SQL console &amp; browser</b> <ul style="list-style-type: none"> <li>✓ Schema sidebar, rows, structure, indexes</li> <li>✓ Values shown as Postgres writes them (uuid, interval, inet, bytea)</li> <li>✓ SQL editor</li> <li>✓ System tables hidden by default, with a show button</li> <li>✓ Runs as the signed-in user; one-run override switch</li> <li>✓ Per-rule override for policy blocks</li> <li>! One statement per run (extended protocol)</li> <li>✓ Runs a script, not just one statement: a result per statement, and one transaction unless it opens its own</li> <li>✓ Each result says which statement produced it; labelling is dropped rather than guessed when a split is unsafe</li> <li>✓ Editor is read-only while a query runs, and <code>⌘/Ctrl+↵</code> no longer starts a second one</li> <li>✓ Workbench layout: fills the window, schema rail folds away, results in tabs, either pane expands</li> <li>✓ Line numbers, and a syntax error reports its line and column and marks the gutter</li> <li>✓ Page heading kept for screen readers after the title block became a toolbar</li> </ul> | Manual; API in v2 §6   |
| ✓ L5 | <b>Blackbox page</b> <ul style="list-style-type: none"> <li>✓ Entries per branch with badges</li> <li>✓ Table / risk / date filters, and "Clear filters"</li> <li>✓ Verify button; a row expands to its statement and session</li> <li>✓ Live: new entries arrive on their own (3s), marked briefly, pausable; never while older pages are being read</li> <li>✓ The chain is visible: entry id, its row hash and the previous entry's, each copyable</li> <li>✓ "Branch from before this change" on the row itself ( <code>main</code> ; explained elsewhere)</li> <li>✓ Covered by the console's Playwright tests</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | v2 §5b; browser; VM ui |

|   |                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                     |                                                                                       |
|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| ✓ | <b>L6 API keys page</b> <ul style="list-style-type: none"> <li>✓ Create, copy, list, revoke</li> <li>✓ A new key is shown inside its connection string (E3's next step)</li> </ul>                                                                                            | <ul style="list-style-type: none"> <li>✓ Covered by the console's Playwright tests</li> </ul>                                                                                                                                                                                                                       | Manual; browser review 21 Sep; VM ui                                                  |
| ✓ | <b>L7 Landing, Guide &amp; Docs pages</b> <ul style="list-style-type: none"> <li>✓ Landing, developer guide, reference</li> </ul>                                                                                                                                             | <ul style="list-style-type: none"> <li>✓ Refreshed against the code (https, sslmode, MCP, Blackbox, import routes)</li> </ul>                                                                                                                                                                                       | Type-check + build                                                                    |
| ✓ | <b>L8 Blackbox integrity page</b> <ul style="list-style-type: none"> <li>✓ Verify, checkpoint, export, branch-before</li> <li>✓ Used signed in; every result matched the CLI</li> </ul>                                                                                       | <ul style="list-style-type: none"> <li>✓ New entries arrive on their own (3s), marked briefly, pausable</li> </ul>                                                                                                                                                                                                  | Type-check + build; browser review 16 Sep                                             |
| ✓ | <b>L9 Policies page</b> <ul style="list-style-type: none"> <li>✓ Rules, warn/block, custom rules, preview, evaluations</li> <li>✓ Used signed in; matched the CLI, wrote only to the chosen branch</li> </ul>                                                                 | <ul style="list-style-type: none"> <li>✓ Non-admin change refused with a readable message</li> <li>✓ Who can override: list, grant, revoke</li> </ul>                                                                                                                                                               | Type-check + build; API in v2 §6; browser review 16 Sep                               |
| ✓ | <b>L10 App sidebar layout</b> <ul style="list-style-type: none"> <li>✓ Every link opens its page, highlighted, with breadcrumb</li> </ul>                                                                                                                                     | <ul style="list-style-type: none"> <li>✓ Collapse persists across a reload; theme toggle persists</li> <li>✓ No console errors on any page</li> </ul>                                                                                                                                                               | Type-check + build; browser review 16 Sep; the under-860px drawer needs a manual look |
| ✓ | <b>L11 Design system &amp; FoxByte theme</b> <ul style="list-style-type: none"> <li>✓ Tokens for colour, type, space, radius, elevation and motion; components use no raw values</li> <li>✓ Ember palette in both themes; filled controls legible ( --accent-ink )</li> </ul> | <ul style="list-style-type: none"> <li>✓ Logo artwork as the mark, wordmark from brand.json accenting the logo's letter, favicon and touch icon</li> <li>✓ Console, Blackbox, Policies and API keys re-laid out; one table style</li> <li>✓ Every page reviewed in both themes; console checked at 375px</li> </ul> | Type-check + build; browser review 21 Sep; not yet reviewed against real data         |

M

## Build, CI & releases

8 of 8 done

| ID   | Feature · sub-features                                                                                                                                                                                                                 | Tested by                                                                                                             |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| ✓ M1 | <b>Makefile targets</b> <ul style="list-style-type: none"><li>✓ build, vet, test, integration suites</li><li>✓ Suites run only in a throwaway test VM (guarded)</li></ul>                                                              | CI                                                                                                                    |
| ✓ M2 | <b>Linux CI</b> <ul style="list-style-type: none"><li>✓ Build, vet, test, gofmt</li><li>✓ Release script tests, checklist sync check</li><li>✓ VM integration suites nightly in CI (one runner per suite)</li></ul>                    | CI                                                                                                                    |
| ✓ M3 | <b>Windows CI</b> <ul style="list-style-type: none"><li>✓ Build, vet, test, Pester, installer encoding</li></ul>                                                                                                                       | CI; no end-to-end WSL install test yet                                                                                |
| ✓ M4 | <b>Releases &amp; GHCR image</b> <ul style="list-style-type: none"><li>✓ Binaries for 5 platforms + fox-verify</li><li>✓ SHA256SUMS merged safely between jobs</li><li>✓ Fails unless fox update 's files are published</li></ul>      | Script tests in CI                                                                                                    |
| ✓ M5 | <b>WSL distro &amp; ZFS builds</b> <ul style="list-style-type: none"><li>✓ Prebuilt distro image</li><li>✓ Downloaded and verified by the installer (seen on Windows)</li><li>✓ Preloaded image tagged as the engine runs it</li></ul> | Actions artifacts; Pester; Windows run 16 Sep; the zstd unpack is unit-tested only, not run on a real Windows install |

|   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                  |
|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| ✓ | <p><b>M6 Postgres image</b></p> <ul style="list-style-type: none"> <li>✓ PostgreSQL 18 + wal-g for a fresh install; one image per supported major (16, 18)</li> <li>✓ The image follows the data: an install on 16 keeps running 16 after an update</li> <li>✓ A branch on the wrong major is refused before <code>docker run</code>, with the way out</li> <li>✓ The major lives in one place, and a test holds the Dockerfile, release matrix and Windows preload to it</li> <li>✓ All three suites pass on PostgreSQL 18.6: 108 + 277 + 51 checks (21 Sep)</li> </ul> | Unit; all three suites on 18                                                     |
| ✓ | <p><b>M7 Product name in one file</b></p> <ul style="list-style-type: none"> <li>✓ <code>brand.json</code> → Go, shell, web and installer blocks, regenerated by <code>make brand</code></li> <li>✓ Stored names brand-free and frozen: a rename never migrates an install</li> <li>✓ Retired env prefixes, state directory, VM names and installs still handled</li> </ul>                                                                                                                                                                                              | Unit (brand, gen, oldnames), in CI via <code>go test</code>                      |
| ✓ | <p><b>M8 Two editions</b></p> <ul style="list-style-type: none"> <li>✓ One tree, two binaries: <code>fox</code> (Standard, AGPL) and <code>fox-enterprise</code></li> <li>✓ <code>enterprise/</code> has its own commercial LICENSE and <code>LicenseRef-</code> headers</li> <li>✓ The Standard binary contains no paid code — checked with <code>go tool nm</code>, not just the source</li> <li>✓ An Enterprise build with no licence behaves exactly like Standard</li> </ul>                                                                                        | Unit (edition, boundary), <code>scripts/test_editions.sh</code> , CI builds both |

## N Not started (roadmap)

7 items

Planned or discussed, nothing built yet. When work starts, move the row into its area with the next id there.

| ID                                  | Item · scope                                                                                                           | Related                                                                                            |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| <input type="checkbox"/>            | <b>Multi-tenant projects</b><br><input type="checkbox"/> Projects / organisations, and roles within them               | G1, H6<br>✓ Per-branch permissions: owner or admin, on every branch-scoped route (G2 of the audit) |
| <input type="checkbox"/>            | <b>Automatic HA failover</b><br><input type="checkbox"/> Health detection, fencing <input type="checkbox"/> Multi-host | D4                                                                                                 |
| <input type="checkbox"/>            | <b>Pipelines: scheduling, incremental / CDC extract, DAG view</b>                                                      | J1                                                                                                 |
| <input type="checkbox"/>            | <b>More import sources: Cassandra, DynamoDB</b>                                                                        | I1–I8                                                                                              |
| <input checked="" type="checkbox"/> | <b>Release signatures</b> — done 22 Sep 2026                                                                           | A9, M4                                                                                             |
| <input type="checkbox"/>            | <b>Hosted cloud tier</b>                                                                                               | —                                                                                                  |
| <input type="checkbox"/>            | <b>Networked storage disaggregation</b> (README roadmap; see the storage engine note on page 1)                        | C1, D1                                                                                             |

### Out of scope by decision

A custom storage engine (PostgreSQL's own engine is used, for native transaction speed), sharding, Raft / distributed transactions, multi-region, HTAP.