


Slip on Faults and Stress Inversion

Prithvi Thakur

Jan 30, 2019

Anderson's Theory of Faulting


- ▶ Earth's free surface cannot support shear, therefore, one of the principal stresses has to be vertical. **Normal, Reverse, Strike-Slip Faulting.**



Anderson's Theory of Faulting

- ▶ **Limitation:** Only works for intact rocks near the free surface.
- ▶ **Limitation:** Can't explain low angle normal faults
- ▶ More realistic faulting style: **oblique-slip faulting**. These occur on pre-existing weakness planes and at a depth, therefore none of the principal stresses are truly vertical.
- ▶ **Pre-existing weakness:** Reactivated faults, bedding planes, weak layer (shale, salt), foliations, anisotropy in materials, etc.

Oblique-slip Faulting



Wallace-Bott Hypothesis

Wallace (1951) suggested that slip on faults occur along the direction and orientation of maximum shear stress. Bott (1959) derived the equations for the same.


Why hypothesis? Due to the following assumptions:

- ▶ Faults move during the same tectonic event independently.
- ▶ No plasticity/ductility during deformation.

Fault Geometry

Range of values for:

Strike: $[0, 360]$; Dip: $[0, 90]$; Rake: $[-90, 90]$



Measuring Fault Slip

We can obtain slip on faults/discontinuities using various methods. All of these can help us constrain stresses.

- ▶ Mesoscale fault outcrops

Measuring Fault Slip

We can obtain slip on faults/discontinuities using various methods. All of these can help us constrain stresses.

- ▶ Mesoscale fault outcrops
- ▶ Earthquake focal mechanisms

Measuring Fault Slip

We can obtain slip on faults/discontinuities using various methods. All of these can help us constrain stresses.

- ▶ Mesoscale fault outcrops
- ▶ Earthquake focal mechanisms
- ▶ Borehole breakouts

Measuring Fault Slip

We can obtain slip on faults/discontinuities using various methods. All of these can help us constrain stresses.



- ▶ Mesoscale fault outcrops
- ▶ Earthquake focal mechanisms
- ▶ Borehole breakouts
- ▶ Microstructures: Calcite twinning

Measuring Fault Slip


We can obtain slip on faults/discontinuities using various methods. All of these can help us constrain stresses.

- ▶ Mesoscale fault outcrops
- ▶ Earthquake focal mechanisms
- ▶ Borehole breakouts
- ▶ Microstructures: Calcite twinning



Earthquake Focal Mechanism




Earthquake Focal Mechanism




Stereographic Projection




Stereographic Projection





Earthquake Focal Mechanism





Earthquake Focal Mechanism



Earthquake Focal Mechanism



Earthquake Focal Mechanism




Determining Focal Mechanism

- ▶ First motion of P-wave. It can give orientation of fault plane but doesn't give much more information


Determining Focal Mechanism

- ▶ First motion of P-wave. It can give orientation of fault plane but doesn't give much more information
- ▶ Moment Tensor inversion: The representation of source strength and fault orientation. If we assume earth's structure, we can calculate green's function and estimate moment tensor components and location of centroid using waveform inversion.

Stress Tensor




Stress Tensor




Another way of representing stress state just like Mohr's circle. The intersection of any plane passing through the center of this ellipsoid with it would give us the stress vector on that plane.



Shape of the stress ellipsoid: stress ratio = $\frac{\sigma_2 - \sigma_3}{\sigma_1 - \sigma_3}$

a

$$\sigma = \begin{pmatrix} \sigma_{11} & \sigma_{12} & \sigma_{13} \\ \sigma_{21} & \sigma_{22} & \sigma_{23} \\ \sigma_{31} & \sigma_{32} & \sigma_{33} \end{pmatrix}$$

b

$$\sigma' = \begin{pmatrix} \sigma_1 & 0 & 0 \\ 0 & \sigma_2 & 0 \\ 0 & 0 & \sigma_3 \end{pmatrix}$$



$$\sigma = \mathbf{R}^T \cdot \sigma' \cdot \mathbf{R}$$

$$\sigma_0 = (\sigma' - \mathbf{I}k_1)k_2$$

$$\sigma_0 = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \phi & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

if $k_1 = 1/(\sigma_1 - \sigma_3)$ and $k_2 = -\sigma_3$ and $\phi = \frac{\sigma_2 - \sigma_3}{\sigma_1 - \sigma_3}$


Estimating Stresses

- ▶ **Forward Problem:** Given a stress tensor, compute the slip on multiple faults with different orientations.


Estimating Stresses

- ▶ **Forward Problem:** Given a stress tensor, compute the slip on multiple faults with different orientations.
- ▶ **Inverse Problem:** Given slip on a fault plane and the orientation of fault plane, we can calculate four out of the six components of the principal stress tensor. For the other two components, we need more information like the pore fluid pressure and the depth of burial of the fault.

Estimating Stresses




Estimating Stresses




► $\sigma \cdot \mathbf{n} = \mathbf{T}$

Estimating Stresses



- ▶ $\sigma \cdot n = T$
- ▶ $(T \cdot n)n =$ the normal component

Estimating Stresses



- ▶ $\sigma \cdot \mathbf{n} = \mathbf{T}$
- ▶ $(\mathbf{T} \cdot \mathbf{n}) \mathbf{n}$ = the normal component
- ▶ \mathbf{T} – normal component = shear component

Estimating Stresses

- ▶ **Input parameters:** Strike, dip, rake. This implies we know the normal vector the slip vector for each fault plane.

Estimating Stresses

- ▶ **Input parameters:** Strike, dip, rake. This implies we know the normal vector the slip vector for each fault plane.
- ▶ Compute the theoretical slip direction for each of the given fault plane using arbitrary stress tensor.

Estimating Stresses

- ▶ **Input parameters:** Strike, dip, rake. This implies we know the normal vector the slip vector for each fault plane.
- ▶ Compute the theoretical slip direction for each of the given fault plane using arbitrary stress tensor.
- ▶ Minimize the misfit between theoretical and observed slip direction.

Estimating Stresses

- ▶ **Input parameters:** Strike, dip, rake. This implies we know the normal vector the slip vector for each fault plane.
- ▶ Compute the theoretical slip direction for each of the given fault plane using arbitrary stress tensor.
- ▶ Minimize the misfit between theoretical and observed slip direction.
- ▶ Depending on the inversion technique used, update the arbitrary stress tensor till you get the best fit.