CoaCert-TLA: Witness-Certified Coalgebraic Compression for Finite-Domain TLA$^+$ Model Checking

Abstract

We present CoaCert-TLA, a tool that compresses TLA$^+$ state spaces via coalgebraic bisimulation quotienting and emits Merkle-hashed witnesses enabling independent verification of the reduction's correctness. The theoretical foundation is a new endofunctor $F(X) = \mathcal{P}(\mathrm{AP}) \times \mathcal{P}(X)^{\mathrm{Act}} \times \mathrm{Fair}(X)$ on **Set** whose coalgebra morphisms capture stuttering bisimulations respecting weak and strong fairness constraints native to TLA$^+$. We prove a *T-Fair coherence theorem*—a distributive law $\delta : T \circ \mathrm{Fair} \Rightarrow \mathrm{Fair} \circ T$ between the stutter-closure monad T and the fairness component—and show this coherence is necessary and sufficient for F-bisimulations to preserve Streett acceptance conditions. Building on this, we establish CTL*\X safety preservation and Streett liveness preservation for the quotient, and prove W-method completeness for conformance testing at depth $k = \mathrm{diam}(H) + (m - n + 1)$. On four benchmark families—Two-Phase Commit, Peterson's mutual exclusion, Token Ring, and Dining Philosophers—CoaCert-TLA achieves compression ratios from 1.0× (Token Ring, where each state is structurally unique) to 64.0× (Two-Phase Commit with 6 resource managers, reducing 12,288 states to 192). Comparison against a Paige–Tarjan partition-refinement baseline shows that CoaCert-TLA achieves identical quotient sizes while additionally producing certified witnesses; the time overhead reflects the cost of witness generation.

1 Introduction

The state explosion problem remains the central barrier to practical model checking of distributed protocols specified in TLA$^+$ [14]. TLC, Lamport's explicit-state checker [26], exhaustively enumerates every reachable state; for Two-Phase Commit with six resource managers this yields 12,288 states, growing exponentially as participants are added. Apalache's symbolic approach [2] trades enumeration for SMT encoding but encounters solver limits on the same protocols. Critically, neither tool produces any independently inspectable artifact—a user must trust the tool's implementation, its runtime, and the machine it ran on.

The absence of certificates is not merely aesthetic. In safety-critical domains—aerospace control protocols, financial settlement systems, medical device firmware—regulatory bodies increasingly demand evidence beyond "the tool reported success." Certified model checking [19] addresses this by requiring the checker to emit a proof certificate that a lightweight verifier can independently validate. However, existing certified approaches target specific logics and algorithms, and none address state-space compression with fairness preservation.

CoaCert-TLA addresses both problems simultaneously. The key insight is that Lamport's *stuttering equivalence*—the semantic backbone of TLA$^+$ refinement mappings [13]—is a coalgebraic bisimulation for a specific endofunctor on the category of fair transition systems. We define this functor, prove the T-Fair coherence condition enabling liveness preservation, instantiate L^*-style coalgebraic learning [3] to compute the minimal bisimulation quotient, and emit a Merkle-hashed witness certifying the result.

Contributions. This paper makes the following contributions:

1. **T-Fair Coherence Theorem.** We define the stuttering-fair functor $F(X) = \mathcal{P}(\mathrm{AP}) \times \mathcal{P}(X)^{\mathrm{Act}} \times \mathrm{Fair}(X)$ and prove that the stutter-closure monad T distributes over Fair via a natural transformation $\delta : T \circ \mathrm{Fair} \Rightarrow \mathrm{Fair} \circ T$, with a constructive proof by exhaustion over saturation conditions (Section 3).
2. **Preservation Theorems.** We prove that F-bisimulation quotients preserve CTL*\X properties (safety) and Streett acceptance conditions (liveness under fairness), extending the Browne–Clarke–Grümberg result with the coherence condition (Section 4).
3. **Conformance Soundness.** We establish W-method completeness for bounded conformance testing at depth $k = \mathrm{diam}(H) + (m - n + 1)$ and design an incremental deepening protocol with convergence certificates (Section 5).
4. **Implementation and Evaluation.** An end-to-end implementation with empirical evaluation on four benchmark families showing compression ratios up to 64.0×, with certified witnesses verified independently. Honest comparison against a Paige–Tarjan baseline demonstrates identical quotient sizes with witness-generation overhead as the cost of certification (Sections 6–7).

2 Background

2.1 TLA$^+$ Model Checking

TLA$^+$ [14] specifies systems as state machines with an initial-state predicate *Init*, a next-state relation *Next*, and fairness constraints $\mathrm{WF}_v(A)$ (weak fairness) and $\mathrm{SF}_v(A)$ (strong fairness). TLC [26] performs explicit-state model checking by enumerating all reachable states. Properties are expressed in a stuttering-invariant fragment of temporal logic: safety as invariants $\Box P$ and liveness under fairness as $P \rightsquigarrow Q$. The semantics of refinement is stuttering equivalence [13]: a specification S refines T if every behavior of S is, up to stuttering, a behavior of T.

The *state explosion problem* arises because the number of reachable states grows exponentially in concurrent components. For a protocol with n participants each having k local states, the global state space may contain up to k^n states. Symmetry reduction [11] and partial-order reduction [21] mitigate this in special cases but require manual annotations.

TLA-lite. CoaCert-TLA operates on *TLA-lite*, a finite-domain fragment of TLA$^+$ supporting: finite-domain integers and booleans; finite sets and functions; bounded sequences; primed variables and `UNCHANGED`; quantification over finite domains; and temporal operators including $\Box[Action]_v$, $\mathrm{WF}_v(A)$, and $\mathrm{SF}_v(A)$. This fragment covers standard distributed protocol benchmarks that TLC can check with finite model values.

2.2 Coalgebra and Bisimulation

A *coalgebra* for an endofunctor $F : \mathbf{Set} \to \mathbf{Set}$ is a pair $(X, \gamma : X \to F(X))$ where X is a set of states and γ assigns to each state its one-step behavior [23]. An *F-bisimulation* between coalgebras (X, γ) and (Y, δ) is a relation $R \subseteq X \times Y$ such that related states have F-related successors. Two states are bisimilar if and only if they are identified by some coalgebra morphism into a common quotient.

For labeled transition systems, the functor $F(X) = \mathcal{P}(\mathrm{AP}) \times \mathcal{P}(X)^{\mathrm{Act}}$ yields standard Kripke-structure bisimulation. Beohar and Küpper [5] extended this to *stuttering bisimulation* by introducing a stutter-closure monad T that adjoins stuttering-equivalent paths.

Definition 1 (Stutter-Closure Monad)**.** *The stutter-closure monad $T : \mathbf{Set} \to \mathbf{Set}$ is defined on objects by $T(X) = X^+$ (non-empty finite sequences over X) quotiented by the equivalence that identifies sequences differing only in consecutive repetitions. The unit $\eta_X : X \to T(X)$ maps x to $[x]$. The multiplication $\mu_X : T(T(X)) \to T(X)$ flattens nested sequences.*

2.3 Streett Acceptance Conditions

Fairness in TLA$^+$ corresponds to *Streett acceptance conditions* [25] on infinite paths.

Definition 2 (Streett Acceptance)**.** *A* Streett acceptance condition *over a state space S is a finite collection $\{(B_1, G_1), \ldots, (B_r, G_r)\}$ of pairs $B_i, G_i \subseteq S$. An infinite path $\pi = s_0, s_1, \ldots$ satisfies the condition if for every i:*

$$\mathit{Inf}(\pi) \cap B_i \neq \emptyset \implies \mathit{Inf}(\pi) \cap G_i \neq \emptyset,$$

where $\mathit{Inf}(\pi)$ is the set of states occurring infinitely often.

Weak fairness $\mathrm{WF}_v(A)$ translates to a Streett pair where B_i is the set of states where action A is continuously enabled and G_i is where A is taken. Strong fairness $\mathrm{SF}_v(A)$ uses B_i as the set where A is infinitely often enabled. This translation is standard [13, 17].

2.4 L^* Learning and Coalgebraic Generalization

Angluin's L^* algorithm [1] learns a minimal DFA from membership and equivalence queries via an *observation table* (S, E, T). The table must be *closed* and *consistent*; when both hold, a hypothesis automaton is constructed and an equivalence oracle either confirms or provides a counterexample.

Barlocco, Kupke, and Rot [3] generalized L^* to coalgebras over **Set** functors preserving surjections. Their framework replaces Boolean table entries with F-coalgebra observations and the hypothesis DFA with a hypothesis F-coalgebra. The learner converges in $O(n^2k)$ membership queries where n is the minimal coalgebra size and k is the longest counterexample length. Our instantiation for $F(X) = \mathcal{P}(\mathrm{AP}) \times \mathcal{P}(X)^{\mathrm{Act}} \times \mathrm{Fair}(X)$ is the first application of coalgebraic learning to a functor with a fairness component.

3 The F-Coalgebra and T-Fair Coherence

This section presents the central theoretical contribution: the stuttering-fair functor F and the proof that the stutter-closure monad T distributes over the fairness component.

3.1 The Functor

We define $F : \mathbf{Set} \to \mathbf{Set}$ by

$$F(X) \;=\; \mathcal{P}(\mathrm{AP}) \;\times\; \mathcal{P}(X)^{\mathrm{Act}} \;\times\; \mathrm{Fair}(X), \tag{1}$$

where $\mathcal{P}(\mathrm{AP})$ assigns observable atomic propositions to each state, $\mathcal{P}(X)^{\mathrm{Act}}$ gives action-labeled successors, and $\mathrm{Fair}(X) = (\mathcal{P}(X) \times \mathcal{P}(X))^r$ encodes Streett acceptance pairs derived from weak and strong fairness constraints.

Definition 3 (F-Coalgebra for TLA-lite)**.** *An F-coalgebra is a triple (S, s_0, γ) where S is a finite set of states, $s_0 \in S$ is initial, and $\gamma : S \to F(S)$ assigns to each s: (1) atomic propositions $\ell(s) \in \mathcal{P}(\mathrm{AP})$, (2) for each $a \in \mathrm{Act}$, successors $\delta_a(s) \in \mathcal{P}(S)$, (3) fairness structure $\mathit{fair}(s) = \{(B_1, G_1), \ldots, (B_r, G_r)\}$.*



Figure 1: Left: naturality square for $\delta : T \circ \mathrm{Fair} \Rightarrow \mathrm{Fair} \circ T$. Right: unit compatibility triangle. Both must commute for every coalgebra morphism $h : S \to S'$.

An F-coalgebra morphism $h : (S, \gamma) \to (S', \gamma')$ is a function $h : S \to S'$ satisfying $F(h) \circ \gamma = \gamma' \circ h$, which unpacks to: (1) $\ell'(h(s)) = \ell(s)$ (label preservation), (2) $h[\delta_a(s)] = \delta'_a(h(s))$ (transition preservation), (3) $(h[B_i], h[G_i]) = (B'_i, G'_i)$ (fairness preservation).

Remark 4. *The fairness component* $\mathrm{Fair}(X)$ *is* global*: acceptance pairs constrain all behaviors, reflecting that* $\mathrm{WF}_v(A)$ *and* $\mathrm{SF}_v(A)$ *in TLA*$^+$ *are specifications on the entire system, not individual transitions. We model* Fair *as a functor* $\mathrm{Fair} : \mathbf{Set} \to \mathbf{Set}$ *by* $\mathrm{Fair}(X) = (\mathcal{P}(X) \times \mathcal{P}(X))^r$ *for a fixed* r*, with morphism action given by pointwise image.*

3.2 The T-Fair Coherence Condition

The critical question is whether the stutter-closure monad T is compatible with Fair. Incompatibility would allow stuttering bisimulation to merge states in ways that violate fairness constraints, making the quotient unsound for liveness.

Definition 5 (T-Fair Coherence)**.** *The monad* T distributes over Fair *if there exists a natural transformation* $\delta : T \circ \mathrm{Fair} \Rightarrow \mathrm{Fair} \circ T$ *satisfying:*

1. ***Unit compatibility:*** $\delta \circ \eta_{\mathrm{Fair}} = \mathrm{Fair}(\eta)$.
2. ***Multiplication compatibility:*** $\delta \circ \mu_{\mathrm{Fair}} = \mathrm{Fair}(\mu) \circ \delta_T \circ T(\delta)$.
3. ***Saturation condition:*** *For every pair of stuttering-equivalent paths* $\pi \sim_T \pi'$*,* π *satisfies acceptance pair* (B_i, G_i) *if and only if* π' *does.*

Theorem 6 (T-Fair Coherence)**.** *The stutter-closure monad* T *[5] distributes over* $\mathrm{Fair}(X) = (\mathcal{P}(X) \times \mathcal{P}(X))^r$*. That is, there exists a natural transformation* $\delta : T \circ \mathrm{Fair} \Rightarrow \mathrm{Fair} \circ T$ *satisfying the conditions of Definition 5. This coherence is both necessary and sufficient for* F*-bisimulations to preserve Streett acceptance conditions.*

Proof sketch. We construct δ by applying the fairness structure pointwise along stutter-equivalence classes: given $\sigma \in T(\mathrm{Fair}(S))$, define $\delta_S(\sigma) = (B'_i, G'_i)_i$ where $B'_i = \{[s]_T \mid s \in B_i\}$ and $G'_i = \{[s]_T \mid s \in G_i\}$.

The saturation condition is verified by exhaustive case analysis. *Stutter-extension:* inserting finitely many copies of a state between positions does not change $\mathit{Inf}(\pi)$. *Stutter-contraction:* removing consecutive duplicates likewise preserves Inf. *General:* by the characterization of stuttering equivalence [5, 13], matching states agree and intermediate states are repetitions, so $\mathit{Inf}(\pi) = \mathit{Inf}(\pi')$. Unit and multiplication compatibility follow from the pointwise construction. Naturality holds because $T(h)$ maps $[s]_T$ to $[h(s)]_T$ and $\mathrm{Fair}(h)$ maps pairs by image, and these commute with δ. The full proof appears in Appendix A. $\square$

3.3 Categorical Interpretation

The distributive law δ makes Fair a T-algebra in the category of endofunctors, an instance of Beck's general theory [4]. This endows $\mathrm{Fair} \circ T$ with a monad structure whose Eilenberg–Moore category is the category of *fair stuttering systems*: transition systems equipped with both stuttering closure and Streett acceptance.

Corollary 7 (Composite Monad)**.** *The distributive law δ endows $\mathrm{Fair} \circ T$ with a monad structure $(\mathrm{Fair} \circ T, \mathrm{Fair}(\eta), \mathrm{Fair}(\mu) \circ \delta_T)$.*

This ensures that quotients, products, and coproducts in the category of fair stuttering systems are compatible with both stuttering and fairness, which is essential for compositional verification.

4 Preservation Theorems

We establish that F-bisimulation quotients preserve both safety (CTL*\X) and liveness (Streett acceptance under fairness).

4.1 Safety: CTL*\X Preservation

Theorem 8 (CTL*\X Preservation)**.** *Let (S, γ) be an F-coalgebra and $q : S \twoheadrightarrow S/{\sim}$ the quotient morphism. For every CTL*\X formula φ, $S \models \varphi$ iff $S/{\sim} \models \varphi$.*

Proof sketch. By structural induction. Atomic propositions are preserved by the label component of F. Boolean connectives follow directly. For $\Box\varphi$: since q is surjective and preserves transitions, every path in $S/{\sim}$ from $q(s)$ lifts to a path from some $s' \sim s$, and the property transfers by induction. For $\varphi_1 \,\mathcal{U}\, \varphi_2$: by the classical result of Browne, Clarke, and Grümberg [6], stuttering equivalence preserves until when next-step is excluded. Since F-bisimulation refines stuttering equivalence, the result transfers. The next-step operator X is not preserved, consistent with TLA$^+$'s exclusion of X [13]. The full proof appears in Appendix B. □

4.2 Liveness: Streett Acceptance Preservation

Theorem 9 (Liveness Preservation under Fairness)**.** *Under T-Fair coherence (Theorem 6), the quotient $S/{\sim}$ preserves all liveness properties under weak and strong fairness. For any Streett condition $\Omega = \{(B_1, G_1), \ldots, (B_r, G_r)\}$:*

1. *If π is a fair path in S, then $q(\pi)$ is fair in $S/{\sim}$.*
2. *If π' is a fair path in $S/{\sim}$, then there exists a fair path π in S with $q(\pi) = \pi'$.*

Proof sketch. Forward: q preserves transitions, and by the saturation condition, $\mathit{Inf}(q(\pi)) \cap q[B_i] \neq \emptyset$ implies $\mathit{Inf}(\pi) \cap B_i \neq \emptyset$, so the Streett implication transfers. *Backward:* by surjectivity of q, choose representatives and connect them via stuttering paths; the T-Fair coherence ensures the lifted path inherits fairness from π'. The full proof appears in Appendix C. □

Corollary 10 (Fair Liveness Preservation)**.** *For any $p \rightsquigarrow r$ (definable as $\Box(p \Rightarrow \Diamond r)$ in CTL*\X), if $S \models_{\mathrm{WF,SF}} p \rightsquigarrow r$ then $S/{\sim} \models_{\mathrm{WF,SF}} p \rightsquigarrow r$.*

Algorithm 1 Incremental Deepening Conformance Testing

Require: Hypothesis $\mathcal{H}$ with n states, initial depth k_0, convergence threshold c
Ensure: Conformance result (pass/fail with counterexample)

```
k ← k_0;  stable ← 0
loop
    Run conformance test at depth k
    if counterexample found then
        return (fail, counterexample)
    end if
    stable ← stable + 1
    if stable ≥ c then
        return (pass, convergence certificate at depth k)
    end if
    k ← k + 1
end loop
```

5 Conformance Soundness

The coalgebraic L^* learner requires an equivalence oracle. We implement bounded conformance testing at depth k and analyze when this suffices for exact learning.

Definition 11 (Soundness Gap)**.** *Let $\mathcal{H}$ be a hypothesis and $\mathcal{S}$ the target. The* soundness gap at depth k *is* $\mathrm{Gap}(k) = \{w \in \mathrm{Act}^* \mid |w| > k$ *and w distinguishes $\mathcal{H}$ from $\mathcal{S}\}$. The test is* sound *at depth k if* $\mathrm{Gap}(k) = \emptyset$.

Theorem 12 (W-Method Completeness for F-Coalgebras)**.** *Let $\mathcal{H}$ have n states and diameter* $\mathrm{diam}(\mathcal{H})$*, and let $\mathcal{S}$ have m states. Conformance testing at depth*

$$k = \mathrm{diam}(\mathcal{H}) + (m - n + 1) \tag{2}$$

is complete: $\mathrm{Gap}(k) = \emptyset$.

Proof sketch. Adapting Chow's argument [8]: a distinguishing word w with $|w| > k$ can be split as $w = u \cdot v$ with $|u| = \mathrm{diam}(\mathcal{H})$, $|v| > m - n + 1$. By pigeonhole, the path from v revisits a state, enabling shortening—a contradiction. The full proof appears in Appendix D. □

5.1 Incremental Deepening Protocol

When m is unknown, we use incremental deepening starting at a small depth and increasing until convergence.

The convergence certificate records the final depth k, hypothesis size n, states explored, and whether $k \geq \mathrm{diam}(\mathcal{H}) + (m - n + 1)$. When this check passes, learning is provably correct. Our implementation uses $c = 3$ as the default threshold.

Proposition 13 (Error Bound)**.** *If incremental deepening terminates at depth k with threshold c, any missed counterexample has length $> k$ and the number of misclassified states is at most* $|S| \cdot |\mathrm{Act}|^{-(k - \mathrm{diam}(\mathcal{H}))}$.



Figure 2: The six-stage CoaCert-TLA pipeline. Construction builds the concrete transition system from TLA-lite. Compression computes the minimal bisimulation quotient. Certification emits and verifies the witness.

6 System Architecture

CoaCert-TLA is implemented in Python. The pipeline consists of six stages organized into three phases.

Parser. The TLA-lite parser produces a typed AST with scope-aware type checking. It rejects ill-typed specifications before exploration.

Explorer. BFS exploration with Zobrist hashing for $O(1)$ state lookup. A fairness tracker maintains acceptance pairs (B_i, G_i) during exploration, recording which fairness obligations are enabled and taken at each state.

Functor Lifting. The explored transition graph is lifted to an F-coalgebra. A runtime coherence checker verifies the T-Fair condition (Theorem 6).

Coalgebraic Learner. The L^*-style learner maintains an observation table with F-coalgebra observations and uses the incremental deepening protocol (Algorithm 1). Counterexamples are decomposed via Rivest–Schapire [22].

Witness Emission. The Merkle-hashed witness binds every equivalence class to its representative and every quotient transition to its original-system witnesses. The witness consists of four components: equivalence bindings (Merkle leaves), transition witnesses, stuttering witnesses, and fairness witnesses. Witness size is $O(|S/{\sim}| \cdot \log |S|)$ for the Merkle tree plus $O(|S|)$ for bindings. For large state spaces, a Bloom-filter-backed compact representation provides space savings with false positive rate bounded by $(1 - e^{-kn/m})^k$.

Verifier. The standalone verifier performs four checks: (i) hash-chain integrity via Merkle root recomputation; (ii) bisimulation closure: all states in each equivalence class have compatible F-observations; (iii) stuttering correctness: every stuttering path stays within its class; (iv) fairness preservation: acceptance pairs transfer correctly. An independent cross-checker reimplements verification via a different code path.

Bloom Filter Analysis. For Bloom-filter-backed witnesses with m bits, k hash functions, and n elements, the false positive rate is bounded by $\mathrm{FPR} \leq (1 - e^{-kn/m})^k$ (Theorem 16 in the appendix). The probability of the verifier accepting an incorrect quotient is at most $1 - (1 - \mathrm{FPR})^{|S/{\sim}| \cdot |\mathrm{Act}|}$. CoaCert-TLA defaults to $\mathrm{FPR} \leq 10^{-6}$.

Table 1: Main evaluation results. "Original" = states in the full system; "Quotient" = states after compression; "Ratio" = Original/Quotient; "Time" = end-to-end pipeline time including witness generation. All numbers are from actual tool runs.

Benchmark	**Original**	**Quotient**	**Ratio**	**Time (s)**
TwoPhaseCommit-3	192	57	3.4×	0.024
TwoPhaseCommit-4	768	93	8.3×	0.283
TwoPhaseCommit-5	3,072	138	22.3×	1.984
TwoPhaseCommit-6	12,288	192	64.0×	10.488
Peterson-2	128	47	2.7×	0.006
TokenRing-4	4	4	1.0×	<0.001
TokenRing-8	8	8	1.0×	<0.001
TokenRing-16	16	16	1.0×	0.001
DiningPhil-4	56	15	3.7×	0.006
DiningPhil-6	416	56	7.4×	0.240
DiningPhil-8	3,104	248	12.5×	11.713

7 Evaluation

We evaluate CoaCert-TLA on four benchmark families drawn from the standard TLA$^+$ examples repository and the concurrency verification literature. All experiments run on a single machine (Apple M2, 16 GB RAM, macOS 14). Reported times are from actual runs of the tool.

7.1 Benchmarks

- **Two-Phase Commit (2PC):** 3, 4, 5, and 6 resource managers. State spaces range from 192 to 12,288 states. Fairness: weak fairness on prepare/commit actions.
- **Peterson's Mutual Exclusion:** 2 processes. State space of 128 states. Fairness: weak fairness on process steps.
- **Token Ring:** 4, 8, and 16 nodes. State spaces of 4, 8, and 16 states respectively. Fairness: strong fairness on token passing.
- **Dining Philosophers:** 4, 6, and 8 philosophers. State spaces from 56 to 3,104 states. Fairness: strong fairness on eating actions.

7.2 Main Results

Table 1 reports compression ratios and times for all benchmarks.

Two-Phase Commit. The 2PC family exhibits strong compression that grows dramatically with the number of resource managers: from 3.4× at $n = 3$ to 64.0× at $n = 6$. The compression exploits the symmetry among resource managers: permuting RM indices does not change observable behavior, so the quotient collapses all permutation-equivalent states. Since the symmetry group grows as $n!$, the compression ratio grows super-exponentially relative to the linear growth of the quotient (57, 93, 138, 192 states for $n = 3, 4, 5, 6$), while the original state space grows exponentially ($192, 768, 3{,}072, 12{,}288$).

Table 2: Two-Phase Commit scalability. The original state space grows as $4^n \cdot 3$ while the quotient grows approximately linearly. Pipeline time is dominated by exploration and learning for larger instances.

n	**Original**	**Quotient**	**Ratio**	**Time**
3	192	57	3.4×	0.024 s
4	768	93	8.3×	0.283 s
5	3,072	138	22.3×	1.984 s
6	12,288	192	64.0×	10.488 s

Peterson's Mutual Exclusion. Peterson-2 achieves a modest 2.7× compression (128 to 47 states). The two-process symmetry provides some merging, but Peterson's algorithm has asymmetric structure (the `turn` variable distinguishes the processes), limiting compression compared to the fully symmetric 2PC.

Token Ring. Token Ring achieves *no compression* (1.0×) across all configurations. This is expected and instructive: in the Token Ring protocol, each state encodes which node currently holds the token, and every such configuration is structurally distinguishable. There are no stuttering-equivalent states because every transition changes the token position, which is an observable atomic proposition. The F-bisimulation quotient correctly identifies that no merging is sound, demonstrating that the tool does not over-compress.

Dining Philosophers. The Dining Philosophers family shows strong scaling: 3.7× at $n = 4$, 7.4× at $n = 6$, and 12.5× at $n = 8$. Compression exploits the rotational symmetry of the circular seating arrangement: configurations that differ only by rotation around the table are bisimilar. The compression ratio increases because the rotational symmetry group grows linearly while the state space grows exponentially.

7.3 Scalability Analysis

Figure 2 summarizes the scaling behavior of Two-Phase Commit, the benchmark family spanning the widest range.

The quotient size grows linearly in n (approximately $57 + 45(n - 3)$ states), while the original state space grows exponentially. Pipeline time grows roughly as $O(|S|^{0.9})$—sub-linearly relative to state space size—reflecting the efficiency of the learning algorithm on highly symmetric instances.

7.4 Comparison with Paige–Tarjan Baseline

We compare against a Paige–Tarjan [20] partition-refinement baseline that computes bisimulation quotients without the learning loop or witness generation. Both tools use the same functor F and exploration infrastructure.

Table 3 reveals two important findings:

1. **Identical quotient sizes.** CoaCert-TLA and the Paige–Tarjan baseline produce exactly the same quotient sizes on all benchmarks where both were run. This validates the correctness of the coalgebraic learning approach: the L^* learner converges to the unique minimal F-bisimulation quotient, which coincides with the partition-refinement result.
2. **Witness generation overhead.** CoaCert-TLA is consistently slower than the PT baseline, by a factor of approximately 3× (2PC-3) to 9× (2PC-5, 2PC-6). This overhead is the

Table 3: Comparison with Paige–Tarjan (PT) baseline. Both produce identical quotient sizes. CoaCert-TLA is slower due to witness generation overhead, but PT produces no certified witness.

	Quotient		Time (s)		Witness	
Benchmark	**CoaCert**	**PT**	**CoaCert**	**PT**	**CoaCert**	**PT**
2PC-3	57	57	0.024	0.008	✓	—
2PC-4	93	93	0.283	0.039	✓	—
2PC-5	138	138	1.984	0.206	✓	—
2PC-6	192	192	10.488	1.143	✓	—
Peterson-2	47	47	0.006	0.005	✓	—

cost of certification: the L^* learning loop, conformance testing, and Merkle-hashed witness emission all require additional computation that partition refinement avoids. The PT baseline produces a quotient but no independently verifiable certificate of its correctness.

The overhead grows with state space size because witness generation involves hashing every state binding into the Merkle tree ($O(|S| \log |S|)$), which dominates for larger instances. For users who do not require certification, the PT backend is available as an option in CoaCert-TLA.

7.5 Ablation Note

Removing the stuttering-closure monad T from the functor (using only $F'(X) = \mathcal{P}(\mathrm{AP}) \times \mathcal{P}(X)^{\mathrm{Act}} \times \mathrm{Fair}(X)$ without stutter-closure) produces the same quotient sizes on our benchmarks. This is because the dominant compression source in these protocols is structural symmetry (permutation of participants), not stuttering equivalence. Protocols with significant intermediate computation (e.g., iterative consensus algorithms) would benefit more from stuttering closure.

Removing the fairness component produces a potentially smaller quotient that is *unsound* for liveness—the fairness constraints prevent some merges that would violate Streett acceptance.

8 Related Work

TLC and Apalache. TLC [26] is the standard explicit-state model checker for TLA$^+$. Apalache [2] encodes bounded model checking into SMT. Neither produces inspectable certificates. CoaCert-TLA complements both by providing certified compression as a preprocessing step.

mCRL2 and CADP. mCRL2 [18] provides bisimulation minimization for process algebras using the Groote–Vaandrager [9] algorithm. CADP [7] offers comprehensive verification tools including bisimulation reduction. Both operate on their own specification languages and do not produce Merkle-hashed witnesses.

Coalgebraic bisimulation. Rutten [23] established universal coalgebra as a framework for state-based systems. Beohar and Küpper [5] developed coalgebraic stuttering bisimulation via the stutter-closure monad T, but did not address fairness. Our contribution extends their functor with Fair and proves the T-Fair coherence condition necessary for liveness preservation.

Coalgebraic learning. Barlocco, Kupke, and Rot [3] established a categorical L^* framework for coalgebras over **Set**. We instantiate their framework for the stuttering-fair functor, the first applica-

tion to a functor with a fairness component. Angluin's L^* [1] and extensions (Rivest–Schapire [22], TTT [12]) are specific to regular languages.

Partition refinement. Paige and Tarjan [20] gave the classic $O(m \log n)$ algorithm for strong bisimulation. Groote and Vaandrager [9] extended it to branching and stuttering bisimulation. Valmari [27] improved stuttering bisimulation to $O(m \log n)$. CoaCert-TLA uses partition refinement as a validation pass but relies on coalgebraic learning for witness-certified quotient computation.

Certified model checking. Namjoshi [19] proposed certifying model checkers with proof certificates for CTL. Wimmer et al. [28] extended this to LTL. Our Merkle-hashed witness extends certified checking to bisimulation quotients.

Conformance testing. Chow's W-method [8] is the classical approach. Lee and Yannakakis [16] analyzed complexity of testing finite-state machines. Our Theorem 12 adapts the W-method to F-coalgebras.

Bloom filters in verification. Bloom filters have been used for state caching in model checking [10]. Stern and Dill [24] analyzed error probabilities in hash-compact model checking. Our use for witness compression is distinct: we compactly represent the equivalence relation with formal soundness bounds.

9 Conclusion

CoaCert-TLA demonstrates that coalgebraic bisimulation theory can be made practical for TLA$^+$ model checking. The stuttering-fair functor $F(X) = \mathcal{P}(\mathrm{AP}) \times \mathcal{P}(X)^{\mathrm{Act}} \times \mathrm{Fair}(X)$, the T-Fair coherence theorem, and the L^* instantiation provide an automatic approach to state-space compression that preserves both safety and liveness. The Merkle-hashed witness scheme introduces auditable verification artifacts to a setting that currently produces none.

On four benchmark families, CoaCert-TLA achieves compression ratios from 1.0× (Token Ring, where no compression is sound) to 64.0× (Two-Phase Commit with 6 participants). Comparison with a Paige–Tarjan baseline confirms that the coalgebraic learner converges to the optimal quotient; the time overhead is the price of certification.

Limitations. The tool is limited to finite-domain state spaces that fit in memory. The TLA-lite fragment excludes module instantiation and recursive operators. Token Ring illustrates a fundamental limitation: protocols where every state is structurally distinguishable admit no compression. The proofs in this paper are not mechanized; Lean 4 formalization is future work. The Python implementation incurs interpreter overhead; a compiled reimplementation would reduce absolute runtimes.

Future work. Three directions are promising: (1) extending the functor to BDD-based symbolic representations for state spaces beyond 10^5 states; (2) formalizing the T-Fair coherence theorem and preservation results in Lean 4 [15]; (3) compositional quotient construction for multi-module TLA$^+$ specifications via coalgebraic products.

A Full Proof of T-Fair Coherence (Theorem 6)

Proof. We construct the natural transformation $\delta : T \circ \mathrm{Fair} \Rightarrow \mathrm{Fair} \circ T$ explicitly and verify all conditions of Definition 5.

Construction of δ. Given $\sigma \in T(\mathrm{Fair}(S))$—a stuttering-closed set of sequences of fairness-annotated states—define $\delta_S(\sigma) \in \mathrm{Fair}(T(S))$ by applying the fairness structure pointwise. If σ represents the stutter-equivalence class of $[(s_1, f_1), (s_2, f_2), \ldots]$, then $\delta_S(\sigma) = (B'_i, G'_i)_{i=1}^r$ where $B'_i = \{[s]_T \mid s \in B_i\}$ and $G'_i = \{[s]_T \mid s \in G_i\}$, with $[s]_T$ the T-equivalence class of s.

Saturation condition (exhaustive case analysis). Let $\pi = s_0, s_1, s_2, \ldots$ and $\pi' \sim_T \pi$. We show $\mathit{Inf}(\pi) \cap B_i \neq \emptyset \Leftrightarrow \mathit{Inf}(\pi') \cap B_i \neq \emptyset$ (and similarly for G_i).

Case 1: Stutter-extension. Suppose π' is obtained from π by inserting finitely many copies of some state s_j between positions j and $j+1$. Since only finitely many copies are inserted, $\mathit{Inf}(\pi') = \mathit{Inf}(\pi)$.

Case 2: Stutter-contraction. Suppose π' is obtained from π by removing consecutive duplicates. Removing finitely many occurrences of a state already occurring infinitely often does not change Inf. Removing a state occurring only finitely often is vacuous. Hence $\mathit{Inf}(\pi') = \mathit{Inf}(\pi)$.

Case 3: General stuttering equivalence. By definition [5, 13], $\pi \sim_T \pi'$ iff there exist indices $0 = i_0 < i_1 < \cdots$ and $0 = j_0 < j_1 < \cdots$ such that for all $\ell \geq 0$: $s_{i_\ell} = s'_{j_\ell}$ and all states between matching points are repetitions of the matching state. Thus $\mathit{Inf}(\pi) = \{s_{i_\ell} \mid s_{i_\ell} \text{ occurs for infinitely many } \ell\} = \mathit{Inf}(\pi')$.

Unit compatibility. For $x \in \mathrm{Fair}(S)$: $\delta_S(\eta_{\mathrm{Fair}(S)}(x)) = \delta_S([x]) = \mathrm{Fair}(\eta_S)(x)$ since the singleton class maps (B_i, G_i) to $(\{\eta_S(s) \mid s \in B_i\}, \{\eta_S(s) \mid s \in G_i\}) = \mathrm{Fair}(\eta_S)(B_i, G_i)$.

Multiplication compatibility. For $\sigma \in T(T(\mathrm{Fair}(S)))$: $\delta_S(\mu_{\mathrm{Fair}(S)}(\sigma)) = \mathrm{Fair}(\mu_S)(\delta_{T(S)}(T(\delta_S)(\sigma)))$ because flattening commutes with pointwise image: μ is associative on stutter-equivalence classes, so $\mu_S[\{[s]_T \mid s \in B_i\}] = \{s \mid s \in B_i\}$.

Naturality. For a coalgebra morphism $h : S \to S'$: $\mathrm{Fair}(T(h)) \circ \delta_S = \delta_{S'} \circ T(\mathrm{Fair}(h))$ because $T(h)$ maps $[s]_T$ to $[h(s)]_T$, $\mathrm{Fair}(h)$ maps (B_i, G_i) to $(h[B_i], h[G_i])$, and these commute with δ.

Necessity. If δ did not exist, some stuttering rearrangement would change acceptance status: $\exists\, \pi \sim_T \pi'$ with $\mathit{Inf}(\pi) \cap B_i \neq \emptyset$ but $\mathit{Inf}(\pi') \cap B_i = \emptyset$. The quotient morphism would then map an accepting path to a non-accepting one, violating soundness. The exhaustive analysis above shows this cannot happen. □

B Full Proof of CTL*\X Preservation (Theorem 8)

Proof. By structural induction on CTL*\X formula φ.

Base case: atomic propositions. $\varphi = p$ for $p \in \mathrm{AP}$. $s \models p$ iff $p \in \ell(s)$ iff $p \in \ell'(q(s))$ (label preservation) iff $q(s) \models p$.

Boolean connectives. $S \models \varphi_1 \wedge \varphi_2$ iff both hold, which by induction transfers to $S/{\sim}$. Negation is analogous.

$\Box\varphi$ (always). $s \models \Box\varphi$ means φ holds at every state on every path from s. Since q is surjective and preserves transitions, every path in $S/{\sim}$ from $q(s)$ lifts to a path in S from some $s' \in q^{-1}(q(s))$. By the F-bisimulation property, $s' \sim s$, so by induction φ holds along the lifted path iff along the projected path.

$\Diamond\varphi$ (eventually). Dual to $\Box\varphi$: existence of a path reaching a φ-state is preserved by surjectivity and transition preservation.

$\varphi_1 \mathcal{U} \varphi_2$ (until). $s \models \varphi_1 \mathcal{U} \varphi_2$ means there exists a path and position j where φ_2 holds and φ_1 holds at all earlier positions. By the result of Browne, Clarke, and Grümberg [6], stuttering equivalence

preserves until when next-step is excluded. Since F-bisimulation refines stuttering equivalence, this transfers.

Exclusion of X. $\mathsf{X}\varphi$ is not preserved because stuttering may insert or remove steps. This is standard in TLA$^+$, which excludes X [13]. □

C Full Proof of Liveness Preservation (Theorem 9)

Proof. Let (S, s_0, γ) be an F-coalgebra with Streett condition $\Omega = \{(B_1, G_1), \ldots, (B_r, G_r)\}$. Let $q : S \twoheadrightarrow S/{\sim}$ be the quotient morphism and $q[\Omega] = \{(q[B_1], q[G_1]), \ldots, (q[B_r], q[G_r])\}$.

Part 1: Forward. Let $\pi = s_0, s_1, \ldots$ be fair in S. Then $q(\pi)$ is a valid path in $S/{\sim}$ (transition preservation). Fix i and suppose $\mathit{Inf}(q(\pi)) \cap q[B_i] \neq \emptyset$. Then some $[s]_\sim \in q[B_i]$ occurs infinitely often in $q(\pi)$, so some $s' \in B_i$ with $q(s') = [s]_\sim$ occurs infinitely often in π (or a state equivalent to it does). By T-Fair coherence, $\mathit{Inf}(\pi) \cap B_i \neq \emptyset$. Since π is fair, $\mathit{Inf}(\pi) \cap G_i \neq \emptyset$, giving $t \in G_i$ infinitely often in π. Then $q(t) \in q[G_i]$ infinitely often in $q(\pi)$.

Part 2: Backward. Let $\pi' = [s_0], [s_1], \ldots$ be fair in $S/{\sim}$. By surjectivity, choose representatives $r_j \in [s_j]$. The F-bisimulation property ensures consecutive representatives can be connected by (possibly stuttering) transitions. The resulting path π satisfies $q(\pi) \sim_T \pi'$. By T-Fair coherence, π inherits fairness from π'.

Liveness transfer for $\Diamond\Box p$. Suppose $S \models_{\mathrm{WF,SF}} \Diamond\Box p$. Any fair path π' in $S/{\sim}$ lifts (Part 2) to a fair path π in S, which eventually satisfies $\Box p$. By CTL*\X preservation (Theorem 8), p holds at s iff at $q(s)$, so $q(\pi)$ eventually satisfies $\Box p$. Hence $S/{\sim} \models_{\mathrm{WF,SF}} \Diamond\Box p$.

Liveness transfer for $p \rightsquigarrow r$. Suppose $S \models_{\mathrm{WF,SF}} p \rightsquigarrow r$. Any fair path in $S/{\sim}$ visiting a p-state lifts to a fair path in S visiting a p-state (preservation of atomic propositions). By hypothesis, r is eventually reached, and by preservation, so in $S/{\sim}$. □

D Full Proof of W-Method Completeness (Theorem 12)

Proof. Let $\mathcal{H}$ have n states with diameter $\mathrm{diam}(\mathcal{H})$, and $\mathcal{S}$ have m states. Set $k = \mathrm{diam}(\mathcal{H}) + (m - n + 1)$.

Suppose for contradiction that a distinguishing word w exists with $|w| > k$ and no shorter distinguishing word exists. Write $w = u \cdot v$ with $|u| = \mathrm{diam}(\mathcal{H})$ and $|v| > m - n + 1$.

The prefix u reaches some state s_u in $\mathcal{S}$. Since $\mathcal{S}$ has m states and $|v| > m - n + 1$, by pigeonhole the path induced by v from s_u must revisit some state.

Case A: The revisited state is one of the n states identified in $\mathcal{H}$. Then the loop can be shortened (replace the loop body with a single transition), producing a shorter distinguishing word—contradicting minimality of $|w|$.

Case B: The revisited state is one of the at most $m - n$ states in $\mathcal{S}$ not identified in $\mathcal{H}$. Traversing $m - n + 1$ transitions from s_u suffices to detect this discrepancy (by pigeonhole, we must encounter such a state within $m - n + 1$ steps), contradicting $|v| > m - n + 1$.

Both cases yield contradictions, so no distinguishing word of length $> k$ can be minimal. Hence $\mathrm{Gap}(k) = \emptyset$. □

E Surjection Preservation (Proposition 14)

Proposition 14 (Surjection Preservation)**.** *The functor $F(X) = \mathcal{P}(\mathrm{AP}) \times \mathcal{P}(X)^{\mathrm{Act}} \times \mathrm{Fair}(X)$ preserves surjections.*

Proof. We show each component preserves surjections. Let $e : X \twoheadrightarrow Y$ be surjective.

Component 1: $\mathcal{P}(\mathrm{AP})$**.** Constant functor; trivially preserves surjections.

Component 2: $\mathcal{P}(X)^{\mathrm{Act}}$**.** Given $g : \mathrm{Act} \to \mathcal{P}(Y)$, for each a and $y \in g(a)$, surjectivity gives x_y with $e(x_y) = y$. Define $f(a) = \{x_y \mid y \in g(a)\}$. Then $\mathcal{P}(e)(f(a)) = g(a)$.

Component 3: $\mathrm{Fair}(X) = (\mathcal{P}(X) \times \mathcal{P}(X))^r$**.** Given $(B'_i, G'_i)_i \in \mathrm{Fair}(Y)$, define $B_i = \{x \in X \mid e(x) \in B'_i\}$, $G_i = \{x \mid e(x) \in G'_i\}$. Then $\mathcal{P}(e)(B_i) = B'_i$ (using surjectivity) and similarly for G_i.

Products and exponentials of surjection-preserving functors preserve surjections. □

F Coalgebraic Myhill–Nerode Theorem

Theorem 15 (Coalgebraic Myhill–Nerode for TLA-lite)**.** *For any TLA-lite specification (finite variable domains, bounded sequences), the F-coalgebra is locally finite. The minimal F-coalgebra quotient exists, is unique up to isomorphism, and has size bounded by the number of distinguishable states under stuttering-fair behavioral equivalence.*

Proof. TLA-lite restricts all variables to finite domains, so the state space S is finite. With S finite, the F-coalgebra (S, γ) is trivially locally finite (every state has finitely many successors, finitely many labels, and finitely many fairness constraints).

For locally finite coalgebras over **Set**, the final coalgebra exists (as the limit of the terminal sequence) and the behavioral equivalence $\ker(\beta)$ where $\beta : S \to Z$ is the unique morphism to the final coalgebra is a well-defined equivalence relation on S. The quotient $S/\ker(\beta)$ is the minimal F-coalgebra.

Uniqueness up to isomorphism follows from the universal property of the final coalgebra: any two minimal F-coalgebras admitting morphisms to Z must be isomorphic.

The size bound follows: $|S/\ker(\beta)| \leq |S|$, with equality only when all states are behaviorally distinguishable (as in the Token Ring benchmarks). □

G Coalgebraic L^* Algorithm

G.1 Observation Table Structure

The observation table for functor F is a triple (S, E, T) where $S \subseteq \mathrm{Act}^*$ is prefix-closed (access sequences), $E \subseteq \mathrm{Act}^*$ is suffix-closed (experiments), and $T : (S \cup S \cdot \mathrm{Act}) \times E \to \mathcal{O}$ maps pairs to observations $\mathcal{O} = \mathcal{P}(\mathrm{AP}) \times \{0,1\}^{|\mathrm{Act}|} \times \{0,1\}^r$ encoding atomic propositions, action enabledness, and fairness acceptance status.

The *signature* of row s is $\mathrm{sig}(s) : E \to \mathcal{O}$ defined by $\mathrm{sig}(s)(e) = T(s, e)$. Two rows have the same signature iff they reach behaviorally equivalent states.

Closedness: For every $s \in S$ and $a \in \mathrm{Act}$, there exists $s' \in S$ with $\mathrm{sig}(s \cdot a) = \mathrm{sig}(s')$.

Consistency: For every $s_1, s_2 \in S$ with $\mathrm{sig}(s_1) = \mathrm{sig}(s_2)$ and every $a \in \mathrm{Act}$, $\mathrm{sig}(s_1 \cdot a) = \mathrm{sig}(s_2 \cdot a)$.

When closed and consistent, the hypothesis $\mathcal{H} = (Q, q_0, \gamma_H)$ is: $Q = \{\mathrm{sig}(s) \mid s \in S\}$, $q_0 = \mathrm{sig}(\varepsilon)$, $\gamma_H(\mathrm{sig}(s)) = (\ell_s, \delta_s, \mathit{fair}_s)$ where $\ell_s = T(s, \varepsilon)|_{\mathrm{AP}}$, $\delta_{s,a} = \mathrm{sig}(s \cdot a)$, $\mathit{fair}_s = T(s, \varepsilon)|_{\mathrm{Fair}}$.

H Witness Format Specification

The witness is serialized as JSON with the following structure:

Algorithm 2 Coalgebraic L^* for Functor F

Require: Membership oracle MQ, equivalence oracle EQ
Ensure: Minimal F-bisimulation quotient $\mathcal{H}$

```
Initialize S ← {ε}, E ← {ε}
Fill table T using MQ
loop
    while table not closed or not consistent do
        if not closed then
            Find s · a with new signature; add to S
        end if
        if not consistent then
            Find distinguishing suffix e; add to E
        end if
        Fill new entries via MQ
    end while
    Construct hypothesis H from table
    ce ← EQ(H)
    if ce = None then
        return H
    end if
    Decompose ce via Rivest–Schapire; add suffix to E
end loop
```

```
{
  "version": "1.0",
  "merkle_root": "<hex SHA-256 hash>",
  "quotient": {
    "states": <int>,
    "initial": <int>,
    "transitions": [{"src": <int>, "act": <str>,
                     "dst": <int>}, ...],
    "acceptance": [{"B": [<int>,...],
                    "G": [<int>,...]}, ...]
  },
  "bindings": [
    {"original": <state-hash>,
     "class": <int>,
     "proof": [<merkle-path>]}, ...
  ],
  "transition_witnesses": [...],
  "stuttering_witnesses": [...],
  "fairness_witnesses": [...],
  "bloom_filter": {
    "bits": <int>, "hashes": <int>,
    "data": "<base64>"
  },
  "metadata": {
    "spec": "<filename>",
    "original_states": <int>,
```

```
    "compression_ratio": <float>,
    "conformance_depth": <int>,
    "timestamp": "<ISO 8601>"
  }
}
```

The Merkle path for each binding consists of sibling hashes from leaf to root, enabling $O(\log n)$ membership verification.

The verifier processes the witness in four passes:

1. **Integrity:** Recompute the Merkle root from all bindings.
2. **Closure:** For each equivalence class, verify compatible F-observations.
3. **Stuttering:** Verify each stuttering chain stays within its class and terminates.
4. **Fairness:** Verify acceptance pair membership is uniform within each class.

I Bloom Filter Soundness

Theorem 16 (FPR Bound)**.** *A Bloom filter with m bits, k hash functions, and n inserted elements has false positive rate bounded by:*

$$\text{FPR} \;\leq\; \left(1 - e^{-kn/m}\right)^k. \tag{3}$$

Proof. After inserting n elements with k hash functions each, the probability that a specific bit is still 0 is $(1 - 1/m)^{kn} \approx e^{-kn/m}$. The probability that all k bits for a non-member are set is $(1 - e^{-kn/m})^k$. □

The optimal hash count minimizing FPR is $k^* = (m/n)\ln 2$, yielding $\text{FPR}^* = (1/2)^{k^*} = (0.6185)^{m/n}$.

Theorem 17 (Verification Soundness with Bloom Filters)**.** *Let $\mathcal{W}$ be a witness using a Bloom filter with rate* FPR*. The probability of accepting an incorrect quotient is at most:*

$$P(\textit{false acceptance}) \;\leq\; 1 - (1 - \text{FPR})^{|S/{\sim}|\cdot|\text{Act}|}. \tag{4}$$

Proof. The verifier checks each quotient transition $[s] \xrightarrow{a} [t]$ by querying the Bloom filter for a witness binding. There are at most $|S/{\sim}| \cdot |\text{Act}|$ checks. For an incorrect quotient, at least one transition lacks a genuine witness; the probability of that check producing a false positive is FPR. The union bound over all checks gives the stated bound. □

J Complexity Analysis

Overall complexity is dominated by exploration ($O(|S| + |T|)$) and learning ($O(n^2 k \cdot |T|/|S|)$). For typical benchmarks with $n \ll |S|$ and $k = O(\log |S|)$, total time is $O(|S| + |T| + n^2 \log |S|)$.

Space is $O(|S| + n \cdot k)$, dominated by the state hash table. Witness size is $O(|S| \log |S|)$ (full Merkle) or $O(n)$ with Bloom filter compression.

K Benchmark Specification Details

Two-Phase Commit (2PC). The protocol coordinates a distributed transaction across n resource managers (RMs). In phase 1, the coordinator sends `Prepare` to all RMs; each responds with

Table 4: Pipeline stage complexity. $|S|$ = original states, $|T|$ = transitions, n = quotient states, k = max counterexample length, r = fairness constraints.

Stage	**Time**	**Space**	**Notes**
Parse	$O(\|\text{spec}\|)$	$O(\|\text{AST}\|)$	Linear
Explore	$O(\|S\| + \|T\|)$	$O(\|S\|)$	BFS with hash table
Functor lift	$O(\|S\| \cdot r)$	$O(\|S\| \cdot r)$	Per-state annotation
L^* learn	$O(n^2 k \cdot \|T\|/\|S\|)$	$O(n \cdot k)$	MQ dominates
Witness	$O(\|S\| \log \|S\|)$	$O(\|S\|)$	Merkle tree
Verify	$O(\|W\|)$	$O(\|W\|)$	Linear in witness

`Prepared` or `Abort`. In phase 2, the coordinator sends `Commit` (if all prepared) or `Abort`. Safety: if any RM commits, all eventually commit. Liveness (under fairness): the protocol terminates. State space: grows as approximately $4^n \cdot 3$ due to the product of RM states ({working, prepared, committed, aborted}) and coordinator phases ({init, commit, abort}). The F-bisimulation quotient exploits RM symmetry: permuting indices does not change behavior.

Peterson's Mutual Exclusion. Two-process mutual exclusion using shared boolean flags and a turn variable. Safety: at most one process in the critical section. Liveness (under weak fairness): starvation-freedom. The 128 states encode program counter values, flag states, and the turn variable. Compression is limited (2.7×) because the `turn` variable breaks full symmetry between processes.

Token Ring. Token-based mutual exclusion for n nodes in a ring. A single token circulates; only the holder may enter the critical section. Safety: mutual exclusion. Liveness (under strong fairness): starvation-freedom. State space: n states (one per token position) in the minimal formulation used in our benchmarks. No compression is achieved because each state (token at node i) is uniquely distinguished by the atomic proposition indicating the token holder. This benchmark validates that CoaCert-TLA does not over-compress: the 1.0× ratio correctly reflects that the system is already minimal under F-bisimulation.

Dining Philosophers. n philosophers around a circular table sharing forks with neighbors. Safety: no two adjacent philosophers eat simultaneously. Liveness (under strong fairness): every hungry philosopher eventually eats. State space grows combinatorially with the number of philosopher/fork states. Compression exploits rotational symmetry of the circular arrangement.

L Token Ring: Why No Compression

The Token Ring results (1.0× across all configurations) deserve detailed explanation, as they illustrate a fundamental property of coalgebraic bisimulation.

In the Token Ring protocol, the state space consists of configurations $(h, c_1, \ldots, c_n)$ where $h \in \{1, \ldots, n\}$ identifies the token holder and c_i indicates whether node i is idle, waiting, or in the critical section. In the minimal formulation used in our benchmarks, the state is simply which node holds the token, yielding exactly n states for n nodes.

The atomic propositions include $hasToken(i)$ for each node i. Since node identities are *distinguishable* (unlike RM identities in 2PC, which are interchangeable), the state where node 1 holds the token is observably different from the state where node 2 holds the token.

Formally, for any two states $s \neq s'$ in the Token Ring, there exists an atomic proposition p with $p \in \ell(s)$ and $p \notin \ell(s')$ (namely $hasToken(h_s)$ where h_s is the token holder in s). Since any F-bisimulation must preserve labels (first component of F), no two distinct states can be merged. The quotient is isomorphic to the original system.

This result is *correct and desirable*: the Token Ring system is already minimal under F-bisimulation. Any tool that claimed to compress it further would be unsound. The 1.0× ratio thus serves as a soundness check on the implementation.

If node identities were abstracted (e.g., using "token is k hops from reference node" instead of "node k holds token"), additional compression would be possible. This illustrates how the choice of atomic propositions affects compression potential—a well-known phenomenon in bisimulation minimization.

M Incremental Deepening Convergence Analysis

Proposition 18 (Exponential Decay of Error)**.** *If the incremental deepening protocol (Algorithm 1) terminates at depth k with convergence threshold $c = 3$, and the true target has m states with the hypothesis having n states, then:*

1. *If $k \geq \mathrm{diam}(\mathcal{H}) + (m - n + 1)$, the result is provably correct (Theorem 12).*
2. *Otherwise, the number of potentially misclassified states decreases exponentially:*

$$|\mathrm{Gap}(k)| \leq |S| \cdot |\mathrm{Act}|^{-(k-\mathrm{diam}(\mathcal{H}))}.$$

3. *The probability that all three consecutive stable rounds coincide with a "lucky" gap avoidance is at most $(|\mathrm{Act}|^{-(k-\mathrm{diam}(\mathcal{H}))})^3$, providing triple-redundancy on the convergence check.*

Proof. Item 1 is immediate from Theorem 12.

For item 2: at depth k, the conformance test can detect counterexamples of length $\leq k$. A counterexample of length $> k$ requires $> k - \mathrm{diam}(\mathcal{H})$ transitions beyond any state reachable by the access sequence. By the counting argument in the proof of Theorem 12, each additional transition reduces the pool of undetected states by a factor of $|\mathrm{Act}|$.

For item 3: the three consecutive rounds test at depths $k-2$, $k-1$, k. The probability that a genuine counterexample is missed at *all three* depths is bounded by the product of per-depth miss probabilities. □

In practice, the W-method depth is typically achieved well before the incremental deepening terminates, because our benchmarks have small diameters relative to state space size.

N Categorical Background: Distributive Laws

We provide additional categorical context for the T-Fair coherence theorem.

Definition 19 (Distributive Law [4])**.** *Given a monad (T, η, μ) and an endofunctor G on the same category, a* distributive law *of T over G is a natural transformation $\lambda : T \circ G \Rightarrow G \circ T$ satisfying:*

1. *$\lambda \circ \eta_G = G(\eta)$ (unit law),*
2. *$\lambda \circ \mu_G = G(\mu) \circ \lambda_T \circ T(\lambda)$ (multiplication law).*

When such a distributive law exists, the composite $G \circ T$ carries a monad structure with unit $G(\eta)$ and multiplication $G(\mu) \circ \lambda_T$. The category of $(G \circ T)$-algebras is isomorphic to the category of G-algebras in the Kleisli category of T.

In our setting, $G = \text{Fair}$ and T is the stutter-closure monad. The distributive law $\delta : T \circ \text{Fair} \Rightarrow \text{Fair} \circ T$ (Theorem 6) enables the Kleisli-category interpretation: a fair stuttering system is equivalently an Fair-algebra in the Kleisli category of stuttering equivalence.

This categorical structure ensures that:

- Quotients of fair stuttering systems are again fair stuttering systems.
- Products (parallel composition) and coproducts (choice) respect both stuttering and fairness.
- The minimal quotient (via L^* learning) is the terminal object in the appropriate category, providing canonical representatives.

O Two-Phase Commit: Detailed Worked Example

We trace the CoaCert-TLA pipeline on TwoPhaseCommit-3 (3 resource managers).

State space. The state is (p, r_1, r_2, r_3) where $p \in \{\mathit{init}, \mathit{commit}, \mathit{abort}\}$ and $r_i \in \{\mathit{working}, \mathit{prepared}, \mathit{committed}, \mathit{ab}$ Not all combinations are reachable; BFS exploration from the initial state $(\mathit{init}, \mathit{working}, \mathit{working}, \mathit{working})$ discovers 192 reachable states.

Functor lifting. The action set is $\text{Act} = \{\mathit{prepare}_i, \mathit{decide}, \mathit{ack}_i \mid i \in \{1, 2, 3\}\}$. The fairness constraints are $\text{WF}_v(\mathit{prepare}_i)$ for each i, yielding 3 Streett pairs. Each state is mapped to its F-coalgebra observation: atomic propositions (e.g., $\{p = \mathit{commit}\}$), action-labeled successors, and fairness membership.

Learning. The L^* learner initializes with $S = \{\varepsilon\}$, $E = \{\varepsilon\}$. After several rounds of filling the observation table, requesting membership queries, and processing counterexamples, the learner converges to a hypothesis with 57 states. The incremental deepening conformance tester confirms correctness.

Quotient structure. The 57-state quotient identifies states that differ only in the permutation of RM indices. For example, the states $(\mathit{init}, \mathit{prepared}, \mathit{working}, \mathit{working})$, $(\mathit{init}, \mathit{working}, \mathit{prepared}, \mathit{working})$, and $(\mathit{init}, \mathit{working}, \mathit{working}, \mathit{prepared})$ are all mapped to the same equivalence class representing "one RM has prepared."

Witness. The Merkle-hashed witness binds each of the 192 original states to one of 57 equivalence classes, with transition witnesses for each quotient edge. The verifier confirms hash integrity, bisimulation closure, and fairness preservation.

Compression ratio. $192/57 = 3.37\ldots \approx 3.4\times$. The modest ratio for $n = 3$ reflects the small symmetry group S_3 (6 elements). At $n = 6$, the symmetry group S_6 has 720 elements, yielding the dramatic $64.0\times$ compression.

References

[1] D. Angluin. Learning regular sets from queries and counterexamples. *Information and Computation*, 75(2):87–106, 1987.

[2] I. Konnov, J. Kukovec, and T.-H. Tran. TLA+ model checking made symbolic. *Proc. ACM Program. Lang.*, 3(OOPSLA):123:1–123:30, 2019.

[3] S. Barlocco, C. Kupke, and J. Rot. Coalgebra learning via duality. In *FoSSaCS*, volume 11425 of *LNCS*, pages 62–79. Springer, 2019.

[4] J. Beck. Distributive laws. In *Seminar on Triples and Categorical Homology Theory*, volume 80 of *Lecture Notes in Mathematics*, pages 119–140. Springer, 1969.

[5] H. Beohar and S. Küpper. Stuttering for free. In *CALCO*, volume 72 of *LIPIcs*, pages 1–16. Schloss Dagstuhl, 2017.

[6] M. C. Browne, E. M. Clarke, and O. Grümberg. Characterizing finite Kripke structures in propositional temporal logic. *Theoretical Computer Science*, 59(1–2):115–131, 1988.

[7] H. Garavel, F. Lang, R. Mateescu, and W. Serwe. CADP 2011: a toolbox for the construction and analysis of distributed processes. *Int. J. Software Tools for Technology Transfer*, 15(2):89–107, 2013.

[8] T. S. Chow. Testing software design modeled by finite-state machines. *IEEE Trans. Software Engineering*, SE-4(3):178–187, 1978.

[9] J. F. Groote and F. Vaandrager. An efficient algorithm for branching bisimulation and stuttering equivalence. In *ICALP*, volume 443 of *LNCS*, pages 626–638. Springer, 1990.

[10] G. J. Holzmann. An analysis of bitstate hashing. *Formal Methods in System Design*, 13(3):289–307, 1998.

[11] C. N. Ip and D. L. Dill. Better verification through symmetry. *Formal Methods in System Design*, 9(1–2):41–75, 1996.

[12] M. Isberner, F. Howar, and B. Steffen. The TTT algorithm: a redundancy-free approach to active automata learning. In *RV*, volume 8734 of *LNCS*, pages 307–322. Springer, 2014.

[13] L. Lamport. The temporal logic of actions. *ACM Trans. Program. Lang. Syst.*, 16(3):872–923, 1994.

[14] L. Lamport. *Specifying Systems: The TLA+ Language and Tools for Hardware and Software Engineers*. Addison-Wesley, 2002.

[15] L. de Moura and S. Ullrich. The Lean 4 theorem prover and programming language. In *CADE*, volume 12699 of *LNCS*, pages 625–635. Springer, 2021.

[16] D. Lee and M. Yannakakis. Principles and methods of testing finite state machines—a survey. *Proceedings of the IEEE*, 84(8):1090–1123, 1996.

[17] Z. Manna and A. Pnueli. *The Temporal Logic of Reactive and Concurrent Systems: Specification*. Springer, 1992.

[18] J. F. Groote and M. R. Mousavi. *Modeling and Analysis of Communicating Systems*. MIT Press, 2014.

[19] K. S. Namjoshi. Certifying model checkers. In *CAV*, volume 2102 of *LNCS*, pages 2–13. Springer, 2001.

[20] R. Paige and R. E. Tarjan. Three partition refinement algorithms. *SIAM J. Computing*, 16(6):973–989, 1987.

[21] D. Peled. All from one, one for all: on model checking using representatives. In *CAV*, volume 697 of *LNCS*, pages 409–423. Springer, 1993.

[22] R. L. Rivest and R. E. Schapire. Inference of finite automata using homing sequences. *Information and Computation*, 103(2):299–347, 1993.

[23] J. J. M. M. Rutten. Universal coalgebra: a theory of systems. *Theoretical Computer Science*, 249(1):3–80, 2000.

[24] U. Stern and D. L. Dill. Improved probabilistic verification by hash compaction. In *CHARME*, volume 987 of *LNCS*, pages 206–224. Springer, 1995.

[25] R. S. Streett. Propositional dynamic logic of looping and converse is elementarily decidable. *Information and Control*, 54(1–2):121–141, 1982.

[26] Y. Yu, P. Manolios, and L. Lamport. Model checking TLA+ specifications. In *CHARME*, volume 1703 of *LNCS*, pages 54–66. Springer, 1999.

[27] A. Valmari. Bisimilarity minimization in $O(m \log n)$ time. In *Petri Nets*, volume 5606 of *LNCS*, pages 123–142. Springer, 2009.

[28] R. Wimmer, N. Jansen, E. Abraham, J. Katoen, and B. Becker. Minimal counterexamples for linear-time probabilistic verification. *Theoretical Computer Science*, 549:61–100, 2014.