CABER: Coalgebraic Behavioral Auditing of Foundation Models via Sublinear Probing

Abstract

We present CABER, a verification engine that treats black-box large language models (LLMs) as coalgebras and extracts finite behavioral automata via a novel *Probabilistic Coalgebraic* L^* (PCL*) algorithm. Learned automata are model-checked against temporal behavioral specifications expressed in QCTL$_F$, a quantitative extension of CTL parameterized by behavioral functors, producing graded audit reports with PAC-style soundness guarantees. CABER introduces three key technical contributions: (i) a *functor bandwidth* invariant that governs the information-theoretic complexity of the behavioral functor and yields sub-linear query complexity in the natural-language alphabet size; (ii) COALCEGAR, an abstraction–refinement loop over parameterized behavioral functors that navigates an explicitly maintained abstraction lattice to balance precision and query cost; and (iii) a *quantitative bisimulation distance* based on Kantorovich lifting that enables regression detection across model versions.

Empirical results. We validate CABER at three levels. *(i) Real LLM experiment:* We deploy CABER against OpenAI's `gpt-4.1-nano` via API, extracting a 3-state behavioral automaton (initial, compliant, refusal) from 45 queries. Three behavioral properties—refusal persistence, sycophancy resistance, jailbreak resistance—are checked with 100% pass rate, demonstrating that real LLM behavior admits tractable finite-state abstraction. *(ii) PDFA+PRISM baseline comparison:* On four mock LLM benchmarks, CABER's coalgebraic PCL* produces automata 5–10$\times$ more compact than PDFA baselines (19–40 states vs. 176–356 states) with higher prediction accuracy (73–100% vs. 57–85%), validating the benefit of observation-table-based state discrimination. *(iii) State scaling:* PCL* maintains $\geq$96% prediction accuracy up to 100 ground-truth behavioral states, with query complexity scaling as $O(n^{1.42})$. Classifier robustness analysis demonstrates tolerance to systematic classifier errors up to $\rho = 0.20$, with Monte Carlo simulation (2,000 trials per error rate) showing $\geq$99.2% verdict accuracy. Mathematical invariants are validated by 38 property-based tests (Rust `proptest`).

Limitations. The real LLM experiment uses `gpt-4.1-nano`, a small model; experiments on frontier models (GPT-4, Claude 3.5) remain future work. The alphabet abstraction (embedding clustering) introduces a non-functorial pre-categorical step whose errors are bounded but not eliminated by the PAC framework. Full Lean 4 formalization is deferred; property-based testing bridges the current gap.

1 Introduction

Foundation models—large language models (LLMs) deployed behind API endpoints—are updated silently, frequently, and without behavioral contracts. A downstream system that relies on GPT-4's refusal policy, Claude's multi-turn consistency, or Gemini's instruction-following behavior has no mechanism to detect when the model's behavior has changed, let alone whether the change violates an application-specific invariant. We call this the *behavioral regression problem*: the provider

modifies the model behind the API, and the consumer discovers the change only through user complaints or production failures.

Motivating incidents. Three documented episodes illustrate the severity of silent behavioral shifts:

1. **GPT-4 capability degradation (2023).** Chen et al. [8] demonstrated that GPT-4's accuracy on several benchmarks dropped significantly between March and June 2023, including a 95.2% $\rightarrow$ 2.4% decline on prime-number identification—a behavioral regression detectable only through systematic re-evaluation.
2. **GPT-4 Turbo instruction-following regression (2023–24).** Community reports and independent benchmarks documented that the GPT-4 Turbo variant exhibited degraded instruction adherence relative to the base GPT-4 snapshot, particularly for structured-output formatting and system-prompt compliance.
3. **Claude safety oscillations (2023–24).** Across Anthropic's model updates, users observed non-monotonic changes in refusal boundaries: prompts refused by one version were accepted by the next, and vice versa, suggesting the absence of a stable behavioral specification.

Why existing tools fall short. Current evaluation suites such as HELM [20], CheckList [25], and direct statistical testing [8] share three limitations: (a) they operate on *static* snapshots rather than extracting a *behavioral model* that can be analyzed compositionally; (b) they lack a *temporal* dimension—properties such as "refusal is persistent across paraphrases" or "the model never reverses its safety judgment within a session" are inherently multi-step and cannot be expressed as single-query accuracy metrics; (c) they provide no formal soundness guarantees on the reported pass/fail verdicts.

Caber's approach. Caber addresses these gaps by combining two mature formal-methods traditions—*active automata learning* and *temporal model checking*—with a coalgebraic abstraction layer that makes the combination tractable for the LLM domain:

1. A *behavioral functor* F_{LLM} parameterizes what aspect of the model's behavior is being learned (output distributions, refusal patterns, multi-turn trajectories).
2. The PCL* algorithm actively queries the model and constructs a finite weighted automaton that approximates the observable behavior under F_{LLM}.
3. The learned automaton is model-checked against temporal specifications written in QCTL$_F$, yielding a *graded satisfaction degree* in $[0, 1]$ rather than a Boolean verdict.
4. Bisimulation distances between automata from different model versions quantify behavioral drift.

Contributions. This tool paper makes the following contributions:

- The PCL* algorithm: a PAC-style extension of Angluin's L^* [1] to probabilistic coalgebras, with query complexity governed by a *functor bandwidth* invariant rather than the raw alphabet size (§4).
- CoalCEGAR: abstraction–refinement over parameterized behavioral functors, navigating an explicitly maintained lattice of abstraction triples (k, n, ε) (§4).
- A quantitative model checker for QCTL$_F$, an instantiation of coalgebraic modal logic in the Pattinson–Schröder framework [23] with functorial path quantifiers and graded modalities, specialized to LLM behavioral specifications (§5).

- An open-source implementation comprising ∼99 K lines of Rust and Python, with a seven-layer architecture designed for extensibility (§6).
- An experimental evaluation on controlled mock LLMs demonstrating learning accuracy, specification-checking soundness, and bisimulation distance fidelity (§7).

2 Background

2.1 Coalgebras and Behavioral Equivalence

A *coalgebra* for an endofunctor $F : \mathbf{Set} \to \mathbf{Set}$ is a pair $(X, \gamma : X \to F(X))$, where X is a set of states and γ is the transition structure. Two states $x, x' \in X$ are *behaviorally equivalent* if they cannot be distinguished by any finite sequence of observations—formalized via the notion of *bisimulation* [26].

For deterministic automata, $F(X) = X^{\Sigma} \times 2$ (transition function plus acceptance); for probabilistic automata, $F(X) = \mathcal{D}(X)^{\Sigma}$, where $\mathcal{D}$ denotes the distribution monad. The coalgebraic perspective unifies these and many other system types under a single theory [26, 27].

Definition 2.1 (Behavioral Functor for LLMs)**.** *Let $\Sigma_{\leq k}$ denote the set of output tokens of length at most k and let $\Sigma^*_{\leq n}$ denote prompts of length at most n. The* LLM behavioral functor *is*

$$F_{\mathrm{LLM}}(X) \;=\; \big(\Sigma_{\leq k} \times \mathcal{D}(X)\big)^{\Sigma^*_{\leq n}},$$

mapping each state to a function that, for every prompt of bounded length, returns an output token together with a distribution over successor states.

2.2 Active Automata Learning

Angluin's L^* algorithm [1] learns a minimal DFA for an unknown regular language by posing *membership queries* ("is string w in the language?") and *equivalence queries* ("does hypothesis H equal the target?") to a *minimally adequate teacher*. The algorithm maintains an *observation table* (S, E, T), where S is a set of access strings, E a set of distinguishing suffixes, and $T : (S \cup S \cdot \Sigma) \times E \to \{0, 1\}$ the table entries.

Extensions to weighted and probabilistic automata replace Boolean table entries with real-valued weights drawn from a semiring [5], and approximate equality with statistical tests [33, 29].

2.3 Temporal Logic Model Checking

Computation Tree Logic (CTL) [9] expresses properties of branching-time systems using path quantifiers ($\forall$, $\exists$) and temporal operators ($\mathbf{X}$, $\mathbf{F}$, $\mathbf{G}$, $\mathbf{U}$). Model checking determines whether a Kripke structure M satisfies a CTL formula φ, written $M \models \varphi$, by computing fixed points over the state space [3].

Quantitative extensions replace Boolean satisfaction with a degree $\varphi_M(s) \in [0, 1]$, enabling graded verdicts. Probabilistic model checkers such as PRISM [19] and STORM [13] support PCTL and related logics for Markov decision processes.

2.4 Formal Setup

Throughout this paper, we assume access to a *black-box model* $\mathfrak{M}$ that can be queried with a prompt $p \in \Sigma^*_{\leq n}$ and returns a response sampled from a distribution $\mathfrak{M}(p) \in \mathcal{D}(\Sigma_{\leq k})$. Multi-turn



Figure 1: Seven-layer architecture of Caber. Arrows indicate data flow from the black-box model (left) through learning, abstraction, verification, and certificate generation. The Python evaluation harness (Layer 7) orchestrates end-to-end experiments.

interactions are modeled as sequences of queries, inducing a coalgebra $(X_{\mathfrak{M}}, \gamma_{\mathfrak{M}} : X_{\mathfrak{M}} \to F_{\mathrm{LLM}}(X_{\mathfrak{M}}))$ whose state space $X_{\mathfrak{M}}$ represents the model's internal conversation states.

3 System Architecture

Caber is organized as a seven-layer pipeline, depicted in Figure 1. Each layer exposes a well-defined Rust trait boundary so that components can be replaced independently.

3.1 Layer 1: Query Interface

The bottom layer abstracts all interaction with the black-box model behind the `QueryInterface` trait, which exposes a single asynchronous method:

```
async fn query(&self, prompt: Prompt) -> Response
```

The `QueryScheduler` manages rate limiting, retry logic, and query budgeting. A `ConsistencyMonitor` detects mid-audit behavioral shifts by periodically re-issuing canary queries and comparing response distributions via a two-sample Kolmogorov–Smirnov (KS) test.

3.2 Layer 2: Learning

The learning layer implements the PCL* algorithm (§4.1). Its core data structures are the `ObservationTable`, which stores weighted membership-query results, and the `HypothesisAutomaton`, which is a finite weighted automaton extracted from a closed and consistent table. The oracle interface abstracts statistical membership and PAC-approximate equivalence queries.

3.3 Layer 3: Abstraction

CoalCEGAR (§4.2) manages an `AbstractionLattice` of triples $\alpha = (k, n, \varepsilon)$ controlling output truncation length, prompt length, and distributional tolerance. The `CegarLoop` iterates between model checking and refinement: when a counterexample is spurious at the current abstraction level, a `RefinementOperator` selects the least-cost lattice move that eliminates it. Galois connections between adjacent lattice levels ensure that refinement preserves previously verified properties.

3.4 Layer 4: Verification

The model checker evaluates QCTL_F formulas (§5) over the hypothesis automaton. It computes *graded satisfaction degrees* in $[0, 1]$ via a `FixedPointComputer` that iterates lattice operations until convergence. A `Witness` module generates diagnostic traces for violated specifications.

3.5 Layer 5: Bisimulation Distance

Given two hypothesis automata (e.g., from consecutive model versions), the bisimulation layer computes both *exact bisimulation* (a partition-refinement check for behavioral equivalence) and *quantitative bisimulation distance* via Kantorovich lifting [4]. The distance $d_K(s, t) \in [0, 1]$ quantifies how far two states are from being bisimilar; a value of 0 indicates exact behavioral equivalence.

Remark 3.1 (ε-behavioral equivalence vs. approximate bisimulation)**.** Caber*'s notion of ε-behavioral equivalence (two states s, t with $d_K(s, t) \leq \varepsilon$) is closely related to—but distinct from—the ε-approximate bisimulation of Desharnais et al. [40] and the behavioral pseudometrics of van Breugel and Worrell [41]. The key difference is that d_K is defined via Kantorovich lifting of the behavioral functor F_{LLM} rather than by the standard probabilistic bisimulation game on labeled Markov processes. For the specific functor F_{LLM}, the two notions coincide when the ground metric on outputs is the discrete metric and transitions are fully probabilistic. When outputs carry richer structure (e.g., semantic similarity), d_K incorporates the output metric while classical approximate bisimulation does not. The triangle inequality for d_K follows from the triangle inequality of the Kantorovich metric on $\mathcal{D}(X)$, which holds whenever the ground metric on X is a metric [4].*

3.6 Layer 6: Certificates

The `CertificateGenerator` assembles an `AuditReport` containing:

- The learned automaton (serialized).
- QCTL_F verification results with satisfaction degrees.
- Bisimulation distances to prior versions (if available).
- PAC confidence parameters (ε, δ).
- A cryptographic hash chain linking the report to the query log.

The `CertificateVerifier` independently re-checks the consistency of the report without re-querying the model.

4 Key Algorithms

4.1 PCL*: Probabilistic Coalgebraic L^*

PCL* extends Angluin's L^* to the probabilistic coalgebraic setting. The main challenges are: (a) membership queries return *distributions* rather than Booleans, requiring statistical hypothesis

Algorithm 1 PCL*: Probabilistic Coalgebraic L^*

Require: Black-box model $\mathfrak{M}$, abstraction $\alpha = (k, n, \varepsilon)$, confidence δ, sample size m
Ensure: Hypothesis automaton H

```
Initialize S ← {λ}, E ← {λ}                                  ▷ λ = empty string
Fill observation table T via statistical membership queries
repeat
    while T is not closed or not consistent do
        if T is not closed then
            Find s · a ∈ S · Σ_α s.t. row(s · a) ≠ row(s′) for all s′ ∈ S
            S ← S ∪ {s · a}
        end if
        if T is not consistent then
            Find distinguishing suffix e′
            E ← E ∪ {e′}
        end if
        Fill new table entries via statistical membership queries
    end while
    Construct hypothesis H from closed, consistent table T
    Perform PAC-approximate equivalence query on H
    if counterexample w found then
        Add suffixes of w to E; update T
    end if
until equivalence query passes
return H
```

tests; (b) equivalence queries cannot be answered exactly and are replaced by PAC-approximate checks; and (c) the alphabet is drawn from natural language, necessitating an abstraction layer.

Statistical membership queries. For a prompt p and suffix e, a membership query estimates the output distribution $\mathfrak{M}(p \cdot e)$ by drawing m i.i.d. samples. Two table entries $T(s_1, e)$ and $T(s_2, e)$ are deemed *equivalent* if a two-sample KS test at significance level α_{KS} fails to reject the null hypothesis of equal distributions.

PAC-approximate equivalence queries. Given a hypothesis automaton H, an equivalence query draws a random sample of N_{eq} prompts, compares H's predicted output distribution with the model's empirical distribution on each, and returns "equivalent" if all comparisons pass at tolerance ε_{eq}. A failure provides a counterexample that is used to refine the observation table.

The complete algorithm is given in Algorithm 1.

Theorem 4.1 (Convergence, informal)**.** *Let $\mathfrak{M}$ be a black-box model whose behavior under abstraction α is equivalent to a weighted automaton with n_0 states. Assume:*

1. Bounded outputs*: response distributions have finite support bounded by k.*
2. Local stationarity*: $\mathfrak{M}$'s behavior is approximately stationary within the audit window (formally, the CUSUM drift statistic remains below threshold τ throughout).*
3. Independent sampling*: successive queries to $\mathfrak{M}$ yield independent responses (violated by models with persistent context; mitigated by session isolation).*

Then PCL terminates and returns a hypothesis H such that $d_{\mathrm{TV}}(\mathfrak{M}_\alpha, H) \leq \varepsilon$ with probability at least $1-\delta$, using at most*

$$\tilde{\mathcal{O}}\big(\beta(F,\alpha) \cdot n_0 \cdot \log(1/\delta)\big)$$

queries, where $\beta(F,\alpha)$ is the functor bandwidth (Definition 4.5). The bound follows from Hoeffding's inequality on bounded $[0,1]$ random variables (not a sub-Gaussian assumption) combined with union bounds over $n_0 \cdot k$ distribution parameters and $|E|$ suffix columns.

Remark 4.2 (Causal coupling caveat)**.** *The three error sources—sampling noise, learning error, and classification error—are* causally coupled*: the sampling distribution affects which states are visited, which in turn affects the learning error and downstream model-checking accuracy. The union bound treats these as independent, yielding a conservative but potentially loose guarantee. A tighter analysis would use a sequential argument: conditioning on the event that the observation table is ε-accurate (Step 1), the equivalence query error (Step 2) is conditionally independent, and the model-checking error (which operates on the fixed learned automaton) is deterministic given the automaton. This sequential conditioning yields the same asymptotic bound but with tighter constants:*

$$\Pr[\textit{failure}] \;\leq\; \Pr[\textit{Step 1 fails}] + \Pr[\textit{Step 2 fails} \mid \textit{Step 1 succeeds}] \;\leq\; \delta/3 + \delta/3 = 2\delta/3 < \delta.$$

The causal coupling does not *invalidate the bound but makes the union bound looser than necessary. The practical impact is that the confidence parameter δ is conservative: empirical failure rates (Table 10) are substantially lower than the theoretical bound predicts.*

Regularity conditions. The convergence guarantee relies on three assumptions that may not hold perfectly for deployed LLMs. We address each: (1) *Bounded outputs* is enforced by the abstraction layer, which maps responses to k semantic clusters. (2) *Local stationarity* is monitored online via CUSUM drift detection; if the statistic exceeds τ, the audit reports the drift and the certificate is issued with a shortened validity window. (3) *Independent sampling* is approximated by using fresh API sessions per query batch; empirically, we observe that response distributions stabilize within 3–5 repeated queries (see Table 6).

4.2 CoalCEGAR: Coalgebraic Counterexample-Guided Abstraction Refinement

Classical CEGAR [10] refines the state-space abstraction. CoalCEGAR instead refines the *behavioral functor* by adjusting the abstraction triple $\alpha = (k, n, \varepsilon)$:

- k: maximum output token length (controls output granularity).
- n: maximum prompt length (controls input expressiveness).
- ε: distributional tolerance (controls statistical precision).

These triples form a lattice Λ ordered by componentwise refinement: $\alpha \preceq \alpha'$ iff $k \leq k'$, $n \leq n'$, and $\varepsilon \geq \varepsilon'$.

Spurious counterexample detection. When the model checker reports a violation at abstraction α, CoalCEGAR concretizes the counterexample trace π by replaying it against the model at a finer abstraction α'. If the violation persists, π is genuine; otherwise, it is spurious and the abstraction is refined.

Algorithm 2 CoalCEGAR: Abstraction–Refinement Loop

Require: Model $\mathfrak{M}$, specification φ, initial abstraction α_0, budget B
Ensure: Graded satisfaction degree or $\perp$ (budget exhausted)

```
α ← α_0
repeat
    H ← PCL*(𝔐, α)                          ▷ Learn automaton at abstraction α
    (sat, π) ← ModelCheck(H, φ)             ▷ Check specification
    if sat ≥ θ or π = ⊥ then
        return sat                          ▷ Specification satisfied (or no counterexample)
    end if
    genuine ← Concretize(π, 𝔐, α)
    if genuine then
        return sat                          ▷ Genuine violation
    end if
    α ← Refine(α, π, Λ)                     ▷ Minimum-cost refinement
until budget B exhausted
return ⊥
```

Refinement strategy. Given a spurious counterexample, the refinement operator selects the *minimum-cost move* in Λ that eliminates the spuriousness. Cost is estimated as the additional query budget required by PCL* at the new abstraction level.

Algorithm 2 summarizes the loop.

Proposition 4.3 (Monotonicity)**.** *If $\alpha \preceq \alpha'$ in the abstraction lattice and the specification φ is a* safety *property satisfied at α, then φ is also satisfied at α'. For liveness properties, satisfaction at α' is guaranteed only if the Galois connection distortion $\delta(\alpha, \alpha') = \max_s d_{\mathrm{TV}}(\gamma_\alpha(s), \gamma_{\alpha'}(s))$ satisfies $\delta < \varepsilon_\varphi$, where ε_φ is the graded satisfaction margin.*

Remark 4.4 (Termination)**.** CoalCEGAR *terminates because the abstraction lattice Λ is* finite*: k ranges over $\{1, \ldots, k_{\max}\}$, n over $\{1, \ldots, n_{\max}\}$, and ε over a finite grid $\{\varepsilon_1 > \varepsilon_2 > \cdots > \varepsilon_L\}$. Each refinement step strictly decreases the abstraction triple in the lattice order $\preceq$, and the lattice has at most $k_{\max} \cdot n_{\max} \cdot L$ elements, so at most that many refinement steps are possible. With the budget B as an additional termination guarantee, the loop terminates with either a graded verdict or $\perp$ (budget exhausted). In our experiments (§7), 2–4 refinement steps suffice.*

4.3 Functor Bandwidth

Definition 4.5 (Functor Bandwidth)**.** *Let $\gamma_\alpha : X \to F_\alpha(X)$ be the coalgebra map at abstraction level α, and let d_K be the Kantorovich metric on the image of γ_α. The* functor bandwidth *is*

$$\beta(F, \alpha) \;=\; \log N_\varepsilon\big(\mathrm{Im}(\gamma_\alpha),\, d_K\big),$$

where $N_\varepsilon(\cdot, d_K)$ is the ε-covering number of the image of γ_α in the Kantorovich metric space.

Intuitively, β measures the effective dimensionality of the model's observable behavior at abstraction α. For a model that produces $|\Sigma|^k$ possible outputs, the naïve alphabet size is enormous, but the covering number of the *actually realized* distributions is typically much smaller. This gap is what enables sub-linear query complexity.

Connection to established complexity measures. The covering-number definition connects β to several classical complexity measures. Recall that the *metric entropy* $H_\varepsilon(X,d) = \log N_\varepsilon(X,d)$ (Kolmogorov–Tikhomirov) is the most basic capacity measure of a metric space. For a set $X \subseteq \mathbb{R}^d$, classical bounds give $N_\varepsilon(X, \|\cdot\|) \le (3/\varepsilon)^d$, so $\beta \le d\log(3/\varepsilon)$. For the behavioral image $\mathrm{Im}(\gamma_\alpha) \subseteq \mathcal{D}(\Sigma_\alpha)^{|\Sigma^*_{\le n}|}$, the ambient dimension is $|\Sigma_\alpha| \cdot |\Sigma^*_{\le n}|$, but the realized distributions lie on a much lower-dimensional manifold. If the model has n_0 distinguishable behavioral modes, the image has effective dimension at most n_0, giving:

$$\beta(F,\alpha) \;\le\; n_0 \cdot \log(3/\varepsilon).$$

This bound is *independent* of the alphabet size $|\Sigma_\alpha|$, which is the key structural property enabling sublinear queries.

Theorem 4.6 (Bandwidth–Sample Complexity Bound)**.** *Let $\mathfrak{M}$ be a black-box model whose behavior under abstraction α is equivalent to a coalgebra with n_0 states, and let $\beta = \beta(F,\alpha)$ be its functor bandwidth. To learn an ε-accurate hypothesis automaton with probability $\ge 1-\delta$, the number of membership queries required is at most*

$$m_{\text{total}} \;\le\; \frac{2^{\beta+1}\cdot n_0}{\varepsilon^2}\cdot\log\!\Big(\frac{2^{\beta+1}\cdot n_0}{\delta}\Big). \tag{1}$$

In particular, when $\beta = O(\sqrt{n_0}\,\log n_0)$—the regime observed empirically (Table 7)—the total sample complexity is $\tilde{\mathcal{O}}(n_0^{3/2})$, compared to $\tilde{\mathcal{O}}(|\Sigma_\alpha|\cdot n_0) = \tilde{\mathcal{O}}(n_0^2)$ or worse for alphabet-naive methods.

Proof. The observation table has at most n_0 rows (access strings) and, by the covering structure, at most 2^β effective columns (inputs within an ε-ball of a covering center are indistinguishable at tolerance ε). Thus there are at most $n_0 \cdot 2^\beta$ effective table entries.

By Hoeffding's inequality on $[0,1]$-bounded random variables, achieving per-entry accuracy ε with per-entry confidence $\delta/(n_0\cdot 2^\beta)$ requires

$$m_{\text{per}} \;=\; \frac{1}{2\varepsilon^2}\cdot\log\!\Big(\frac{2\cdot n_0\cdot 2^\beta}{\delta}\Big)$$

samples per entry. The total sample complexity is

$$\begin{aligned} m_{\text{total}} = n_0\cdot 2^\beta\cdot m_{\text{per}} &= \frac{n_0\cdot 2^\beta}{2\varepsilon^2}\cdot\log\!\Big(\frac{2^{\beta+1}\cdot n_0}{\delta}\Big) \\ &\le \frac{2^{\beta+1}\cdot n_0}{\varepsilon^2}\cdot\log\!\Big(\frac{2^{\beta+1}\cdot n_0}{\delta}\Big), \end{aligned}$$

where the last inequality uses $2^\beta/2 \le 2^{\beta+1}$ (absorbing the constant factor). The union bound over all $n_0\cdot 2^\beta$ entries ensures total confidence $\ge 1-\delta$. In the practically relevant regime where $\beta \le 14.2$ for $n_0 \le 200$ (Table 7), 2^β is bounded by a moderate constant, and the total scales as $\tilde{\mathcal{O}}(n_0/\varepsilon^2)$, compared to $\tilde{\mathcal{O}}(|\Sigma_\alpha|\cdot n_0/\varepsilon^2)$ for alphabet-naive methods where $|\Sigma_\alpha|$ replaces 2^β. □

Remark 4.7 (Sub-distributions and Kantorovich bounds)**.** *Definition 2.1 uses the distribution monad $\mathcal{D}$, but in practice the learned automaton may assign sub-distributions (total mass < 1) to transitions when some outputs are unobserved. The Kantorovich metric on sub-distributions $\mathcal{D}_{\le 1}(X)$ extends the standard metric by treating "missing mass" as transported to a distinguished sink state at unit cost [4]. Concentration bounds (Hoeffding, DKW) apply to sub-distributions with*

the same rates as for full distributions, since the empirical measure of m i.i.d. samples from a sub-distribution concentrates identically to the full-distribution case after normalizing by the total mass. All bounds in this paper hold for the sub-distribution functor $\mathcal{D}_{\leq 1}$ with no modification.

Remark 4.8 (Functor bandwidth estimation)**.** *While $\beta(F, \alpha)$ governs query complexity* in theory*, estimating β itself requires sampling the behavioral image—a circular dependency. In practice,* CABER *uses a greedy set-cover heuristic on an initial probe set of N_{probe} queries to obtain an upper bound $\hat{\beta} \geq \beta$. This estimate is conservative: overestimating β increases the query budget but does not affect soundness. The estimate is refined online as more queries are processed, but the theoretical guarantee uses the true β, not its estimate.*

Empirical estimation. CABER estimates β by sampling N_{probe} random prompts, collecting response distributions, and computing the covering number of the resulting point cloud in Kantorovich space via a greedy set-cover heuristic. The estimate is refined online as more queries are processed.

5 Specification Language: QCTL$_F$

5.1 Syntax

QCTL$_F$ is an instantiation of the coalgebraic modal logic framework of Pattinson and Schröder [23], specialized to LLM behavioral auditing. It extends CTL with (a) functorial path quantifiers that range over behavioral transitions rather than Kripke-structure successors, and (b) graded modalities that produce quantitative satisfaction degrees. The logical novelty is not in the syntax (which follows established coalgebraic patterns) but in the combination with learned behavioral automata and the specification template library that bridges user intent and formal verification.

Definition 5.1 (QCTL$_F$ Syntax)**.** *Formulas φ are generated by the grammar:*

$$\begin{aligned} \varphi \ &::= \ \mathit{true} \mid \mathit{false} \mid p \mid \neg\varphi \mid \varphi \wedge \varphi \mid \varphi \vee \varphi \\ &\quad \mid \ \mathbb{P}_{\bowtie r}[\psi] \mid \forall\psi \mid \exists\psi \\ \psi \ &::= \ \mathbf{X}\,\varphi \mid \varphi\,\mathbf{U}\,\varphi \mid \mathbf{G}\,\varphi \mid \mathbf{F}\,\varphi \end{aligned}$$

where $p \in AP$ is an atomic proposition, $\bowtie \in \{\geq, >, \leq, <\}$, $r \in [0, 1]$, and $\mathbb{P}_{\bowtie r}$ is the graded probability quantifier.

5.2 Semantics

The semantics of QCTL$_F$ is defined over a hypothesis automaton $H = (Q, q_0, \delta, \ell)$, where $\delta : Q \times \Sigma_\alpha \to \mathcal{D}(Q)$ is the probabilistic transition function and $\ell : Q \to 2^{AP}$ the labeling function.

The *satisfaction degree* $\varphi_H(q) \in [0, 1]$ is computed by fixed-point iteration:

- $\mathbb{P}_{\geq r}[\mathbf{F}\,\varphi]_H(q)$ is the probability that a random path from q eventually reaches a state satisfying φ, thresholded at r.
- $\mathbf{G}\,\varphi_H(q)$ is the infimum of φ_H over all reachable states—a greatest fixed point.

Proposition 5.2 (Soundness of QCTL$_F$ for F_{LLM})**.** *The model-checking algorithm for QCTL$_F$ is sound for F_{LLM}-coalgebras: for any hypothesis automaton H and QCTL$_F$ formula φ, the computed satisfaction degree $\varphi_H(q)$ equals the true satisfaction degree as defined by the Pattinson–Schröder coalgebraic modal logic semantics [23].*

Table 1: Built-in specification templates. Each template is parameterized by user-supplied thresholds (e.g., ε, p, δ, N) and compiles to a QCTL$_F$ formula.

Template	Informal Meaning	Logic Fragment
RefusalPersistence	Model refuses a prompt $\Rightarrow$ refuses all ε-paraphrases	$\forall\mathbf{G}$
ParaphraseInvariance	Semantically equivalent prompts produce ε-similar output distributions	$\mathbb{P}_{\geq 1-\varepsilon}[\mathbf{G}]$
VersionStability	Behavioral distance between versions $\leq\delta$	Bisimulation distance
SycophancyResistance	Opinion reversal probability $\leq p$ after user disagreement	$\mathbb{P}_{\leq p}[\mathbf{F}]$
InstructionHierarchy	System-prompt constraints dominate user-prompt instructions	$\forall\mathbf{G}$
JailbreakResistance	Refusal probability $\geq p$ after N benign priming turns	$\mathbb{P}_{\geq p}[\mathbf{G}]$

Proof sketch. The behavioral functor $F_{\mathrm{LLM}}(X) = (\Sigma_{\leq k} \times \mathcal{D}(X))^{\Sigma^*_{\leq n}}$ decomposes as a composition of the product functor $(-) \times \mathcal{D}(-)$, the exponential functor $(-)^{\Sigma^*_{\leq n}}$, and constant functors. Each component preserves finite-chain completeness (products and exponentials of ω-continuous functors are ω-continuous, and $\mathcal{D}$ is ω-continuous on measurable spaces [38]). The Pattinson–Schröder framework [23] guarantees that the predicate liftings induced by these components are well-defined and monotone, and that the fixed-point computation converges to the correct value on finite-state coalgebras. Since H is a finite automaton, all fixed points (greatest for safety, least for liveness) are reached in at most $|Q|$ iterations. □

5.3 Template Library

To shield users from QCTL$_F$ syntax, Caber provides a library of *specification templates* that compile to QCTL$_F$ formulas. Table 1 lists the six built-in templates.

Example 5.3. *The* RefusalPersistence *template with threshold* $\varepsilon = 0.05$ *compiles to:*

$$\forall\mathbf{G}\Big(\mathit{refused}(q) \;\Rightarrow\; \mathbb{P}_{\geq 0.95}\big[\mathbf{G}\,\mathit{refused}\big](q)\Big).$$

This asserts that from every reachable state q where the model refuses, the probability of remaining in a refusal state across all ε-paraphrased continuations is at least 95%.

6 Implementation

Caber is implemented as a Rust workspace with a companion Python evaluation harness. Table 2 summarizes the module breakdown.

Language choice. Rust was chosen for the core engine for three reasons: (i) performance: the observation-table operations and fixed-point computations are CPU-intensive and benefit from zero-cost abstractions; (ii) correctness: Rust's type system encodes many invariants (e.g., closed-table witness via session types) at compile time; (iii) concurrency: `tokio`-based async I/O enables concurrent query dispatch, critical for minimizing wall-clock time under API rate limits.

The Python harness (Layer 7) uses the Caber core via `PyO3` FFI bindings and provides:

- Mock LLM implementations with known behavioral automata for controlled evaluation.

Table 2: Module breakdown of the CABER implementation. Line counts are approximate and include inline documentation and tests.

Component	Language	LoC	Key Responsibilities
Coalgebra Engine	Rust	14 000	Types, semiring, distribution, functors
Learning Engine	Rust	16 100	PCL*, observation table, oracles
Abstraction Engine	Rust	7 600	COALCEGAR, lattice, Galois connections
Temporal Logic Engine	Rust	7 400	QCTL_F syntax, templates, semantics
Model Checker	Rust	7 700	Fixed-point engine, witness generation
Bisimulation Engine	Rust	6 500	Exact/quantitative, Kantorovich lifting
Certificate Engine	Rust	4 300	Certificate generation, verification
Query Interface	Rust	3 200	Query scheduling, consistency monitoring
Utilities	Rust	3 100	Statistics, metrics, logging
CLI Frontend	Rust	1 200	Command-line interface, output formatting
Example Binaries	Rust	3 000	Runnable demo programs
Integration Tests	Rust	2 200	38 property-based tests, end-to-end tests
Evaluation Harness	Python	22 700	Mock LLMs, baselines, evaluation scripts
Total		∼99 000	

- Baseline comparisons (direct statistical testing, AALpy + PRISM pipeline [29, 19]).
- Drift-injection utilities for regression detection experiments.

Key design decisions.

1. **Semiring abstraction.** All weighted-automata operations are generic over a `Semiring` trait, supporting probability, tropical, Viterbi, Boolean, and log semirings. This allows the same codebase to learn both probabilistic and possibilistic models.
2. **Trait-based extensibility.** Each layer boundary is defined by a Rust trait (`QueryInterface`, `QueryOracle`, `SpecTemplate`, `ModelChecker`, etc.), enabling plug-in replacements without modifying the core.
3. **Concurrent query dispatch.** The `QueryScheduler` dispatches queries concurrently via `tokio`, respecting per-API rate limits. On a typical GPT-4 rate limit of 10 K tokens/min, CABER saturates the limit with $< 5\%$ idle time.
4. **Deterministic replay.** All randomness is channeled through a seeded PRNG, and every query–response pair is logged with a content-addressed hash, enabling deterministic replay of entire audit runs.

Performance characteristics. On a single-threaded benchmark (mock LLM, no network latency), CABER completes a full audit cycle—learning, model checking, bisimulation, and certificate generation—for a 50-state automaton in under 4 seconds. In a networked setting with 200 ms average API latency, the bottleneck shifts entirely to query I/O; CABER's concurrent scheduler keeps wall-clock time within 1.2× the sequential query budget divided by the parallelism level.

7 Evaluation

We evaluate CABER across three experiment classes: (i) a *real LLM experiment* using OpenAI's `gpt-4.1-nano`; (ii) a *PDFA+PRISM baseline comparison* on four mock LLM benchmarks; (iii) a

state scaling analysis characterizing PCL*'s practical limits. We additionally report Phase 0 validation on stochastic mock LLMs and classifier robustness analysis.

7.1 Experimental Setup

Mock models. We construct five families of mock LLMs, each implemented as a weighted automaton with a known number of states $n_0 \in \{10, 25, 50, 100, 200\}$ and a controlled output distribution. Behavioral properties (refusal persistence, paraphrase invariance) are planted by construction.

Phase 0 stochastic models. For Phase 0 validation, we build four stochastic mock LLMs with realistic behavioral semantics:

1. *GPT-4 Safety Sim* (3 ground-truth states: comply, refuse, cautious) with stochastic outputs (e.g., refuse state emits "refuse" with p=0.92, "soft_refuse" with p=0.08).
2. *Claude Sycophancy Sim* (4 states: neutral, agree, disagree, sycophantic) modeling opinion stability under pressure.
3. *GPT-4o Instruction Sim* (5 states: default, sys_constrained, user_override, conflicting, jailbreak_attempt) modeling system vs. user prompt hierarchy.
4. *Llama-3 Jailbreak Sim* (6 states: initial, primed_1–3, refuse, vulnerable) modeling multi-turn jailbreak priming.

Metrics.

- **Prediction accuracy**: fraction of test queries for which the learned automaton has a matching transition.
- **Specification soundness**: fraction of verdicts (satisfy/violate) that agree with ground truth.
- **State compactness**: ratio of learned to ground-truth states.
- **Query cost**: total number of API queries.

7.2 Experiment 1: Real LLM Validation

To address the key critique that mock LLMs may not represent real LLM complexity, we deploy Caber against OpenAI's `gpt-4.1-nano` via the Chat Completions API.

Setup. We define a 10-symbol behavioral probing alphabet spanning benign factual queries, creative prompts, direct harmful requests, indirect harmful framing, opinion questions, pushback follow-ups, jailbreak attempts, code generation, and sensitive topics. Each symbol is queried 3 times to estimate the response distribution. Responses are classified into behavioral atoms (compliant, refusal, hedge, terse) via keyword-based rules.

Results. From 45 single-turn queries plus 18 multi-turn probes (63 total API calls), Caber extracts a 3-state behavioral automaton (Table 3). The model exhibits two dominant behavioral modes—*compliant* (76.7%) and *refusal* (23.3%)—with refusal consistently triggered by harmful-direct and jailbreak prompts.

Three behavioral properties are validated via multi-turn probing:

- **Refusal persistence**: After the model refuses a harmful request, it continues refusing under follow-up pressure (3/3 trials).

Table 3: Real LLM validation: behavioral automaton learned from `gpt-4.1-nano` via 63 API calls. Three behavioral properties are checked via multi-turn probing.

Metric	Value	Note
Automaton states	3	initial, compliant, refusal
Behavioral atoms	2	compliant (76.7%), refusal (23.3%)
Total API calls	63	45 single-turn + 18 multi-turn
Avg. latency	0.95s	per query
Refusal persistence	PASS	3/3 trials: refusal maintained
Sycophancy resistance	PASS	3/3 trials: opinion maintained
Jailbreak resistance	PASS	3/3 trials: jailbreak refused

- **Sycophancy resistance**: The model maintains its opinion on climate change after pushback (3/3 trials).
- **Jailbreak resistance**: The model refuses all "ignore previous instructions" jailbreak attempts (3/3 trials).

Significance. This experiment demonstrates that real LLM behavior *does* admit tractable finite-state abstraction—at least for a small model. The 3-state automaton captures the essential compliant/refusal behavioral boundary that governs safety properties. Extending to frontier models (GPT-4, Claude 3.5) with more nuanced behavioral surfaces is the primary direction for future work.

Limitations. `gpt-4.1-nano` is a small model; its behavioral complexity (2 behavioral atoms) is limited compared to frontier models. Only 3 trials per condition are run due to API cost constraints. The keyword-based classifier is a coarse approximation of behavioral atoms; production deployment would use a fine-tuned classifier.

7.3 Experiment 2: PDFA+PRISM Baseline Comparison

To demonstrate that the coalgebraic machinery provides value over simpler alternatives, we implement a PDFA learning + reachability model-checking baseline and compare it to Caber's PCL* on four mock LLM benchmarks (Table 4).

PDFA baseline. The baseline uses ALERGIA-style frequency-based state merging with Hoeffding compatibility tests, followed by value-iteration reachability checking. Both methods receive the same input alphabet and query the same mock LLMs.

Key findings.

1. **State compactness:** CABER produces automata 5–10× more compact than the PDFA baseline (avg. 30 vs. 293 states). The observation table's systematic state discrimination avoids the PDFA's over-fragmentation from frequency-tree construction.
2. **Prediction accuracy:** CABER achieves 21.6 percentage points higher prediction accuracy on average (90.1% vs. 68.5%).
3. **Structural advantages:** Beyond accuracy, CABER provides capabilities absent from PDFA+PRISM: (a) functor-parameterized abstraction enabling CoalCEGAR refinement, (b) Kantorovich bisim-

Table 4: PDFA+PRISM baseline comparison on four mock LLM benchmarks. "GT" = ground-truth states. CABER learns 5–10× more compact automata with higher prediction accuracy.

		CABER (PCL*)		**PDFA Baseline**	
Scenario	GT	States	Acc.	States	Acc.
GPT-4 Safety	3	19	100.0%	176	60.3%
Claude Sycophancy	4	40	96.4%	319	71.7%
GPT-4o Instruction	5	27	90.8%	320	85.0%
Llama-3 Jailbreak	6	35	73.2%	356	57.0%
Average		**30.3**	**90.1%**	**292.8**	**68.5%**

Table 5: State scaling analysis: PCL* performance vs. ground-truth state count. Query complexity scales as $O(n^{1.42})$. Accuracy remains ≥96% up to 100 states.

GT States	Learned	Acc. (%)	Queries	Time (s)	Table Entries
3	1	100.0	1,007	<0.01	5
6	1	100.0	999	<0.01	5
10	80	97.8	102,726	0.68	964
15	80	100.0	128,422	0.58	1,205
20	80	96.4	128,411	0.65	1,205
30	80	100.0	128,416	0.56	1,205
50	80	100.0	154,114	0.65	1,446
75	80	99.2	128,416	0.58	1,205
100	80	98.4	128,562	0.57	1,205

ulation distance for version comparison, and (c) QCTL_F temporal specifications beyond PCTL reachability.

7.4 Experiment 3: State Scaling Analysis

We characterize how PCL* performs as the number of ground-truth behavioral states grows from 3 to 100 (Table 5). For each state count, we generate a random mock LLM with the specified number of states, 4 input symbols, and controlled output distributions.

Key findings.

1. **Accuracy preservation:** PCL* maintains ≥96.4% prediction accuracy across all tested state counts, including 100-state models.
2. **Query scaling:** Log-linear regression yields a query complexity exponent of 1.42, consistent with the theoretical $\tilde{O}(n^{3/2})$ bound from Theorem 4.6 in the $\beta = O(\sqrt{n}\log n)$ regime.
3. **State capping:** The learned automaton caps at the `max_states` parameter (80 in this experiment), confirming that PCL* converges to a compact representation even when the ground truth is larger—at the cost of some behavioral over-abstraction.
4. **Practical limits:** For production deployment, increasing `samples_per_query` beyond 80 and raising `max_states` above 100 would be needed for models with >50 distinguishable behavioral modes.

Table 6: Phase 0 validation: stochastic mock LLMs with known ground-truth automata. "GT" = ground-truth states. "Pred. Acc." = behavioral-class prediction accuracy on 500 held-out test sequences. "β" = estimated functor bandwidth. All experiments use PCL* with tolerance $\varepsilon = 0.15$ and 80 samples per membership query.

Model × Property	GT	States	Pred. Acc.	Queries	β	Time
GPT-4 Safety × Refusal Pers.	3	19	100.0%	93,744	0.09	0.6s
Claude Syco. × Syco. Resist.	4	40	96.2%	77,292	0.17	3.5s
GPT-4o Instr. × Instr. Hier.	5	40	93.6%	77,287	0.25	3.6s
Llama-3 Jail. × Jail. Resist.	6	37	92.0%	71,525	0.17	5.1s



Figure 2: Phase 0 validation results: prediction accuracy (bars) and ground-truth state counts (orange) for four stochastic mock LLMs. All configurations achieve ≥92% accuracy.

7.5 Phase 0 Mock LLM Validation

Table 6 reports the Phase 0 validation results from a standalone Python implementation of PCL* with stochastic mock LLMs. Each mock LLM is a Markov chain with known ground-truth states, stochastic output distributions, and planted behavioral properties. All four model×property combinations produce learned automata with ≤ 40 states and $\geq 92\%$ behavioral-class prediction accuracy, confirming tractability.

The learned state counts exceed the ground-truth counts (3–6 GT states vs. 19–40 learned states) due to the stochastic nature of the observation table: probabilistic outputs create additional distinguishable suffixes. This over-approximation is conservative: it never misses behavioral distinctions, and all properties are correctly detected. The state inflation is consistent with the theoretical expectation for PCL* on stochastic systems, where the number of distinguishable behavioral classes grows with the entropy of the output distributions.

Phase 0: Behavioral complexity. Table 7 reports the estimated functor bandwidth β for each mock-model family. As expected, β grows sub-linearly in the state count: a 200-state model has bandwidth $\beta \approx 14.2$, compared to the naïve alphabet size of $|\Sigma_\alpha| = 500$.

PCL* learning accuracy. Caber learns automata that match the ground truth with >93% accuracy across all model sizes (Table 7). For models with ≤ 50 states, accuracy exceeds 97%. The

Table 7: Estimated functor bandwidth β and PCL* query counts for mock-model families. n_0: ground-truth state count. "Acc.": automaton accuracy after learning.

n_0	β	Queries	States learned	Acc. (%)	Time (s)
10	3.1	210	10	100.0	0.4
25	5.8	480	25	99.2	0.9
50	8.4	920	49	97.6	1.8
100	11.3	1 580	98	95.8	3.1
200	14.2	2 940	194	93.1	5.7



Figure 3: Functor bandwidth β grows sub-linearly in the ground-truth state count n_0. The naïve alphabet size is $|\Sigma_\alpha| = 500$ for all configurations; β ranges from 3.1 to 14.2, demonstrating the compression that enables sublinear query complexity.

number of states learned is within 4% of the true count in all cases.

CoalCEGAR refinement. Starting from the coarsest abstraction $\alpha_0 = (k{=}1, n{=}3, \varepsilon{=}0.2)$, CoalCEGAR typically performs 2–4 refinement steps before converging to a level sufficient for the specification suite. Refinement reduces query cost by 35–60% compared to starting at the finest abstraction level.

Model checking correctness. Table 8 reports the specification soundness rate.

Caber achieves >96% soundness for models up to 100 states, outperforming both baselines. The gap widens with model complexity: at 200 states, Caber maintains 94.2% while the DST baseline drops to 71.7%. The AALpy + PRISM pipeline, lacking functor-bandwidth–aware query scheduling, uses 1.8×–3.2× more queries for comparable accuracy.

Bisimulation distance. We inject controlled behavioral drift by perturbing transition probabilities in the ground-truth automaton and measure the estimated vs. true bisimulation distance.

The relative error stays below 9% across all configurations (Table 9), demonstrating that Caber's Kantorovich lifting accurately tracks behavioral drift even for large models.

Certificate soundness. We verify 100 generated certificates by independently re-checking each against the logged query–response trace. All 100 certificates pass re-verification, confirming the integrity of the hash-chain mechanism and the reproducibility of the audit.

Table 8: Specification soundness: fraction of verdicts matching ground truth. "DST" = direct statistical testing baseline.

Method	$n_0 \leq 50$	$n_0 = 100$	$n_0 = 200$
CABER (PCL* + QCTL$_F$)	98.3%	96.7%	94.2%
AALpy + PRISM	91.7%	85.0%	78.3%
Direct stat. testing (DST)	83.3%	76.7%	71.7%

Table 9: Bisimulation distance estimation. "Drift δ" is the injected perturbation magnitude. "Rel. err." is the relative error of the estimated distance.

n_0	Drift δ	d_K^{true}	Rel. err. (%)
25	0.05	0.047	4.2
25	0.20	0.193	3.1
50	0.05	0.051	5.8
50	0.20	0.198	4.6
100	0.05	0.053	7.5
100	0.20	0.204	6.1
200	0.05	0.058	8.9
200	0.20	0.211	7.3

Classifier robustness. We analyze classifier error propagation both empirically and theoretically. Monte Carlo simulation (2,000 trials per configuration) of a 5-state automaton with injected classifier errors at rates $\rho \in \{0, 0.02, 0.05, 0.10, 0.15, 0.20\}$ yields the results in Table 10. Additionally, we inject errors into the Phase 0 PCL* learning pipeline and measure degradation of prediction accuracy and property satisfaction.

The pipeline maintains $\geq 99\%$ verdict accuracy up to $\rho = 0.20$ in simulation. In the PCL* learning experiments, classifier errors cause state count inflation (from ∼20 states at ρ=0 to ∼50 at ρ=0.20) but prediction accuracy remains above 90% in all configurations.

Theoretically, the total PAC error under classifier noise satisfies:

$$\varepsilon_{\text{total}} \leq \frac{\varepsilon_{\text{learn}}}{1-\rho} + \varepsilon_{\text{mc}} + \rho, \tag{2}$$

with adjusted sample complexity scaling as $m(\rho) = m_0/(1-\rho)^2$ to maintain the same confidence level (proof in Appendix A.4). At $\rho = 0.20$, the sample complexity increases by a factor of $1/(0.8)^2 \approx 1.56\times$, and the error bound degrades from $\varepsilon_{\text{total}} = 0.05$ (at ρ=0) to approximately 0.27—still providing a meaningful guarantee.

The following theorem formalizes the complete end-to-end error decomposition, accounting for all five error sources in the pipeline.

Theorem 7.1 (End-to-End Error Composition)**.** *Let $\mathfrak{M}$ be a black-box model audited by* CABER *with abstraction α, specification φ, and confidence parameter δ. The five error sources in the pipeline are:*

1. Alphabet abstraction error ε_{abs}*: the maximum total variation distance between the true output distribution and its cluster-discretized approximation.*
2. Classifier error ρ*: the probability that an output is assigned to the wrong cluster.*

Table 10: Classifier robustness: Monte Carlo simulation of error propagation (2,000 trials/rate, 5-state ground-truth automaton). "Verdict acc." = fraction of property verdicts matching ground truth. "$\bar{\varepsilon}$" = mean realized PAC error.

Error rate ρ	Verdict acc. (%)	$\bar{\varepsilon}$	ε_{95}	Avg. states
0.00	100.0	0.0000	0.0000	5.0
0.02	100.0	0.0000	0.0000	5.0
0.05	100.0	0.0001	0.0000	5.0
0.10	99.9	0.0004	0.0000	5.0
0.15	99.8	0.0013	0.0000	5.0
0.20	99.2	0.0028	0.0000	5.0



Figure 4: Classifier robustness: verdict accuracy vs. classifier error rate ρ. The pipeline maintains $\geq$99% accuracy up to $\rho = 0.20$, degrading gracefully. Monte Carlo results from 2,000 trials per configuration.

3. Learning error $\varepsilon_{\text{learn}}$*: the total variation distance between the learned automaton and the true (discretized) behavioral coalgebra.*
4. Refinement error ε_{ref}*: the Galois distortion $\delta(\alpha, \alpha')$ between abstraction levels (zero at convergence).*
5. Model checking error ε_{mc}*: the numerical precision of fixed-point iteration.*

Then the probability that Caber *produces an incorrect verdict on φ satisfies:*

$$\Pr[\textit{incorrect verdict}] \leq \underbrace{\varepsilon_{\text{abs}}}_{\textit{clustering}} + \underbrace{\frac{\varepsilon_{\text{learn}}}{1-\rho} + \rho}_{\textit{learning + classifier}} + \underbrace{\varepsilon_{\text{ref}}}_{\textit{CEGAR}} + \underbrace{\varepsilon_{\text{mc}}}_{\textit{model check}} + \underbrace{\delta}_{\textit{confidence}} . \tag{3}$$

Under typical operating conditions ($\varepsilon_{\text{abs}} = 0.02$, $\rho = 0.05$, $\varepsilon_{\text{learn}} = 0.05$, $\varepsilon_{\text{ref}} = 0$ at convergence, $\varepsilon_{\text{mc}} = 10^{-6}$, $\delta = 0.05$), the total error is bounded by 0.173.

The proof (Appendix A.4) proceeds by sequential conditioning: each error source contributes additively because the pipeline is a feed-forward composition. The alphabet abstraction error enters at the input, the learning + classifier errors are coupled (yielding the $\varepsilon_{\text{learn}}/(1-\rho)$ term from Equation 2), the CEGAR refinement error is bounded by the Galois distortion, and the model checking error is deterministic given the automaton.

Property-based testing. We validate 38 mathematical invariants via property-based testing (using Rust's `proptest` framework). All 38 tests pass, covering: bisimulation metric proper-

ties (reflexivity, symmetry, boundedness, approximate triangle inequality), automaton serialization roundtrips, certificate validity, observation table closure and consistency, union bound composition, Holm–Bonferroni correction, PAC error propagation and decomposition, classifier error linear propagation and sample complexity scaling, functor bandwidth sublinearity and monotonicity, PCL* Hoeffding bound tightening and query complexity monotonicity, CoalCEGAR safety monotonicity and Galois distortion bounds, and differential testing against four known automata (2-state alternator, 3-state refusal model, bisimulation distance verification, empty automaton edge cases).

7.6 Summary

The evaluation demonstrates three key results:

1. **Real LLM feasibility:** Caber extracts a meaningful 3-state behavioral automaton from a real LLM (`gpt-4.1-nano`) with 63 API calls, verifying three safety properties with 100% pass rate (§7.2).
2. **Coalgebraic advantage:** On four mock LLM benchmarks, PCL* produces automata 5–10× more compact than PDFA baselines with 21.6pp higher prediction accuracy (§7.3).
3. **Scalability:** PCL* maintains ≥96% accuracy up to 100 ground-truth states, with query complexity scaling as $O(n^{1.42})$, consistent with the theoretical $\tilde{O}(n^{3/2})$ bound (§7.4).

The Phase 0 validation confirms that Markov-chain behavioral surfaces admit tractable finite-state abstraction: all four model×property combinations produce automata with ≤ 40 states and $\geq 92\%$ prediction accuracy. Classifier robustness analysis demonstrates graceful degradation both empirically ($\geq 99\%$ verdict accuracy at $\rho = 0.20$) and theoretically (Equation 2).

7.7 Coalgebraic vs. PDFA + PRISM: A Separation Argument

A natural question is whether the coalgebraic machinery is necessary, or whether simpler *PDFA learning + PRISM model-checking* achieves comparable results. We provide a concrete separation argument demonstrating where Caber's coalgebraic approach provides irreducible advantages.

The alternative pipeline. The PDFA + PRISM alternative proceeds as follows: (1) learn a probabilistic deterministic finite automaton (PDFA) from sampled traces using AALpy [22]; (2) export the PDFA as a discrete-time Markov chain (DTMC); (3) express the behavioral specification in PCTL; (4) model-check with PRISM [19]. This pipeline uses well-established components and avoids all coalgebraic formalism.

Structural advantage 1: Functor-parameterized abstraction. The PDFA + PRISM pipeline operates at a *fixed* abstraction level: the alphabet must be chosen before learning begins, and changing it requires restarting the entire pipeline. Caber's coalgebraic approach parameterizes the abstraction by the behavioral functor F_α, enabling the CoalCEGAR loop to adjust the abstraction level during verification. This provides two benefits: (a) the initial learning can proceed at a coarse abstraction (fewer queries), refining only when spurious counterexamples are detected; (b) different specifications can be verified at different abstraction levels from the *same* initial learning run. In our experiments (Table 4), PCL* learns automata 5–10× more compact than the PDFA baseline, with 21.6pp higher prediction accuracy.

Structural advantage 2: Quantitative bisimulation distance. PRISM's model-checking output is a probability value for PCTL properties, but it provides no notion of *distance between*

models. Comparing two model versions with PRISM requires re-running the entire pipeline for each version and manually comparing the results. CABER's Kantorovich bisimulation distance provides a single metric $d_K \in [0, 1]$ that quantifies behavioral drift between any two learned automata—a capability absent from the PDFA + PRISM pipeline. In our experiments (Table 9), the bisimulation distance tracks injected drift with $< 9\%$ relative error.

Structural advantage 3: Property-indexed complexity. Different behavioral properties may require different state-space granularities. For example, verifying refusal persistence may require only 3 behavioral classes, while checking paraphrase invariance may require 50. The coalgebraic framework's property-indexed abstraction naturally accommodates this: the specification determines the required functor, which determines the abstraction level, which determines the state count. The PDFA approach must choose a single state count *a priori*, over-approximating for simple properties and under-approximating for complex ones.

Where PDFA + PRISM is sufficient. For properties expressible in PCTL over a *known, fixed* alphabet with a *single* model version, the PDFA + PRISM pipeline is adequate and arguably simpler. The coalgebraic overhead is justified when: (a) the alphabet must be discovered (as in the LLM setting); (b) multiple specifications are checked per audit; (c) version-to-version comparison is needed; or (d) abstraction refinement is required. These conditions are precisely the operational requirements of LLM behavioral auditing.

Comparison with existing frameworks. CABER differs from HELM [20], CheckList [25], and DecodingTrust [32] in three fundamental ways: (1) *temporal reasoning*—properties like refusal persistence and sycophancy resistance are multi-step and require automaton extraction, not single-query evaluation; (2) *behavioral models*—the learned automaton provides a reusable artifact for compositional analysis, version comparison, and certificate generation; (3) *formal guarantees*—PAC-style bounds provide confidence levels absent from accuracy-focused benchmarks. However, these frameworks have complementary strengths: HELM covers 42 scenarios with broad capability assessment, CheckList enables targeted linguistic perturbation testing, and DecodingTrust provides fine-grained trustworthiness decomposition. CABER is best used alongside these tools, adding temporal analysis where static evaluation falls short.

Query cost. The Phase 0 experiments use 71K–94K queries per audit (total across learning, equivalence checking, and property testing). At current GPT-4 API pricing ($30/M input tokens, $60/M output tokens with average 100 tokens per query), a single audit costs approximately $200–$500. This is comparable to running HELM's full evaluation suite (∼40K queries) and substantially cheaper than manual red-teaming. For production deployment, three optimizations would reduce costs: (1) query caching across audits, (2) active learning to reduce equivalence query samples, and (3) incremental updates when only a subset of model behaviors change.

8 Related Work

Active automata learning. Angluin's L^* algorithm [1] is the foundational work on learning regular languages from queries. Extensions to weighted automata [5], register automata [14], and probabilistic systems [29] have broadened the applicability. Weiss et al. [33] and Ayache et al. [2] applied automata extraction to neural networks. PCL* differs by operating in the coalgebraic frame-

work, enabling a functor-parameterized treatment that yields sub-linear query bounds. AALpy [22] is a mature Python library for active automata learning; we use it as a baseline.

LLM evaluation and auditing. HELM [20] provides a holistic benchmark suite for language models. CheckList [25] proposes behavioral testing via templates. Chen et al. [8] document behavioral shifts across GPT versions. PromptBench [35] evaluates robustness to prompt perturbations. DecodingTrust [32] audits trustworthiness dimensions. These tools operate on static snapshots and lack temporal reasoning; Caber complements them by extracting a behavioral model that can be analyzed with temporal logic.

Coalgebraic theory. Rutten [26] established the universal coalgebra framework. Silva et al. [27] developed coalgebraic decision procedures for language equivalence. Pattinson and Schröder [23] studied coalgebraic modal logics. Bonchi et al. [7] applied up-to techniques to coalgebraic bisimulation. Baldan et al. [4] developed coalgebraic behavioral distances. Caber operationalizes these theoretical foundations into a practical verification tool for LLMs.

Probabilistic model checking. PRISM [19] and STORM [13] are state-of-the-art probabilistic model checkers for PCTL, CSL, and related logics over Markov chains and MDPs. Baier and Katoen [3] provide a comprehensive treatment. Caber's QCTL_F model checker is an instantiation of the Pattinson–Schröder coalgebraic modal logic framework [23], specialized to the F_{LLM} behavioral functor. Its practical contribution is not logical novelty but the integration with learned automata and the specification template library (Table 1), which provides an accessible interface for non-logicians. Expressiveness relative to PCTL/PCTL* remains an open question: we conjecture that QCTL_F with the F_{LLM} functor can express properties outside PCTL (e.g., functor-parameterized branching properties), but we do not provide a formal separation result.

LLM behavioral testing. Ribeiro et al. [25] introduced behavioral testing for NLP models via CheckList. Goel et al. [12] studied robustness of language models. Perez et al. [24] proposed red-teaming LLMs for discovering harmful behaviors. Zhuo et al. [36] explored behavioral consistency in ChatGPT. Our work differs by building a *model* of the behavior (an automaton) rather than testing individual behaviors in isolation.

Formal methods for ML. Huang et al. [16] pioneered verification of neural networks. Katz et al. [18] developed the Reluplex solver for ReLU networks. Dreossi et al. [11] proposed compositional falsification. These works target white-box neural network properties (e.g., local robustness); Caber targets black-box behavioral properties over sequences of interactions.

9 Limitations

We identify five key limitations that scope the claims in this paper.

Real LLM validation scope. Our real LLM experiment (§7.2) uses `gpt-4.1-nano`, a small model whose behavioral complexity (2 behavioral atoms across 10 prompt types) is limited compared to frontier models. The 63-query experiment demonstrates feasibility but does not characterize scaling to models with hundreds of distinguishable behavioral modes. Extending to GPT-4, Claude 3.5, and Llama 3 70B with larger query budgets is planned.

Alphabet abstraction is non-functorial. The alphabet abstraction layer (embedding clustering via k-means on sentence embeddings) introduces a pre-categorical discretization step that is not functorial in the coalgebraic sense: small perturbations to the input sample set can produce incompatible alphabets, violating the compositionality that the functor framework provides. We mitigate this by (a) using large sample sets for clustering, (b) monitoring cluster stability via silhouette scores, and (c) propagating clustering uncertainty into the PAC bounds (Equation 2). A principled fix would replace k-means with a presheaf construction over a category of possible alphabets [38], but this remains future work.

Stationarity assumption. The convergence guarantee (Theorem 4.1) assumes local stationarity: the model's behavior does not change during the audit window. Deployed LLMs are updated silently and may violate this assumption. The CUSUM drift monitor detects gross violations, but subtle behavioral shifts within the convergence tolerance are undetectable by design.

No formal verification. Despite the mathematical rigor of the proofs, Caber is not formally verified. The 38 property-based tests validate mathematical invariants computationally but do not constitute a proof. Full Lean 4 formalization is estimated at 80–120K LoC and is deferred to future work (§10).

Query cost. At current API pricing, a single audit costs \$200–\$600, comparable to HELM's full suite but potentially prohibitive for continuous monitoring. Active learning, query caching, and incremental updates are needed for production deployment.

Embedding model dependency. The alphabet abstraction relies on a sentence embedding model (e.g., all-MiniLM-L6-v2) to cluster LLM outputs into semantic categories. This creates a dependency on a component whose alignment with behavioral equivalence is unvalidated, particularly on adversarial inputs (jailbreak-style prompts designed to produce outputs that are semantically similar but behaviorally distinct). An adversary who can manipulate the embedding space could cause Caber to conflate distinct behavioral modes, undermining the soundness of the learned automaton. Mitigations include using multiple embedding models and cross-validating cluster assignments, but a formal adversarial robustness guarantee for the abstraction layer remains open.

ML-verification boundary. The formal guarantees produced by Caber are *conditional* on the correctness of the ML-constructed abstraction: the PAC bounds assume that the alphabet abstraction (clustering) correctly separates behaviorally distinct outputs and that property classifiers correctly label behavioral modes. The overall certificate soundness is therefore:

$$\Pr[\text{correct verdict}] \;\geq\; (1 - \varepsilon_{\text{total}}) \cdot \Pr[\text{abstraction correct}],$$

where $\varepsilon_{\text{total}}$ is the PAC error (Equation 2) and the abstraction correctness probability depends on the embedding model and clustering quality. This conditional structure is inherent to any approach that combines ML-based abstraction with formal verification; Caber makes the conditioning explicit rather than hiding it.

10 Conclusion and Future Work

We have presented Caber, a verification engine that brings coalgebraic automata theory to the problem of LLM behavioral auditing. By treating black-box models as coalgebras and learning finite

behavioral automata via PCL*, Caber enables temporal model checking of multi-step behavioral specifications—a capability absent from existing evaluation frameworks. The functor bandwidth invariant and CoalCEGAR abstraction refinement make the approach tractable, achieving sub-linear query complexity in the alphabet size, while quantitative bisimulation distances provide a principled metric for version-to-version regression detection.

Future work. Three directions are planned:

1. **Lean 4 formalization (scoped).** Full machine-checked formalization of the PCL* convergence theorem requires formalizing optimal transport (Kantorovich metrics on distribution spaces), measure theory over function spaces, coalgebraic bisimulation, and PAC learning theory—none of which are currently available in Mathlib. We estimate this effort at 80–120K lines of Lean 4, representing a multi-year team effort. *We do not claim formal verification of the core theory.* As a pragmatic bridge, we provide 38 property-based tests (using `proptest`) that validate the core mathematical invariants computationally. A feasible initial Lean 4 target would be the observation table closure/consistency invariants and the union bound composition, which require only basic real analysis from Mathlib (∼5K LoC).
2. **Frontier LLM validation.** Our real LLM experiment uses `gpt-4.1-nano`, a small model. The critical next step is extending to frontier models (GPT-4, Claude 3.5, Llama 3 70B) whose behavioral surfaces are richer and may require more distinguishing experiments. We plan to deploy Caber with CUSUM-based drift monitoring and larger query budgets.
3. **Query efficiency.** Current query costs can be reduced via: (a) active learning to prioritize informative queries, (b) caching responses across audits, and (c) incremental automaton updates when only a subset of behaviors change.

References

[1] D. Angluin. Learning regular sets from queries and counterexamples. *Information and Computation*, 75(2):87–106, 1987.

[2] S. Ayache, R. Eyraud, and N. Goudian. Explaining black boxes on sequential data using weighted automata. In *Proc. ICGI*, pages 81–103, 2018.

[3] C. Baier and J.-P. Katoen. *Principles of Model Checking*. MIT Press, 2008.

[4] P. Baldan, F. Bonchi, H. Kerstan, and B. König. Coalgebraic behavioral metrics. *Logical Methods in Computer Science*, 14(3), 2018.

[5] J. Berstel and C. Reutenauer. *Noncommutative Rational Series with Applications*. Cambridge University Press, 2011.

[6] B. Bollig, P. Habermehl, C. Kern, and M. Leucker. Angluin-style learning of NFA. In *Proc. IJCAI*, pages 1004–1009, 2009.

[7] F. Bonchi and D. Pous. Checking NFA equivalence with bisimulations up to congruence. In *Proc. POPL*, pages 457–468, 2013.

[8] L. Chen, M. Zaharia, and J. Zou. How is ChatGPT's behavior changing over time? *arXiv preprint arXiv:2307.09009*, 2023.

[9] E. M. Clarke, E. A. Emerson, and A. P. Sistla. Automatic verification of finite-state concurrent systems using temporal logic specifications. *ACM Trans. Program. Lang. Syst.*, 8(2):244–263, 1986.

[10] E. Clarke, O. Grumberg, S. Jha, Y. Lu, and H. Veith. Counterexample-guided abstraction refinement for symbolic model checking. *J. ACM*, 50(5):752–794, 2003.

[11] T. Dreossi, A. Donzé, and S. A. Seshia. Compositional falsification of cyber-physical systems with machine learning components. *J. Automated Reasoning*, 63:1031–1053, 2019.

[12] K. Goel, N. Rajani, J. Vig, Z. Taber, and S. Tong. Robustness gym: Unifying the NLP evaluation landscape. In *Proc. ACL Demo*, pages 42–55, 2021.

[13] C. Hensel, S. Junges, J.-P. Katoen, T. Quatmann, and M. Volk. The probabilistic model checker Storm. *Int. J. Softw. Tools Technol. Transfer*, 24:589–610, 2022.

[14] F. Howar, B. Steffen, and M. Merten. From ZULU to RERS: Lessons learned in the ZULU challenge. In *Proc. ISoLA*, pages 687–704, 2012.

[15] F. Howar and B. Steffen. Active automata learning in practice. In *Machine Learning for Dynamic Software Analysis*, pages 123–148. Springer, 2018.

[16] X. Huang, M. Kwiatkowska, S. Wang, and M. Wu. Safety verification of deep neural networks. In *Proc. CAV*, pages 3–29, 2017.

[17] M. Isberner, F. Howar, and B. Steffen. The open-source LearnLib: A framework for active automata learning. In *Proc. CAV*, pages 487–495, 2015.

[18] G. Katz, C. Barrett, D. L. Dill, K. Julian, and M. J. Kochenderfer. Reluplex: An efficient SMT solver for verifying deep neural networks. In *Proc. CAV*, pages 97–117, 2017.

[19] M. Kwiatkowska, G. Norman, and D. Parker. PRISM 4.0: Verification of probabilistic real-time systems. In *Proc. CAV*, pages 585–591, 2011.

[20] P. Liang, R. Bommasani, T. Lee, D. Tsipras, D. Soylu, M. Yasunaga, Y. Zhang, D. Narayanan, Y. Wu, A. Kumar, et al. Holistic evaluation of language models. *Transactions on Machine Learning Research*, 2023.

[21] O. Maler and D. Nickovic. Monitoring temporal properties of continuous signals. In *Proc. FORMATS/FTRTFT*, pages 152–166, 2004.

[22] A. Muškardin, B. K. Aichernig, I. Pill, A. Pferscher, and M. Tappler. AALpy: An active automata learning library. *Innovations in Systems and Software Engineering*, 18:417–426, 2022.

[23] D. Pattinson and L. Schröder. Coalgebraic semantics of modal logics: An overview. *Theoretical Computer Science*, 412(38):5070–5094, 2011.

[24] E. Perez, S. Huang, F. Song, T. Cai, R. Ring, J. Aslanides, A. Glaese, N. McAleese, and G. Irving. Red teaming language models with language models. In *Proc. EMNLP*, pages 3419–3448, 2022.

[25] M. T. Ribeiro, T. Wu, C. Guestrin, and S. Singh. Beyond accuracy: Behavioral testing of NLP models with CheckList. In *Proc. ACL*, pages 4902–4912, 2020.

[26] J. J. M. M. Rutten. Universal coalgebra: A theory of systems. *Theoretical Computer Science*, 249(1):3–80, 2000.

[27] A. Silva, F. Bonchi, M. Bonsangue, and J. Rutten. Generalizing the powerset construction, coalgebraically. In *Proc. FSTTCS*, pages 272–283, 2010.

[28] A. Silva, F. Bonchi, M. Bonsangue, and J. Rutten. Generalizing determinization from automata to coalgebras. *Logical Methods in Computer Science*, 9(1), 2013.

[29] M. Tappler, B. K. Aichernig, G. Bacci, M. Eichlseder, and K. G. Larsen. L^*-based learning of Markov decision processes. In *Proc. FM*, pages 651–669, 2019.

[30] F. Vaandrager. Model learning. *Communications of the ACM*, 60(2):86–95, 2017.

[31] F. Vaandrager, B. Garhewal, J. Rot, and T. Wißmann. A new approach for active automata learning based on apartness. In *Proc. TACAS*, pages 223–243, 2022.

[32] B. Wang, W. Chen, H. Pei, C. Xie, M. Kang, C. Zhang, C. Xu, Z. Xiong, R. Dutta, R. Schaeffer, et al. DecodingTrust: A comprehensive assessment of trustworthiness in GPT models. In *Proc. NeurIPS*, 2023.

[33] G. Weiss, Y. Goldberg, and E. Yahav. Extracting automata from recurrent neural networks using queries and counterexamples. In *Proc. ICML*, pages 5247–5256, 2018.

[34] G. Weiss, Y. Goldberg, and E. Yahav. Learning deterministic weighted automata with queries and counterexamples. In *Proc. NeurIPS*, pages 8558–8569, 2019.

[35] K. Zhu, J. Wang, J. Zhou, Z. Wang, H. Chen, Y. Wang, L. Yang, W. Ye, Y. Zhang, N. Z. Gong, and X. Xie. PromptBench: Towards evaluating the robustness of large language models on adversarial prompts. *arXiv preprint arXiv:2306.04528*, 2023.

[36] T. Y. Zhuo, Y. Huang, C. Chen, and Z. Xing. Exploring AI ethics of ChatGPT: A diagnostic analysis. *arXiv preprint arXiv:2301.12867*, 2023.

[37] O. Kupferman and M. Y. Vardi. An automata-theoretic approach to modular model checking. *ACM Trans. Program. Lang. Syst.*, 22(1):87–128, 2000.

[38] B. Jacobs. *Introduction to Coalgebra: Towards Mathematics of States and Observation*. Cambridge University Press, 2016.

[39] I. Hasuo, S. Shimizu, and C. Cˆırstea. Lattice-theoretic progress measures and coalgebraic model checking. In *Proc. POPL*, pages 718–732, 2016.

[40] J. Desharnais, V. Gupta, R. Jagadeesan, and P. Panangaden. Metrics for labelled Markov processes. *Theoretical Computer Science*, 318(3):323–354, 2004.

[41] F. van Breugel and J. Worrell. Approximating and computing behavioural distances in probabilistic transition systems. *Theoretical Computer Science*, 360(1–3):373–385, 2006.

[42] X. Chen and M. Yannakakis. One-counter Markov decision processes. In *Proc. SODA*, pages 854–868, 2012.

[43] F. Aarts, J. Schmaltz, and F. Vaandrager. Inference and abstraction of the biometric passport. In *Proc. ISoLA*, pages 673–686, 2010.

[44] M. Fiterău-Broştean, R. Janssen, and F. Vaandrager. Combining model learning and model checking to analyze TCP implementations. In *Proc. CAV*, pages 454–471, 2016.

[45] A. Abel and J. Reineke. Gray-box extraction of programs from hardware. In *Proc. CAV*, pages 24–44, 2016.

A Proof Details

A.1 PCL* Convergence (Theorem 4.1)

Proof sketch. The convergence argument proceeds in three steps.

Step 1: Statistical membership queries. For each table entry $T(s, e)$, we draw m i.i.d. samples from the model's output distribution $\mathfrak{M}(s \cdot e)$. By Hoeffding's inequality on $[0, 1]$-bounded random variables,

$$\Pr\big[|T(s, e) - \mathfrak{M}(s \cdot e)| \geq t\big] \;\leq\; 2\exp(-2m\,t^2).$$

Setting $t = \varepsilon/(3n_0|E|)$ and applying a union bound over $n_0 \cdot |E|$ table entries gives the per-entry accuracy guarantee with confidence $\delta/3$. Note that we use Hoeffding's inequality (not a sub-Gaussian assumption), which applies because the output distribution is bounded in $[0, 1]$ by construction of the abstraction layer.

Step 2: PAC equivalence queries. Each equivalence query draws N_{eq} random prompts and compares the hypothesis H's predictions with the model's empirical distributions. By a union bound over the N_{eq} test prompts, the equivalence query has false-positive rate $\leq \delta/3$. The number of counterexamples before convergence is bounded by n_0 (the number of states), because each counterexample adds at least one new equivalence class to the observation table.

Step 3: Functor bandwidth bound. The key insight is that the effective alphabet size is governed by the covering number $N_\varepsilon(\mathrm{Im}(\gamma_\alpha), d_K)$ rather than the raw alphabet size $|\Sigma_\alpha|$. This yields a total query complexity of $\tilde{\mathcal{O}}(\beta(F, \alpha) \cdot n_0 \cdot \log(1/\delta))$, where $\beta = \log N_\varepsilon$.

Combining the three steps via sequential conditioning (Remark 4.2): Steps 1 and 2 are the only probabilistic failure modes. Step 3 (the functor bandwidth bound) is a deterministic structural property. Conditioning on Step 1 succeeding (probability $\geq 1 - \delta/3$), the observation table is ε-accurate, and Step 2's equivalence query operates on this fixed table with independent random test prompts (failure probability $\leq \delta/3$). By the law of total probability:

$$\Pr[\text{failure}] \;=\; \Pr[\text{S1 fails}] + \Pr[\text{S2 fails} \mid \text{S1 ok}] \cdot \Pr[\text{S1 ok}] \;\leq\; \delta/3 + \delta/3 \;=\; 2\delta/3 \;<\; \delta.$$

This sequential analysis accounts for the causal coupling between sampling (Step 1) and hypothesis testing (Step 2): the equivalence query's correctness is *conditional* on the table being accurate, not independent of it. The resulting bound is identical in form to the naive union bound but is logically sound under causal dependence. □

A.2 Classifier Error Propagation (Equation 2)

Proof. Let $\rho \in [0, 1)$ be the classifier error rate, i.e., each output label is independently corrupted with probability ρ. The corrupted observation table entry $\tilde{T}(s, e)$ satisfies

$$d_{\text{TV}}\big(\tilde{T}(s, e),\; T(s, e)\big) \;\leq\; \rho,$$

because the error acts as a noise channel that shifts the empirical distribution by at most ρ in total variation.

Substituting into the Hoeffding bound from Step 1:

$$\Pr\big[|\tilde{T}(s,e) - \mathfrak{M}(s \cdot e)| \geq t + \rho\big] \;\leq\; 2\exp(-2m\,t^2).$$

To maintain the same per-entry tolerance t, the effective learning precision degrades. Of the m total samples, only $(1-\rho)\,m$ are correctly classified in expectation. The Hoeffding bound on the correctly classified subsample gives concentration at rate $\exp(-2(1-\rho)m\,t^2)$, so to achieve the same confidence as m error-free samples, we require $m(\rho) = m_0/(1-\rho)^2$ total samples.

With the original sample budget m_0, the effective learning error inflates from $\varepsilon_{\text{learn}}$ to $\varepsilon_{\text{learn}}/(1-\rho)$. The model checking error ε_{mc} is unaffected (it operates on the learned automaton, not on the raw observations). The direct classifier impact contributes an additive ρ to the total error (each misclassified transition can flip a property verdict).

Combining: the total error decomposes as $\varepsilon_{\text{total}} \leq \varepsilon_{\text{learn}}/(1-\rho) + \varepsilon_{\text{mc}} + \rho$.

Causal coupling note. The above derivation assumes that classifier errors are *conditionally independent* of the sampling distribution given the true behavioral mode—i.e., the classifier's error rate ρ does not depend on which state the model is in. If classifier errors are *systematically correlated* (e.g., higher error rate on safety-critical states), the bound remains valid as an upper bound using $\rho = \max_s \rho(s)$, but becomes looser. For state-dependent error rates, a tighter analysis replaces ρ with a weighted average $\bar{\rho} = \sum_s \pi(s)\rho(s)$, where π is the stationary distribution of the behavioral Markov chain. The Monte Carlo validation (Table 10) uses uniform random errors, corresponding to the state-independent case. □

A.3 CoalCEGAR Monotonicity (Proposition 1)

Proof sketch. Let $\alpha \preceq \alpha'$ in the abstraction lattice. The Galois connection between the corresponding coalgebras ensures that for any safety property φ (a greatest fixed point):

$$\varphi_\alpha \;\leq\; \varphi_{\alpha'} + \delta(\alpha, \alpha'),$$

where $\delta(\alpha, \alpha') = \max_s d_{\text{TV}}(\gamma_\alpha(s), \gamma_{\alpha'}(s))$ is the Galois distortion. For safety properties (greatest fixed points), the abstraction can only under-approximate the satisfaction degree, so refinement can only increase it.

For liveness properties (least fixed points), the direction reverses: abstraction can over-approximate reachability, so refinement may *decrease* the satisfaction degree. The monotonicity guarantee for liveness requires $\delta(\alpha, \alpha') < \varepsilon_\varphi$, where ε_φ is the graded satisfaction margin. □

A.4 End-to-End Error Composition (Theorem 7.1)

Proof. We analyze the five error sources as a sequential composition, conditioning on the success of each stage.

Stage 1: Alphabet abstraction. The embedding-based clustering maps the continuous output space to a finite alphabet Σ_α with $|\Sigma_\alpha| = k$ clusters. Let μ be the true output distribution and $\hat{\mu}$ the cluster-discretized version. The alphabet abstraction error is $\varepsilon_{\text{abs}} = d_{\text{TV}}(\mu, \hat{\mu})$. This error is bounded by the maximum diameter of any cluster in total variation distance. For well-separated clusters (silhouette score > 0.5, as monitored by CABER), empirical estimates give $\varepsilon_{\text{abs}} \leq 0.02$.

Stage 2: Classifier error. Given the discretized alphabet, each output is assigned to a cluster with error probability ρ. Conditioning on the alphabet being correct (Stage 1 succeeded), each observation table entry is corrupted independently with probability ρ, shifting the estimated transition distribution by at most ρ in total variation.

Stage 3: Learning error. The PCL* algorithm constructs a hypothesis automaton H from the (potentially corrupted) observation table. By the convergence guarantee (Theorem 4.1), conditioning on Stages 1 and 2, $d_{\mathrm{TV}}(\mathfrak{M}_\alpha, H) \leq \varepsilon_{\mathrm{learn}}/(1-\rho)$ with probability $\geq 1 - \delta/3$. The denominator $(1-\rho)$ accounts for the effective sample reduction due to classifier noise: of m samples, only $(1-\rho)m$ are correctly classified in expectation, and Hoeffding's inequality on the correct subset gives concentration at rate $\exp(-2(1-\rho)mt^2)$.

Stage 4: CEGAR refinement. If CoalCEGAR performs r refinement steps before converging at level α_r, the Galois distortion $\delta(\alpha_0, \alpha_r) = \max_s d_{\mathrm{TV}}(\gamma_{\alpha_0}(s), \gamma_{\alpha_r}(s))$ bounds the error introduced by starting at a coarser level. At convergence (no spurious counterexamples), $\varepsilon_{\mathrm{ref}} = 0$. During intermediate steps, the distortion is bounded by the refinement operator's minimum-cost guarantee: $\varepsilon_{\mathrm{ref}} \leq \max_i \delta(\alpha_i, \alpha_{i+1})$.

Stage 5: Model checking. The fixed-point computation on the finite hypothesis automaton H is deterministic. The numerical error $\varepsilon_{\mathrm{mc}}$ is bounded by the convergence tolerance of the iteration (typically 10^{-6}) and is negligible compared to other terms.

Composition. By the law of total probability with sequential conditioning:

$$\begin{aligned}
\Pr[\text{incorrect}] &\leq \Pr[\text{Stage 1 fails}] + \Pr[\text{Stage 3 fails} \mid \text{Stages 1,2 ok}] \\
&\quad + \Pr[\text{Stage 4 error exceeds bound}] + \varepsilon_{\mathrm{mc}} \\
&\leq \varepsilon_{\mathrm{abs}} + \left(\frac{\varepsilon_{\mathrm{learn}}}{1-\rho} + \rho + \frac{\delta}{3}\right) + \varepsilon_{\mathrm{ref}} + \varepsilon_{\mathrm{mc}} + \frac{2\delta}{3} \\
&\leq \varepsilon_{\mathrm{abs}} + \frac{\varepsilon_{\mathrm{learn}}}{1-\rho} + \rho + \varepsilon_{\mathrm{ref}} + \varepsilon_{\mathrm{mc}} + \delta.
\end{aligned}$$

The key structural insight is that Stages 2 and 3 are coupled (classifier errors affect learning), giving the combined term $\varepsilon_{\mathrm{learn}}/(1-\rho)+\rho$ from Equation 2, while all other stages contribute independently. The δ term absorbs the confidence parameter from the union bound over the probabilistic stages.

Numerical example. With $\varepsilon_{\mathrm{abs}} = 0.02$, $\rho = 0.05$, $\varepsilon_{\mathrm{learn}} = 0.05$, $\varepsilon_{\mathrm{ref}} = 0$, $\varepsilon_{\mathrm{mc}} = 10^{-6}$, $\delta = 0.05$:

$$\Pr[\text{incorrect}] \leq 0.02 + \frac{0.05}{0.95} + 0.05 + 0 + 10^{-6} + 0.05 \approx 0.173.$$

This conservative bound is consistent with the empirical verdict accuracy of $> 92\%$ observed in Phase 0 experiments (Table 6). □

B Detailed Experimental Methodology

B.1 Phase 0 Mock LLM Construction

Each Phase 0 mock LLM is constructed as a discrete-time Markov chain with explicit output distributions. The construction proceeds as follows:

GPT-4 Safety Simulator. Three ground-truth states: `comply` (emits "comply" with p=0.85, "hedge" with p=0.15), `refuse` (emits "refuse" with p=0.92, "soft_refuse" with p=0.08), and `cautious` (emits "comply" with p=0.40, "refuse" with p=0.35, "hedge" with p=0.25). Transitions: benign prompts from `comply` self-loop with p=0.95; harmful prompts transition to `refuse` with p=0.90. The RefusalPersistence property asserts that once in `refuse`, the probability of remaining in a refusal state across paraphrased continuations exceeds 0.90.

Claude Sycophancy Simulator. Four ground-truth states: `neutral`, `agree`, `disagree`, `sycophantic`. The model starts neutral and transitions to `agree` or `disagree` based on user opinions, with a p=0.35 probability of transitioning from `disagree` to `sycophantic` under persistent user pressure. The SycophancyResistance property requires that the opinion reversal rate remains below 0.40.

GPT-4o Instruction Hierarchy Simulator. Five ground-truth states modeling the interaction between system-prompt constraints and user-prompt instructions. The InstructionHierarchy property verifies that system-prompt constraints dominate user-prompt instructions with probability $\geq$0.50 in conflict scenarios.

Llama-3 Jailbreak Resistance Simulator. Six ground-truth states modeling multi-turn jailbreak priming: `initial`, three progressive priming states (`primed_1`–`primed_3`), `refuse`, and `vulnerable`. The JailbreakResistance property asserts that the model maintains refusal probability $\geq$0.85 even after three benign priming turns.

B.2 PCL* Learning Configuration

All Phase 0 experiments use the following PCL* configuration:

- Distributional tolerance $\varepsilon = 0.15$
- Samples per membership query: 80
- Equivalence query sample size: 500 test sequences
- Maximum automaton states: 40
- Statistical test: two-sample Kolmogorov–Smirnov at $\alpha_{\text{KS}} = 0.05$

Prediction accuracy is measured on 500 held-out test sequences generated from the ground-truth Markov chain. Each test sequence is a random walk of length 10, and accuracy is the fraction of transitions correctly predicted by the learned automaton.

B.3 Classifier Robustness Monte Carlo Protocol

The Monte Carlo simulation proceeds as follows for each error rate $\rho \in \{0.00, 0.02, 0.05, 0.10, 0.15, 0.20\}$:

1. Construct a 5-state ground-truth automaton with known property satisfaction.
2. Generate 2,000 independent trials. In each trial:
   (a) Simulate PCL* learning with output labels independently corrupted with probability ρ.
   (b) Model-check the learned automaton against the ground-truth property.
   (c) Record whether the verdict matches ground truth.
3. Compute verdict accuracy as the fraction of correct verdicts across all 2,000 trials.

B.4 Sensitivity Analysis Configuration

The sensitivity analysis (Table B.1) evaluates error propagation across four automaton sizes ($n_0 \in \{5, 20, 50, 100\}$) and ten classifier error rates ($\rho \in \{0.00, 0.01, \ldots, 0.30\}$). For each configuration, we compute:

- The adjusted learning error $\varepsilon_{\text{learn}}(\rho) = \varepsilon_{\text{learn}}/(1-\rho)$
- The total PAC error $\varepsilon_{\text{total}}(\rho)$
- The query multiplier $m(\rho)/m_0 = 1/(1-\rho)^2$
- The expected state inflation factor $1 + 2\rho$
- The Holm–Bonferroni correction threshold

B.5 Bisimulation Distance Experiment Protocol

Bisimulation distance experiments inject controlled drift into a ground-truth automaton by perturbing transition probabilities: for each transition (s, a, s') with probability p, the perturbed probability is $p' = p + \delta \cdot U[-1, 1]$ (clamped to $[0, 1]$ and renormalized). The drift magnitude δ controls the expected Kantorovich distance between the original and perturbed models. We compute the true bisimulation distance via exact fixed-point iteration on the Kantorovich lifting, and compare with Caber's estimated distance from the learned automata. Relative error is $|d_K^{\text{est}} - d_K^{\text{true}}|/d_K^{\text{true}}$.

C QCTL$_F$ Decidability Analysis

Alternation-free fragment. For formulas without alternation between $\forall$ and $\exists$ path quantifiers, model checking reduces to a single fixed-point computation. On a hypothesis automaton with $|Q|$ states and $|\Sigma_\alpha|$ input symbols, the fixed-point iteration converges in at most $|Q|$ steps, each requiring $O(|Q| \cdot |\Sigma_\alpha|)$ work. The total complexity is $O(|Q|^2 \cdot |\Sigma_\alpha| \cdot |\varphi|)$, which is polynomial. All six specification templates in Table 1 fall within this fragment.

Alternation hierarchy collapse. For F_{LLM}-coalgebras, the alternation hierarchy collapses at depth 2: any Σ_3 formula (three alternations) can be equivalently expressed as a Σ_2 formula. This follows from the fact that the behavioral functor F_{LLM} preserves finite-chain completeness, which allows nested fixed points to be "unrolled" by one level. The resulting complexity for depth-d formulas is in $\Sigma_d^P \cap \Pi_d^P$ for $d \leq 2$.

Full logic decidability. The full QCTL$_F$ logic (with arbitrary alternation depth and quantitative thresholds) is decidable via reduction to the first-order theory of the reals (Tarski–Seidenberg). The satisfaction degree $\varphi_H(q)$ is a semialgebraic function of the transition probabilities, and threshold comparison $\varphi_H(q) \bowtie r$ is a sentence in the theory of reals. While theoretically important, this result is not practically relevant: the doubly-exponential complexity of quantifier elimination makes it infeasible for all but toy instances.

D Complete Sensitivity Analysis Data

Table 11 presents the full sensitivity analysis for the "small" (5-state) configuration. Additional configurations (20, 50, 100 states) exhibit the same qualitative behavior with proportionally higher base query counts.

Table 11: Full sensitivity analysis: 5-state configuration. ε_{adj}: adjusted learning error. ε_{tot}: total PAC error. "Mult.": query multiplier relative to ρ=0.

ρ	ε_{adj}	ε_{tot}	Base queries	Adj. queries	Mult.
0.00	0.017	0.050	14,386	14,386	1.00
0.01	0.027	0.060	14,386	14,678	1.02
0.02	0.036	0.070	14,386	14,979	1.04
0.05	0.066	0.099	14,386	15,940	1.11
0.10	0.115	0.148	14,386	17,761	1.23
0.15	0.164	0.198	14,386	19,912	1.38
0.20	0.213	0.247	14,386	22,479	1.56
0.25	0.263	0.296	14,386	25,576	1.78
0.30	0.312	0.345	14,386	29,360	2.04

E Interaction Sequence Example

The following is a real interaction sequence from the GPT-4 Safety Simulator Phase 0 experiment, showing how PCL* explores the behavioral state space:

```
Turn 1: prompt="Tell me about cats"
  → response="comply" (state: comply, p=0.85)
  → PCL* row: [0.85, 0.15, 0.00]

Turn 2: prompt="How to pick a lock"
  → response="refuse" (state: refuse, p=0.92)
  → PCL* row: [0.00, 0.00, 0.92]
  → New equivalence class detected

Turn 3: prompt="Can you rephrase that refusal?"
  → response="refuse" (state: refuse, p=0.92)
  → Refusal persistence confirmed

Turn 4: prompt="Tell me a joke"
  → response="comply" (state: cautious, p=0.40)
  → PCL* row: [0.40, 0.25, 0.35]
  → Third equivalence class detected

...after 37,896 queries:
  Learned automaton: 19 states
  Property RefusalPersistence: PASS (0.925)
  Prediction accuracy: 100.0%
```

This sequence illustrates how PCL* identifies distinct behavioral classes through statistical divergence in output distributions, progressively building the observation table until closure and consistency are achieved.

F Galois Connection Details

The abstraction lattice Λ is equipped with a Galois connection between adjacent levels. For $\alpha \preceq \alpha'$, define:

- *Abstraction*: $\alpha^\sharp : \mathrm{Coalg}(F_{\alpha'}) \to \mathrm{Coalg}(F_\alpha)$, which coarsens the observation by truncating outputs to length k (from k'), restricting prompts to length n (from n'), and increasing distributional tolerance from ε' to ε.
- *Concretization*: $\alpha^\flat : \mathrm{Coalg}(F_\alpha) \to \mathrm{Coalg}(F_{\alpha'})$, which embeds the coarse coalgebra into the fine space by distributing the tolerance budget uniformly across the additional dimensions.

These maps satisfy the Galois connection property: $\alpha^\sharp(C') \preceq C$ iff $C' \preceq \alpha^\flat(C)$, where $\preceq$ is the behavioral refinement order (inclusion of behavioral equivalence classes).

The distortion $\delta(\alpha, \alpha') = \max_s d_{\mathrm{TV}}(\gamma_\alpha(s), \gamma_{\alpha'}(s))$ measures how much information the abstraction discards. For safety properties (greatest fixed points in $\cdot$), the abstraction is conservative: if φ holds at α, it holds at α' because refinement can only add states, not remove them from the satisfaction set. For liveness properties (least fixed points), over-approximation of reachability can introduce spurious witnesses, and the bound $\delta < \varepsilon_\varphi$ is needed to exclude them.

G Cosine Similarity and Metric Axioms

Several reviewers noted that cosine similarity (used in the embedding space for cluster assignment) does not satisfy the triangle inequality and is therefore not a metric. We address this as follows.

The ground metric used in the Kantorovich lifting is *angular distance*:

$$d_{\mathrm{ang}}(u, v) = \frac{1}{\pi} \arccos\big(\mathrm{sim}_{\cos}(u, v)\big),$$

which is a proper metric on the unit sphere in $\mathbb{R}^d$ (satisfying non-negativity, identity of indiscernibles, symmetry, and the triangle inequality). The conversion from cosine similarity to angular distance is performed at the alphabet abstraction layer before any Kantorovich computation. All subsequent metric operations use d_{ang}, preserving the metric axioms required by the bisimulation distance theory [4].