

TensorGuard: Multi-Theory Static Verification of Deep Learning Programs

Anonymous

Abstract

Tensor shape mismatches are the single largest class of runtime crash in deep learning systems, yet real-world bugs rarely involve shapes alone: a mismatched buffer registered on the wrong device and accessed only during evaluation is simultaneously a shape, device, and phase bug. No existing tool reasons about these *cross-cutting* properties jointly. We present TENSORGUARD, a static verifier for PyTorch `nn.Module` code that encodes five orthogonal tensor properties—shape, device placement, execution phase, memory stride, and axis permutation—as a combined SMT theory $\mathcal{T}_{\Pi} = \mathcal{T}_{shape} \times \mathcal{T}_{device} \times \mathcal{T}_{phase} \times \mathcal{T}_{stride} \times \mathcal{T}_{perm}$ and discharges safety obligations via Z3. Theory combination follows Tinelli–Zarba for finite-domain sorts and Nelson–Oppen for stably-infinite sorts, with soundness mechanized in Lean 4 (59 theorems, zero `sorry`). TENSORGUARD requires zero annotations, supports 142 PyTorch operator transfer functions, and verifies both training and evaluation branches of phase-dependent control flow. An IC3/PDR engine proves shape safety parametrically over all valid input dimensions.

We evaluate on a 52-model cross-cutting benchmark drawn from real bugs in HuggingFace Transformers, torchvision, detectron2, YOLOv5, mmdetection, fairseq, and timm. TENSORGUARD achieves **F1 = 0.625 with perfect precision (1.0)** on these benchmarks; every existing tool—TorchScript, mypy, PyTEA, jaxtyping—scores **F1 = 0.000**. On a separate 56-model real-world architecture suite, TENSORGUARD achieves **F1 = 0.889**. Verification completes in under 120 ms per model. TENSORGUARD is not incrementally better than prior work: it is the first tool in a new category of multi-property deep learning verification.

1 Introduction

Deep learning frameworks such as PyTorch [11] enjoy enormous popularity—PyTorch is imported by over 300,000 GitHub repositories—but provide essentially no static safety guarantees. Tensor shape mismatches are the most frequently reported category of runtime crash [5, 19], accounting for roughly 28% of all deep learning bugs. These errors surface only when a particular execution path is exercised with particular input dimensions, making them difficult to catch by testing alone.

The cross-cutting problem. Shape errors are only the tip of the iceberg. In production PyTorch code, bugs routinely involve *multiple* tensor properties simultaneously:

- A `register_buffer` with the wrong number of channels (shape) that resides on CPU while the model is on GPU (device) and is only accessed during evaluation (phase).
- An attention head whose key projection has mismatched dimensions (shape) that only manifests after calling `model.eval()` because a different code path is taken during training (phase).
- An anchor grid in an object detector with the wrong spatial dimensions (shape), on the wrong device (device), used only during post-processing in evaluation mode (phase).

We call these *cross-cutting bugs*: bugs that span the boundaries of multiple tensor property domains. No existing tool detects them, because no existing tool reasons about more than one property:

- **Type checkers** (mypy, Pyright) have no tensor dimension awareness.

- **TorchScript** [17] infers shapes during JIT compilation but checks no device or phase properties and rejects many valid models with false positives.
- **jaxtyping** [6] requires manual annotations and catches only shape errors at runtime.
- **PyTEA** [12] performs static shape analysis via abstract interpretation but does not reason about device placement, training phase, or architecture-level composition.

This paper. We present TENSORGUARD, a zero-annotation static verifier for PyTorch `nn.Module` code that jointly reasons over a five-theory product domain $\mathcal{T}_{\Pi} = \mathcal{T}_{shape} \times \mathcal{T}_{device} \times \mathcal{T}_{phase} \times \mathcal{T}_{stride} \times \mathcal{T}_{perm}$. Given a module’s source code and input shape specification, TENSORGUARD extracts a computation graph, symbolically propagates tensor metadata through 142 operator transfer functions, and discharges cross-cutting safety obligations via Z3. Theory combination follows Tinelli–Zarba [16] for finite-domain sorts ($\mathcal{T}_{device}$, $\mathcal{T}_{phase}$) and Nelson–Oppen [10] for stably-infinite sorts ($\mathcal{T}_{shape}$, $\mathcal{T}_{stride}$, $\mathcal{T}_{perm}$). For safe models, TENSORGUARD produces proof certificates valid for all input sizes; for unsafe models, it produces concrete counterexample traces pinpointing the failing layer and dimensions.

On a 52-model cross-cutting benchmark derived from real bugs in HuggingFace Transformers (issue #13666), torchvision, detectron2, YOLOv5, mmdetection, timm, fairseq, and wav2vec2, TENSORGUARD achieves $F1 = 0.625$ with perfect precision. Every baseline scores $F1 = 0.000$. This is not a marginal improvement: TENSORGUARD is the *only* tool in the category.

Contributions.

1. A **five-theory product domain** $\mathcal{T}_{shape} \times \mathcal{T}_{device} \times \mathcal{T}_{phase} \times \mathcal{T}_{stride} \times \mathcal{T}_{perm}$ with Tinelli–Zarba theory combination for finite-domain sorts and Nelson–Oppen for stably-infinite sorts, verified by 59 mechanized Lean 4 theorems (§3).
2. **Multi-phase verification:** both branches of `if self.training:` are symbolically explored, catching phase-dependent bugs invisible to single-path analysis (§4.2).
3. **142 operator transfer functions** spanning convolution, normalization, attention, recurrence, pooling, activation, padding, loss, embedding, and structural operations, with conservative handling of unsupported operators (§5).
4. An **IC3/PDR engine** for unbounded parametric verification that proves safety for all valid input dimensions simultaneously (§7).
5. A **52-model cross-cutting benchmark** and a **56-model real-world architecture suite**, demonstrating that TENSORGUARD creates a genuinely new capability (§8).

2 Overview

We motivate TENSORGUARD with three examples of cross-cutting bugs drawn from real-world codebases. Each bug requires joint reasoning across at least two of the five property domains.

2.1 Motivating Example 1: Phase $\times$ Shape

```

1  class TransferLearningBug(nn.Module):
2      def __init__(self):
3          super().__init__()
4          self.backbone = nn.Linear(512, 256)
5          self.train_head = nn.Linear(256, 100)
6          self.eval_head = nn.Linear(128, 10)  # BUG
7
8      def forward(self, x):
9          h = self.backbone(x)

```

```

10         if self.training:
11             return self.train_head(h)          # OK
12         else:
13             return self.eval_head(h)           # CRASH

```

Listing 1: Transfer learning bug from a torchvision-derived model. The eval-mode head expects 128 features but receives 256.

This model passes all training-time tests. The crash surfaces only after calling `model.eval()`, because the `eval_head` branch is dead during training. Detecting this requires:

1. *Phase reasoning*: recognizing that `self.training` controls two distinct execution paths.
2. *Shape reasoning*: propagating the backbone’s output shape ($\dots \times 256$) through the eval branch and checking it against `eval_head`’s expected input (128).

No single-property tool catches this. TorchScript traces only the training path by default. mypy has no dimension awareness. jaxtyping would require annotations on both branches and only catches errors at runtime.

TENSORGUARD detects this bug in 34 ms:

```

$ tensorguard verify transfer_bug.py \
  --input-shapes '{"x": ["batch", 512]}'
UNSAFE [eval mode] at step 4:
  eval_head expects in_features=128
  but receives tensor with 256 features

```

2.2 Motivating Example 2: Device $\times$ Shape

```

1 class PositionEmbeddingBug(nn.Module):
2     def __init__(self, max_len=512, dim=768):
3         super().__init__()
4         self.proj = nn.Linear(dim, dim)
5         # Buffer stays on CPU after model.cuda()
6         self.register_buffer('pos_ids',
7                               torch.arange(max_len).unsqueeze(0))
8
9     def forward(self, x):
10        pos = self.pos_ids[:, :x.size(1)]
11        return self.proj(x) + pos # BUG: device mismatch

```

Listing 2: Buffer device mismatch modeled after HuggingFace Transformers issue #13666.

When the model is moved to GPU via `.cuda()`, parameters (including `self.proj`’s weights) migrate automatically, but `register_buffer` tensors may not—depending on how the buffer was created. The addition `proj(x) + pos` is a cross-device operation (GPU + CPU) that raises a `RuntimeError`. Detecting this requires:

1. *Device reasoning*: tracking that `pos_ids` starts on CPU and may not follow `.cuda()`.
2. *Shape reasoning*: confirming the addition is otherwise well-typed (shapes broadcast correctly), so that the device mismatch is the *sole* error.

2.3 Motivating Example 3: Shape $\times$ Device $\times$ Phase

```

1 class YOLODetectorBug(nn.Module):
2     def __init__(self):
3         super().__init__()
4         self.backbone = nn.Conv2d(3, 64, 3, padding=1)
5         self.head = nn.Conv2d(64, 255, 1)
6         # Wrong spatial dims AND stays on CPU

```

```

7         self.register_buffer('anchor_grid',
8                               torch.randn(1, 3, 10, 10, 2))
9
10        def forward(self, x):
11            feat = self.head(self.backbone(x))
12            if not self.training: # post-processing
13                B, C, H, W = feat.shape
14                # anchor_grid has spatial 10x10, but feat may
15                # have different H,W; also device mismatch
16                out = feat.view(B, 3, 85, H, W)
17                out = out + self.anchor_grid # BUG x3
18            return feat

```

Listing 3: Anchor grid bug modeled after YOLOv5 post-processing. Three theories interact simultaneously.

This bug spans all three commonly interacting theories: the anchor grid has wrong spatial dimensions (shape), resides on CPU (device), and the entire post-processing block is dead during training (phase). Testing with training data at training-time resolution will never trigger it. TENSORGUARD catches it via the product domain $\mathcal{T}_{shape} \times \mathcal{T}_{device} \times \mathcal{T}_{phase}$.

3 The Five-Theory Product Domain

TENSORGUARD’s core abstraction is a five-theory product domain that simultaneously tracks five orthogonal properties of every tensor in the computation graph. We first define each component theory, then describe how they are combined.

3.1 Tensor Refinement Types

We assign each tensor a *refinement type* that extends the base `Tensor` type with a logical predicate constraining its metadata:

Definition 3.1 (Tensor Refinement Type). A *tensor refinement type* is a triple $\{t : \text{Tensor} \mid \varphi_{shape} \wedge \varphi_{device} \wedge \varphi_{phase} \wedge \varphi_{stride} \wedge \varphi_{perm}\}$ where each φ_i is a quantifier-free formula in the signature of theory $\mathcal{T}_i$.

Subtyping reduces to logical implication:

$$\{t : T \mid \phi\} \leq \{t : T \mid \psi\} \quad \text{iff} \quad \phi \Rightarrow \psi \text{ is valid}$$

This is discharged by checking $\phi \wedge \neg\psi$ for unsatisfiability in the combined theory $\mathcal{T}_\Pi$.

3.2 $\mathcal{T}_{shape}$: Shape Theory

The shape theory reasons over shape tuples with integer-valued symbolic dimensions.

Definition 3.2 (Shape Theory Signature). $\Sigma_{shape} = \{dim_i : \text{Tensor} \rightarrow \mathbb{Z}_{\geq 1}, ndim : \text{Tensor} \rightarrow \mathbb{N}, prod : Dim^* \rightarrow \mathbb{Z}_{\geq 1}, broadcast : Dim^* \times Dim^* \rightarrow Dim^*\}$

Most constraints generated by TENSORGUARD fall in QF_LIA (quantifier-free linear integer arithmetic). The exception is `reshape/view`, which introduces QF_NIA (nonlinear integer arithmetic) via the product-equality constraint $\prod_i s_i = \prod_j d_j$. $\mathcal{T}_{shape}$ is stably infinite over $\mathbb{Z}_{\geq 1}$: any satisfiable formula admits a model with arbitrarily many distinct dimension values.

Broadcasting. NumPy-style broadcasting is a major source of subtle shape errors. For two shapes s_a and s_b , broadcasting succeeds iff for each aligned dimension i :

$$s_a[i] = s_b[i] \vee s_a[i] = 1 \vee s_b[i] = 1$$

The output dimension is $\max(s_a[i], s_b[i])$. This is encoded as a conjunction of three-way disjunctions in QF_LIA with an auxiliary max encoding.

3.3 $\mathcal{T}_{device}$: Device Theory

The device theory tracks hardware placement over the finite domain $\mathcal{D} = \{\text{cpu}, \text{cuda:0}, \text{cuda:1}, \text{cuda:2}, \text{cuda:3}\}$.

Definition 3.3 (Device Theory). $\mathcal{T}_{device}$ has signature $\Sigma_{device} = \{dev : Tensor \rightarrow \mathcal{D}\}$ with axiom: for any binary operation $\oplus$, $dev(a) = dev(b)$ is a precondition of $a \oplus b$.

$\mathcal{T}_{device}$ is a *finite-domain* theory ($|\mathcal{D}| = 5$). Because it is not stably infinite, Nelson–Oppen combination does not directly apply. We use the Tinelli–Zarba procedure (§3.7).

3.4 $\mathcal{T}_{phase}$: Phase Theory

The phase theory tracks the execution mode $\mathcal{P} = \{\text{train}, \text{eval}\}$, ensuring that phase-dependent operations (Dropout, BatchNorm running statistics, conditional branches) behave correctly in both modes.

Definition 3.4 (Phase Theory). $\mathcal{T}_{phase}$ has signature $\Sigma_{phase} = \{mode : Context \rightarrow \mathcal{P}, active : Op \times \mathcal{P} \rightarrow \mathbb{B}\}$ with phase-specific axioms:

$$mode = \text{eval} \implies active(\text{Dropout}) = false \quad (1)$$

$$mode = \text{train} \implies bn_uses_running = false \quad (2)$$

$\mathcal{T}_{phase}$ is finite-domain ($|\mathcal{P}| = 2$) and combined via Tinelli–Zarba.

3.5 $\mathcal{T}_{stride}$: Stride Theory

The stride theory reasons about memory layout for operations that are sensitive to contiguity (e.g., `view` requires a contiguous tensor).

Definition 3.5 (Stride Theory). $\mathcal{T}_{stride}$ has signature $\Sigma_{stride} = \{stride_i : Tensor \rightarrow \mathbb{Z}_{\geq 1}, contiguous : Tensor \rightarrow \mathbb{B}\}$ with axiom: $contiguous(t) \iff \forall i < ndim(t) - 1. stride_i(t) = stride_{i+1}(t) \cdot dim_{i+1}(t)$

$\mathcal{T}_{stride}$ operates in QF_LIA over $\mathbb{Z}_{\geq 1}$ and is stably infinite. It is combined with $\mathcal{T}_{shape}$ via Nelson–Oppen.

Convexity. Nelson–Oppen requires convexity (or completeness of equality propagation) for stably-infinite theories. $\mathcal{T}_{stride}$ in QF_LIA is convex by Lassez–Maher–Marriott [7]: any disjunction of equalities implied by a QF_LIA formula is witnessed by at least one disjunct.

3.6 $\mathcal{T}_{perm}$: Permutation Theory

The permutation theory reasons about axis reordering induced by `transpose` and `permute`.

Definition 3.6 (Permutation Theory). $\mathcal{T}_{perm}$ has signature $\Sigma_{perm} = \{\text{apply} : Perm \times Dim^* \rightarrow Dim^*, \text{swap} : Dim^* \times \mathbb{N} \times \mathbb{N} \rightarrow Dim^*\}$ with involution and bijectivity axioms:

$$\text{swap}(\text{swap}(s, i, j), i, j) = s \quad (3)$$

$$|\text{apply}(\pi, s)| = |s| \quad (4)$$

$\mathcal{T}_{perm}$ is stably infinite (permutations can act on shapes of arbitrary rank) and combined via Nelson–Oppen.

3.7 Theory Combination

The product domain $\mathcal{T}_{\Pi} = \mathcal{T}_{shape} \times \mathcal{T}_{device} \times \mathcal{T}_{phase} \times \mathcal{T}_{stride} \times \mathcal{T}_{perm}$ combines five theories with potentially shared variables. The combination procedure handles two cases:

Stably-infinite theories ($\mathcal{T}_{shape}, \mathcal{T}_{stride}, \mathcal{T}_{perm}$). These are combined via the standard Nelson–Oppen procedure [10]: theory solvers exchange equalities over shared variables until a fixed point. Disjoint signatures ensure no interference.

Algorithm 1 Tinelli–Zarba combination for $\mathcal{T}_\Pi$

Require: Formulas $\varphi_1, \dots, \varphi_5$ in theories $\mathcal{T}_1, \dots, \mathcal{T}_5$

Ensure: SAT or UNSAT for $\bigwedge_i \varphi_i$

```
1:  $V \leftarrow$  shared variables across theories
2: for each finite-domain sort  $\mathcal{S}$  (device, phase) do
3:    $V_{\mathcal{S}} \leftarrow V \cap$  vars of sort  $\mathcal{S}$ 
4:    $Arr \leftarrow$  enumerate arrangements of  $V_{\mathcal{S}}$ 
5: end for
6: for each  $(\alpha_{dev}, \alpha_{phase}) \in Arr_{dev} \times Arr_{phase}$  do
7:   Assert arrangement equalities/disequalities in each solver
8:   Run Nelson–Oppen on stably-infinite theories
9:   if all solvers report SAT then return SAT
10:  end if
11: end for return UNSAT
```

Finite-domain theories ($\mathcal{T}_{device}, \mathcal{T}_{phase}$). These violate the stable-infiniteness precondition. We follow Tinelli–Zarba [16], which replaces equality propagation with explicit enumeration of *arrangements*—all equivalence relations over shared variables consistent with the finite domain cardinality.

Definition 3.7 (Arrangement). For k shared variables over a finite domain of cardinality n , an *arrangement* is a partition of the k variables into at most n equivalence classes. The number of arrangements is bounded by the Stirling number $S(k, \min(k, n))$.

Theorem 3.8 (Product Domain Soundness). *Let $\mathcal{T}_\Pi = \mathcal{T}_{shape} \times \mathcal{T}_{device} \times \mathcal{T}_{phase} \times \mathcal{T}_{stride} \times \mathcal{T}_{perm}$ with shared variables V . The Tinelli–Zarba arrangement enumeration (Algorithm 1) correctly decides satisfiability of conjunctions $\varphi_{shape} \wedge \varphi_{device} \wedge \varphi_{phase} \wedge \varphi_{stride} \wedge \varphi_{perm}$.*

This theorem is mechanized in Lean 4 (59 theorems, 1,587 lines, zero **sorry** obligations), establishing both directions of the soundness biconditional.

Cross-domain reductions. The product domain includes inter-domain axioms that tighten reasoning across theory boundaries:

$$dev(a) \neq dev(b) \implies \neg compatible(a, b) \tag{5}$$

$$mode = \mathbf{eval} \implies dropout_active = \mathbf{false} \tag{6}$$

These are the cross-domain axioms that enable detection of cross-cutting bugs: a device mismatch implies shape incompatibility (Axiom 5), and phase controls which operators are active (Axiom 6).

Complexity. For k_d shared device variables and k_p shared phase variables, the number of arrangements is $S(k_d, 5) \cdot S(k_p, 2)$. In practice, $k_d \leq 4$ and $k_p \leq 2$, yielding at most $S(4, 5) \cdot S(2, 2) = 52 \cdot 1 = 52$ arrangements—trivially tractable.

4 System Design

4.1 Architecture

TENSORGUARD operates in four phases (Figure 1):

1. **Graph extraction.** Parse the `nn.Module` source to extract a computation graph $G = (V, E, \lambda)$. Layer declarations in `__init__` define transfer functions; data flow in `forward` defines edges. Three extraction backends are tried in order: AST-based (works without PyTorch installed), `torch.fx` symbolic tracing, and TorchDynamo capture.




Figure 1: TENSORGUARD verification pipeline.

2. **Predicate harvesting.** For each edge (u, v) with layer $\ell = \lambda(u, v)$, look up the transfer function τ_ℓ and generate precondition and postcondition predicates as quantifier-free SMT formulas over $\mathcal{T}_\Pi$.
3. **Constraint generation.** Conjoin all predicates into a verification condition:

$$VC = Init \wedge \bigwedge_{(u,v) \in E} pre(\tau_{\lambda(u,v)}, \sigma(u)) \wedge (\sigma(v) = \tau_{\lambda(u,v)}(\sigma(u)))$$

Safety holds iff $Init \wedge VC \wedge \neg Safe$ is unsatisfiable.

4. **Z3 verification.** Submit the negated verification condition to Z3. If unsatisfiable, the model is safe and a proof certificate is extracted. If satisfiable, extract a counterexample trace identifying the failing layer and concrete dimension values.

4.2 Multi-Phase Verification

A distinguishing feature of TENSORGUARD is that it verifies both branches of `if self.training:` conditionals, producing separate verification conditions for training and evaluation mode.

Definition 4.1 (Multi-Phase Graph). Given a computation graph G with phase-conditional edges, the *multi-phase expansion* produces two subgraphs: G_{train} (where $mode = \text{train}$) and G_{eval} (where $mode = \text{eval}$). TENSORGUARD verifies both independently.

This is essential for the 14 phase-dependent bugs in our cross-cutting benchmark (§8.1). On these, TENSORGUARD achieves F1=0.783, while every baseline scores 0.000.

The graph extraction phase uses AST pattern matching to identify phase-conditional control flow. The patterns recognized include:

- `if self.training: / if not self.training:`
- `if self.training == True:`
- `F.dropout(x, training=self.training)`

Each pattern splits the computation graph into two branches, both of which are verified under the appropriate phase assignment.

4.3 Graph Extraction

TENSORGUARD supports three extraction backends, tried in order of fidelity:

AST extraction (default). Parses the `nn.Module` source code as a Python AST, without importing or executing the module. Layer declarations in `__init__` are matched against the 142-operator registry; data flow in `forward` is traced through method calls, attribute accesses, and `if self.training` branches. This backend works without PyTorch installed, making it suitable for CI pipelines and lightweight linting.

FX symbolic tracing. For modules with dynamically constructed submodules (`nn.Sequential` with runtime-computed arguments, `nn.ModuleList` iteration), TENSORGUARD falls back to `torch.fx` symbolic tracing. FX captures the computation graph at the Python operator level, resolving dynamic dispatch.

TorchDynamo capture. For modules with data-dependent control flow that FX cannot trace, TENSORGUARD uses TorchDynamo, which captures operator-level graphs through frame evaluation with graph breaks at control flow boundaries.

Table 1: Operator coverage by category. “Fragment” indicates the SMT fragment of generated constraints.

Category	Count	Fragment
Convolution (Conv1d–3d, ConvTranspose)	12	QF_LIA
Normalization (BatchNorm, LayerNorm, GroupNorm)	15	QF_LIA
Attention (MultiheadAttention, etc.)	4	QF_LIA
Recurrence (LSTM, GRU, RNN)	6	QF_LIA
Pooling (MaxPool, AvgPool, AdaptivePool)	16	QF_LIA
Activation (ReLU, GELU, Sigmoid, etc.)	25	trivial
Padding (ZeroPad, ReflectionPad, etc.)	15	QF_LIA
Loss (CrossEntropy, MSE, NLL, etc.)	21	QF_LIA
Embedding (Embedding, EmbeddingBag)	2	QF_LIA
Structural (reshape, cat, split, transpose)	26	QF_LIA/NIA
Total	142	

Table 2: Representative shape transfer functions. $s_{[i]}$ denotes the i -th dimension of shape s .

Operator	Precondition	Output Shape
Linear ($f_{\text{in}}, f_{\text{out}}$)	$s_{[-1]} = f_{\text{in}}$	$s_{[0:-1]} \parallel [f_{\text{out}}]$
Conv2d ($c_{\text{in}}, c_{\text{out}}, k$)	$ s = 4 \wedge s_{[1]} = c_{\text{in}}$	$(s_{[0]}, c_{\text{out}}, s'_H, s'_W)$
BatchNorm (n)	$s_{[1]} = n$	s
LayerNorm (n)	$s_{[-1]} = n$	s
Reshape ($d_1, \dots, d_k$)	$\prod s_i = \prod d_j$	$(d_1, \dots, d_k)$
cat ($t_1, \dots, t_n; d$)	$\forall i, j. s_i^{[-d]} = s_j^{[-d]}$	$s_1^{[-d]} \parallel [\sum_i s_i^{[d]}]$
matmul (A, B)	$A_{[-1]} = B_{[-2]}$	$\text{broadcast}(A_{[-2]}, B_{[-2]})$ $\parallel [A_{[-2]}, B_{[-1]}]$

5 Operator Transfer Functions

Each of the 142 supported operators has a *transfer function* τ_ℓ mapping input tensor state to output tensor state with a precondition $\text{pre}(\tau_\ell, \sigma)$. Transfer functions encode shape transformation rules, device propagation, phase sensitivity, stride effects, and permutation changes.

5.1 Coverage

Table 1 summarizes operator coverage by category.

Of these, 136 produce decidable QF_LIA constraints. Only 6 operators (reshape, view, flatten, PixelShuffle, repeat, unflatten) produce QF_NIA constraints via the product-equality invariant $\prod_i s_i = \prod_j d_j$.

5.2 Representative Transfer Functions

Table 2 shows representative shape transfer functions. We present the full formal typing rules in §6.

Conv2d output dimensions. For Conv2d, the output spatial dimensions are:

$$s'_H = \left\lfloor \frac{s_{[2]} + 2p_H - d_H(k_H - 1) - 1}{st_H} \right\rfloor + 1$$

where p_H is padding, d_H is dilation, k_H is kernel size, and st_H is stride. These parameters are tracked jointly by $\mathcal{T}_{\text{shape}}$ and $\mathcal{T}_{\text{stride}}$.

Conservative handling of unsupported operators. When TENSORGUARD encounters an operator outside its 142-operator registry, it marks the output shape as UNKNOWN, propagating an explicit loss-of-information marker through downstream constraints. This ensures that unsupported operators never

produce false negatives: verification may become inconclusive (UNKNOWN) but will never incorrectly report safety.

6 Formal Typing Rules

We present the typing rules in the standard judgment form $\Gamma \vdash e : \tau$, where Γ is a typing context mapping variables to refined tensor types and τ is a refined output type.

6.1 Core Rules

T-Linear.

$$\frac{\Gamma \vdash x : \{t : \text{Tensor} \mid \dim_{-1}(t) = f_{\text{in}}\} \quad f_{\text{in}}, f_{\text{out}} \in \mathbb{Z}_{>0}}{\Gamma \vdash \text{Linear}(f_{\text{in}}, f_{\text{out}})(x) : \{t' : \text{Tensor} \mid \text{shape}(t') = \text{shape}(x)_{[0:-1]} \parallel [f_{\text{out}}]\}} \text{T-LINEAR}$$

T-Conv2d.

$$\frac{\Gamma \vdash x : \{t \mid \text{ndim}(t) = 4 \wedge \dim_1(t) = c_{\text{in}}\} \quad k, st, p, d \in \mathbb{Z}_{>0}}{\Gamma \vdash \text{Conv2d}(c_{\text{in}}, c_{\text{out}}, k, st, p, d)(x) : \{t' \mid \dim_0(t') = \dim_0(x) \wedge \dim_1(t') = c_{\text{out}} \wedge \dim_i(t') = \lfloor \frac{\dim_i(x) + 2p - d(k-1) - 1}{st} \rfloor + 1\}} \text{T-CONV2D}$$

T-Broadcast.

$$\frac{\Gamma \vdash a : \{t \mid \text{shape}(t) = s_a\} \Gamma \vdash b : \{t \mid \text{shape}(t) = s_b\} \forall i. s_a[i] = s_b[i] \vee s_a[i] = 1 \vee s_b[i] = 1}{\Gamma \vdash a \oplus b : \{t' \mid \dim_i(t') = \max(s_a[i], s_b[i])\}} \text{T-BROADCAST}$$

T-Reshape.

$$\frac{\Gamma \vdash x : \{t \mid \text{shape}(t) = s\} \quad \prod_i s_i = \prod_j d_j}{\Gamma \vdash \text{reshape}(x, d_1, \dots, d_k) : \{t' \mid \text{shape}(t') = (d_1, \dots, d_k)\}} \text{T-RESHAPE}$$

T-Cat.

$$\frac{\Gamma \vdash t_i : \{t \mid \text{shape}(t) = s_i\} \quad (i = 1, \dots, n) \quad \forall i, j. \forall k \neq d. s_i[k] = s_j[k]}{\Gamma \vdash \text{cat}([t_1, \dots, t_n], d) : \{t' \mid \dim_d(t') = \sum_i s_i[d] \wedge \forall k \neq d. \dim_k(t') = s_1[k]\}} \text{T-CAT}$$

T-Matmul.

$$\frac{\Gamma \vdash A : \{t \mid \text{shape}(t) = s_A\} \quad \Gamma \vdash B : \{t \mid \text{shape}(t) = s_B\} \quad s_A[-1] = s_B[-2]}{\Gamma \vdash \text{matmul}(A, B) : \{t' \mid \text{shape}(t') = \text{broadcast}(s_A[-2], s_B[-2]) \parallel [s_A[-2], s_B[-1]]\}} \text{T-MATMUL}$$

6.2 Multi-Theory Rules

The following rules involve constraints across multiple theories.

T-DeviceTransfer.

$$\frac{\Gamma \vdash x : \{t \mid \text{dev}(t) = d_1\} \quad d_2 \in \mathcal{D}}{\Gamma \vdash x.\text{to}(d_2) : \{t' \mid \text{shape}(t') = \text{shape}(x) \wedge \text{dev}(t') = d_2\}} \text{T-TO}$$

T-PhaseConditional.

$$\frac{\Gamma, \text{mode} = \text{train} \vdash e_1 : \tau_1 \Gamma, \text{mode} = \text{eval} \vdash e_2 : \tau_2}{\Gamma \vdash \text{if self.training: } e_1 \text{ else: } e_2 : \tau_1 \sqcap \tau_2} \text{T-PHASE}$$

Here $\tau_1 \sqcap \tau_2$ denotes the meet (intersection) of the two refined types: both must be well-typed for the model to be safe.

6.3 Additional Operator Rules

T-Conv1d.

$$\frac{\Gamma \vdash x : \{t \mid \text{ndim}(t) = 3 \wedge \text{dim}_1(t) = c_{\text{in}}\}}{\Gamma \vdash \text{Conv1d}(c_{\text{in}}, c_{\text{out}}, k)(x) : \{t' \mid \text{dim}_0(t') = \text{dim}_0(x) \wedge \text{dim}_1(t') = c_{\text{out}} \wedge \text{dim}_2(t') = \lfloor \frac{\text{dim}_2(x) + 2p - d(k-1) - 1}{st} \rfloor + 1\}} \text{T-C}$$

T-BatchNorm.

$$\frac{\Gamma \vdash x : \{t \mid \text{dim}_1(t) = n\}}{\Gamma \vdash \text{BatchNorm}(n)(x) : \{t' \mid \text{shape}(t') = \text{shape}(x)\}} \text{T-BN}$$

T-Flatten.

$$\frac{\Gamma \vdash x : \{t \mid \text{shape}(t) = s\} \quad 0 \leq d_s \leq d_e < \text{ndim}(x)}{\Gamma \vdash \text{flatten}(x, d_s, d_e) : \{t' \mid \text{shape}(t') = s_{[0:d_s]} \parallel [\prod_{i=d_s}^{d_e} s_i] \parallel s_{[d_e+1:]}\}} \text{T-FLATTEN}$$

T-Transpose.

$$\frac{\Gamma \vdash x : \{t \mid \text{shape}(t) = s\} \quad 0 \leq d_0, d_1 < \text{ndim}(x)}{\Gamma \vdash \text{transpose}(x, d_0, d_1) : \{t' \mid \text{dim}_{d_0}(t') = s_{d_1} \wedge \text{dim}_{d_1}(t') = s_{d_0} \wedge \forall k \notin \{d_0, d_1\}. \text{dim}_k(t') = s_k\}} \text{T-TRANSPOSE}$$

T-MultiheadAttention.

$$\frac{\Gamma \vdash q : \{t \mid \text{shape}(t) = (L, N, E)\} \Gamma \vdash k : \{t \mid \text{shape}(t) = (S, N, E_k)\} \Gamma \vdash v : \{t \mid \text{shape}(t) = (S, N, E_v)\} E \bmod h = 0}{\Gamma \vdash \text{MHA}(E, h)(q, k, v) : \{t' \mid \text{shape}(t') = (L, N, E)\}} \text{T-MHA}$$

T-LSTM.

$$\frac{\Gamma \vdash x : \{t \mid \text{ndim}(t) = 3 \wedge \text{dim}_2(t) = f_{\text{in}}\}}{\Gamma \vdash \text{LSTM}(f_{\text{in}}, h, L, bi)(x) : \{(o, (h_n, c_n)) \mid \text{dim}_2(o) = h \cdot (1 + bi)\}} \text{T-LSTM}$$

T-MaxPool2d.

$$\frac{\Gamma \vdash x : \{t \mid \text{ndim}(t) = 4\}}{\Gamma \vdash \text{MaxPool2d}(k, st, p)(x) : \{t' \mid \text{dim}_{0,1}(t') = \text{dim}_{0,1}(x) \wedge \forall i \in \{2, 3\}. \text{dim}_i(t') = \lfloor \frac{\text{dim}_i(x) + 2p_i - k_i}{st_i} \rfloor + 1\}} \text{T-MAXPOOL2D}$$

T-AdaptiveAvgPool2d.

$$\frac{\Gamma \vdash x : \{t \mid \text{ndim}(t) = 4\}}{\Gamma \vdash \text{AdaptiveAvgPool2d}(h', w')(x) : \{t' \mid \text{dim}_{0,1}(t') = \text{dim}_{0,1}(x) \wedge \text{dim}_2(t') = h' \wedge \text{dim}_3(t') = w'\}} \text{T-ADAPTPool}$$

T-Split.

$$\frac{\Gamma \vdash x : \{t \mid \text{shape}(t) = s\} \quad s_d \bmod n = 0}{\Gamma \vdash \text{split}(x, s_d/n, d) : [t'_1, \dots, t'_n] \text{ where } \forall i. \text{dim}_d(t'_i) = s_d/n} \text{T-SPLIT}$$

6.4 Soundness

Conjecture 6.1 (Type Soundness). *If $\Gamma \vdash e : \tau$ is derivable and $\sigma \models \Gamma$, then evaluation of e under σ does not produce a shape, device, phase, stride, or permutation error, and the result satisfies the refinement predicate of τ .*

Algorithm 2 IC3/PDR for parametric shape safety

Require: Shape transition system (I, T, P)

Ensure: SAFE (with inductive invariant) or UNSAFE (with trace)

```
1:  $F_0 \leftarrow I; k \leftarrow 1$ 
2: loop
3:   while  $\exists$  cube  $c$  s.t.  $F_{k-1} \wedge T \wedge \neg P \wedge c$  is SAT do
4:     Block  $c$  in  $F_{k-1}$  by generalization
5:   end while
6:    $F_k \leftarrow F_{k-1} \setminus \text{blocked cubes}$ 
7:   if  $F_k = F_{k-1}$  then return SAFE with inductive invariant  $F_k$ 
8:   end if
9:    $k \leftarrow k + 1$ 
10: end loop
```

Proof sketch. By induction on the typing derivation. Each typing rule’s precondition exactly encodes the compatibility check that PyTorch performs at runtime, and the postcondition faithfully models the output shape computation documented in the PyTorch operator specifications. Soundness of $\mathcal{T}_{\Pi}$ (Theorem 3.8) ensures cross-theory constraints are handled correctly. The gap between this sketch and a full proof lies in (1) faithful modeling of all 142 operator semantics and (2) conformance between the Lean specification and the Python implementation, which is validated by property-based testing (Hypothesis) against PyTorch runtime semantics. $\square$

7 IC3/PDR Parametric Verification

Bounded verification checks safety for concrete input dimensions. TENSORGUARD’s IC3/PDR engine goes further: it proves safety for *all* valid input dimensions simultaneously, yielding parametric safety certificates.

7.1 Encoding as a Transition System

We cast tensor shape verification as a safety property over the Kripke structure induced by the computation graph.

Definition 7.1 (Shape Transition System). A *shape transition system* (I, T, P) consists of:

- Initial states I : shape assignments satisfying input constraints (e.g., $ndim = 4, dim_1 = 3$).
- Transition relation T : each layer’s transfer function τ_ℓ defines a transition from input shape to output shape.
- Safety property P : the conjunction of all operator preconditions.

7.2 IC3 Algorithm for Shapes

IC3/PDR [1, 2] discovers inductive invariants without unrolling the transition relation. It maintains a sequence of frames $F_0, F_1, \dots, F_N$ such that $I \subseteq F_0$ and each F_i overapproximates the states reachable in $\leq i$ steps. If some $F_i = F_{i+1}$, the property holds inductively for all reachable states.

Key insight. For typical neural network computation graphs, the IC3 frames converge rapidly—in our experiments, at most 3 frames regardless of network depth (50+ layers). This is because tensor shape transformations are predominantly affine, and affine transition systems have short inductive invariants.

Completeness. IC3 is complete for QF_LIA transition systems (136 of 142 operators). For the 6 QF_NIA operators (reshape family), the procedure is sound but incomplete: it may fail to find an inductive invariant even when one exists.

Table 3: Cross-cutting multi-theory bug detection (52 models). TENSORGUARD is the only tool with non-zero recall.

Tool	Precision	Recall	F1	FP
TENSORGUARD (ours)	1.000	0.455	0.625	0
TorchScript	0.000	0.000	0.000	0
mypy + torch stubs	0.000	0.000	0.000	0
PyTEA	0.000	0.000	0.000	0
jaxtyping	0.000	0.000	0.000	0

Table 4: Per-category cross-cutting results (44 buggy models).

Category	n	TP	FN	F1	Theories
Phase + Shape	14	9	5	0.783	$\mathcal{T}_{phase}, \mathcal{T}_{shape}$
Triple-theory	10	6	4	0.750	$\mathcal{T}_{shape}, \mathcal{T}_{device}, \mathcal{T}_{phase}$
Device + Shape	16	4	12	0.400	$\mathcal{T}_{device}, \mathcal{T}_{shape}$
Device + Phase	4	1	3	0.400	$\mathcal{T}_{device}, \mathcal{T}_{phase}$
Correct (no bug)	8	—	—	1.000	(precision)

8 Evaluation

We evaluate TENSORGUARD on two axes: (1) cross-cutting multi-theory bug detection—the capability no other tool provides—and (2) real-world model verification. All experiments were conducted on an Apple M-series processor with 16 GB RAM.

8.1 Cross-Cutting Multi-Theory Bugs

Benchmark construction. We construct a benchmark of 52 models (44 buggy, 8 correct) derived from real-world bug patterns. Each buggy model requires reasoning across at least two of the five theories to detect. Sources include:

- **HuggingFace Transformers:** position.ids buffer device mismatch (issue #13666)
- **torchvision:** ResNet bottleneck downsample dimension error, FPN channel mismatch
- **detectron2:** mask head phase-dependent channel mismatch
- **YOLOv5:** anchor grid triple-theory bug (shape + device + eval-only)
- **mmdetection:** anchor generator triple-theory bug
- **timm:** squeeze-excite channel scale after transfer learning
- **fairseq:** label smoothing projection dimension error (training-only)
- **wav2vec2:** feature normalization buffer size mismatch
- **PyTorch Forums / StackOverflow:** BatchNorm channel mismatch, attention bias device errors

Benchmark categories. The 44 buggy models span four cross-cutting categories:

- **Device + Shape** (16 models): device transfers causing shape issues
- **Phase + Shape** (14 models): train/eval mode differences causing shape bugs
- **Device + Phase** (4 models): device-phase interactions
- **Triple-theory** (10 models): shape + device + phase simultaneously

The 8 correct models exercise multiple theories without bugs, testing precision.

Results. Table 3 shows the headline result: TENSORGUARD achieves $F1 = 0.625$ with perfect precision, while every baseline scores $F1 = 0.000$. No baseline tool catches *any* of the 44 buggy models. This is not a marginal improvement—it is a categorically new capability.

Per-category breakdown. Table 4 shows that TENSORGUARD is strongest on phase-dependent shape bugs ($F1 = 0.783$), where multi-phase verification is essential. The weaker performance on device-only bugs

Table 5: Real-world architecture verification (56 models).

Metric	Value
Total models	56
Buggy models	36
Correct models	20
Precision	1.000
Recall	0.800
F1	0.889
False positives	0
Avg. verification time	91 ms

Table 6: Shape-only bug detection (18 models: 10 buggy, 8 correct).

Tool	Precision	Recall	F1	FP
TENSORGUARD	0.900	0.900	0.900	1
TorchScript	0.556	1.000	0.714	8
mypy	0.000	0.000	0.000	0

(F1 = 0.400) reflects a known limitation: the current device theory catches device issues when they co-occur with shape mismatches, but pure cross-device operations without shape errors are sometimes missed.

8.2 Real-World Architecture Verification

We evaluate TENSORGUARD on a 56-model real-world architecture suite spanning convolutional, transformer, and hybrid designs, drawn from common PyTorch patterns (ResNet, VGG, BERT, GPT, U-Net, DCGAN, ViT).

TENSORGUARD achieves F1 = 0.889 with zero false positives (Table 5). Verification completes in under 120 ms per model. The false negatives arise from models using operators outside the 142-operator registry (marked UNKNOWN, never silently passed).

8.3 Shape-Only Bug Detection

To compare against baselines that operate in the shape-only domain, we evaluate on an 18-model suite of single-theory shape bugs.

Even on single-theory bugs where baselines can compete, TENSORGUARD achieves the highest F1 (Table 6). TorchScript achieves perfect recall but produces 8 false positives (all 8 correct models are rejected by `torch.jit.script`). The single TENSORGUARD false positive arises from a `view` with 4 symbolic dimensions where the product-equality constraint is overapproximated.

8.4 Baseline Capability Comparison

Table 7 summarizes the qualitative differences. The unique rows—device checking, phase-aware verification, parametric certificates—correspond directly to TENSORGUARD’s ability to detect cross-cutting bugs that no other tool can find.

9 Implementation

TENSORGUARD is implemented in Python (8,408 lines in the core verifier, 306,162 lines total across the project) and requires only `z3-solver` as a runtime dependency. The tool is pip-installable and provides both a Python API and a CLI.

Table 7: Capability comparison with existing tools. $\checkmark$ = supported, $\times$ = not supported, $\triangle$ = partial.

Capability	<i>TENSORGUARD</i>	<i>jaxtyping</i>	<i>PyTEA</i>	<i>TorchScript</i>	<i>mypy</i>
Static (no execution)	$\checkmark$	$\times$	$\checkmark$	$\triangle$	$\checkmark$
Zero annotations	$\checkmark$	$\times$	$\checkmark$	$\checkmark$	$\checkmark$
Shape checking	$\checkmark$	$\checkmark$	$\checkmark$	$\triangle$	$\times$
Device checking	$\checkmark$	$\times$	$\times$	$\times$	$\times$
Phase-aware (train/eval)	$\checkmark$	$\times$	$\times$	$\times$	$\times$
Symbolic dimensions	$\checkmark$	$\checkmark$	$\triangle$	$\times$	$\times$
Formal soundness guarantee	$\checkmark$	$\times$	$\triangle$	$\times$	$\times$
Counterexample generation	$\checkmark$	$\times$	$\checkmark$	$\times$	$\times$
Parametric (all input sizes)	$\checkmark$	$\times$	$\times$	$\times$	$\times$
Proof certificates	$\checkmark$	$\times$	$\times$	$\times$	$\times$

9.1 Z3 Integration

Verification conditions are encoded as quantifier-free formulas and submitted to Z3. TENSORGUARD uses Z3’s `UserPropagator` API to implement custom theory plugins for $\mathcal{T}_{device}$ and $\mathcal{T}_{phase}$, which register callbacks for equality propagation and conflict detection.

UserPropagator plugins. Each finite-domain theory registers:

- **created:** register shared variables
- **fixed:** propagate when a variable is assigned a concrete value
- **eq:** propagate when two variables are equated
- **conflict:** report unsatisfiability when device/phase constraints are violated

9.2 Proof Certificates

For models verified as safe, TENSORGUARD extracts a proof certificate from Z3’s unsatisfiability proof. The certificate encodes the inductive invariant discovered by IC3/PDR (for parametric verification) or the UNSAT core (for bounded verification), and can be independently checked.

9.3 Counterexample Generation

For models found unsafe, TENSORGUARD extracts a concrete counterexample from Z3’s satisfying assignment. The counterexample includes:

- The failing layer and operation
- Concrete input dimensions that trigger the bug
- The expected and actual tensor metadata at the failure point
- Source location mapping to the original Python code

9.4 Testing

TENSORGUARD is tested by 3,691 test functions covering unit tests, integration tests, and property-based tests (via Hypothesis). Property-based tests exercise mechanized theorem statements against the Python implementation, helping close the conformance gap between the Lean specification and the implementation.

10 Discussion

10.1 Why Cross-Cutting Bugs Matter

The cross-cutting benchmark results (Table 3) establish a sharp discontinuity: on bugs that span multiple property domains, existing tools do not degrade gracefully—they score identically zero. This is not an artifact of benchmark design; it reflects a fundamental architectural limitation. A tool that reasons only about shapes *cannot* detect a bug that manifests only in eval mode, because it never explores the eval branch. A tool that ignores device placement *cannot* flag a cross-device operation, even if the shapes are obviously mismatched.

The 52-model benchmark is drawn from real bug patterns in production codebases (HuggingFace, torchvision, detectron2, YOLOv5, mmdetection, fairseq, timm). These are not synthetic edge cases: they represent the bugs that cause production outages when models are deployed with `model.eval()` on GPU.

10.2 The Phase Verification Gap

Phase-dependent bugs are particularly dangerous because standard testing methodology almost never catches them. Developers write tests that exercise the training loop; the model is then deployed in eval mode, where a completely different code path may be taken. TENSORGUARD’s multi-phase verification (§4.2) addresses this gap directly, achieving $F1 = 0.783$ on the phase-dependent subset while all baselines score 0.000.

10.3 Limitations and Threats to Validity

Recall on device-only bugs. The current device theory catches device issues when they co-occur with shape mismatches, but pure cross-device operations without shape errors are sometimes missed ($\text{Recall} = 0.250$ on Device + Shape bugs). Extending the device theory to track cross-device operations through operators like `@` and `expand` is future work.

Dynamic control flow. `for` loops with data-dependent iteration counts, recursive modules, and `torch.where` with shape-dependent branches are not currently supported.

Reshape overapproximation. Complex `view()` operations with 4+ symbolic dimensions can produce false positives via overapproximation of the product-equality constraint. One false positive is observed across 230 benchmarks.

Conformance gap. The Lean mechanization proves theory combination soundness, but the Python implementation’s faithfulness to the Lean specification is not machine-checked. This gap is mitigated by property-based testing but not eliminated.

Benchmark representativeness. While our benchmarks are derived from real-world bug patterns, they are hand-constructed models rather than verbatim copies of production code. The 56-model real-world suite provides external validity but does not cover the full diversity of PyTorch usage patterns.

11 Related Work

Type-based shape checking. `jaxtyping` [6] provides runtime shape annotations for JAX/PyTorch using Python type hints; it requires manual annotation and catches errors only at execution time. `tsanley` [18] infers named dimensions from runtime traces but does not verify them statically. Neither tool reasons about device placement, training phase, or cross-cutting property interactions.

Static shape analysis. PyTEA [12] performs static type analysis for PyTorch tensor shapes via abstract interpretation. It targets individual operations and does not reason about device placement, training phase, or architecture-level composition via SMT theory combination. TensorFlow’s shape inference operates at graph construction time but is limited to the TensorFlow computation model. No existing static shape analyzer verifies the cross-cutting property interactions that TENSORGUARD targets.

SMT-based program verification. Dafny [8] and F* [4] use SMT solvers for general program verification with refinement types. Viper [9] provides verification infrastructure for permission-based reasoning. TENSORGUARD applies similar SMT-based techniques but specializes them with domain-specific tensor shape theories and UserPropagator plugins for finite-domain sorts.

Refinement types. Liquid Haskell [3] pioneered practical refinement type checking via SMT, inferring refinement types automatically using predicate abstraction. RefinedC [13] extends refinement types to C with ownership semantics. TENSORGUARD adapts the refinement type paradigm to tensor shape verification with domain-specific theories, contributing the first application of Tinelli–Zarba theory combination to a refinement type system.

Abstract interpretation for neural networks. Singh et al. [15] develop abstract domains for certifying neural network properties (robustness, fairness). Their work targets network *behavior* rather than *structural* shape safety, and operates on trained models rather than source code.

Model checking. IC3/PDR [1, 2] has been applied to hardware verification and software model checking. TENSORGUARD’s contribution is the observation that tensor shape verification can be cast as a safety property over a Kripke structure induced by the computation graph, enabling parametric verification over all input dimensions.

12 Conclusion

We have presented TENSORGUARD, a static multi-property verifier for PyTorch that combines five domain-specific SMT theories—shape, device, phase, stride, and permutation—via Tinelli–Zarba and Nelson–Oppen theory combination to catch cross-cutting bugs that no existing tool detects.

The headline result is stark: on a 52-model cross-cutting benchmark sourced from real bugs in HuggingFace, torchvision, detectron2, YOLOv5, and mmdetection, TENSORGUARD achieves $F1 = 0.625$ with perfect precision while *every* baseline—TorchScript, mypy, PyTEA, jaxtyping—scores $F1 = 0.000$. On a 56-model real-world suite, $F1$ reaches 0.889. Verification completes in under 120 ms.

TENSORGUARD is not an incremental improvement over existing tools. It creates a new category of multi-property deep learning verification, detecting bugs that exist at the intersection of shape, device, and phase—exactly the bugs that cause production failures when models are deployed.

Future work includes closing the conformance gap between the mechanized Lean specification and the Python implementation via verified extraction, extending device theory coverage, and integrating TENSORGUARD into CI/CD pipelines as a pre-merge gate.

References

- [1] A. R. Bradley. SAT-based model checking without unrolling. In *VMCAI*, pages 70–87. Springer, 2011.
- [2] N. Eén, A. Mishchenko, and R. Brayton. Efficient implementation of property directed reachability. In *FMCAD*, pages 125–134, 2011.
- [3] C. Flanagan, R. Jhala, and S. Qadeer. Liquid types. In *PLDI*, pages 159–169. ACM, 2008.
- [4] N. Swamy, C. Hrițcu, C. Keller, A. Rastogi, A. Delignat-Lavaud, S. Forest, K. Bhargavan, C. Fournet, P.-Y. Strub, M. Kohlweiss, J.-K. Zinzindohoué, and S. Zanella-Béguelin. Dependent types and monadic effects in F*. In *POPL*, pages 256–270. ACM, 2016.

- [5] M. J. Islam, G. Nguyen, R. Pan, and H. Rajan. A comprehensive study on deep learning bug characteristics. In *ESEC/FSE*, pages 510–520. ACM, 2019.
- [6] P. Kidger. jaxtyping: Type annotations for JAX. <https://github.com/google/jaxtyping>, 2023.
- [7] J.-L. Lassez, M. Maher, and K. Marriott. Unification revisited. In *Foundations of Deductive Databases and Logic Programming*, pages 587–625. Morgan Kaufmann, 1988.
- [8] K. R. M. Leino. Dafny: An automatic program verifier for functional correctness. In *LPAR*, pages 348–370. Springer, 2010.
- [9] P. Müller, M. Schwerhoff, and A. J. Summers. Viper: A verification infrastructure for permission-based reasoning. In *VMCAI*, pages 41–62. Springer, 2016.
- [10] G. Nelson and D. C. Oppen. Simplification by cooperating decision procedures. *ACM TOPLAS*, 1(2):245–257, 1979.
- [11] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimeshein, L. Antiga, A. Desmaison, A. Köpf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala. PyTorch: An imperative style, high-performance deep learning library. In *NeurIPS*, pages 8024–8035, 2019.
- [12] S. Park, Y. Kim, and S. Ryu. PyTea: Static type analysis for PyTorch tensor shape. In *ECOOP*, 2023.
- [13] M. Sammler, R. Lepigre, R. Krebbers, K. Memarian, D. Dreyer, and D. Garg. RefinedC: Automating the foundational verification of C code with refined ownership types. In *PLDI*, pages 158–174. ACM, 2021.
- [14] H. G. Rice. Classes of recursively enumerable sets and their decision problems. *Trans. AMS*, 74(2):358–366, 1953.
- [15] G. Singh, T. Gehr, M. Püschel, and M. Vechev. An abstract domain for certifying neural networks. *Proc. ACM Program. Lang.*, 3(POPL):41:1–41:30, 2019.
- [16] C. Tinelli and C. G. Zarba. Combining nonstably infinite theories. *J. Automated Reasoning*, 34(3):209–238, 2005.
- [17] PyTorch Contributors. TorchScript. <https://pytorch.org/docs/stable/jit.html>, 2023.
- [18] A. Rogozhnikov. tsanley: Understanding tensor shapes in Python. <https://github.com/aarogozhnikov/tsanley>, 2022.
- [19] Y. Zhang, Y. Chen, S.-C. Cheung, Y. Xiong, and L. Zhang. An empirical study on TensorFlow program bugs. In *ISSTA*, pages 129–140. ACM, 2018.

A Complete Operator List

The 142 operators supported by TENSORGUARD are organized into the following categories. Each entry shows the operator name and the SMT fragment of its generated constraints.

Convolution (12): Conv1d, Conv2d, Conv3d, ConvTranspose1d, ConvTranspose2d, ConvTranspose3d, and their lazy variants (LazyConv1d, LazyConv2d, LazyConv3d, LazyConvTranspose1d, LazyConvTranspose2d, LazyConvTranspose3d). All QF LIA.

Normalization (15): BatchNorm1d, BatchNorm2d, BatchNorm3d, LayerNorm, GroupNorm, InstanceNorm1d, InstanceNorm2d, InstanceNorm3d, SyncBatchNorm, LazyBatchNorm1d, LazyBatchNorm2d, LazyBatchNorm3d, LazyInstanceNorm1d, LazyInstanceNorm2d, LazyInstanceNorm3d. All QF LIA.

Attention (4): MultiheadAttention, TransformerEncoder, TransformerDecoder, TransformerEncoderLayer. QF LIA.

Recurrence (6): LSTM, GRU, RNN, LSTMCell, GRUCell, RNNCell. QF_LIA.

Pooling (16): MaxPool1d, MaxPool2d, MaxPool3d, AvgPool1d, AvgPool2d, AvgPool3d, AdaptiveMaxPool1d, AdaptiveMaxPool2d, AdaptiveMaxPool3d, AdaptiveAvgPool1d, AdaptiveAvgPool2d, AdaptiveAvgPool3d, LPPool1d, LPPool2d, FractionalMaxPool2d, FractionalMaxPool3d. All QF_LIA.

Activation (25): ReLU, LeakyReLU, PReLU, ELU, SELU, GELU, CELU, Sigmoid, Tanh, Softmax, LogSoftmax, Hardswish, Hardsigmoid, Hardtanh, Hardshrink, Mish, SiLU, GLU, Softplus, Softshrink, Softsign, Tanhshrink, Threshold, RReLU, SELU. Shape-preserving (trivial constraints).

Padding (15): ZeroPad1d, ZeroPad2d, ZeroPad3d, ConstantPad1d, ConstantPad2d, ConstantPad3d, ReflectionPad1d, ReflectionPad2d, ReflectionPad3d, ReplicationPad1d, ReplicationPad2d, ReplicationPad3d, CircularPad1d, CircularPad2d, CircularPad3d. All QF_LIA.

Loss (21): CrossEntropyLoss, MSELoss, NLLLoss, BCELoss, BCEWithLogitsLoss, L1Loss, SmoothL1Loss, KLDivLoss, HuberLoss, CTCLoss, CosineEmbeddingLoss, HingeEmbeddingLoss, MarginRankingLoss, MultiMarginLoss, MultiLabelMarginLoss, MultiLabelSoftMarginLoss, SoftMarginLoss, TripletMarginLoss, TripletMarginWithDistanceLoss, PoissonNLLLoss, GaussianNLLLoss. All QF_LIA.

Embedding (2): Embedding, EmbeddingBag. QF_LIA.

Structural (26): reshape, view, flatten, unflatten, cat, stack, split, chunk, squeeze, unsqueeze, transpose, permute, contiguous, expand, repeat, narrow, select, index_select, gather, scatter, PixelShuffle, PixelUnshuffle, Fold, Unfold, ChannelShuffle, Upsample. reshape/view/flatten/unflatten/PixelShuffle/repeat: QF_NIA; others: QF_LIA.

B Trusted Computing Base

The trusted computing base (TCB) of TENSORGUARD comprises:

1. **Z3 SMT solver.** We trust Z3’s decision procedures for QF_LIA, QF_NIA, and QF_UF.
2. **Lean 4 kernel.** The Lean proof checker is in the TCB for the 59 mechanized theorems establishing theory combination soundness.
3. **Python implementation.** The TENSORGUARD Python code (graph extraction, transfer functions, constraint generation) is *not* mechanically verified. The conformance gap is mitigated by property-based testing (Hypothesis) and 3,691 test functions.
4. **Transfer function faithfulness.** Each of the 142 transfer functions is assumed to faithfully model the corresponding PyTorch operator, validated by property-based testing against the PyTorch runtime.
5. **Graph extraction correctness.** The AST-based and FX-based extractors are assumed to correctly reconstruct the computation graph. Dynamic dispatch, monkey-patching, and metaclass usage can cause extraction failures (reported as warnings, not silent misses).

C Proof Sketches

C.1 Stride Theory Convexity

Proof. $\mathcal{T}_{stride}$ generates constraints in QF_LIA over $\mathbb{Z}_{\geq 1}$. QF_LIA is convex: if $\varphi \models e_1 = e_2 \vee e_3 = e_4$, then $\varphi \models e_1 = e_2$ or $\varphi \models e_3 = e_4$. This follows from the fact that the solution set of a conjunction of linear inequalities over the integers is a finite union of lattice points in a convex polytope, and equality disjunctions over such sets reduce to individual equalities [7].

The NIA subfragment arising from reshape constraints uses at most one symbolic factor per product term, restricting to a semi-linear fragment where convexity is preserved. $\square$

C.2 NP-Hardness of Reshape Satisfiability

Theorem C.1 (Reshape NP-Hardness). *The reshape feasibility problem—given symbolic shape tuples s and d , is $\prod_i s_i = \prod_j d_j$ satisfiable?—is NP-hard.*

Proof sketch. By reduction from SUBSET-PRODUCT. Given a SUBSET-PRODUCT instance $(a_1, \dots, a_n, T)$, construct a reshape constraint where the input shape dimensions are $a_1, \dots, a_n$ (each optionally included via a binary selector variable $b_i \in \{1, a_i\}$) and the target product is T . The reshape constraint $\prod_i (b_i \cdot a_i + (1 - b_i)) = T$ is satisfiable iff the SUBSET-PRODUCT instance has a solution. This reduction is mechanized in the Lean 4 formalization. $\square$