



FEX RESTful API User Manual

Version: 1.0
Release date: 2025-07-07

Use of this document and any information contained therein is subject to the terms and conditions set forth in Exhibit 1. This document is subject to change without notice.

Version History

Version	Date	Author	Description
1.0	2025-07-07	IT	Official release

MediaTek Confidential / No Disclosure

Table of Contents

Version History	2
Table of Contents	3
1 API Prefix	6
2 Access Token API Documentation	7
2.1 Fetch Refresh Token	7
2.1.1 Endpoint	7
2.1.2 Headers	7
2.1.3 Authentication	7
2.1.4 Request Parameters	7
2.1.5 Response	8
2.1.6 Errors	8
2.2 Fetch Access Token	8
2.2.1 Endpoint	8
2.2.2 Headers	8
2.2.3 Authentication	8
2.2.4 Request Parameters	9
2.2.5 Response	9
2.2.6 Errors	9
3 P2P Client API Documentation	10
3.1 Create Upload Request	10
3.1.1 HTTP Request	10
3.1.2 Headers	10
3.1.3 Body	10
3.1.4 Response	11
3.1.5 Errors	11
3.2 Upload files	11
3.3 Get Request Detail via Request Id	12
3.3.1 HTTP Request	12
3.3.2 Headers	12
3.3.3 Response	12
3.3.4 Errors	12
3.4 Query Shared History	12
3.4.1 HTTP Request	12
3.4.2 Headers	12
3.4.3 Body	13
3.4.4 Response	13
3.4.5 Errors	13
3.5 Query Received History	14
3.5.1 HTTP Request	14
3.5.2 Headers	14
3.5.3 Body	14
3.5.4 Response	14
3.5.5 Errors	15

3.6	Get Aspera Download Token By Request Id	15
3.6.1	HTTP Request	15
3.6.2	Headers	15
3.6.3	Response	15
3.6.4	Errors	16
3.7	Get Http Download Token And URL By Request Id	16
3.7.1	HTTP Request	16
3.7.2	Headers	16
3.7.3	Response	16
3.7.4	Errors	16
3.8	Download files	17
4	MySpace API Documentation	18
4.1	Get My Space List	18
4.1.1	HTTP Request	18
4.1.2	Headers	18
4.1.3	Response	18
4.1.4	Errors	19
4.2	Get Sub Folders and Files	19
4.2.1	HTTP Request	19
4.2.2	Headers	19
4.2.3	Response	19
4.2.4	Errors	20
4.3	Get File Info	20
4.3.1	HTTP Request	20
4.3.2	Headers	20
4.3.3	Response	20
4.3.4	Errors	21
4.4	Create Folder	21
4.4.1	HTTP Request	21
4.4.2	Headers	21
4.4.3	Body	21
4.4.4	Response	21
4.4.5	Errors	21
4.5	Rename Folder or File	22
4.5.1	HTTP Request	22
4.5.2	Headers	22
4.5.3	Body	22
4.5.4	Response	22
4.5.5	Errors	22
4.6	Delete Folder or File	22
4.6.1	HTTP Request	22
4.6.2	Headers	23
4.6.3	Response	23
4.6.4	Errors	23
4.7	Upload Files via HTTP	23

4.7.1	HTTP Request	23
4.7.2	Headers	23
4.7.3	Body.....	23
4.7.4	Response	24
4.7.5	Errors	24
4.8	Download Files via HTTP.....	24
4.8.1	HTTP Request	24
4.8.2	Headers	24
4.8.3	Body.....	25
4.8.4	Response	25
4.8.5	Errors	25
4.9	Upload Files via Aspera.....	25
4.9.1	HTTP Request	25
4.9.2	Headers	25
4.9.3	Body.....	25
4.9.4	Response	26
4.9.5	Errors	26
4.10	Upload Files via Aspera.....	26
4.10.1	HTTP Request	26
4.10.2	Headers	26
4.10.3	Body.....	26
4.10.4	Response	27
4.10.5	Errors	27
5	Sample Code.....	28
6	URL Migration Checklist	29
7	SDKs and Libraries.....	30
8	Contact Information.....	31
	Exhibit 1 Terms and Conditions.....	32

1 API Prefix

- Token : <https://api.mediatek.com/oauth/Customer/MOL/v1/token>
- FEX : <https://api.mediatek.com/Customer/FEX/P2P/v1>

MediaTek Confidential / No Disclosure

2 Access Token API Documentation

It handles fetching new tokens from an API server, storing them locally, and retrieving or generating tokens as needed. For detailed process, please refer to `api_token.py`.

Notes on obtaining Apigee OAuth Token

- The `access_token` is valid for 1 hour, and the `refresh_token` is valid for 7 days. A retry mechanism needs to be added to keep the token valid.
- Once a new `access_token` is generated, the old `access_token` will become invalid immediately.
- Every time you use Refresh token to refresh token (`/token?granttype=refresh_token`), new `access_token` will be generated.
- The OAuth API has a flow control mechanism: within an hour of the `oauth/token` API, the number of calls to the same AP and the same server cannot exceed 10 times (`oauth/token` will increase the flow limit, and the number of calls per AP is 10 times/1h)

2.1 Fetch Refresh Token

Fetches a new token from the API server.

2.1.1 Endpoint

POST `/oauth/token`

2.1.2 Headers

Content-Type: `application/x-www-form-urlencoded`

2.1.3 Authentication

Uses HTTP Basic Authentication with the client ID and secret.

2.1.4 Request Parameters

Parameter	Type	Description
username	string	The username for authentication.
password	string	The password for authentication.

Parameter	Type	Description
client_id	string	The client ID for authentication.
secret	string	The secret for authentication.

2.1.5 Response

Returns a JSON object containing the refresh token.

```
{
  "access_token": "",
  "scope": "",
  "expires_in": 239,
  "token_type": "Bearer",
  "refresh_token": "",
  "refresh_token_expires_in": 86399,
  "refresh_count": "",
  "username": ""
}
```

2.1.6 Errors

Raises a `requests.HTTPError` if the POST request fails with a non-200 status code.

2.1.7 Endpoint

POST /oauth/token

2.2 Fetch Access Token

Fetches a new access token from the server using a refresh token.

2.2.1 Headers

Content-Type: application/x-www-form-urlencoded

2.2.2 Authentication

Uses HTTP Basic Authentication with the client ID and secret.

2.2.3 Request Parameters

Parameter	Type	Description
refresh_token	string	The refresh token for authentication.
client_id	string	The client ID for authentication.
secret	string	The secret for authentication.

2.2.4 Response

Returns a JSON object containing the access token.

```
{
  "access_token": "",
  "scope": "",
  "expires_in": 239,
  "token_type": "Bearer",
  "refresh_token": "",
  "refresh_token_expires_in": 86399,
  "refresh_count": "",
  "username": ""
}
```

2.2.5 Errors

Raises a `requests.HTTPError` if the POST request fails with a non-200 status code.


```

    {
        "Email": "abc@xyz.com" # The email address of the recipient.
    }
]
},
"Subject": "demo", # The subject of the request.
"System": "API" # The system from which the request is made.
}

```

3.1.4 Response

```

"code": 200,
"count": 1,
"message": "Success",
"results": {
    "RequestId": "REQ20000087953", # request id
    "ascpargs": "{{ascp.exe path}} --ignore-host-key -d -T -U 2 -k 2 --
mode=send -i {{openssh file path}} -P 33001 -O 33001 --user=MFT3_SYS --
host=172.21.144.160 -W
ATM3_ACSJF20tTCTs_2TO9PT42bWFA6gloTs_04PexohumM4gG8AAFJdggQ6mw_NH4bArS5Vikb_3MTA -l
100000 -m 100000 \"{{file dir}}/123.txt\" \"{{aspera/DATA/MFT3_SYS/REQ20000087953}}\",
# aspera command line template
    ...
}
}

```

3.1.5 Errors

Raises a `requests.HTTPError` if the GET request fails with a non-200 status code.

3.2 Upload files

Please refer to `p2p_client.py:upload_files_by_aspera` and `p2p_client.py:upload_files_by_http`

3.3 Get Request Detail via Request Id

Description: Retrieves the details of a request by request ID.

3.3.1 HTTP Request

GET /Customer/FEX/P2P/v1/requests/{request_id}

3.3.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

3.3.3 Response

```
{
  "results": {
    // Request details
  }
}
```

3.3.4 Errors

Raises a requests.HTTPError if the GET request fails with a non-200 status code.

3.4 Query Shared History

Description: Queries shared history based on filter criteria.

3.4.1 HTTP Request

POST /Customer/FEX/P2P/v1/sharedRequestsQuerier

3.4.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8

Authorization	Bearer {access_token}
---------------	-----------------------

3.4.3 Body

```
{
  "PageIndex": 1,
  "PageSize": 10,
  "Status": "Ready",
  "RequestIn": "REQ20000087953",
  "RecceiveLike": "receiver@example.com",
  "SubjectLike": "demo",
  "ShareTimeFrom": "2023-01-01T00:00:00Z",
  "ShareTimeTo": "2023-12-31T23:59:59Z",
  "FileNameLike": "123.txt"
}
```

3.4.4 Response

```
{
  "results": {
    "Count": int, # The total number of upload requests.
    "DataList": [
      {
        "RequestId": str, # The unique identifier for the request.
        "Subject": str, # The subject of the request.
        "ShareTime": str, # The time when the request was shared
        (YYYY/MM/DD HH:MM:SS).
        "ExpireTime": str or None, # The time when the request will expire
        (YYYY/MM/DD HH:MM:SS) or None if not applicable.
        "Status": str, # The status of the request (e.g., "Uploading").
        "System": str, # The system from which the request was made.
        "Count": int # The total count of requests.
      }
    ]
  }
}
```

3.4.5 Errors

Raises a requests.HTTPError if the GET request fails with a non-200 status code.

3.5 Query Received History

Description: Queries received history based on filter criteria.

3.5.1 HTTP Request

POST /Customer/FEX/P2P/v1/receivedRequestsQuerier

3.5.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

3.5.3 Body

```
{
  "PageIndex": 1,
  "PageSize": 10,
  "Status": "Ready",
  "RequestIn": "",
  "SendLike": "sender@example.com",
  "SubjectLike": "demo",
  "ReceivedTimeFrom": "2023-01-01T00:00:00Z",
  "ReceivedTimeTo": "2023-12-31T23:59:59Z",
  "FileNameLike": "123.txt"
}
```

3.5.4 Response

```
{
  "results": {
    "Count": int, # The total number of received requests.
    "DataList": [
      {
        "MailId": str, # The unique identifier for the mail.
        "UserEmail": str, # The email address of the user who received the
request.
        "System": str, # The system from which the request was made.
        "SendTime": str, # The time when the request was sent (YYYY/MM/DD
HH:MM:SS).
        "ExpireTime": str, # The time when the request will expire
(YYYY/MM/DD HH:MM:SS).
        "Title": str, # The title of the request.

```

```

        "Status": str, # The status of the request (e.g., "Ready").
        "RequestId": str, # The unique identifier for the request.
        "Downloaded": bool, # Indicates whether the request has been
downloaded.
        "Count": int # The total count of requests.
    }
]
}
}

```

3.5.5 Errors

Raises a `requests.HTTPError` if the GET request fails with a non-200 status code.

3.6 Get Aspera Download Token By Request Id

Description: Retrieves Aspera download tokens by request ID.

3.6.1 HTTP Request

GET /Customer/FEX/P2P/v1/requests/{request_id}/AsperaDownloadCommands

3.6.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}
filenames	file1.txt/file2.txt (optional) # The names of the files to download.

3.6.3 Response

```

{
  "results": {
    "ascpargs": "", # The Aspera command arguments for downloading the file.
    "CompleteDate": "" # The date and time when the download was completed.
  }
}

```

3.6.4 Errors

Raises a `requests.HTTPError` if the GET request fails with a non-200 status code.

3.7 Get Http Download Token And URL By Request Id

Description: Retrieves HTTP download tokens by request ID.

3.7.1 HTTP Request

GET /Customer/FEX/P2P/v1/requests/{request_id}/HTTPDownloadURLs

3.7.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}
filenames	file1.txt/file2.txt (optional) # The names of the files to download.

3.7.3 Response

```
{
  "results": [
    {
      "DownloadUrl": "", # The URL to download the file.
      "FileName": "", # The name of the file to be downloaded.
      "RequestId": "", # The unique identifier for the request.
      "CompleteDate": "", # The date and time when the download was
completed.
      "Token": "" # The token for authentication.
    }
  ]
}
```

3.7.4 Errors

Raises a `requests.HTTPError` if the GET request fails with a non-200 status code.

3.8 Download files

Please refer to `p2p_client.py:download_files_by_aspera` and `p2p_client.py:download_files_by_http`

MediaTek Confidential / No Disclosure

4 MySpace API Documentation

provides methods to perform various operations such as creating, updating, deleting spaces, uploading and downloading files, and retrieving information about spaces and files. `access_token` is required for all requests. For detailed instructions on obtaining the access token, see the sample code: `api_token.py`.

4.1 Get My Space List

Retrieve the list of spaces for the current account.

4.1.1 HTTP Request

GET /Customer/FEX/MySpace/v1/spaces

4.1.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

4.1.3 Response

```
{
  "results": [
    {
      "SpaceId": 22222,
      "SpaceName": "xx",
      "Creator": "xxx",
      "Description": "xx",
      "Members": [
        {
          "Email": "xx"
        }
      ],
      "Owned": true,
      "LastModified": "2024/09/26 11:03:32",
      "Created": "2024/09/26 11:03:32",
      "MemberDelete": false,
      "MemberModify": false,
      "Owners": [
        {

```

```
        "Email": "xxx"
      }
    ],
    "RetentionDays": 180,
    "IpWhiteList": null,
    "Visitors": null
  }
]
```

4.1.4 Errors

Raises a requests.HTTPError if the GET request fails with a non-200 status code.

4.2 Get Sub Folders and Files

Retrieve the list of files and subfolders within a specified folder.

4.2.1 HTTP Request

```
GET /Customer/FEX/MySpace/v1/foldersAndFiles?path={encoded_path}
```

4.2.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

4.2.3 Response

```
{
  "results": {
    "Count": 4,
    "DataList": [
      {
        "Name": "xx",
        "Path": "xx",
        "Modified": "2023/07/31 17:39:48",
        "Type": "File",
        "Size": 4058079,
        "Count": 4
      }
    ]
  }
}
```

```
    }  
  ]  
}  
}
```

4.2.4 Errors

Raises a requests.HTTPError if the GET request fails with a non-200 status code.

4.3 Get File Info

Retrieve information about a specified file.

4.3.1 HTTP Request

GET /Customer/FEX/MySpace/v1/foldersAndFiles?path={encoded_path}

4.3.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

4.3.3 Response

```
{  
  "results": {  
    "Count": 4,  
    "DataList": [  
      {  
        "Name": "xxx",  
        "Path": "xxx",  
        "Modified": "2023/07/31 17:39:48",  
        "Type": "File",  
        "Size": 4058079,  
        "Count": 4  
      }  
    ]  
  }  
}
```

4.3.4 Errors

Raises a `requests.HTTPError` if the GET request fails with a non-200 status code.

4.4 Create Folder

Create a new folder under the specified parent path.

4.4.1 HTTP Request

POST /Customer/FEX/MySpace/v1/folders?path={encoded_parent_path}

4.4.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

4.4.3 Body

```
{
  "name": "NewFolder"
}
```

4.4.4 Response

```
{
  "results": {
    "Success": true
  }
}
```

4.4.5 Errors

Raises a `requests.HTTPError` if the GET request fails with a non-200 status code.

4.5 Rename Folder or File

Rename an existing folder or file under the specified path.

4.5.1 HTTP Request

```
PUT /Customer/FEX/MySpace/v1/foldersAndFiles?path={encoded_current_path}
```

4.5.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

4.5.3 Body

```
{
  "name": "NewName"
}
```

4.5.4 Response

```
{
  "results": {
    "Success": true
  }
}
```

4.5.5 Errors

Raises a requests.HTTPError if the GET request fails with a non-200 status code.

4.6 Delete Folder or File

Delete an existing folder or file under the specified path.

4.6.1 HTTP Request

```
DELETE /Customer/FEX/MySpace/v1/foldersAndFiles?path={encoded_current_path}
```

4.6.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

4.6.3 Response

```
{
  "results": {
    "Success": true
  }
}
```

4.6.4 Errors

Raises a requests.HTTPError if the GET request fails with a non-200 status code.

4.7 Upload Files via HTTP

Upload multiple files to the specified parent folder using HTTP. Please refer to `my_space_client.py:upload_files_via_http`.

4.7.1 HTTP Request

POST /Customer/FEX/MySpace/v1/files/HTTPUploadURLs

4.7.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

4.7.3 Body

```
{
  "ServerPath": "/test2/1232",
  "ClientPaths": [
```

```

    {
      "path": "path/to/file1.txt",
      "size": 1024
    },
    {
      "path": "path/to/file2.txt",
      "size": 2048
    }
  ]
}

```

4.7.4 Response

```

{
  "results": {
    "token": "upload_token",
    "url": "upload_url",
    "requestId": "request_id"
  }
}

```

4.7.5 Errors

Raises a `requests.HTTPError` if the GET request fails with a non-200 status code.

4.8 Download Files via HTTP

Download a file from the server to the specified target file path using HTTP. Please refer to `my_space_client.py:download_files_via_http`

4.8.1 HTTP Request

POST /Customer/FEX/MySpace/v1/files/HTTPDownloadURLs

4.8.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

4.8.3 Body

```
{
  "Paths": [
    "encoded_server_file_path"
  ]
}
```

4.8.4 Response

```
{
  "results": {
    "Url": "download_url",
    "Token": "download_token"
  }
}
```

4.8.5 Errors

Raises a requests.HTTPError if the GET request fails with a non-200 status code.

4.9 Upload Files via Aspera

Upload multiple files to the specified parent folder using Aspera. Please refer to `my_space_client.py:upload_files_via_aspera`.

4.9.1 HTTP Request

POST /Customer/FEX/MySpace/v1/files/AsperaUploadCommands

4.9.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

4.9.3 Body

```
{
```

```

"ServerPath": "/test2/1232",
"ClientPaths": [
    "path/to/file1.txt",
    "path/to/file2.txt"
]
}

```

4.9.4 Response

```

{
  "results": {
    aspera_cmd: "xxx"
    .....
  }
}

```

4.9.5 Errors

Raises a requests.HTTPError if the GET request fails with a non-200 status code.

4.10 Upload Files via Aspera

Upload multiple files to the specified parent folder using Aspera. Please refer to `my_space_client.py:upload_files_via_aspera`.

4.10.1 HTTP Request

POST /Customer/FEX/MySpace/v1/files/AsperaDownloadCommands

4.10.2 Headers

Header	Value
Content-Type	application/json; charset=utf-8
Authorization	Bearer {access_token}

4.10.3 Body

```

{
  "ServerPath": [

```

```
        "/test2/1232/t.txt"  
    ]  
}
```

4.10.4 Response

```
{  
  "results": {  
    "aspera_cmd": "xxx",  
    .....  
  }  
}
```

4.10.5 Errors

Raises a `requests.HTTPError` if the GET request fails with a non-200 status code.

5 Sample Code

[sample code.zip](#)

MediaTek Confidential / No Disclosure

6 URL Migration Checklist

New URL Path	Old URL Path
/FEX/P2P/v1/fileUploadRequests	api/ts/CreateRequest
/FEX/P2P/v1/receivedHistoriesQuerier	api/ts/ReceivedHistory
/FEX/P2P/v1/fileUploadRequests/{FEX_ID}	api/ts/requests/{FEX_ID}
/FEX/P2P/v1/requests/{FEX_ID}/AsperaDownloadCommands	api/ts/download/aspera/{FEX_ID}
/FEX/P2P/v1/requests/{FEX_ID}/HTTPDownloadURLs	api/ts/download/http/{FEX_ID}
/FEX/P2P/v1/sharedHistoriesQuerier	api/ts/SharedHistory
/FEX/MySpace/v1/spaces	api/myspace/list
/FEX/MySpace/v1/spaces	api/myspace/list
/FEX/MySpace/v1/spaces	api/myspace/list/edit
/FEX/MySpace/v1/spaces	api/myspace/list/delete
/FEX/MySpace/v1/subFoldersAndFiles	api/myspace/files/browse
/FEX/MySpace/v1/subFolders	api/myspace/files/action
/FEX/MySpace/v1/subFoldersAndFiles	api/myspace/files/action
/FEX/MySpace/v1/subFoldersAndFiles	api/myspace/files/action
/FEX/MySpace/v1/fileUploadRequestTokensForAspera	api/myspace/files/upload
/FEX/MySpace/v1/fileUploadRequestTokensForHTTP	api/myspace/files/upload/http
/FEX/MySpace/v1/fileDownloadRequestTokensForAspera	api/myspace/files/download
/FEX/MySpace/v1/fileDownloadRequestTokensForHTTP	api/myspace/files/download/http
/FEX/MySpace/v1/notifications	api/myspace/notification

7 SDKs and Libraries

Sample Code Python Version: 3.12.6. requests version:2.32.3

MediaTek Confidential / No Disclosure

8 Contact Information

Please send mail to srv_cfs_admin@mediatek.com

MediaTek Confidential / No Disclosure

Exhibit 1 Terms and Conditions

Your access to and use of this document and the information contained herein (collectively this “Document”) is subject to your (including the corporation or other legal entity you represent, collectively “You”) acceptance of the terms and conditions set forth below (“T&C”). By using, accessing or downloading this Document, You are accepting the T&C and agree to be bound by the T&C. If You don’t agree to the T&C, You may not use this Document and shall immediately destroy any copy thereof.

This Document contains information that is confidential and proprietary to MediaTek Inc. and/or its affiliates (collectively “MediaTek”) or its licensors and is provided solely for Your internal use with MediaTek’s chipset(s) described in this Document and shall not be used for any other purposes (including but not limited to identifying or providing evidence to support any potential patent infringement claim against MediaTek or any of MediaTek’s suppliers and/or direct or indirect customers). Unauthorized use or disclosure of the information contained herein is prohibited. You agree to indemnify MediaTek for any loss or damages suffered by MediaTek for Your unauthorized use or disclosure of this Document, in whole or in part.

MediaTek and its licensors retain titles and all ownership rights in and to this Document and no license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted hereunder. This Document is subject to change without further notification. MediaTek does not assume any responsibility arising out of or in connection with any use of, or reliance on, this Document, and specifically disclaims any and all liability, including, without limitation, consequential or incidental damages.

THIS DOCUMENT AND ANY OTHER MATERIALS OR TECHNICAL SUPPORT PROVIDED BY MEDIATEK IN CONNECTION WITH THIS DOCUMENT, IF ANY, ARE PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE. MEDIATEK SPECIFICALLY DISCLAIMS ALL WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, FITNESS FOR A PARTICULAR PURPOSE, COMPLETENESS OR ACCURACY AND ALL WARRANTIES ARISING OUT OF TRADE USAGE OR OUT OF A COURSE OF DEALING OR COURSE OF PERFORMANCE. MEDIATEK SHALL NOT BE RESPONSIBLE FOR ANY MEDIATEK DELIVERABLES MADE TO MEET YOUR SPECIFICATIONS OR TO CONFORM TO A PARTICULAR STANDARD OR OPEN FORUM.

Without limiting the generality of the foregoing, MediaTek makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does MediaTek assume any liability arising out of the application or use of any product, circuit or software. You agree that You are solely responsible for the designing, validating and testing Your product incorporating MediaTek’s product and ensure such product meets applicable standards and any safety, security or other requirements.

The above T&C and all acts in connection with the T&C or this Document shall be governed, construed and interpreted in accordance with the laws of Taiwan, without giving effect to the principles of conflicts of law.