

SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION
Encroachment Permit

Permit No : 282671
Permit Decision Date : 8/1/2024
Expiration Date : 8/1/2025

Type Permit

COMMUNICATIONS (Cable
TV, Telephone & Other)

Location:

<u>District</u>	<u>Work County</u>	<u>Type</u>	<u>Route</u>	<u>Aux</u>	<u>Begin MP</u>	<u>End MP</u>
3	Greenville, SC	S-	546	None	2.284	3.119

Contact Information

Applicant: Lumos

Phone: (720)597-5320

Contact: Craig Black

Address: 13 Saluda Dam
Road,

City: Greenville,

State: SC

Zip: 29611

Comments

34.977890, -82.278875(Attach sketch indicating roadway features such as: pavement width, shoulder width, sidewalk and curb and gutter location, significant drainage structure, north arrow, right of way width, and location of the proposed encroachment with respect to the roadway centerline and the nearest intersecting road on the State system.)

Special Provisions:

0004 - SCDOT SHALL BE NOTIFIED WHEN WORK DEFINED IN THE PERMIT STARTS AS WELL AS WHEN THE WORK IS COMPLETED. REFERENCE SHALL BE MADE BY PERMIT NUMBER.

0101 - SHOULDER SOD DESTROYED BY THIS INSTALLATION TO BE REPLACED FOR THE ENTIRE AREA. THE AREA SHALL BE RE-SHAPED AND ROLLED TO THE CROSS SECTION EXISTING PRIOR TO THIS WORK.

0102 - BORE PITS SHALL BE CLOSED IMMEDIATELY AFTER INSTALLATION.

0103 - THE PROPOSED ENCROACHMENT SHALL BE TRENCHED TO A MINIMUM DEPTH OF 42" BELOW THE CROSS SECTION AS ORIGINALLY CONSTRUCTED.

0105 - ALL EXCAVATED MATERIAL SHALL BE PLACED ON THE SIDE OF THE TRENCH AWAY FROM THE TRAVELED ROADWAY, AND SHALL BE NO CLOSER THAN FIFTEEN (15) FEET TO THE EDGE OF PAVEMENT.

0107 - TRENCH TO BE PROPERLY BACK-FILLED AND THOROUGHLY TAMPED. THE ENTIRE DISTURBED AREA SHALL BE RE-SHAPED AND DRESSED OUT IN A WORKMANSHIP LIKE MANNER.

0108 - FLOWABLE FILL SHALL BE USED AS BACK-FILL MATERIAL.

~~0110 - FLOWABLE FILL MAY BE USED AS AN ALTERNATE FOR TRENCH BACK FILL~~

MATERIAL.

0111 - OPEN CUTS AND/OR BELL HOLES WITHIN THE ROAD PAVEMENT SHALL BE CUT IN NEAT LINES AND REPAIRED.

0112 - ALL WATER METERS, AIR VALVES, ELECTRIC TRANSFORMERS, CATV CONNECTION BOXES, TELEPHONE PEDESTALS, AND/OR OTHER UTILITY/SPLICE BOXES SHALL BE PLACED AT THE RIGHT-OF-WAY LINE.

0115 - WHERE PAVEMENT IS CUT THE WORK SHALL BE DONE IN CLEAR WEATHER WHEN TRAFFIC IS LIGHTEST. THERE SHALL BE NO TRENCH LEFT OPEN IN THE TRAVELED WAY WHEN WORK IS NOT IN PROGRESS.

0116 - PAVEMENT SHALL BE CUT TO NEAT LIES AND THE TRENCH BACK-FILLED USING FLOWABLE MATERIAL AND TAMPED IN 6" LAYERS TO 95% DENSITY.

0117 - OPEN TRENCHES SHALL BE COVERED WITH METAL PLATES WHEN THE PAVEMENT CANNOT BE RESTORED THE SAME DAY. PLATES SHALL BE MONITORED PERIODICALLY TO ENSURE THAT THE TRENCH IS PROPERLY COVERED.

0118 - AN OPEN CUT IS AUTHORIZED ONLY TO THE EXTENT NECESSARY TO MAKE A CONNECTION TO THE EXISTING LINE. DRY BORE UNDER REMAINING ROAD TO THE EXISTING LINE.

0119 - INSTALLATION TO BE MADE BY THE WET OR DRY BORE METHOD IN SUCH A MANNER AS NOT TO DISTURB EXISTING PAVEMENT.

0121 - BELL HOLE CUT MUST BE COVERED WITH A STEEL PLATE UNTIL A PERMANENT PATCH HAS BEEN MADE. PLATE SHALL BE MONITORED PERIODICALLY TO ENSURE THAT BELL HOLE IS PROPERLY COVERED.

0123 - ALL WORK PERFORMED IN CONNECTION WITH THIS PERMIT SHALL CONFORM TO THE SCDOT "A POLICY FOR ACCOMODATING UTILITIES ON HIGHWAY RIGHT-OF-WAY" MOST CURRENT EDITION.

0125 - ALL CROSSLINE PIPES ARE TO BE LOCATED AND FLAGGED PRIOR TO BEGINNING OPERATION.

0209 - DISTURBED VEGETATION SHALL BE RESEDED ACCORDING TO THE SPECIFICAION FOR HIGHWAY CONSTRUCTION.

0301 - THE DITCHES AND/OR SHOULDERS DISTURBED DURING THE INSTALLATION SHALL BE RE-ESTABLISHED TO PROPER GRADE, ORIGINAL CROSS SECTION, STABILIZED, AND ALL DRAIN PIPES CLEARED.

0302 - NO EXCAVATION SHALL BE LEFT OPEN ALONG HIGHWAY.

0303 - THE ENTIRE DISTURBED AREA SHALL BE TOP-SOILED USING 3" OF SELECTED MATERIAL AND RE-GRASSED TO SCDOT SPECIFICATIONS.

0304 - PAVEMENT MARKINGS ALTERED DURING THIS INSTALLATION SHALL BE RESTORED BY THE APPLICANT.

0306 - TRAFFIC CONTROL, LIGHTS, SIGNS AND FLAG-MEN WILL BE FURNISHED BY APPLICANT AND WILL CONFORM TO PART VI OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

0307 - NO PART OF THE TRAVEL-WAY IS TO BE BLOCKED DURING CONSTRUCTION AND MAINTENANCE.

0308 - WORK SHALL NOT BE PERFORMED DURING THE HOURS OF 7-9 AM OR 4-6 PM.

0310 - FIELD CHANGES, IF NECESSARY, MUST BE APPROVED IN WRITING BEFORE ACTUAL CONSTRUCTION OF PROPOSED CHANGES.

0311 - SEDIMENT AND EROSION CONTROL DEVICES SHALL BE USED TO

MINIMIZE THE MOVEMENT OF SEDIMENT.

0312 - THE PERMITTEE SHALL HOLD THE DEPARTMENT HARMLESS FOR DAMAGES TO BOTH UPSTREAM AND DOWNSTREAM PROPERTIES.

0316 - ALL NON-PERMITTED OBJECTS ON THE RIGHT-OF-WAY, WHICH MUST BE REMOVED, SHALL NOT BE REPLACED ON THE RIGHT-OF-WAY WITHOUT WRITTEN PERMISSION OF THE DEPARTMENT.

0317 - THE APPLICANT IS TO PROVIDE ALL THE NECESSARY MAINTENANCE TO THE AREA BEAUTIFIED.

0318 - THE APPLICANT SHALL BE RESPONSIBLE FOR IMMEDIATE REMOVAL OF SUCH TRAFFIC HAZARDS AS MUD, DEBRIS, LOOSE STONE, AND TRASH AS MAY BE WASHED OR SPILLED ON THE TRAVELED ROADWAY AS A RESULT OF THE PROPOSED WORK.

0320 - ALL DEBRIS TO BE CLEARED FROM THE RIGHTS-OF-WAY WITHIN TEN (10) DAYS.

9999 - See Attached for Additional Special Provisions