

ROADMAP MODEL

ICCT Roadmap model v2.18 documentation

9/29/2025



Table of Contents

INTRODUCTION	1
<i>Acknowledgments</i>	2
SALES	2
<i>Historical sales</i>	3
<i>Projected sales</i>	6
<i>Used vehicle imports</i>	6
STOCK TURNOVER	8
<i>From-age-zero turnover</i>	8
<i>Year-over-year turnover</i>	10
<i>Major Markets</i>	10
MILEAGE	10
<i>Mileage degradation</i>	11
<i>Scrappage policies</i>	11
<i>Passenger-freight activity</i>	11
VEHICLE EFFICIENCY	12
EMISSIONS	13
<i>Emissions standards</i>	13
<i>Emission factors</i>	14
<i>Emission deterioration</i>	16
<i>Plug-in hybrid electric vehicles (PHEVs)</i>	17
<i>High emitters</i>	17
<i>Sulfur effects</i>	18
<i>Biodiesel effects on local air pollutants</i>	19
<i>Well-to-wheel GHG emissions</i>	19
POLICIES AND SCENARIOS	20
<i>Scenario inputs</i>	21
<i>Subregional policies</i>	22
<i>Vehicle segmentation</i>	22
<i>Combining Subregions and Segments</i>	23

INTRODUCTION

The ICCT's Roadmap model is a global transportation emissions model covering all on-road vehicle activity in over 185 countries. The Roadmap model is intended to help policymakers worldwide to identify and understand trends in the transportation sector, assess emission impacts of different policy options, and frame plans to effectively reduce emissions of both greenhouse gases (GHGs) and local air pollutants. It is designed to allow transparent, customizable estimation of transportation emissions for a broad range of policy cases.

Making use of the ICCT's worldwide tracking of transportation policies, the model provides annual estimates of historical and future emissions under currently adopted policies out to 2050 for USA, and 2070 everywhere else. Roadmap estimates historical and projected well-to-wheel CO₂ emissions disaggregated by powertrain and fuel type as well as emissions of 15 local air pollutants. This version of the model includes six vehicle types and 11 powertrain and fuel combinations, as shown in Tables 1 and 2, respectively.

Table 1: *Roadmap vehicle types.*

Roadmap name	Vehicle category	Description
MC	MC	Two and three wheelers
PC	LDV	Passenger cars (GVW < 3.5 tonnes)
LCV	LDV	Light commercial vehicles (GVW < 3.5 tonnes)
Bus	HDV	Urban and coach buses (GVW ≥ 3.5 tonnes)
MDT	HDV	Medium-duty trucks (GVW 3.5-15 tonnes)
HDT	HDV	Heavy-duty trucks (GVW > 15 tonnes)

Table 2: *Roadmap powertrain types.*

Roadmap powertrain	Roadmap fuel	Description
ICE Diesel	Diesel	Internal combustion engines and conventional hybrids powered by diesel and biodiesel blends
ICE Gasoline	Gasoline	Internal combustion engines and conventional hybrids powered by gasoline and ethanol blends
ICE Biodiesel	Biodiesel	Pure biodiesel powertrains
ICE Ethanol	Ethanol	Pure ethanol powertrains
PHEV Diesel	Diesel, Electricity	Plug-in hybrid electric vehicles powered by diesel fuel and electricity
PHEV Gasoline	Gasoline, Electricity	Plug-in hybrid electric vehicles powered by gasoline fuel and electricity

ICE CNG	CNG	Internal combustion engines powered by compressed natural gas and biogas
ICE LNG	LNG	Internal combustion engines powered by liquefied natural gas
ICE LPG	LPG	Internal combustion engines powered by liquefied petroleum gas
BEV	Electricity	Battery electric vehicles
FCEV	Hydrogen	Fuel cell electric vehicles powered by hydrogen

Specifically, the ISO codes of countries modeled in this version of Roadmap are: ABW, AFG, AGO, ALB, ARE, ARG, ARM, ATG, AUS, AUT, AZE, BDI, BEL, BEN, BFA, BGD, BGR, BHR, BHS, BIH, BLR, BLZ, BMU, BOL, BRA, BRB, BRN, BTN, BWA, CAF, CAN, CHE, CHL, CHN, CIV, CMR, COD, COG, COL, COM, CPV, CRI, CUB, CYM, CYP, CZE, DEU, DJI, DMA, DNK, DOM, DZA, ECU, EGY, ERI, ESP, EST, ETH, FIN, FJI, FRA, GAB, GBR, GEO, GHA, GIN, GMB, GNB, GNQ, GRC, GRD, GTM, GUY, HND, HRV, HTI, HUN, IDN, IND, IRL, IRN, IRQ, ISL, ISR, ITA, JAM, JOR, JPN, KAZ, KEN, KGZ, KHM, KIR, KNA, KOR, KWT, LAO, LBN, LBR, LBY, LCA, LKA, LSO, LTU, LUX, LVA, MAR, MDA, MDG, MDV, MEX, MKD, MLI, MLT, MMR, MNE, MNG, MOZ, MRT, MUS, MWI, MYS, NAM, NER, NGA, NIC, NLD, NOR, NPL, NZL, OMN, PAK, PAN, PER, PHL, PNG, POL, PRK, PRT, PRY, PYF, QAT, ROU, RUS, RWA, SAU, SDN, SEN, SGP, SLB, SLE, SLV, SOM, SRB, SSD, STP, SVK, SVN, SWE, SWZ, SYC, SYR, TCD, TGO, THA, TJK, TKM, TLS, TON, TTO, TUN, TUR, TZA, UGA, UKR, URY, USA, UZB, VCT, VEN, VNM, VUT, WSM, YEM, ZAF, ZMB, ZWE.

Many of the default model inputs are sourced from the IEA Mobility Model (MoMo)’s 2025 version. Activity projections (on a vehicle-kilometer basis, for each vehicle category) have been updated based on comparisons with IEA World Energy Outlook 2024 results and with previous IEA activity projections. In some cases, activity projections were adjusted based on implied vehicle sales in 2030 or 2050, or ratios between vkm and GDP per capita growth. Additional country-specific data is included for key regions where available. Using sales inputs and calibrated survival curves, Roadmap’s turnover module first compiles a detailed inventory of vehicle stock. Applying per-vehicle mileage rates and energy intensities, the model next calculates detailed energy consumption estimates. These, in turn, are a key input to the emissions calculations. This document describes the inputs and methods used in each major calculation step as well as some additional optional components available to users.

Acknowledgments

Roadmap was first developed in 2019 by Caleb Braun, Lingzhi Jin, and Josh Miller. Version 2.18 was developed in 2025 by Stefan Walzer-Goldfeld, Jonathan Benoit, and Gabe Hillman Alvarez.

SALES

Together with vehicle survival curves, annual vehicle sales are the main driver of vehicle stock within Roadmap. Default historical data on vehicle sales are sourced from country-specific data sources and from the MoMo database, which provides historical sales data for 45 regions, including 31 individual countries.

Historical sales

For countries within aggregate MoMo regions, new vehicle sales are disaggregated based on each country's share of energy consumption within the region. Energy balances are derived from IEA's World Energy Balances 2025 edition, which covers road transport energy consumption by fuel type from 1971-2023. Energy consumption estimates for 2024 (the final historical year) are extended from 2023 by applying growth rates derived from MoMo's energy consumption. Multiplying each country's fuel consumption shares by the regional total sales volumes gives country-specific vehicle sales for each of the 11 powertrain types. Finally, the ratio of used imports to new vehicle sales in each MoMo region is used to split the total sales volumes into new vehicle sales and used imports.

Note that the World Energy Balances lack data on LNG and Hydrogen and as such, the total sales are assumed to be 0 unless otherwise specified by an alternative data source. LNG and CNG are grouped into a single category in the World Energy Balances, while the MoMo data only include CNG. Therefore, no ICE LNG specific vehicle sales or stock are present in the model at the time of writing, so this does not pose an issue. For hydrogen, historical and projected sales of FCEVs are specified independently.

Historical sales for several countries are updated using country-specific data. Table 3 shows these data sources, ordered by priority. If an ISO + Vehicle + CY combination appears multiple times, assume that the first source in the table is the final source.

Table 3: Data sources for historical new vehicle sales. This table is ordered by priority, meaning that the top row of data takes precedence over all data below it.

Source	Vehicles	Region / ISO	Data Type	Calendar Years
Atlas Public Policy	PC, LCV	USA	New Sales volumes, new sales shares by powertrain	2020-2023
National Automobile Dealers Association	HDT	USA	New Sales volumes, new sales shares by powertrain	2020
Oak Ridge National Laboratory	HDT, MDT, Bus	USA	New Sales volumes, new sales shares by powertrain	2020-2023
S&P Global	HDT, MDT, Bus	USA	New sales volumes, new sales shares by powertrain	2011-2020, 2024 (MDT, HDT)

MOVES4	All	USA	New sales volumes, new sales shares by powertrain	2000-2022
ZEDATA	PC, LCV, Bus, MDT, HDT	CHN	New sales volumes, new sales shares by powertrain	2020-2022 (PC, LCV), 2012-2023 (Bus, MDT, HDT)
Gasgoo	All	CHN	New sales volumes, new sales shares by powertrain	2023 (PC, LCV) and 2024
VAMM	MC	VNM	New sales volumes, new sales shares by powertrain	2017-2021
INEGI	Bus, MDT, HDT	MEX	New sales volumes, new sales by powertrain shares	2018-2024
Mexican Automotive Industry Association (AMIA)	PC, LCV	MEX	New sales volumes, new sales shares by powertrain	2005-2020
Jato	PC, LCV	BRA, MEX	New sales volume, new sales shares by powertrain	2021-2024 (only 2024 for BRA sales shares by powertrain)
ADK Automotive	All	BRA	New sales volumes	1970-2020
Asociación Nacional de Movilidad Sostenible (ANDEMOS)	All	COL	New sales volumes, new sales shares by powertrain for BEVs and PHEVs	2024
Australian Infrastructure Statistics with the Federal Chamber of Automotive Industries 2024 sales data	PC, LCV	AUS	New sales volumes, new sales shares by powertrain	1997-2024

Statistics Canada Transportation Statistics	PC, LCV	CAN	New sales volumes, new sales shares by powertrain	2010-2024
EV Volumes	PC, LCV	ARE, ARG, BRA, CHL, COL, IDN, ISR, JPN, KOR, MEX, MYS, NZL, PHL, RUS, SAU, SGP, THA, TUR, UKR, USA, VNM, ZAF	New sales volumes, new sales shares by powertrain	2011-2024. Note: only 2024 for ARG and VNM
ICCT's Pocketbook	PC, LCV	European Union, ISL, GBR, NOR, CHE, TUR	New sales volumes, new sales shares by powertrain	2001-2023
IHS Europe (now S&P Global)	Bus, MDT, HDT	European Union aggregated and selected European countries	New sales volumes, new sales shares by powertrain	2005-2023
Dataforce	PC, LCV, Bus, MDT, HDT	European Union	New sales volumes, new sales shares by powertrain	2024
ACEA Bus, MDT, HDT (PC / LCV available if not covered in Pocketbook) European Union, ISL, GBR, NOR, CHENew sales volumes2000-2018 (MC), 2000-2019 (PC), 1997-2019 (LCV), 1980-2021 (Bus, MDT, HDT). Note: Pocketbook data for LDV and IHS/S&P data for HDV take priority wherever available India Emissions Model and Segment Y	All	IND	New sales volumes, new sales shares by powertrain	2000-2024
IEA's Mobility Model (MoMo 2025)*	All	All	All	1970-2024

* In some cases, MoMo 2024 data is used instead of MoMo 2025, where expert analysis found the data for MoMo 2025 to be implausible.

Projected sales

New vehicle sales volumes are projected using compound annual growth rates (CAGRs) which have been calibrated based on projected vehicle activity growth rates. For EU countries, sales growth rates are calibrated such that modeled activity growth matches the EU Reference Scenario 2020's projected change in passenger transport activity and freight demand. For the USA, MOVES4 projected sales are provided and utilized for the full range out to 2050. For the rest of the world, long-term sales growth rates are calibrated to targets derived from expert analysis of MoMo's freight and passenger activity projections under the IEA's Stated Policy Scenario ([STEPS](#)). Activity growth targets from the latest release (2025) of STEPS are used preferentially; however, in cases where those projections are deemed unrealistic, targets are instead derived from either (a) an averaging of previous (2020-2024) releases of STEPS, or (b) a single previous release which is advanced using modeled activity growth through 2024.

Given the disparity in annual projections because of COVID-19 related disruptions, the model tries to use an average estimate wherever possible. For India, the projected sales from the IEM BAU scenario are used until 2026-2030, specifically till 2026 for Buses, 2028 for heavy trucks and light commercial vehicles, and 2030 for other vehicle types. This is done to ensure that the short-term sales projections are more accurate than those made by the IEA; after this point the calibrated growth rates are used. Similarly for China, sales growth rates for Bus, LCV, MDT, and HDT are adjusted based on recent market trends and published projections from the China Society of Automotive Engineers. The following equation is used to project new sales for each country (C) and vehicle type (V):

$$Sales_{C,V,y2} = Sales_{C,V,y1} \times (1 + CAGR_{C,V,G})^{y2-y1}$$

Where:

- $y1$ = The first year of the growth period
- $y2$ = The second year of the growth period
- G = The growth period $y1$ to $y2$

The timeline may be broken into multiple growth periods (e.g., 2024-2030, 2030-2050, 2050-2070), but in all cases, the last year ($y2$) of the last growth period is the model end year (2070). The first year ($y1$) of the first growth period is 2024.

Used vehicle imports

Roadmap includes default data quantifying total imports of used vehicles and estimates their characteristics based on country-specific import policies. The top vehicle-importing regions are Africa (excluding South Africa), the Middle East (excluding Israel), Latin America (excluding Argentina, Brazil, and Chile), Japan, Russia, and New Zealand. It should be noted, however, that data on used vehicle flows is sparse and often lacks detail on vehicle types and final destinations. For example, a large quantity of used vehicles imported to the United Arab Emirates are quickly re-exported to African countries ([UNEP, 2020](#)) and as a result may be reported as imports to both the United Arab Emirates and the final

destination. Roadmap adjusts vehicle survival rates to align with real-world stock data that accounts for the export of used vehicles.

To support flexibility in modeling used vehicle imports, Roadmap calculates how many used imports enter the fleet for each new vehicle sold using a ratio of used to new sales. Users can therefore provide the model with alternate data for new sales, used sales, or total sales individually without needing to adjust the other assumptions.

As per Ecologic ([Ecologic, 2020](#)), Intra-EU trade is largely from Western European countries such as Germany, France, Netherlands etc. to Eastern European countries such as Poland, Romania, and Bulgaria. EU countries are also allowed to export vehicles to select non-EU neighbors such as Serbia, Turkey, and Albania. Passenger cars are the most imported used vehicle. Most countries will consider the amount of air pollution that is generated by an imported vehicle when calculating their registration tax, and some countries such as Finland, Hungary, and Serbia outright ban the import of vehicles that do not adhere to certain EU pollution standards (generally at least Euro 3 for passenger vehicles, and Euro 5 for commercial vehicles).

The Ecologic report also estimates the volume of used vehicles imported by specific European countries in 2017. These volumes are used in conjunction with the new vehicle sales data from the model to obtain used/new sales shares for each country and vehicle type, which by default is assumed to be constant going into the future. Outside of Europe, the ratio of used to new sales from MoMo is utilized by default, except when UNEP 2015-2020 LDV trade flow data reports imports in regions where MoMo reports none. In those regions, the ratio of used LDV imports from UNEP to new LDV sales from MoMo is utilized for LDV instead.

The ages and emission control technologies of used vehicle imports are determined one of several ways:

1. Based on the maximum age limit set by some vehicle-importing countries
2. Based on the minimum Euro standard set by some vehicle-importing countries
3. Based on country-specific assumptions for the average age of used vehicle imports
4. Based on default ages applied to countries with no specific input data

In all cases, we assume the entry age is subject to an upper limit of 15 years for HDV, 10 years for LDV and MC, and 3 years for all ZEVs (configurable by scenario input). See the emission standards section for more details on determining the age of used vehicle imports.

Because vehicle imports are highly variable year to year, by default the model assumes that the future ratio of used imports to new vehicle sales is an average of the 5 most recent years of data. This share is assumed to remain constant for all projected years; however, users may provide alternate ratios to replace the default assumptions.

Although the total number of used imports is determined by scaling the number of new vehicle sales, the powertrain shares for used imports are calculated independently.

For LDV and MC, the model uses the source shares of used imports (default shares obtained from UNEP LDV trade flow data) to extract the used powertrain shares in the importing countries from the new powertrain shares in the exporting countries at model year $MY = CY - \text{EntryAge}$. E.g., if used cars are entering at age five, their powertrain share is assumed to be that of new cars in their source country, five years ago. Both the source shares and resulting used powertrain shares defaults may be overwritten by user inputs.

For HDV, the default powertrain shares of used imports are taken directly from MoMo shares for the importing countries and conservatively forward filled, as less robust data on the trade flow patterns is available for these vehicles. Nonetheless, these can also be overwritten by the user. Used HDV import restrictions are also modeled following UNEP's global overviews ([UNEP, 2024](#)).

STOCK TURNOVER

Roadmap keeps track of the age distribution of the fleet at every timestep based on new vehicle sales, the import age of used vehicles, and region- and vehicle-specific retirement rates. There are two methods used to estimate stock turnover: one is based on the fraction of vehicles surviving from the original sales year, and the other is based on the fraction of vehicles surviving from one year to the next. Detailed baseline stock by age is provided for four major markets: EU, USA, China, and India.

From-age-zero turnover

From-age-zero survival curves represent the fraction of vehicles surviving from the original sales year. These survival curves are modeled using Weibull distributions (see [Hao et al. \(2011\)](#) for more details).

These survival curves are defined as:

$$e^{-(x/\lambda)^k}$$

Where:

- x = Age of vehicle
- λ = Steepness parameter
- k = Shape parameter = 5

Example from-age-zero survival curves




Figure 1: Example from-age-zero survival curves.

The steepness parameter is calibrated using historical stock and sales inventories and subject to reasonable limits determined by expert judgment. These limits were added to account for the fact that the stock reported in many emerging markets and developing economies is simply cumulative annual registrations (and hence does not correctly account for vehicle scrappage). Since the 2025 IEA road database update attempted to calibrate vehicle ages to meet these reported stocks in several such countries (with similar limits imposed, so that reported stocks were not actually met), these limits were informed by previous versions of the IEA road database and were added to ensure reasonable lifetimes were assumed. The limits are provided in Table 4.

Table 4: Upper and lower limits on survival curve steepness parameter.

Limit	MC	PC	LCV	Bus	MDT	HDT
Upper limit	15*	28	28	24	28	28
Lower limit	9	15	7	13	13	11

* With the exception of Vietnam as a result of expert analysis and [published research](#)

For most regions, the default from-age-zero survival curves are calibrated using stock and sales data from the MoMo database; however, some regions use more-detailed national fleet data for recent years. For each country (C) and vehicle type (V), the vehicle stock in a calendar year (CY) of a given model year (MY) is calculated:

$$Stock_{CY,MY} = Sales_{MY} \times Survival_{C,V}(CY - MY)$$

From-age-zero survival curves are applied by default to all countries for new sales as well as used vehicle imports. For used vehicles, these survival curves apply starting from when the vehicle enters the country.

Year-over-year turnover

The alternate method for estimating fleet turnover uses year-over-year survival curves. These curves represent the fraction of vehicles surviving from one year to the next. To be used effectively, a comprehensive inventory of the fleet broken down by age should be given for the base year. Unlike the from-age-zero survival curve method, used vehicles are actually treated as the age they are and not considered "new" when they enter a fleet. In this case, for each country (C) and vehicle type (V), the vehicle stock in a calendar year (CY) of a given model year (MY) is calculated:

$$Stock_{CY,MY} = Stock_{CY-1,MY} \times Survival_{C,V}(CY - MY)$$

In the case of age zero vehicles ($CY = MY$), sales are used instead of the previous year's stock:

$$Stock_{CY,MY} = Sales_{MY} \times Survival_{C,V}(0)$$

The year-over-year curves are applied by default to EU countries for new sales as well as used vehicle imports. This method is applied to accommodate detailed inputs on the starting age distribution of the vehicle stock and to model intra-EU vehicle trade.

Major Markets

The EU, USA, India, and China each have baseline stock by age and survival curves for stock turnover. The EU data are derived from ACEA for PC and LCV till 2024 and from [ACEM](#) for MC till 2024. For HDVs (MDT, HDT, Bus), data till 2024 are from an internal compilation of stock data from ACEA that is disaggregated by age using sales data from the IHS (now S&P) and IEA's Mobility Model. For the USA, the stock by age and survival curves data come from MOVES4 and for India, the same data are from IEM with additional inputs from transportation sector experts in the country. For China, stock by age is aggregated and used with from-age-zero survival curves which are derived from an internal meta-analysis of data from VECC and China Statistical Yearbook.

MILEAGE

Total vehicle-kilometers traveled (VKT) is calculated by multiplying the number of vehicles in the stock by the average annual mileage, based on the vehicle type and country. Historical per-vehicle mileages are calibrated to align model estimates of energy consumption with historical energy balances, within reasonable limits determined by expert judgment. The limits were defined based on the lower and upper quintiles of the global vehicle mileage distribution over recent years from the 2025 version of IEA road database and Roadmap. Setting lower and upper bounds on mileage enables identification of cases

of countries where the mileage estimates for a given vehicle type are very low, while they are very high for another vehicle type, and where the modelled fuel consumption by both vehicle categories is likely misallocated. For instance, if MDT mileages in a given country are close to the lower limits, and HDT mileages are close to the upper limits, both mileages can be reasonably adjusted closer to the mean global values to provide a better overall estimate of mileage (and diesel consumption) across trucks. The limits are provided in Table 5.

Table 5: *Upper and lower limits on annual vehicle-kilometers traveled per vehicle.*

Limit	MC	PC	LCV	Bus	MDT	HDT
Lower Limit	1700	5000	7300	8000	10700	14800
Upper Limit	16400	27700	43000	58000	66000	87000

Unless otherwise specified, annual mileages are assumed to remain constant in future years.

Mileage degradation

Optionally, an age-based mileage adjustment can be made which applies mileage degradation curves to the fleet. This does not significantly alter total VKT, but it shifts mileage to newer vehicles. Mileage degradation is regionally implemented for European Union, China and USA based on ICCT internal analysis except for USA – where the data is directly taken from MOVES. For every other region, global average mileage degradation factors are used.

Scrappage policies

Roadmap can also model the impacts of policies that are designed to shift activity from older, typically more polluting, vehicles to newer vehicles. Examples of such policies include scrappage and/or retrofit programs and low-emission zones. While these policies are likely to have effects on vehicle stock, these policies are currently only modeled as shifts in VKT among vehicle technologies as opposed to affecting the total level of VKT or vehicle stock. In other words, any scrappage of older vehicles (that would have traveled a certain amount of VKT) is treated as an equivalent increase in VKT by newer vehicles.

This module takes as an input the percent of VKT for each specified vehicle population (based on any of age, standard, vehicle type, fuel type) that should be reassigned to newer vehicles. Users can also specify the fuel type and model year of the vehicles that receive the shifted activity.

Passenger-freight activity

Alongside the calculation of vehicle activity, Roadmap calculates passenger-freight activity by multiplying load factors—defined as the number of passengers or amount of freight (in tonnes) a vehicle carries on average—by VKT. Passenger activity (passenger-km) is calculated for Bus, PC, and MC; while freight activity (tonne-km) is calculated for LCV, MDT, and HDT.

Default data for load factors come from IEA STEPS projections, though users can specify their own load factors for specific ISOs, vehicle types, and years. The calculation of passenger-freight activity is performed alongside other Roadmap calculations and does not impact vehicle stock, sales, or other quantities.

VEHICLE EFFICIENCY

Roadmap's default data on the energy intensities of new vehicles are derived from a combination of country-specific data sources, ICCT analyses, and historical data from the MoMo database. Vehicle- and powertrain-specific energy intensities by model year are sales-weighted and adjusted to reflect differences between on-road performance and test cycle values. USA energy intensity data are based on detailed energy consumption and vehicle mileage data from MOVES4. Adjustments to EU energy intensity data for PC and LCV are based on the real world-type approval gap data provided by the [European Environmental Agency](#). China energy intensity data are based on inputs developed for an ICCT analysis of China's 15th Five Year Plan, which include the impact of [Stage 4 fuel consumption standards](#) for HDVs. Data on energy intensity for ICE Diesel MDT and HDT in India are sourced from [ICCT research](#) on truck fuel efficiency in India. In countries that are not covered individually by available data sources or analysis, default energy intensities are based on the matching aggregate region in the MoMo database.

Energy intensities for each of the powertrain types are derived from the “Default AFV MPGGE (MPDGE) Relative Ratio” values found in the Argonne National Laboratory [AFLEET Tool 2020](#). In order to match the more aggregated vehicle types in the Roadmap model, the vehicle types given in the AFLEET Tool are weighted in their respective Roadmap equivalents using their vehicle miles traveled. These weights are subsequently used to calculate the aggregated ratio for Roadmap vehicle types. The final energy intensity values for alternative powertrain types (everything but ICE Gasoline and ICE Diesel) are calculated using the ratio to the ICE value that is predominant for that vehicle type. This is ICE Gasoline for PC and MC and ICE Diesel for all other vehicle types. The equation below represents the calculation, where $[w_1, \dots, w_n]$ represents all the weights of AFLEET vehicle types that compose a Roadmap vehicle type.

$$EI_{alternative} = \left(\sum_{i=w_1}^{w_n} \frac{i}{AFLEET\ Ratio} \right) \times EI_{ICE}$$

Users can adjust these energy intensity ratios for any combination of countries, vehicle types, and model years.

Historical energy intensities from the MoMo database are bounded to be within reasonable limits as determined by expert judgement. The limits were determined based on the distribution of energy intensities across all regions for each powertrain type. The bounds are applied to the most recent year of data (2024). The year-over-year change in energy intensity for each powertrain in each region are also

bounded, following expert judgement, to ensure realistic assumptions on yearly technological developments.

Projected new vehicle energy intensities are calculated based on user-specified inputs. By default, these inputs are specified as annualized rates of efficiency improvement by vehicle type for 16 world regions (defined in the model as RoadmapRegion); however, the user can supply detailed inputs for any combination of countries, vehicle types, fuel types, and calendar years. These inputs are intended to reflect changes in real-world fuel consumption (after applying on-road adjustment / CO₂ gap).

EMISSIONS

Emissions standards

On-road emissions are heavily dependent on the emissions control technologies of the vehicle fleet. The Roadmap model contains a frequently updated database of emission control regulations for at least 75 countries and the EU. Roadmap assumes that from the year a regulation takes effect onward, all new vehicles are sold with the required emission control technologies. (For more on how Roadmap accounts for tampered/degraded controls, see High emitters below.) Emission standards are classified based on their closest equivalents within the Euro emission standard categories.

The emission standards of imported vehicles are more difficult to determine. Many countries have policies that restrict old or dirty vehicles. The three cases included in Roadmap are:

1. A complete ban of used vehicle imports
2. Restrictions based on vehicle's age
3. Restrictions based on vehicle's standard

In case 1, the country cannot import used vehicles at all, so all vehicles follow the same emission standard timeline.

In case 2, it is conservatively assumed that all imported vehicles are the maximum age allowed. The import year and import age are used to calculate the model year of the entering vehicles. For LDV and MC, used imports are disaggregated by exporting country, and the vehicle's model year is matched to the emission standard timeline of the *exporting* country. For HDV, we lack trade flow data to disaggregate the vehicles by exporting country, so the model year is matched to the standard timeline of the *importing* country.

In case 3, the emission standard is restricted to the earliest standard that complies with the importing country's policies. This case can also be used to directly input the emission control levels assumed for imported used vehicles. Using the reverse process used in case 2, this standard is used to estimate the age of the entering vehicle. Similarly, it is conservatively assumed that all imported vehicles are the maximum age that still comply with the control standard.

In all cases, Roadmap assumes the emissions performance of used vehicle imports is equivalent to or worse than new vehicles.

Emission factors

Tailpipe emission factors are sourced from a combination of emission factor models, remote sensing campaigns, ICCT analyses, and other technical studies. Emission factors for vehicles certified to European-equivalent standards are based on real-world measurements from The Real Urban Emissions Initiative ([TRUE](#)), the European Environment Agency's European Monitoring and Evaluation Programme (EMEP), the Handbook Emission Factors for Road Transport (HBEFA), and ICCT adjustments (e.g., for deterioration). Emission factors for vehicles certified to US-equivalent and Mexico standards are sourced from EPA's Motor Vehicle Emission Simulator (MOVES) and Eastern Research Group's (ERG) application of US-based MOVES to Mexico (MOVES-Mexico), respectively, both with ICCT adjustments (e.g., based on real-world measurements). China standards come from ICCT's China model. Currently the Roadmap model does not estimate non-exhaust emissions such as brake and tire wear.

In cases where real-world measurement or region-specific modeling is not available (see Table 6), countries are assigned a proxy and emission factors are applied from that region. Countries are assigned proxy regions based on expert judgement following several criteria: fuel sulfur content, inspection and maintenance practices, import and used vehicle policies, income, and regional proximity. In cases where a country is expected to perform worse than its proxy region, adjustments are made (see High Emitters section).

Table 6: Summary of remote sensing emission factor data coverage from TRUE campaigns.

Location of campaign	Pollutants	Vehicle categories
Colorado and Virginia, USA	NO _x	HDV
>15 campaigns in various European regions	PM _{2.5} , NO _x , CO	HDV, LDV
Bogotá, Colombia	PM _{2.5} , NO _x , CO	HDV, LDV, MC
Jakarta, Indonesia	NO _x , CO	HDV, LDV, MC
São Paulo, Brazil	PM _{2.5} , NO _x , CO, NH ₃	HDV, LDV, MC
Kampala, Uganda	NO _x , BC	HDV, LDV, MC
Mexico City and State of Mexico, Mexico	PM _{2.5} , NO _x , CO	LDV

Data from more than 15 TRUE remote-sensing campaigns in various European regions are combined into a unified set of PM_{2.5} and NO_x emission factors, which form the basis of these emission factors. For heavy-duty trucks and buses, emission factors are observed to vary significantly across different road types (highway, suburban, urban), so we calculate an average emission factor weighted by road type activity shares using data from HBEFA. Because heavy-duty trucks were sampled predominantly on urban roads, highway and suburban road type emission factors for HDTs are estimated by using the ratio

of urban to non-urban emission factors from EMEP. For light-duty vehicles, fuel-specific emission factors are observed to vary minimally across different road types, so no such adjustments were necessary. Remote sensing data measured at high altitudes (Bogotá) are adjusted to represent national average conditions by taking a weighted average of high-altitude measurements and European TRUE data—assumed to represent sea level conditions—by the share of activity at high and low altitudes. Remote sensing data from Mexico City and the State of Mexico are combined into nationally representative emission factors that account for worse inspection and maintenance (I&M) enforcement outside of Mexico City (using the State of Mexico as a proxy for regions with worse I&M).

For all vehicle types, the ages of Euro 5/V and later vehicles captured in European remote-sensing campaigns were below the age threshold for full deterioration; in these cases, deterioration adjustments were made to obtain accurate lifetime average emission factors starting from the base year of the model. We calculate those lifetime average emission factors using the average age of vehicles measured, default survival curves, and emission factor deterioration values informed by MOVES4, [Davison et al. 2022](#), [Borken-Kleefeld and Chen, 2015](#), and [Chen and Borken-Kleefeld, 2016](#). For remote sensing data captured outside of Europe, deterioration adjustments vehicles scale emission factors to the expected performance at average vehicle ages when the mean vehicle age sampled is below the expected fleet average for non-diesel. PM_{2.5} emission factors are also broken down into emission factors for each component of PM_{2.5} using MOVES 2014a PM_{2.5} speciation fractions.

Gaps in the available TRUE data for two-and-three wheelers, niche powertrains (e.g. gasoline HDVs, ethanol LCVs), CH₄, N₂O, NH₃, CO, and VOCs are filled using modeled EMEP values. Where both EMEP and TRUE data contain gaps, HBEFA data were used to fill in values for a limited set of HDV powertrains. As both HBEFA and EMEP provide emission factors at a greater level of detail than Roadmap, we first aggregated the emission factors to the Roadmap categories. EMEP emission factors are weighted by vehicle segment, weight class, and road type. By default, other countries that follow the EU regulatory pathway use emission factors based on the average fleet composition from the EU countries with available data; however, users can supply any set of country-specific emission factors.

For the United States and Canada, vehicle emission factors are based on EPA's MOVES4 model. MOVES estimates diesel, gasoline, and natural gas emission factors for vehicles following the US standards. Rather than binning emission factors based on EPA's emission standards (e.g. US 2007 and US 2010), Roadmap preserves the level of detail in MOVES4, incorporating emission factors for all model years from 1985 to 2060; these emission factors were calculated using MOVES4 outputs of emissions and energy consumption for available vehicle and fuel combinations. For Mexico, diesel and gasoline emission factors for HDVs come from ERG's MOVES-Mexico model emission factors and energy intensity data. Following the approach for the US, Roadmap models separate emission factors in Mexico for each model year provided from 1980 to 2050. China-specific emission factors are sourced from the ICCT's China model, which incorporates data from the Vehicle Emission Control Center and Tsinghua University.

Further adjustments were made to the PM and NOx emission factors certified to US regulatory pathways based on real-world performance data, including remote sensing measurements, recent PEMS testing, and planned updates to MOVES. For NOx, the MOVES4-based emission factors for the US were adjusted to align with real-world emissions data from TRUE campaigns in the US. Roadmap also supports additional speciation of PM_{2.5} for all regions into components BC, OC, non-carbon organic matter, NO₃, NH₄, SO₄, elemental metals, and unspciated PM, based on Table C-1 and Table C-3 of [MOVES 2014a](#). For all US-based emission factors and most Mexico emission factors, no PM speciation is required, because MOVES4 or MOVES-Mexico provides detailed emission factors for the components directly.

For alternative fuels, such as Ethanol, Biodiesel, CNG, and LPG, the emission factors are taken from the sources listed above where available. For any missing combinations of emission standards and fuels, the emission factors are calculated based on available data for similar emission standards and fuels. For example, for a given vehicle type and standard, if emission factors are not available for China, but they are available for an equivalent standard and fuel type in Europe, then the missing data for China are imputed as follows. The ratio of the predominant ICE emission factor (for gasoline or diesel depending on vehicle type) and the alternative fuel emission factor for the equivalent Euro standard is used to calculate the unknown alternative fuel emission factor for China using its known ICE emission factor.

$$EF_{China,AltFuel} = \frac{EF_{Euro,AltFuel}}{EF_{Euro,ICE}} \times EF_{China,ICE}$$

The emission factors may also be optionally adjusted according to age using an emission deterioration profile. This option allows for vehicles to deteriorate over time and thus emit more as they age.

Emission deterioration

Roadmap can model emission deterioration by using age-specific multipliers for emission factors. Except for in regions with US-equivalent or Mexico standards, emission factor inputs represent lifetime average emission rates; in these cases, to avoid double-counting, emission deterioration is set to 1 for all ages. In cases where zero-mile emission rates are input and deterioration is modelled separately, the multiplier will increase from 1 as the vehicle ages, meaning that the vehicle will produce more emissions than when it was brand new.

Deterioration values for the US come directly from MOVES4 for all species and model years 2015 and later. For Mexico, heavy-duty diesel PM deterioration values come directly from MOVES-Mexico inputs provided by ERG. For all other species, vehicles, and model years that were not directly provided, US and Mexico (HDVs only) emission factor deterioration are calculated for by normalizing emission factors over time to the youngest age values in the MOVES4 and MOVES-Mexico datasets.

Plug-in hybrid electric vehicles (PHEVs)

PHEVs are modeled partly as ICE vehicles and partly as electric. Based on internally-developed numbers for the share of PHEV activity using fossil fuel versus the share using electricity, PHEVs are first divided into their two modes. Each of the driving modes have separate energy intensities and emission factors, and thus the model reports energy consumption and emissions separately for both fuel types.

High emitters

As described above, the Roadmap model incorporates real-world emission factors from remote sensing data for a growing number of regions. We also use the remote-sensing based emission factors as proxy data where we lack direct real-world measurements. We expect that these remote-sensing based emission factors already reflect excess emissions from high emitters—a fraction of vehicles whose emissions control systems are malfunctioning as a result of tampering, poor maintenance, or failure. In some cases, where we expect real-world compliance and enforcement to be worse than in proxy regions where measurements were taken, we make further assumptions for additional incidence of high emitting vehicles.

By default, these additional high emitter effects are currently only considered for PM and NO_x emissions from gasoline and diesel vehicles. Roadmap assumes shares of high-emitting vehicles ranging from 0% for some vehicle types and regions up to 20% for others. These shares are based on region-specific estimates and general compliance and enforcement levels for PM and NO_x, building on [Klimont et al. \(2017\)](#) and [Miller and Jin \(2018\)](#). An emissions multiplier is used for each control level to determine the emission factors of high-emitting vehicles relative to Roadmap's default emission factors of the same type.

As tampering, malfunction, and poor maintenance affect emissions based on the vehicle's age, we follow EMFAC and MOVES's approach to estimate high emitters' emission deterioration. As shown in the figure below, this approach models a linear increase in emission rates from the end of the warranty period (the first dashed line) up to the defined useful life age (the second dashed line). Once the useful life age is reached, we assume a constant emission rate equal to the product of the emissions multiplier and the baseline emission factor. Roadmap derives both the warranty age and the useful life age from region-specific regulations and vehicle activity.

Mileage was converted to age based on region-specific data that show how quickly different types of vehicles accumulate miles. We use TRACCS data for the EU and activity data from VECC for China, which is also consistent with the estimate from Huo et al. ([Huo et al., 2012](#)). We use the same ages for the US as in MOVES. In addition, we distinguish warranty and useful life ages by control level. For example, China only starts to have warranty requirements in China VI, and more recent standards, for example, China VI, Euro VI and US2004+, require a longer useful life than earlier standards.




Figure 2: Emission rate timeline by age, used to model mileage degradation.

Qualitative depiction of the implementation of tampering, mal-maintenance, and malfunction (TM&M) age effects. Adapted from MOVES2014 technical report.

Sulfur effects

Fuel sulfur effects on sulfate (SO_4) and sulfur dioxide (SO_2) running emissions apply [MOVES2014a methods](#) (equations 9-1 and 9-3).

$$SO_2(g) = FC(g) \times [S](ppm) \times \frac{MW_{SO_2}}{MW_S} \times f_{SO_2} \times \left(\frac{10^6}{ppm} \right)$$

Where:

- $FC(g)$ = fuel consumption (grams)
- $[S](ppm)$ = fuel-sulfur level (ppm)
- $\frac{MW_{SO_2}}{MW_S}$ = the ratio of molecular weight of sulfur dioxide to sulfur = 2.0
- f_{SO_2} = Fraction of fuel sulfur that is converted to gaseous SO_2 emissions (1 - fraction converted to SO_4).

This equation simplifies to:

$$SO_2(g) = FC(g) \times SO_2 EF (g/ppm) \times S(ppm)$$

where $SO_2 EF$ is the emission factor specific to HDVs and LDVs by emission control technology.

SO_4 emissions are calculated:

$$SO4_x = NonECPMB \times S_B \times \left[1 + F_B \times \left(\frac{x}{x_B} - 1 \right) \right]$$

Where:

- $NonECPMB$ = the reference non-elemental carbon $PM_{2.5}$ emission rate
- S_B = the sulfate reference fraction
- x = the user-supplied fuel sulfur level
- x_B = the reference fuel sulfur level
- F_B = the percentage of sulfate originating from the fuel sulfur in the reference case
- $SO4_x$ = sulfate emissions at the user-supplied fuel sulfur level

The S_B , F_B , and x_B , parameters vary by vehicle type, model year group, and emission process.

Biodiesel effects on local air pollutants

Roadmap can also optionally model the impact of biodiesel blends on tank-to-wheel NO_x and PM emissions. Emission multipliers developed by the [ICCT](#) consider country-specific differences in feedstock, fuel sulfur level, and biodiesel blend level. Biodiesel effects on local air pollutants are only available for the United States, Indonesia, and Brazil; all other regions do not account for the combustion effects of biofuel blends.

Well-to-wheel GHG emissions

Roadmap reports emissions for three GHGs (CO_2 , CH_4 , and N_2O) as well as climate forcers BC, OC, and sulfate aerosols. By default, the model calculates tank-to-wheel (TTW), well-to-tank (WTT), and well-to-wheel (WTW) GHG emissions, and a supplementary tool is provided to append WTT emissions of non-GHG pollutants. TTW emissions of all pollutants except CO_2 depend on vehicle emission control technologies and are calculated from those detailed emission factors as described above in the ‘Emission factors’ section. On the other hand, TTW and WTT emissions of CO_2 and WTT emissions of all other pollutants are calculated based on energy consumption and fuel emission intensity. These fuel-level emission intensities are taken from the R&D GREET model ([2023rev1](#)) developed by Argonne National Laboratory. Roadmap applies these emission intensities to calculate emissions for each pollutant. Additionally, Roadmap calculates CO_2e emissions using GWP values for 20-year and 100-year horizons. AR6 GWP values are used for all pollutants except SO_2 whose AR5 value is retained from (AR5 WG1 Chapter 8 Supplemental (8SM) Table 8.SM.17):

Table 7: GWP values for calculating GHG emissions.

Pollutant	GWP20	GWP100
CO_2	1	1
CH_4	82.5	29.8
N_2O	273	273

BC	3200	900
OC	-240	-69
SO ₂	-141.1	-38.4

While TTW CO₂ emission intensities are typically globally consistent for a given fuel, WTT emissions can vary significantly depending on the regional production processes and feedstocks. Roadmap considers the emission intensities of different feedstocks for biodiesel, biogas, ethanol, and hydrogen. Where available, feedstock shares are used to calculate an aggregate WTT intensity for each fuel. A global default, calculated based on the share of production of various biofuels in the countries for which we have data, is applied instead in regions where detailed feedstock data are not available.

WTT emission intensities for each feedstock are specified as the sum of production and indirect land use change (ILUC) emission intensities, the latter of which can be significant for biofuels. Production emission intensities are sourced from GREET, whereas ILUC intensities are generally sourced from [ICAO CORSIA](#) (2022), which harmonizes results from two ILUC models and therefore provides a reasonable central estimate. For less common biofuel feedstocks not covered in CORSIA, we apply ILUC values from [IIASA GLOBIOM](#) (2015).

Most biofuels are blended into a primary fuel type such as gasoline or diesel and as such, they will have a proportionate effect on total emissions based on this blend share. The relative blend levels of biodiesel, biogas, and ethanol in diesel, CNG, and gasoline respectively are informed for a few countries by national biofuel blend targets. For other regions, the biofuel blend shares are calculated as the ratio of bio- to fossil-fuel consumption reported in the World Energy Balances.

Base year global inputs for the CH₄ and N₂O intensity of electricity generation by power plant type are sourced from GREET. These are combined with historical and projected values of CO₂ emission intensity, shares of electricity generation by type (grid mix) from IEA's World Energy Outlook (WEO) 2024, and country-specific transmission and distribution loss data from [World Bank](#) (2025) to obtain default aggregate grid emission intensity values for electricity generation. Using this technique, Roadmap builds regional aggregate grid intensity values for CO₂, CH₄, and N₂O in the IEA's Stated Policy Scenario (STEPS) and Announced Policy Scenario (APS). Aggregate grid intensity values for CO₂ only are also available for the Net Zero Emissions Scenario (NZE), which lacks the regional grid mix projections needed for default CH₄ and N₂O estimates. Users may select any of these pre-built IEA grid projection scenarios, specify custom scenarios of generation shares, or specify custom scenarios of aggregate grid emission intensity for CO₂, CH₄, and N₂O.

POLICIES AND SCENARIOS

The Roadmap model is designed to explore the implications of national and regional policies. Users can provide inputs defining alternate scenario pathways or updating baseline assumptions.

Scenario inputs

Scenarios can define the inputs shown in Table 8.

Table 8: *Descriptions of scenario inputs.*

Input	Description
Sales powertrain shares	Share of new vehicle sales by powertrain type
Sales used/new ratio	Ratio of used imports to new vehicle sales
Sales	Historical country-specific new vehicle sales
Sales growth rate	Compound annual growth rate of new vehicle sales
Survival curves	Vehicle survival rates by age
Average retirement age	Mean value, used when no detailed survival curves are available
Energy intensity	New vehicle energy intensity (absolute or relative to the baseline)
Fuel sulfur	Diesel and gasoline sulfur content by year
New vehicle standards	Emission standard timeline for new vehicles
Import restrictions	Age or standard-based restrictions on used vehicle imports
Import source	Share of used imports coming from different exporters
Import powertrain shares	Share of used imports by powertrain type
Entry age for used imported ZEVs	Maximum entry age for used imported ZEVs
VKT per vehicle	Annual average activity by vehicle type (and optionally powertrain)
Mileage degradation	Scaling factors to alter VKT per vehicle by age
PHEV usage patterns	Share of PHEV activity in charge-depleting mode
Fleet renewal policies	Annual activity shifts by vehicle and technology which could represent low emission zones, retrofits, or scrappage policies
Emission factors	Emission factors by country, vehicle, powertrain, fuel, and control technology
Emission deterioration	Emission deterioration multipliers by country, vehicle, powertrain, fuel, age, and control technology
High emitter parameters	High emitter shares, emissions multipliers, warranty length and useful life ages
Biofuel blend shares	Annual biofuel blend shares for diesel, gasoline, or CNG
Feedstock shares	Biofuel feedstock shares
Fuel emission intensity	GHG and upstream air pollutant fuel emission intensities (excluding electricity)

Electricity grid mix	Grid mix by generation source
Electricity emission intensity	Electricity grid emission intensity by year per generation source (excluding transmission and distribution losses)
Transmission and distribution losses	Regional transmission and distribution (T&D) loss multipliers
Aggregate electricity emission intensity	Electric grid aggregate GHG intensity including T&D losses
Load factors	Passenger or freight load factors, in number of passengers or tonnes
Regional emissions mapping	Mapping of ISOs to regions with real-world emission factors

Subregional policies

Roadmap's default data inputs represent best estimates of each country's total fleet of on-road vehicles. For some analyses, however, it can be useful to model the effects of policies implemented at a more granular level, such as states or provinces within a country. Roadmap can run analyses for any number of arbitrary subregions by using national fleet data, if appropriate downscaling factors are provided. When running in the subregion mode, all model results including vehicle stock, sales, activity, energy consumption, and emissions are output for each subregion.

In order to toggle the subregion mode, users must provide a mapping file indicating in which country/region (denoted by ISO alpha-3 code in the model) the subregion is located. Additionally, sales for all vehicle types must be provided for each subregion, either as a share of the regional total or as absolute numbers of vehicles. If data are only available for a subset of years, the model will extrapolate the subregional sales shares to cover all model years. Note that the specified subregions do not have to cover the entire country/region, in which case a subregion labeled "Other" is created to represent the missing share. Further downscaling factors are only required if modeling a subregion within a country/region that uses year-over-year survival curves, which requires downscaling factors for stock distribution by age. Subregional stock totals are also required if calibrating subregion-specific survival curves.

Besides the inputs used as downscaling factors, all other subregion inputs such as annual vehicle mileage, energy intensity, and emission factors are inferred from the larger region by default. The user may optionally provide subregional detail for any of the scenario input files that are supported by the model, except for total vehicle sales. As a subregion's total vehicle sales or share of national sales are used to define its baseline vehicle fleet as a subset of the national fleet, varying subregion sales as a scenario input is not supported.

Vehicle segmentation

Roadmap can be run for any of six vehicle types by default, including two- and three-wheelers (MC), passenger cars (PC), light commercial vehicles (LCV), urban and coach buses (Bus), medium-duty trucks

(MDT), and heavy-duty trucks (HDT). These categories are intentionally broad, as there is little consistency in terms of classifications and data availability across all global regions. Many countries, however, do have greater detail on vehicle segments. In these cases, Roadmap can accept additional data on how to segment the larger categories and run with a greater level of detail.

Vehicle segmentation inputs are very similar to subregional inputs, described above. To toggle the segmentation mode, users must provide a mapping file of segments to Roadmap vehicle types, as well as indicate in which countries/regions (denoted by ISO alpha-3 code) the mapping applies. Different levels of segmentation can be applied for different ISOs. As with subregions, detailed sales must also be provided for each segment, either as a share of the Roadmap vehicle type total or as absolute numbers of vehicles. An example of a basic segment map is provided in Table 9.

Table 9: *Example segment map.*

ISO	Vehicle	Segment
USA	Bus	Urban
USA	Bus	Coach

With detailed vehicle segments, it is highly recommended to provide scenario inputs for key characteristics of each segment. Many segments are typically defined by gross vehicle weight or activity patterns which make it unrealistic to assume variables like energy intensity and mileage would be the same as the broader vehicle category. All supported scenario inputs can be specified at the segment level.

The Roadmap model data pipeline also provides the option to output MOVES4 model inputs by vehicle segment. In this case, the user must define their configuration to utilize these data.

Combining Subregions and Segments

Roadmap has the capability to run scenarios that use both subregional and segmented data. In this case, users must include mapping and sales files for subregions and segments separately. Default data is disaggregated first using subregional downscaling factors, then by segments. It is important to note that inputs for both levels of disaggregation must not both be totals, as this can lead to conflicting values. When defining further scenario inputs, it is required to provide the full level of detail in each input file; that is, the inputs should include detail for both subregion and vehicle segments.