# Why Artificial Intelligence Took Seventy Years: A Historical Journey from the Dartmouth Conference to Modern Large Language Models

**Author:** Ishita Batra
**Affiliation:** Independent Researcher / Academic Review

---

## Abstract

Artificial Intelligence (AI) was formally established as an academic discipline in 1956. However, the realization of practical, ubiquitous intelligent systems required approximately seven decades of cyclical technological progress. This review provides a comprehensive analysis of the historical evolution of AI, tracing its trajectory from the hubris of the Dartmouth Summer Research Project, through the programmatic and financial retrenchments known as the "AI Winters," to the empirical breakthroughs of deep learning and transformer-based architectures. This paper argues that computing infrastructure and massive data aggregation—rather than linear optimization of rule-based programming algorithms—served as the critical gatekeepers for modern foundational models.
**Keywords:** Artificial Intelligence, Machine Learning, Deep Learning, Moravec's Paradox, AI History, Transformers, Foundational Models

---

## 1. Introduction

Artificial Intelligence has transitioned from an esoteric branch of computer science into the defining general-purpose technology of the twenty-first century. While contemporary societal discourse often treats the sudden emergence of Large Language Models (LLMs) as an overnight revolution, the baseline theoretical architectures have been in development for seventy years.

The historical timeline of AI is characterized by an enduring mismatch between academic prediction and empirical reality. Early pioneers operating in the mid-20th century viewed human-level intelligence through a lens of formal mathematical logic, assuming that cognitive faculties could be fully simulated given a concise mathematical framework. This paper explores the deep-seated roadblocks that delayed the fruition of their vision, analyzing the core

paradigms that ultimately unlocked modern generative capabilities.

# 2. Historical Development of Artificial Intelligence

## 2.1 The Birth of Artificial Intelligence and Symbolic Optimism (1950s–1960s)

The formal genesis of Artificial Intelligence occurred during the summer of 1956 at the Dartmouth Summer Research Project. Organized by John McCarthy, Marvin Minsky, Nathaniel Rochester, and Claude Shannon, the workshop aimed to operate under the conjecture that *"every aspect of learning or any other feature of intelligence can in principle be so precisely described that a machine can be made to simulate it."*

Early computer programs developed during this era, such as the Logic Theorist and the General Problem Solver, achieved rapid success in closed environments. They successfully proved mathematical theorems, solved intricate algebraic puzzles, and executed game-playing logic such as checkers. This structural mastery over formal logic led to profound institutional confidence. Pioneers boldly predicted that a fully autonomous machine capable of human-level cognitive breadth would be realized within a single generation. This perspective, however, failed to account for the qualitative difference between calculation and comprehension.

## 2.2 Reconciling Human and Machine Cognition: Moravec's Paradox (1960s–1970s)

As systems attempted to scale beyond highly structured mathematical frameworks, researchers hit an insurmountable computational wall. They discovered that formal logical reasoning constitutes only a fractional, surface-level layer of human intelligence. True baseline cognitive functioning relies heavily on subconscious sensory processing: vision, audio perception, localized motor movement, contextual awareness, and intuitive common sense.

This baseline divergence was later formalized as **Moravec's Paradox** by roboticists and AI researchers Hans Moravec, Rodney Brooks, and Marvin Minsky in the 1980s. The paradox states:

*"It is comparatively easy to make computers exhibit human adult-level performance on intelligence tests or playing checkers, but difficult or impossible to give them the skills of a one-year-old when it comes to perception and mobility."*

From an evolutionary standpoint, human sensory-motor skills have been refined over millions of years of biological survival, making complex tasks like walking across a cluttered room or recognizing a face in low light feel entirely effortless. Conversely, abstract logical computation (such as calculus or chess) is an exceedingly recent human development, requiring conscious effort. For silicon processors, the reverse is true: executing a million matrix multiplications takes microseconds, whereas parsing the physical environment to manipulate a fragile object requires

flabbergasting amounts of localized processing power.

## 2.3 Institutional Retrenchment: The AI Winters (1970s–1990s)

When early multi-million dollar investments failed to produce autonomous robotic assistants or fully accurate machine translators, funding bodies grew skeptical. The discipline suffered through two distinct structural contractions known as the "AI Winters":

| Historical Era | Primary Catalysts & Triggers | Structural Consequences |
|---|---|---|
| **The First AI Winter (1970s)** | Publication of the **Lighthill Report (1973)**; criticism of "combinatorial explosion" where micro-solutions failed to scale. | Sweeping cuts in government and institutional research grants across Europe and North America. |
| **The Second AI Winter (1980s)** | Collapse of the commercial **"Expert Systems"** market; software proved too brittle, expensive, and unable to handle out-of-distribution cases. | Massive withdrawal of venture capital and systemic loss of institutional interest. |

## 2.4 The Empirical Shift and the Deep Learning Revolution (1990s–2010s)

AI emerged from its second winter by abandoning hard-coded, symbolic logic in favor of probabilistic, data-driven statistical modeling. Instead of instructing a machine on the strict rules of what constitutes a concept, researchers began designing algorithms that allowed machines to derive rules independently via statistical observation.

This statistical paradigm, known as **Machine Learning**, found its ultimate expression in deep neural networks. However, the theoretical mathematics governing backpropagation and multi-layered neural networks had been established since the late 1980s. The execution of these models was bottlenecked by a lack of infrastructure, requiring a convergence of three distinct external phenomena:

- **Massive Data Aggregation:** The rapid expansion of the consumer internet provided the first large-scale, unstructured datasets. Millions of global users uploading text, consumer patterns, and labeled imagery (such as the ImageNet database) provided the essential material needed to train deep models.
- **Commoditized Storage:** The drastic drop in the per-gigabyte cost of digital storage allowed institutions to host and query petabyte-scale training sets economically.
- **The GPU Infrastructure Shift:** Originally engineered for parallel arithmetic processing in high-definition video games, Graphics Processing Units (GPUs) were discovered to be

highly optimal for executing the massive matrix multiplications required by neural network training layers.

The empirical proof of this infrastructure convergence occurred in 2012 with **AlexNet**. Designed by Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, this deep convolutional neural network won the ImageNet competitive challenge by a massive margin. AlexNet demonstrated conclusively that deep learning models scaled with compute power and data volume, outperforming decades of hand-engineered computer vision techniques.

### 2.5 The Modern Foundational Era (2010s–Present)

Following the deep learning boom, breakthroughs in machine autonomy scaled rapidly across different domains:

- **2016 (Reinforcement Learning):** Google DeepMind's **AlphaGo** defeated world champion Lee Sedol in the ancient game of Go. Go possesses more potential board configurations than there are atoms in the observable universe, making brute-force computation impossible. AlphaGo's success demonstrated that deep neural networks combined with tree search could mimic human-like intuition and long-term strategic positioning.
- **2017 (The Transformer Architecture):** A team of Google researchers published the seminal paper **"Attention Is All You Need"**, introducing the **Transformer architecture**. Prior sequential architectures, like Recurrent Neural Networks (RNNs) and Long Short-Term Memory networks (LSTMs), processed text word-by-word, which limited long-range contextual recall and prevented parallelized training across GPUs. The Transformer architecture bypassed this by utilizing a mathematical mechanism known as **Self-Attention**. This allowed the model to analyze an entire block of text simultaneously, computing the contextual relationship between every single word regardless of distance, and unlocking the scalable training paths that power modern Large Language Models.

# 3. Discussion

The historical trajectory of Artificial Intelligence reveals that early twentieth-century computer scientists drastically miscalculated the biological and structural complexity of human cognition. Human intelligence is not a cleanly isolated stack of mathematical execution vectors; it is a highly integrated, emergent phenomenon relying on the simultaneous orchestration of sensory perception, linguistic nuances, and context-dependent reasoning.

The transition from symbolic logic to deep neural networks proves that the bottleneck to AI was never a lack of clever algorithmic programming. Progress was structurally bound to raw compute availability, storage infrastructure, and dataset scale. Modern transformers do not think via logical deduction; they represent a highly scaled convergence of statistics and compute, mapping the structural patterns of human expression onto high-dimensional vector spaces.

# 4. Conclusion

Artificial Intelligence required nearly seventy years of volatile, interdisciplinary research to mature from a speculative summer workshop proposal into a viable technological stack. The discipline evolved by navigating extreme cycles of public hyper-optimism and systemic financial collapse. Ultimately, replicating human intelligence proved to be one of the most complex scientific endeavors in human history, demonstrating that the elements of cognition we find most effortless are precisely the ones that require the deepest technological scaffolding to replicate.

---

## Conflict of Interest

The author declares no conflict of interest.

## Acknowledgement

The author acknowledges the foundational contributions of the pioneering computer scientists, roboticists, and cognitive researchers whose cumulative discoveries over the last seventy years established the framework for contemporary deep learning.

---

## References

1. McCarthy, J., Minsky, M. L., Rochester, N., & Shannon, C. E. (1955). *A Proposal for the Dartmouth Summer Research Project on Artificial Intelligence*.
2. Turing, A. M. (1950). Computing Machinery and Intelligence. *Mind*, 59(236), 433-460.
3. Moravec, H. (1988). *Mind Children: The Future of Robot and Human Intelligence*. Harvard University Press.
4. Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). ImageNet Classification with Deep Convolutional Neural Networks. *Advances in Neural Information Processing Systems*, 25, 1097-1105.
5. Silver, D., Huang, A., Maddison, C. J., Guez, A., Sifre, L., Van Den Driessche, G., ... & Hassabis, D. (2016). Mastering the Game of Go with Deep Neural Networks and Tree Search. *Nature*, 529(7587), 484-489.
6. Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., ... & Polosukhin, I. (2017). Attention Is All You Need. *Advances in Neural Information Processing Systems*, 30.
7. Lighthill, J. (1973). *Artificial Intelligence: A General Survey*. Artificial Intelligence: a paper symposium, Science Research Council.
8. Deng, J., Dong, W., Socher, R., Li, L. J., Li, K., & Fei-Fei, L. (2009). ImageNet: A large-scale hierarchical image database. *IEEE Conference on Computer Vision and Pattern Recognition*, 248-255.
9. Bahdanau, D., Cho, K., & Bengio, Y. (2014). Neural machine translation by jointly learning

to align and translate. *arXiv preprint arXiv:1409.0473*.

© 2026 Ishita Batra. All Rights Reserved.