Jev in a Multi-Step Workflow

Decisions Predict Failures, Not Which Reviews Pay

Thejas P Rao[1] and Tushar M[2]

[1] thejasrao262003@gmail.com
[2] tusharm3040@gmail.com

Abstract. Structured decision models such as Jev, TypeSafe's typed decision API, return well-typed answers with numeric confidence, and Jev's primitives have been benchmarked on single tasks. We study an operational question that single-task benchmarks leave open: when a workflow chains heterogeneous typed decisions, which signals identify the cases where it fails, and can those signals identify the specific costly errors for which human review is worthwhile? We chain Jev's three primitives, a categorical `choice`, a binary `noul` and an ordinal `score`, into a dependent bug-triage workflow (route, assess, rate severity) and evaluate it on 202 Mozilla bugs labeled by triage and 240 Linux kernel bugs labeled by their reporters, then in pre-registered tests on 500 new bugs and four further models. Three pre-registered findings carry the paper. First, a frozen estimator built on what the model decided ranked wrong workflow actions better than final-step confidence (AUROC 0.76 vs. 0.55). Second, this held across five evaluated models from four sources, including an independently trained Jev-style model, to which Jev's frozen estimator transferred unchanged; the signal was mostly the chosen action's historical error rate. Third, that predictive signal did not become a cost-effective review policy. At a 10% review budget no review strategy cost less than no review at all; the action-based rule beat random selection for the two Jev-style models but was not shown to beat confidence-ranked review. An oracle shows the expensive errors exist, but the signals we tested could not isolate them within an action. A case-level score developed on training bugs failed a pre-registered feasibility check (power at most 0.20 under the natural bug mix), so the confirmatory study was stopped before collecting new data. Supporting results characterize the primitives inside the workflow: `choice` confidence is saturated yet discriminative (AUROC 0.90 [0.83, 0.96] and 0.98 [0.95, 1.00]), `noul`'s value is uninformative about its own correctness (AUROC 0.53 [0.42, 0.65] and 0.41 [0.32, 0.50]), fixed thresholds designed on constructed data lose their selectivity on real text (73% escalated on constructed items, 88% and 78% on real bugs, against targets of 41–42%), and `score` compresses severity toward the middle level without its confidence indicating it. Predicting which decisions are wrong is not the same as knowing which are worth correcting.

Keywords: Uncertainty quantification · Calibration · Structured outputs · Decision workflows · Escalation · Bug triage

1 Introduction

A model can return a perfectly valid, well-typed structured response and still make the wrong decision. When several such decisions are chained into a workflow, errors at one step propagate to the next. A common hope is that each step's reported confidence can be composed into a workflow-level signal that says when to hand a case to a human.

Prior work has benchmarked Jev's primitives and calibration on single tasks [10,25,9], and recent work has examined uncertainty across multi-step agent trajectories [23]. We study a different, operational question. *When a workflow chains heterogeneous typed decisions, which signals identify the cases where it fails, and can those signals identify the specific costly errors for which human review is worthwhile?* The two halves can come apart: a signal can rank failures well and still not say which reviews pay. Heterogeneity matters because Jev exposes three primitives whose uncertainty is *structurally* different. `choice` returns a distribution over labels plus a scalar confidence. `score` returns an ordinal distribution plus a scalar confidence. `noul` returns a single probability with no separate confidence field. Treating these numbers as one kind of quantity is a modeling assumption, and this paper tests it.

What TypeSafe documents. TypeSafe's documentation describes Jev's `confidence` for `choice` and `score` as a number that "collapses" the output distribution into a value between 0 and 1. It is 1 when all probability is on one outcome and 0 when probability is spread evenly. The documentation calls this "one reasonable way to summarize a distribution, not the only one", and advises setting thresholds from one's own data [34]. For `noul`, it returns "a single probability" with "no separate `confidence`". Our results are therefore not a test of a calibration claim. They are a measurement of how these documented concentration statistics behave as escalation signals when Jev's primitives are chained, which the documentation leaves open.

Contributions. The main findings concern workflow-level prediction and its decision utility.

1. **Workflow failure prediction** (Sections 8 and 9, pre-registered). A frozen decision-feature estimator ranks wrong workflow actions better than final-step confidence on 500 new bugs. The gap replicates across five evaluated models from four sources, and Jev's frozen estimator transfers unchanged to an independently trained Jev-style model. Most of the signal is the chosen action's historical error rate.
2. **Prediction is not intervention utility** (Section 10, pre-registered). At a 10% review budget, that predictive signal does not yield a lower cost than confidence-ranked review, and no strategy beat no review. An oracle shows the reason: the expensive errors exist, but the signals we tested could not isolate them within an action. A case-level score developed on training bugs did not meet a pre-registered feasibility criterion under the natural bug mix, so the planned confirmatory study was stopped before any new data.

3. **Supporting evidence on the primitives** (Sections 4 to 7). Inside this workflow, the three primitives' confidence signals behave differently; fixed thresholds set on constructed content lose their selectivity on real text; `score` compresses severity on two trackers with different labeling processes; and confidence-based escalation rules did not consistently beat random selection (exploratory, with a confound we identify). Primitive-level calibration of Jev has been studied elsewhere on single tasks [10,25]; these results are the foundation for the workflow study rather than its main claim.
4. **Method** (Section 11). A pre-registration and audit process that caught six design or implementation defects, most of them before any evaluation data existed.

Non-claims. We make no claim about general calibration, other Jev versions or other APIs, domains beyond software bug triage, or real-world operational benefit.

2 Related work

Evaluations of Jev and open decision models. Jev has been benchmarked zero-shot on 37 datasets (346,009 requests), where its `choice` probabilities were well calibrated and supported selective prediction, while its binary probabilities ranked well but sat poorly relative to a 0.5 threshold, and thresholds tuned on training data improved F1 [10]. A calibration audit with released per-item outputs (described by its author as exploratory) compared Jev with open and general-purpose classifiers on SST-2 and AG News [25]. It found that calibration changed with the question form (a yes/no form was underconfident, a choice form close to calibrated), that 71.6% of four-class answers sat at exactly 1.00, so a threshold on the top-class probability had only 53 operating points, that one fitted temperature removed most miscalibration, and that no threshold on Jev's scores certified a 5% automatic tier on the four-class task under its procedure; and a comparison on seven political-science replications found its calibration advantage over other models not consistent [9]. An early evidence audit of 28 papers on typed decision models found no independent accuracy advantage yet for the typed readout over comparable label-probability readouts, and proposed an evaluation checklist [32]. Open instruction-tuned models can produce Jev-like decisions by reading answer-label logits in one forward pass [17], the same kind of readout we use for the general models in Section 9. These studies evaluate single requests; none studies `score` inside a workflow, composition of dependent decisions, or the cost of human review. Our results agree with them where they overlap: `choice` confidence is saturated yet discriminative, and thresholds must be validated on the target data, which our transfer result shows directly. On `noul` the measures differ. The audits report calibration and accuracy on sentiment, where the yes/no form was accurate and recalibratable; on our regression question, `noul`'s probability did not discriminate its own correctness (AUROC near or below 0.5). Binary-probability quality therefore looks task-dependent.

Calibration of single decisions. Post-hoc calibration [29,26] and the miscalibration of modern networks [19] are well studied, and confidence estimation for language models has been surveyed in [16].

Selective prediction and deferral. Risk–coverage trade-offs and reject options [13,14,15], learning to defer [24] and prediction sets in human–AI teams [5] address *one* decision. Closest to our intervention result, recent work argues that error risk is not review value under bounded review budgets: review priority should depend on wrongness, repairability, impact and cost, and ranking by review value left less residual error than ranking by risk on a question-answering benchmark [28]. Our intervention finding is an instance of that distinction in a dependent typed-decision workflow, with a frozen cost table and pre-registered tests.

Conformal methods and composition. Conformal prediction [3] and conformal risk control [4] give distribution-free guarantees. Composition across stages has been studied for two stages [40] and for multi-stage NLP and LLM pipelines, where errors compound across stages and independently calibrated stages lack a joint coverage guarantee [22]. Error propagation through pipeline steps has also been quantified [8]. Classical reliability theory composes component reliabilities [6].

Cascades and escalation. Cascades route a *single* query through model tiers. Prior work studies early abstention [37], the optimal depth and deferral thresholds of cascades [7], conformal cascades [11], confidence tuning [31] and judges with escalation guarantees [20].

Combining confidence across components. Fixed combination rules such as the product rule are classical [21]. The product rule's usual justification assumes conditional independence and comparable probability scales, and these are precisely the assumptions our strategy S2 makes implicitly. At the system level, a recent taxonomy argues that uncertainty in LLM applications must be studied across the whole compound system, as it propagates within models, across system components and through socio-technical processes [36]. Cost-sensitive deferral to multiple experts under workload limits [2] is closely related to the budgeted escalation setting our follow-up uses.

Ordinal outputs and central tendency. LLM raters have been reported to compress ordinal scores toward the middle of the scale, for example in clinical scoring, where prompt changes did not remove the effect [38]. Few-label calibration of ordinal LLM outputs models such flattening explicitly [35]. Our severity result is consistent with this literature. What we add is that it appears in bug triage, against two labeling processes, and that the primitive's own confidence gives no sign of it.




Fig. 1. The three-step workflow. Each node is called three times. The action rule F uses only c_2 and c_3.

Agents and trajectories. Closest to our workflow framing, a counterexample shows that step-level calibration need not imply trajectory-level calibration for LLM agents, and step errors are empirically coupled along trajectories [23]. Related work calibrates agent trajectories [39] and studies uncertainty propagation in multi-step agentic decisions [12].

Positioning. Prior work benchmarks Jev's primitives on single requests, studies calibration of single decisions, cascades of the *same* decision and agent trajectories, and argues in general that risk differs from review value. Our contribution is narrower and empirical: in a dependent workflow of three *structurally different* typed decisions, against real labels, held-out data and five evaluated models, we test which signals predict workflow failure and whether they identify the costly errors that make human review worthwhile. We are not aware of prior work with this specific design, but we make no priority claim. Our literature search was web-based, did not systematically cover reliability engineering or HCI escalation research, and the Jev literature is growing quickly: the studies cited above appeared in September and October 2026.

3 Setting

Jev and repeats. All calls go to the TypeSafe API with model `jev-latest`, which resolved to `jev-1.13.0` in every one of our calls. Each node is called three times, and the three answers are reduced to one decision. For `choice` and `score` we take the modal decision with a tie tolerance of 0.02; a node with no two-of-three majority is *repeat-unstable*. For `noul` we threshold the mean probability at 0.5, and its confidence-like value is $2\,|\bar{p} - 0.5|$.

Workflow. Node 1 (`choice`) routes the incident to a network or storage subsystem. Node 2 (`noul`) assesses a binary property: customer impact on constructed data, regression on real bugs. Node 3 (`score`) rates severity on three levels. Each node reads the evidence plus the upstream decisions, appended by a fixed adapter (Fig. 1).

Target action. The target is $a^* = F(c_2^*, c_3^*)$, where F maps an *unclear* c_2 to *request more evidence*, $c_3 = 2$ to *escalate*, $c_3 = 1$ with $c_2 = 1$ to *defer*, and everything else to *accept* (Table 5). F is a construct we defined, not an independently validated outcome, and every strategy result is conditional on it.

Strategies.

- **S1:** F applied to the node decisions.
- **S4a:** S1 plus escalation on repeat instability.
- **S2:** escalate the $\lceil qn \rceil$ instances with the lowest product of per-node confidences and accept the rest. Here q is the share of non-accept targets.
- **S5:** the same, ranked by per-primitive rank-normalized uncertainty.
- **2h / 5h:** S1 plus confidence-ranked escalation of a fixed 10% budget.
- **R:** the same budget escalated at random.

Statistics. Agreement rates carry Wilson 95% intervals. AUROCs use the Mann–Whitney estimator, with 95% percentile bootstrap intervals over bugs ($B = 2{,}000$, fixed seed). Bugs are distinct reports with no shared unit, so we resample bugs. Paired strategy comparisons use the exact McNemar test on discordant pairs, and the difference in $P(Y_{\text{decision}})$ gets a bootstrap interval. Within every resample, the set-relative rankings (S2, 2h) are recomputed. We compare the two trackers through the difference of their paired differences, with independent bootstraps per tracker. We do not compare their p-values. For budgeted overrides, the reference is the *exact* expected cost of k random overrides. The randomization p-value (10,000 random k-subsets) is conditional on the evaluated bugs, and a bootstrap interval over bugs gives the sampling uncertainty. An interval that covers the null value is read as *no evidence of an effect*, not as evidence of no effect. The scripts are `paper_statistics.py` and `mozilla_exploratory_analysis.py`.

Outcomes. Outcomes are $P(Y_{\text{decision}})$, the probability that the action equals a^*, and the cost under a frozen matrix (Table 6), in which a wrong *accept* costs 6–10, any other mismatch 1, and each escalation an extra 1 for human time.

4 Characterization: incompatible uncertainty semantics

Table 1 and Fig. 2 show three incompatible profiles. `choice`'s confidence is almost always near 1.0. It still discriminates, because the rare low-confidence answers are where its errors are. The high-confidence error subgroup found on deliberately ambiguous constructed items does not recur on real text (2 of 6 kernel errors are at ≥ 0.90). `noul`'s confidence-like value carries no usable information about correctness on either tracker. Its Mozilla interval covers 0.5, and its kernel interval lies at or just below 0.5 (weakly anti-informative). `score`'s confidence does not vary with the true level, so it gives no warning of the systematic bias in Section 6. Any composition rule that multiplies or averages these numbers inherits this mix.

5 Fixed thresholds lose their selectivity on real text

The rules in Fig. 3 fail in two different ways. On real text the trigger fired on 85% (Mozilla) and 96% (kernel) of bugs, and the product cut escalated 88% and 78%

Table 1. Per-primitive behavior of the confidence signal. AUROC is for predicting the node's own agreement with the reference label, with 95% bootstrap intervals.

	Constructed items	Mozilla (n=202, triage)	Kernel (n=240, reporter)
`choice`	High-confidence error subgroup: mean confidence 0.915, accuracy 0.333 (n=6)	85% at ≥ 0.90, agreeing 0.96; AUROC 0.90 [0.83, 0.96]; ECE 0.05	96% at ≥ 0.90, agreeing 0.99; AUROC 0.98 [0.95, 1.00]; ECE 0.02
`noul`	24/24 correct, confidence below accuracy in every bin	Agreement flat across bands (0.71–0.84); AUROC 0.53 [0.42, 0.65]; ECE 0.36	Non-monotonic (0.58–0.93); AUROC 0.41 [0.32, 0.50]; ECE 0.36
`score`	Tracks the most severe sentence (6/6); confidence varies by 0.173 with sentence order alone (1 of 3 items)	Confidence $\approx$0.6 at every true level; AUROC 0.58 [0.50, 0.66]	Confidence 0.65 / 0.62 / 0.61 by true level; AUROC 0.57 [0.50, 0.64]

against targets of 41% and 42% (constructed pilot: 27/30 fired; 73% escalated against 67%). The `choice` trigger is non-selective *everywhere*, because `choice` confidence is saturated: that is a design failure, visible only once measured. The product cut is *distribution-sensitive*. It was near its target on constructed data and far from it on real data, because real text pulls `noul` toward 0.5 and so pulls the product down. A fixed threshold carries the confidence scale of the data it was set on, and our constructed data was too clean to reveal this. The two Revision-10 strategies built on these thresholds scored 0.37–0.40 (Mozilla) and 0.34–0.37 (kernel). We replaced them with rank-based rules at a matched escalation rate before any evaluation.

6 Real-data validation on two trackers

Data. Mozilla: 202 fixed Firefox networking and storage bugs. Severity S1–S4 is assigned by triage and mapped to levels 2/2/1/0, and the regression flag is a keyword. Bugs whose severity was revised were excluded. *Linux kernel:* 240 fixed networking and storage bugs. Severity (blocking/high/normal/low $\rightarrow$ 2/2/1/0) is set by the reporter, and the regression flag is a dedicated field. Severity is rarely changed after filing: 15 of the 240 sampled bugs, all moving away from the default "normal". Both samples are balanced at 40 per (subsystem, level) cell where available. Texts are cleaned, privacy-scrubbed and truncated to 2,000 characters. Agreement is with the reference label, not ground truth.

Routing and regression. `choice` agrees with the component label well above baseline on both trackers (Table 2). It still agrees 0.84 on Mozilla texts with no subsystem keyword. `noul`'s errors change direction between trackers. On Mozilla




Fig. 2. Reliability diagrams (five equal-width confidence bins, bins with $n \geq 5$; the label is n; dashed line: perfect calibration). `choice` puts nearly all bugs in its top bin, and that bin is accurate. `noul`'s confidence-like value $2|\bar{p} - 0.5|$ sits far *below* its agreement (underconfidence), and agreement does not rise with it.



Fig. 3. Selectivity of the two fixed-threshold rules, set on constructed data and measured on each rule's own input signals. The trigger fires on 85–96% of instances everywhere. The product cut is near its target on the constructed pilot and far above it on real text.

it mostly misses regressions (23 misses vs. 17 false alarms). On the kernel it overflags them (63 false alarms vs. 3 misses), which leaves it below the always-"no" baseline. The kernel false-alarm rate is the same on bugs explicitly marked "not a regression" (33/100) as on bugs with the field unset (30/94). So unset labels do not explain it, and on bugs with a set field `noul` beats its baseline (110/146 vs. 100/146).

Severity compression. Figure 4 shows the row-normalized confusion of `score`. On both trackers, most minor bugs are rated higher than their label: 79% [0.67, 0.88] on Mozilla and 75% [0.65, 0.83] on the kernel. A large share of serious bugs are rated lower: 43% and 56%. The middle level absorbs both. With Mozilla's own severity definitions in place of ours, serious bugs improve but normal bugs are pushed up, and agreement moves only from 0.53 to 0.56. The criteria matter, but the compression persists. The two trackers differ in project, bug population and labeling process. They share Jev, the prompts, our sampling design and,

Table 2. Node agreement with reference labels (Wilson intervals). Each baseline is the most frequent label.

	Mozilla		Kernel	
Node	Agreement [95% CI]	Baseline	Agreement [95% CI]	Baseline
`choice`	0.89 [0.83, 0.92]	0.59	0.975 [0.95, 0.99]	0.50
`noul`	0.80 [0.74, 0.85]	0.74	0.725 [0.67, 0.78]	0.81
`score`	0.53 [0.46, 0.60]	0.40	0.44 [0.38, 0.50]	0.33




Fig. 4. Row-normalized confusion of `score` against reference severity (repeat-unstable outputs excluded). On both trackers the middle column absorbs mass from both extremes: minor bugs are rated up, serious bugs down.

plausibly, training-data exposure, so the replication speaks against an artifact of one *labeling* process, not against every shared factor. The pattern matches central-tendency bias reported for LLM raters in other domains [38].

7 Composition (exploratory)

All analyses in this section were specified after the Mozilla results had been seen. They are hypothesis-generating. The pre-registered tests that followed are reported in Sections 8 to 10.

The naive comparison is confounded. On Mozilla, decision composition (S1) beats confidence composition (S2) by 0.17 [0.08, 0.27] in $P(Y_{\text{decision}})$, with 61 vs. 27 discordant pairs (exact McNemar $p = 0.0004$). But S2 never reads the node decisions, while a^* escalates on the severity *decision*. To be right on a serious bug, S2 needs low confidence to *mean* high severity, so the comparison mostly measures whether confidence can stand in for severity. On the kernel the difference is smaller and inconclusive: 0.06 [−0.03, 0.15], 66 vs. 51 discordant pairs, $p = 0.20$. The difference between trackers is 0.11 [−0.01, 0.24]. Its interval covers zero, so we have *no evidence that the effect differs* between trackers, only a weaker estimate on one of them.




Fig. 5. Every AUROC in the paper with its interval; dashed line: chance. Only `choice`'s confidence discriminates its own errors. Composed confidence is at chance for both escalation targets, (A) and (B).

The fair question, and two different targets. Does confidence add anything *beyond* the decisions? Starting from the decision-based action F, we also escalate the k least-confident bugs that F did not escalate, for every k, and compare with the exact expectation under random selection (Fig. 6). We report two AUROCs with different prediction targets, which should not be conflated:

- **(A) Missed serious bugs.** Among bugs that F did not escalate, does low composed confidence rank those whose target is *escalate* first? This is what an override budget can fix. AUROC 0.49 [0.37, 0.61] on Mozilla and 0.50 [0.40, 0.60] on the kernel.
- **(B) Any decision error.** Across all bugs, does low composed confidence rank those where F's action is wrong first? AUROC 0.54 [0.45, 0.63] on Mozilla and 0.47 [0.40, 0.54] on the kernel.

Every interval covers 0.5 (Fig. 5). The data show no evidence that composed confidence ranks either target better than chance, but they cannot rule out a modest signal (AUROC up to about 0.6).

Budgeted overrides, scored by cost. At a fixed budget of $k = \lceil 0.1n \rceil$ overrides ($k = 21$ on Mozilla, 24 on the kernel), let T be the total cost of the confidence-ranked overrides and μ the exact expected total under k overrides drawn uniformly from the same candidates. Two analyses answer two different questions.

- **Randomization test, conditional on the evaluated bugs.** This asks whether the ranking selected worse or better overrides than random selection *on these bugs*. The statistic is $|T-\mu|$. The null distribution comes from 10,000 random k-subsets of the candidates, and the test is two-sided.
- **Bootstrap over bugs.** This asks how stable the per-bug difference $(T-\mu)/n$ is under resampling of the bugs, with rankings and μ recomputed in each resample.




Fig. 6. Adding confidence-ranked escalations on top of decision composition. At $k = 0$ the curve is S1. Neither ranking consistently improves on random selection of the same number of cases: deviations are a few points at most and change sign between rankings and trackers. For example, per-primitive ranks run slightly above random on Mozilla for $k \approx 15$–35, and the confidence product runs below.

On Mozilla, $T = 390$ against $\mu = 357.2$. The observed value sits at the edge of the null distribution (2.5–97.5% range 323–388), so $p = 0.05$. The per-bug difference is +0.16 [−0.01, 0.24], and 97% of resamples are positive. That is borderline evidence that the product ranking chose *worse* overrides than random on Mozilla. On the kernel, $T = 338$ against $\mu = 358.6$ ($p = 0.18$), a per-bug difference of −0.09 [−0.23, 0.06]: inconclusive, and in the opposite direction. These analyses are exploratory and uncorrected for multiplicity. We read them as no consistent benefit from confidence-ranked overrides, with one borderline harmful estimate that did not replicate, and not as an established harm.

A structural reason. In this workflow the only discriminative confidence (`choice`, AUROC 0.90–0.98) belongs to the one node that F does not use. The informative signal never reaches the action, and the two signals that do reach it are close to uninformative.

8 A pre-registered held-out test

Design. The exploratory analyses above suggested that a model's *decisions* carry the information its confidence lacks. We tested this prospectively, as follows.

- **Estimator.** We trained one decision-feature estimator (E_{dec}: L_2-regularized logistic regression on the `score` level, the `noul` decision and the workflow action, with $\lambda = 1$) on all 442 previously collected bugs. We froze it by hash, before any new data existed.
- **Fresh bugs.** We collected 500 new bugs: 250 per tracker, sampled at each tracker's *natural* mix, with no overlap with the training bugs. That required 4,500 Jev calls.

– **Hypotheses (pre-registered).** HR1: E_{dec} ranks wrong workflow actions better than low final-step confidence. HR2: E_{dec} ranks above chance on each tracker. One-sided bootstrap tests, Holm-corrected.

Result. Both hypotheses are supported.

– **HR1:** E_{dec} reaches AUROC 0.763 against 0.549 for final-step confidence, a difference of +0.214 (one-sided 95% lower bound +0.158).
– **HR2:** AUROC is 0.811 on Mozilla (lower bound 0.761) and 0.697 on the kernel (lower bound 0.643).
– **Calibration:** the estimator's predicted failure rate matches the observed rate overall. But it outputs only 7–8 distinct risk levels (ECE 0.18–0.20).

9 Cross-model replication

Models. To test whether the result is specific to Jev, we ran the same 942 bugs, questions and three-step adapter through four further models.

– **OpenJev 27B** [27]: an independently trained Jev-style decision model (Hugging Face `openjev/openjev`, commit `b4a89f5`; several unrelated projects share the name). It is served on one H100 exactly as its authors specify, with their calibrated readout. Its 2,826 requests had 0 failures. (An unofficial architectural reconstruction of Jev also exists [18], but it has no trained weights, so it could not be evaluated.)
– **Three general instruct models:** Qwen2.5-7B [30], OLMo-2-7B [33] and Phi-3.5-mini [1]. Each runs behind a Jev-compatible readout: next-token probabilities over the allowed labels (as in [17]), with TypeSafe's documented confidence formulas.

Each model's estimator was trained on that model's own outputs for the 442 training bugs and tested on its 500 held-out bugs. The pre-registered tests mirror HR1 and HR2, with Holm correction across all 8 tests.

Deviations, disclosed. We recorded three pre-registration amendments.

– OpenJev was added before any of its outputs existed.
– OLMo-2 needed a newer `transformers` release.
– A readout bug, in which a SentencePiece word-start token was shared by all digit labels, was found after interim results had been seen. All three general models were re-run under one corrected readout. The conclusions did not change.

Result. All 8 pre-registered tests are supported (Fig. 7, Table 3).

– **Decision estimators:** AUROC 0.64–0.76.
– **Final-step confidence:** 0.40–0.58.
– **Weakest model:** OLMo-2 (0.637 vs. 0.551; one-sided $p = 0.037$, passing at the last Holm step).
– **Transfer:** Jev's frozen estimator, never refitted, reaches 0.76 [0.72, 0.80] on OpenJev's outputs, as well as OpenJev's own estimator does.




Fig. 7. Across five models, the decision-feature estimator ranks wrong workflow actions better than the model's own final-step confidence. The intervals overlap only for OLMo-2.

Table 3. Per-model results on the same 500 held-out bugs. AUROC columns rank wrong workflow actions (95% bootstrap CI): the decision-feature estimator fitted on each model's own training outputs, the model's final-step confidence, the action-conditional error-rate rule, and Jev's frozen estimator applied unchanged. Cost columns are from the pre-registered intervention test (Section 10); the oracle is an upper bound that must spend all 50 reviews, and "wrong accepts" is their share of no-review cost. Absolute failure rates are not a clean quality comparison, because the Jev-style and general models use different interfaces.

			Held-out AUROC for wrong actions				Cost at 10% review budget			
Model	Type	Fail rate	Decision est.	Final-step conf.	Action rule	Jev est.	No review	Best review arm	Oracle	Wrong accepts
Jev	TypeSafe, hosted	0.43	0.76 [0.72, 0.80]	0.55 [0.49, 0.60]	0.76	—	658	681 (conf. product)	370	52%
OpenJev	Jev-style, 27B	0.47	0.75 [0.70, 0.79]	0.57 [0.53, 0.63]	0.75	0.76	660	674 (confidence)	441	40%
Qwen2.5	general, 7B	0.74	0.74 [0.68, 0.79]	0.47 [0.41, 0.54]	0.70	0.74	903	910 (estimator)	856	14%
Phi-3.5	general, 3.8B	0.72	0.68 [0.62, 0.73]	0.40 [0.34, 0.46]	0.69	0.70	831	890 (confidence)	890	4%
OLMo-2	general, 7B	0.80	0.64 [0.58, 0.69]	0.55 [0.48, 0.62]	0.58	0.64	893	916 (all arms tie)	916	1%

The signal is simple. A class-frequency rule, "the historical error rate of the action the workflow chose" (estimated on training bugs only), matches the estimator for Jev (0.76) and OpenJev (0.75), and comes close for the others (0.58–0.70). Single uncertainty signals each sit at chance for workflow failure:

- routing confidence: 0.48–0.52;
- regression confidence: 0.45–0.56;
- severity entropy: 0.40–0.55.

The predictive information is therefore mostly *which action was chosen* and how often that action has been wrong before.

Failure modes differ by model family.

- **Jev-style models (Jev and OpenJev):** both pull severity to the middle level.
- **General instruct models:** they push severity to "blocking" for 67–100% of bugs, whatever the true level, and are wrong far more often (72–80% vs. 43–47%).




Fig. 8. Total cost at a 10% review budget. No feasible strategy beats no review. A perfect reviewer (oracle, an upper bound using held-out outcomes) would cut Jev's cost by 44% and OpenJev's by 33%. For the general models it saves little or nothing: they escalate most cases themselves, leaving few reviewable errors (Phi-3.5's oracle exceeds no review because 50 reviews must be spent on 63 candidates, only 4 of which gain).

The absolute failure rates are not a clean quality comparison, because the two groups use different interfaces. The within-model contrast is.

10 Does the predictive signal reduce cost?

Design. We pre-registered the test before computing any cost outcome.

- **Budget:** 50 reviews (10%) per model on the held-out bugs. A review escalates the case to a human, priced with the frozen cost matrix.
- **Primary arm (A1):** rank candidates by the *action-level expected saving* of a review, estimated on training bugs. It is cost-aware rather than error-rate-based, because a wrong *defer* costs no more than an escalation.
- **Comparators:** confidence-ranked review (B) and random review (C).

Result. Two of ten pre-registered tests are supported: A1 beats random for Jev and OpenJev, by about 10–12 cost units. A1 is not shown to beat confidence for any model (for Jev its point estimate is 4 units lower, with an interval spanning zero). Every review arm costs more than no review at all; for Jev, 658 with no review against 681–714 with review (Fig. 8).

Where the cost is. A descriptive follow-up separates two regimes.

- **Jev-style models:** 40–52% of no-review cost comes from wrongly *accepted* serious or regression bugs. An oracle that picked the right 50 cases would save 33–44%. But those cases are 15–16% of accepted cases. The action rule cannot separate them, because every accept looks alike to it, and confidence cannot either. The value exists; the identification fails.
- **General models:** cost is dominated by over-escalation (*escalate* when the target is *accept*). More review cannot reduce that; even the oracle saves at most 5%.

Ranking which actions are wrong is therefore not the same as finding which reviews save money: frequent errors and expensive errors differ.

A case-level score, and a stopping decision. We then asked whether a per-case score could find the expensive errors. It was developed on the 442 training bugs only, under a plan committed before any score was computed. A parameter-free plug-in score was selected by a pre-stated rule over a small logistic model and frozen. It ranks accepted cases by expected saving from review, $9p_2 + 6p_1q - 2(1 - p_2 - p_1q)$, using Jev's `score` mass on levels 1 and 2 (p_1, p_2) and its `noul` probability q. On the training mix it cut cost by 12% against no review (630 vs. 713) and captured 22% of the oracle saving. But the training bugs were quota-sampled. Reweighted to each tracker's natural label mix, a 10% budget is projected to cost *more* than no review, with power near zero.

- **Feasibility check.** Before generating any fresh case, we pre-registered a check that varied only the review budget (1–10%). Viability required power ≥ 0.80 to show lower cost than no review, with at most 1,000 fresh bugs, and a negative median projected cost change. Each simulated study first resampled the training bugs, so uncertainty in error prevalence and ranking quality was propagated.
- **Result.** No budget was viable. The highest power was 0.20 (1% budget, 1,000 bugs), with a median change of -2 and an 80% range of $[-46, +20]$. Every budget of 2% or more had a positive median cost change, and power below 0.15.
- **Decision.** By the binding stop rule, the confirmatory study was not run and no further designs were searched. No fresh API calls were made.

This is a feasibility assessment, not evidence that review cannot help. The oracle shows that a good selector would save substantially; the signals available here cannot identify the cases well enough to pay for the reviews.

11 Method: audits that caught defects

Table 4 lists the defects the study's own audits caught. Most were found before the data that would have exposed them existed. The exception is the confound, found after a result. It would have been caught earlier by asking, for every strategy and every target class: *can this strategy be right here, and through what information?* We recommend this check, together with measuring each trigger's selectivity on pilot inputs, before freezing any escalation policy.

12 Limitations

- **Generality.** Five models in one domain (bug triage) and one workflow. Jev was version 1.13.0. The general instruct models use our prompt and readout, not a trained decision interface. Later versions and other domains may behave differently.

- **References are not truth.** Mozilla's triage sample excludes re-triaged bugs, which biases agreement upward. Kernel labels are reporters' claims, and the kernel's middle level is a default value.
- **Small constructed samples.** The `choice` error subgroup is $n = 6$, and `noul`'s perfect accuracy on constructed data is 24 items.
- **Constructed target.** $a^* = F(\cdot)$ is constructed, and all strategy results are conditional on it.
- **Memorization.** Old public bugs may appear in training data. The recent subsets are small (Mozilla 54, kernel 35).
- **Cross-model deviations.** Three amendments to the cross-model pre-registration, including a readout bug fixed after interim results were seen. On 3% of OLMo-2's requests, most of the probability fell outside the allowed labels; excluding them does not change its result.
- **Intervention scope.** One budget and one cost table, both frozen in advance. Reviewers are assumed correct, and the oracle is an upper bound, not a strategy.
- **Protocol revisions.** The protocol went through twelve revisions. All are dated and disclosed, and each was made before the data it affects existed. The number is nonetheless large.

13 Pre-registered follow-up (planned; not yet run)

No result in this paper comes from the studies in this section.

Case-level expensive-error estimator (stopped). The case-level follow-up proposed after the intervention test was developed and then stopped before data collection by its own pre-registered feasibility rule (Section 10). It is not pending.

Template study. To test the composition question under control, we pre-registered a study on deterministic template content: 3,103 units, each instance describing one incident about one service, with value-neutral sentence frames and 13 automated audits. Its primary tests are H1, confidence-ranked vs. random overrides at a 10% budget scored by cost, and H2, per-primitive vs. raw-product ranking, with a sign-flip test clustered by service. Both are Holm-corrected. The sample size is set from a second calibration pilot, with a content ceiling of 720 instances. Given the results above, a null H1 is a live outcome, and it would be reported as the answer to the composition question. Deterministic templates raise their own external-validity questions. That is why the real-data studies above are reported separately, and why their conclusions do not depend on the follow-up.

14 Conclusion

Structured outputs make uncertainty *look* uniform: every Jev primitive returns a number between 0 and 1. In the evaluated workflow, Jev's three primitives

showed distinct confidence failure modes, fixed thresholds on them did not transfer, and severity compression appeared on two trackers while the primitive's own confidence gave no sign of it.

Pre-registered tests then showed that what the workflow *decided* predicts its failures better than how confident it was. This held on 500 new bugs and across five evaluated models from four sources, and it was driven mostly by the chosen action's historical error rate. Jev-style decision models and general instruct models failed in different ways: compression versus over-escalation.

That prediction did not become a cheaper review policy. The expensive errors are real, but they hide inside actions that look alike. Knowing which decisions are likely wrong is different from knowing which are worth correcting. Workflow uncertainty has to be evaluated against the decision it is meant to improve. A case-level score that targeted the expensive errors directly helped on the training mix, but it failed our pre-registered feasibility check under the natural mix, and we stopped there by rule rather than search for a design that would pass.

References

1. Abdin, M., Aneja, J., Awadalla, H., et al.: Phi-3 technical report: A highly capable language model locally on your phone. arXiv preprint arXiv:2404.14219 (2024)
2. Alves, J.V., Leitão, D., Jesus, S., Sampaio, M.O.P., Liébana, J., Saleiro, P., Figueiredo, M.A.T., Bizarro, P.: Cost-sensitive learning to defer to multiple experts with workload constraints. Transactions on Machine Learning Research (2024)
3. Angelopoulos, A.N., Bates, S.: A gentle introduction to conformal prediction and distribution-free uncertainty quantification. arXiv preprint arXiv:2107.07511 (2021)
4. Angelopoulos, A.N., Bates, S., Fisch, A., Lei, L., Schuster, T.: Conformal risk control. In: International Conference on Learning Representations (ICLR) (2024)
5. Babbar, V., Bhatt, U., Weller, A.: On the utility of prediction sets in human-AI teams. In: Proceedings of IJCAI (2022)
6. Barlow, R.E., Proschan, F.: Mathematical Theory of Reliability. Wiley (1965)
7. Bouchard, D.: Is escalation worth it? On the depth of LLM cascades. arXiv preprint arXiv:2605.06350 (2026), v2; v1 was titled "Is Escalation Worth It? A Decision-Theoretic Characterization of LLM Cascades"
8. Chowdhury, A., Magdon-Ismail, M., Yener, B.: Quantifying contribution and propagation of error from computational steps, algorithms and hyperparameter choices in image classification pipelines. arXiv preprint arXiv:1903.00405 (2019)
9. Denney, S., DiGiuseppe, M.: JEV versus LLMs: Accuracy, cost and calibration on seven political science replications. arXiv preprint arXiv:2610.06625 (2026)
10. Deußer, T., Sparrenberg, L., Sifa, R.: Evaluating and benchmarking the system one model Jev. arXiv preprint arXiv:2609.37647 (2026)
11. Dou, Y., Lian, S., Li, S.: Conformal cascade: Distribution-free accuracy guarantees for multi-tier LLM inference. arXiv preprint arXiv:2607.25018 (2026)
12. Duan, J., Diffenderfer, J., Madireddy, S., Chen, T., Kailkhura, B., Xu, K.: UProp: Investigating the uncertainty propagation of LLMs in multi-step agentic decision-making. arXiv preprint arXiv:2506.17419 (2025)
13. El-Yaniv, R., Wiener, Y.: On the foundations of noise-free selective classification. Journal of Machine Learning Research **11** (2010)

14. Geifman, Y., El-Yaniv, R.: Selective classification for deep neural networks. In: Advances in Neural Information Processing Systems (NeurIPS) (2017)
15. Geifman, Y., El-Yaniv, R.: SelectiveNet: A deep neural network with an integrated reject option. In: Proceedings of the 36th International Conference on Machine Learning (ICML) (2019)
16. Geng, J., Cai, F., Wang, Y., Koeppl, H., Nakov, P., Gurevych, I.: A survey of confidence estimation and calibration in large language models. In: Proceedings of NAACL (Volume 1: Long Papers). pp. 6577–6595 (2024)
17. Geuter, J., Cheng, A., Alvarez-Melis, D.: Releasing the inner Jev: A simple recipe for open decision models. arXiv preprint arXiv:2610.17205 (2026)
18. Gomez, K.: open-jev: an unofficial reconstruction of Jev's architecture. `https://github.com/kyegomez/open-jev` (2026), untrained architecture with random weights. Accessed 2026-10-17
19. Guo, C., Pleiss, G., Sun, Y., Weinberger, K.Q.: On calibration of modern neural networks. In: Proceedings of the 34th International Conference on Machine Learning (ICML) (2017)
20. Jung, J., Brahman, F., Choi, Y.: Trust or escalate: LLM judges with provable guarantees for human agreement. In: International Conference on Learning Representations (ICLR) (2025)
21. Kittler, J., Hatef, M., Duin, R.P.W., Matas, J.: On combining classifiers. IEEE Transactions on Pattern Analysis and Machine Intelligence **20**(3), 226–239 (1998)
22. Kotte, V.: PASC: Pipeline-aware conformal prediction with joint coverage guarantees for multi-stage NLP and LLM pipelines. arXiv preprint arXiv:2605.18812 (2026)
23. Lin, M., Lan, Q., Guan, S., Jing, W., Fan, J., Gregg, D., Botterweck, G.: Uncertainty quantification for LLM agents: A taxonomy, an evaluation protocol, and an empirical study. arXiv preprint arXiv:2609.07395 (2026)
24. Madras, D., Pitassi, T., Zemel, R.: Predict responsibly: Improving fairness and accuracy by learning to defer. In: Advances in Neural Information Processing Systems (NeurIPS) (2018)
25. Meng, L.: How far can a commercial decision model's probabilities be trusted? A calibration audit of TypeSafe Jev against open and general-purpose classifiers. Code, data and paper, Zenodo, `https://doi.org/10.5281/zenodo.22935043` (2026), version 1.0.0
26. Naeini, M.P., Cooper, G., Hauskrecht, M.: Obtaining well calibrated probabilities using Bayesian binning. In: Proceedings of the AAAI Conference on Artificial Intelligence (2015)
27. OpenJev: OpenJev: an open-weights decision model. `https://huggingface.co/openjev/openjev` (2026), hugging Face commit b4a89f5884f3482a5e894b2e7ff01db8ea033726; CC BY-NC 4.0 weights; states it is independent of TypeSafe. Not the same project as other repositories named OpenJev. Accessed 2026-10-17
28. Park, S., Choi, M., Kim, J., Kang, M.: Risk is not review value: Wrong-answer exposure under bounded review budgets. In: SeT-LLM Workshop at KDD (2026), arXiv:2609.07095
29. Platt, J.C.: Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods. Tech. rep., Microsoft Research (1999)
30. Qwen, Yang, A., et al.: Qwen2.5 technical report. arXiv preprint arXiv:2412.15115 (2024)

31. Rabanser, S., Rauschmayr, N., Kulshrestha, A., Poklukar, P., Jitkrittum, W., Augenstein, S., Wang, C., Tombari, F.: Gatekeeper: Improving model cascades through confidence tuning. arXiv preprint arXiv:2502.19335 (2025)
32. Tang, L., Zheng, Y.: Typed decision models: An early evidence audit and evaluation checklist. arXiv preprint arXiv:2609.32160 (2026)
33. Team OLMo, Walsh, P., Soldaini, L., et al.: 2 OLMo 2 furious. arXiv preprint arXiv:2501.00656 (2024)
34. TypeSafe: Confidence. TypeSafe documentation, `https://docs.typesafe.ai/confidence` (2026), accessed 2026-10-16
35. Wang, X., Wang, P., Halgamuge, S.: CORDIAL: Calibrating ordinal LLM outputs from few labels. arXiv preprint arXiv:2609.29807 (2026)
36. Xia, B., Zhu, L., Gao, E., Lu, Q., Xue, M., Sejdinovic, D.: Uncertainty propagation in LLM-based systems. arXiv preprint arXiv:2604.23505 (2026)
37. Zellinger, M.J., Liu, R., Thomson, M.: Cost-saving LLM cascades with early abstention. arXiv preprint arXiv:2502.09054 (2025)
38. Zhang, J., Elluri, S., Cherukuvada, B., Joffe, Y., Sena, J., Contreras, M., Siegel, S., Nerella, S., Price, C., Rashidi, P.: Auditing multimodal LLM raters: Central tendency bias in clinical ordinal scoring. arXiv preprint arXiv:2605.16386 (2026)
39. Zhang, J., Xiong, C., Wu, C.S.: Agentic confidence calibration. arXiv preprint arXiv:2601.15778 (2026)
40. Zhang, W., Amin, S., Perakis, G.: Decomposition-based modular conformal prediction for two-stage modeling. arXiv preprint arXiv:2510.04406 (2025)

A Action rule and cost matrix

Table 5. The action rule $F(c_2, c_3)$. *Unclear* is checked first.

$c_2 \setminus c_3$	0	1	2
1 (yes)	accept	defer	escalate
0 (no)	accept	accept	escalate
unclear	request evidence (any c_3)		

Table 6. Frozen cost matrix $\text{cost}(a, a^*)$. One unit of human cost is added per escalation. "req. ev." = request evidence.

action \ target	accept	escalate	req. ev.	defer
accept	0	10	6	8
escalate	1	0	1	1
req. ev.	1	1	0	1
defer	1	1	1	0

B Reproducibility

All calls used `jev-1.13.0`. Real-data calls: Mozilla 2,424 (including a label-wording arm) plus a 252-call smoke test; kernel 2,160 plus a 216-call smoke test. All returned HTTP 200 and parsed. Every dataset, raw response, execution manifest and analysis is hash-locked in the accompanying repository, as are the pre-registration documents and their revision history. The figure data in this paper are generated from committed result files by `make_figure_data.py`.

Table 4. Defects found by the study's own audits.

Defect	Detected by	When
A "primitive-aware" arm structurally identical to the baseline	inspecting the action rule	before evaluation
A trigger firing on ≈90% of inputs	selectivity on input signals only	before evaluation
A threshold sensitive to the data distribution	smoke test vs. pilot	before the full run
Four silent runner defects (e.g. the literal "None" shown to the model; partial data analyzed)	adversarial probing	before the live run
The confidence-vs-decisions confound	post-hoc review	after the Mozilla result
Template content whose labels were recoverable from punctuation alone (100%) and whose sentences leaked cross-label cues	independent review (separate AI agent)	before the controlled study