| | |
|---|---|
| **Status** | Finished |
| **Started** | Friday, 9 October 2026, 3:06 PM |
| **Completed** | Friday, 9 October 2026, 3:24 PM |
| **Duration** | 17 mins 37 secs |
| **Grade** | **10.00** out of 10.00 (**100**%) |

Question **1**

Correct

Mark 2.00 out of 2.00

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

1 <= orderValue< 10e100000

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

**For example:**

| Test | Result |
|---|---|
| `print(christmasDiscount(578))` | 12 |

**Answer:** (penalty regime: 0 %)

Reset answer

```
def christmasDiscount(ordervalue):
    total=0
    for ch in str(ordervalue):
        if ch in "2357":
            total+=int(ch)
    return total
```

| | Test | Expected | Got | |
|---|---|---|---|---|
| ✓ | `print(christmasDiscount(578))` | 12 | 12 | ✓ |
| ✓ | `print(christmasDiscount(57))` | 12 | 12 | ✓ |
| ✓ | `print(christmasDiscount(222))` | 6 | 6 | ✓ |
| ✓ | `print(christmasDiscount(77777))` | 35 | 35 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **2**

Correct

Mark 2.00 out of 2.00

A strobogrammatic number is a number that looks the same when rotated 180 degrees (looked at upside down).

Write a program to determine if a number is strobogrammatic. The number is represented as a string.

**Example 1:**

**Input:**

69

**Output:**

true

**Example 2:**

**Input:**

88

**Output:**

true

**Example 3:**

**Input:**

962

**Output:**

false

**Example 4:**

**Input:**

1

**Output:**

true

**For example:**

| Test | Result |
|---|---|
| `print(Strobogrammatic(69))` | `True` |
| `print(Strobogrammatic(962))` | `False` |

**Answer:** (penalty regime: 0 %)

Reset answer

```
def Strobogrammatic(s):
    rev=""
    for ch in str(s):
        if ch=='6':
            rev='9'+rev
        elif ch=='9':
            rev='6'+rev
        elif ch in '018':
            rev=ch+rev
        else:
            return False
    return True
```

| | Test | Expected | Got | |
|---|---|---|---|---|
| ✓ | `print(Strobogrammatic(69))` | `True` | `True` | ✓ |
| ✓ | `print(Strobogrammatic(88))` | `True` | `True` | ✓ |
| ✓ | `print(Strobogrammatic(962))` | `False` | `False` | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **3**

Correct

Mark 2.00 out of 2.00

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: U = 2^a * 3^b * 5^c, where a, b and c are nonnegative integers.

**For example:**

| Test | Result |
|---|---|
| `print(checkUgly(6))` | `ugly` |
| `print(checkUgly(21))` | `not ugly` |

**Answer:** (penalty regime: 0 %)

Reset answer

```
def checkUgly(n):
    if n<=0:
        return "not ugly"
    for i in [2,3,5]:
        while n%i == 0:
            n//=i
    if n==1:
        return "ugly"
    else:
        return "not ugly"

```

| | Test | Expected | Got | |
|---|---|---|---|---|
| ✓ | `print(checkUgly(6))` | `ugly` | `ugly` | ✓ |
| ✓ | `print(checkUgly(21))` | `not ugly` | `not ugly` | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **4**

Correct

Mark 2.00 out of 2.00

complete function to implement coin change making problem i.e. finding the minimum

number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

**Answer:** (penalty regime: 0 %)

Reset answer

```
def coinChange(n):
    count = 0
    for coin in [4,3,2,1]:
        count+=n//coin
        n%=coin
    return count

```

| | Test | Expected | Got | |
|---|---|---|---|---|
| ✓ | `print(coinChange(16))` | 4 | 4 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **5**

Correct

Mark 2.00 out of 2.00

Write a function that returns the value of a+aa+aaa+aaaa with a given digit as the value of a.

Suppose the following input is supplied to the program:

9

Then, the output should be:

9+99+999+9999=11106

Sample Input Format:

9

Sample Output format:

11106

**For example:**

| Test | Result |
|---|---|
| print(Summation(8)) | 9872 |

**Answer:** (penalty regime: 0 %)

Reset answer

```
def Summation(n):
    a=str(n)
    total=int(a)+int(a*2)+int(a*3)+int(a*4)
    return total
```

| | Test | Expected | Got | |
|---|---|---|---|---|
| ✓ | print(Summation(8)) | 9872 | 9872 | ✓ |
| ✓ | print(Summation(10)) | 10203040 | 10203040 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

| | |
|---|---|
| **Status** | Finished |
| **Started** | Tuesday, 20 October 2026, 10:07 PM |
| **Completed** | Tuesday, 20 October 2026, 10:10 PM |
| **Duration** | 3 mins 12 secs |
| **Grade** | **15.00** out of 15.00 (**100**%) |

Question **1**

Correct

Mark 1.00 out of 1.00

Which of the following is not the type of function argument?

- a. default argument
- b. Keyword argument
- c. initial argument ✓
- d. Required argument

Question **2**

Correct

Mark 1.00 out of 1.00

**Python function always returns a value**

Select one:

- True ✓
- False

Question **3**

Correct

Mark 1.00 out of 1.00

Which of the following statement is a function call?

- a. def sum
- b. function sum
- c. sum ✓
- d. call sum

Question **4**

Correct

Mark 1.00 out of 1.00

**What is the output of the add() function call?**

```
def add(a, b):
    return a+5, b+5
result = add(3, 2)
print(result)
```

a. 8

b. Syntax Error

c. (8,7) ✓

d. 15

Question **5**

Correct

Mark 1.00 out of 1.00

Which of the following is not the scope of variable?

a. None of the mentioned

b. Outside ✓

c. Global

d. Local

Question **6**

Correct

Mark 1.00 out of 1.00

**Which of the following function headers is correct?**

a. def fun(a = 2, b, c = 3)

b. def fun(a, b = 2, c = 3) ✓

c. def fun(a = 2, b = 3, c)

d. def fun(a, b, c = 3, d)

Question **7**

Correct

Mark 1.00 out of 1.00

**What will be the output of the following Python code?**

```
def sayHello():
    print('Hello World!')
sayHello()
sayHello()
```

a. Hello
Hello

b. 'Hello World!'
'Hello World!'

c. Hello World! ✓
Hello World!

d. None of the mentioned

Question **8**

Correct

Mark 1.00 out of 1.00

Write the output of : print(abs(-45))

a. None of the mentioned

b. -45

c. 45 ✓

d. 45.0

Question **9**

Correct

Mark 1.00 out of 1.00

Which of the following number can never be generated by the following code: random.randrange(0, 100)

a. 1

b. 99

c. 0

d. 100 ✓

Question **10**

Correct

Mark 1.00 out of 1.00

The function can be called in the program by writing function name followed by _____.

a. [ ]

b. None of the mentioned

c. { }

d. ( ) ✓

Question **11**

Correct

Mark 1.00 out of 1.00

Choose the incorrect statement.

a. print(pow(2.3, 3.2))

b. print(pow(2, 3, 2))

c. None of the mentioned ✓

d. print(pow(2, 3))

Question **12**

Correct

Mark 1.00 out of 1.00

Write the output of : print(max([1, 2, 3, 4], [4, 5, 6], [7]))

a. [7] ✓

b. [4, 5, 6]

c. 7

d. [1, 2, 3, 4]

Question **13**

Correct

Mark 1.00 out of 1.00

**Which one of the following is the correct way of calling a function?**

a. function function_name()

b. call function_name()

c. function_name() ✓

d. ret function_name()

Question **14**

Correct

Mark 1.00 out of 1.00

In a program, a function can be called _____ times.

- a. 3
- b. 5
- c. Multiple times ✓
- d. 2

Question **15**

Correct

Mark 1.00 out of 1.00

Choose the correct statement

- a. We can create function with no argument and no return value.
- b. We can create function with no argument and with return value(s)
- c. All of the mentioned ✓
- d. We can create function with argument(s) and no return value.